Gain and Phase Analyzer

Interim Report

2014, December 5th

Gain and Phase Analyzer

- Requirements
- Design
- Prototyping
- Schedule
- Budget
- Next Steps

Purpose

- Test the frequency behavior of filters, amplifiers
- Generate Bode plot with amplitude and phase



Requirements



Design — Software





Design — Microcontroller





Design — Signal Generation









Design — Signal Output







Design — Phase Detection



Design — Detection









Timeline


October
November
December
Requirements
Development Plan
System Architecture
Prototypes Built

Schedule

Item	Start Date	End Date	Percent Complete
PRS	2014-10-03	2014-10-17	100%
PDP	2014-10-17	2014-10-31	100%
Architecture	2014-10-31	2014-11-14	100%
Interim Report	2014-11-14	2014-12-05	100%
Proto. built	2014-11-14	2014-12-05	100%
Proto. firmware	2014-11-10	2014-12-05	100%

Budget

Item	Expended	Actual	Estimated to Completion	Estimated at Completion
Synthesizer	$60	$60	$0	$60
Input	$70	$70	$0	$70
Output amp.	$66	$66	$0	$66
Power supply	$0	$0	$0	$0
Final build	$0		$120	$120
Enclosure	$0		$30	$30
Misc/re-spins	$0		$100	$100
Total	$196	$196	$250	$446

Next Steps

Hardware

- Combine prototypes into a final product

Software

- Finish firmware with full analysis capability
- Write PC software that receives and plots data

Conclusion

- Product can capture Bode plots
- Uses signal synthesizer, output amplifier, input frontend, ADC, and microcontroller
- These have been prototyped and tested