

Eng: Chris Pavlina		
Gain/Phase Analyzer		
WCP52		
Sheet: /InputFrontend/Buffer_Filter/ File: Buffer_Filter.sch		
Title: Input Buffer and Filter		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product		Id: 9/13



Gain/Phase Analyzer

WCP52

Sheet: /Comm/
File: Comm.sch

Title:


Size: USLegal

Date: 2015-03-10


Rev:


KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product

Id: 2/13




Eng: Chris Pavlina		
Gain/Phase Analyzer		
WCP52		
Sheet: /InputFrontend/Detector/		
File: Detector.sch		
Title: Logarithmic Detector		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product		Id: 10/13







Eng: Chris Pavlina		
Gain/Phase Analyzer		
WCP52		
Sheet: /OutputAmp/LPF/		
File: LPF.sch		
Title: LPF for Output Amplifier		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product		Id: 5/13



Eng: Chris Pavlina		
Gain/Phase Analyzer		
WCP52		
Sheet: /MPU/		
File: MPU.sch		
Title: MPU		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product		Id: 13/13







This is a power input, conditioning and protection circuit for the entire instrument.

- While the circuit is powered down, @R11 discharges the gates of @Q2 and @Q3, switching them off.
- At startup, @C3 holds the gates to the sources, keeping them switched off.
- @Q2's substrate diode allows current to flow through despite the FET being switched off, but @Q3's diode faces the other direction.
- @U1 provides a fixed 2.5V reference voltage for comparison.
- @U2B compares the input voltage to the reference; when it exceeds a threshold, the output falls to 0V and @Q1 is switched on.
- When @Q3 enters the linear region, it along with @C4 forms a circuit known as a Miller integrator, integrating the input voltage.
- Once @Q3 falls into the saturation region, @Q2 is also in this region, bypassing its substrate diode and providing a path to ground.
- If the input voltage exceeds a higher threshold, @U2A switches on. This saturates @Q1, yanking the gates of @Q2 and @Q3 down to ground.
- When this happens, @D1 pulls @U2A's reference voltage down, latching the circuit in this position. It will not return to normal operation until the input voltage is brought back below the threshold.

Sheet: /PowerInput/ File: PowerInput.sch		
Title:		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product	Id: 11/13	



Eng: Chris Pavlina		
Gain/Phase Analyzer		
WCP52		
Sheet: /InputFrontend/Protection/		
File: Protection.sch		
Title: Input Protection		
Size: USLegal	Date: 2015-03-10	Rev:
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product		Id: 7/13



Eng: Chris Pavlina

Gain/Phase Analyzer

WCP52

Sheet: /InputFrontend/Switching/
File: Switching.sch

Title: Input Switching

Size: USLegal Date: 2015-03-10
KiCad E.D.A. kicad (2015-03-09 BZR 5487)-product

Rev:
Id: 8/13

