

A Survey Report of Two Enterprise-Class RDBMSs

Andrew Figueroa
Western Connecticut State University
181 White St
Danbury, CT 06810
figueroa039@connect.wcsu.edu

Steven Rollo
Western Connecticut State University
181 White St
Danbury, CT 06810
rollo003@connect.wcsu.edu

ABSTRACT

Microsoft SQL Server and PostgreSQL are two widely used enterprise-class Relational Database Management Systems (RDBMSs). Both systems provide implementations of the SQL standard for data management. This paper is a report of a study of contrasting these two DBMSs. Through the implementation of multiple non-trivial schemas, we identified and categorized several common database design, development and administration activities. We will discuss the similarities and differences we found while performing these activities, and how the approach that each DBMS took to implement these activities compares with what is described in the SQL standard. Additionally, we will consider if PostgreSQL is technically suitable for enterprise applications.

This comparison can serve as a baseline for identifying the types of issues that could arise during the migration of schemas from one DBMS to another, and as an addition to the kinds of considerations made while choosing an appropriate DBMS to manage an application's requirements.

Categories and Subject Descriptors

H.2.4 [Database Management]: Systems – *Relational databases*.

Keywords

Microsoft SQL Server 2016 Express, PostgreSQL 9.6, Relational Database Management System (RDBMS), Schema migration.

1. INTRODUCTION

Relational database management systems (RDBMSs) are widely used to store and manage data. The wide adoption of these systems has led to the availability of a large number of RDBMSs. For an undergraduate research project, we sought to better understand the differences between enterprise-class DBMSs. In particular, we will be comparing Microsoft SQL Server (MSSQL) and PostgreSQL (Postgres).

In this paper, we identify design, development, and administration activities common among RDBMSs. We will then use illustrative examples to show how these tasks differ between MSSQL and Postgres. Sections 2, 3, and 4 will introduce the design, development, and administration activities, respectively. Additionally, these sections will detail the differences found between the two DBMSs for each activity. Finally, section 5 will summarize the differences found between MSSQL and Postgres, based on the activities we identified. We will summarize how the

SQL implementation of each DBMS compares to the SQL standard, and determine how technically suitable PostgreSQL is to enterprise applications.

1.1 Identifying and Categorizing Activities

To compare MSSQL and Postgres, we identified common design, development, and administration activities performed in RDBMSs. Prior to this comparison, we took three separate schemas originally designed for Oracle Database and migrated them to both MSSQL and Postgres. During this process, we observed activities that commonly occurred in the SQL code of each schema, and activities that were needed to work with each DBMS. We then categorized each activity as a design, development, or administration activity. Any feature that affects how a schema is created at the conceptual or logical level, such as data type differences, is considered a design activity. Development activities include anything that involves writing SQL code that relies on the specific implementation of the DBMS. Administration activities include installation, managing users and permissions, and DBMS configuration. It is apparent from these definitions that there is overlap between each category, so each activity is placed in the category it is most relevant to.

1.2 DBMSs Used

We used two enterprise-class DBMSs for this comparison, Microsoft SQL Server (MSSQL) and PostgreSQL (Postgres).

Microsoft SQL Server is commercial software produced by Microsoft. We used MSSQL 2016 Express, version 13.0.4001 for this comparison. The SQL implementation used by MSSQL is Microsoft's Transact SQL (T-SQL).

PostgreSQL (Postgres) is available as free and open source software under a BSD like license [5]. We used Postgres version 9.6 for this comparison. The SQL implementation used by Postgres is PL/pgSQL (pgSQL).

1.3 Working Examples

Throughout this paper, we provide SQL code examples to show the differences between these two DBMSs. To create these examples, we took three separate schemas previously created for other projects and created versions of each schema for both MSSQL and Postgres.

Advert: This schema describes a system for managing advertisement orders for a fictional newspaper.

Shelter: This schema describes a system for managing animal care and adoptions at a fictional animal shelter.

Babysitting: This schema describes a fictional babysitting co-op where members earn and use credits through babysitting each other's children.

Classroom: This schema represents an environment where students in a course are allowed appropriate access to a DBMS in order to experiment and complete assignments. Instructors for this course also have access to the student's work inside of the DBMS.

The full SQL code for each schema is provided in the appendix.

This paper is the product of a student directed study advised by Dr. Sean Murthy at Western Connecticut State University. The goal of the study is to better understand the differences between enterprise-class DBMSs. MSSQL and Postgres are the two DBMSs this study focuses on. Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

© 2017 Andrew Figueroa, Steven Rollo, Sean Murthy. CC BY-NC-SA 4.0

| SQL:1999 Standard | SQL Server | PostgreSQL |
|---|--|---|
| DATE (years 0001-9999) | DATE (years 0001-9999, 3B) | DATE (years 4713 B.C.E - 5874897 C.E., 4B) |
| TIME (6 fs) fs = fractional seconds | TIME (7 fs, 3-5B) | TIME (6 fs, 8 or 12B, time zone) |
| TIMESTAMP (years 0001-9999, 6 fs) | DATETIME (years 1753-9999, 3 fs, 8B) DATETIME2 (years 0001-9999, 7 fs, 6-8B) SMALLDATETIME (years 1900-2079, 0 fs, 4B) DATETIMEOFFSET (years 0001-9999, 7 fs, 8-10B, time zone) | TIMESTAMP (years 4713 B.C.E. - 294276 C.E., 6 fs, 8B, time zone) |
| INTEGER SMALLINT BIGINT (ranges not defined) | INTEGER (-2^{31} to $2^{31} - 1$, 4B) SMALLINT (-2^{15} to $2^{15} - 1$, 2B) BIGINT (-2^{63} to $2^{63} - 1$, 8B) TINYINT (0 to 255, 1B) | INTEGER (-2^{31} to $2^{31} - 1$, 4B) SMALLINT (-2^{15} to $2^{15} - 1$, 2B) BIGINT (-2^{63} to $2^{63} - 1$, 8B) |
| NUMERIC DECIMAL (ranges not defined) | NUMERIC and DECIMAL (up to 38 digits of precision) | NUMERIC and DECIMAL (up to 131072 digits before decimal, up to 16383 after) |
| REAL DOUBLE PRECISION FLOAT (ranges not defined) | REAL (identical to FLOAT (24)) FLOAT (n) (1-24: 7 digit precision, 25-53: 15 digit precision) | REAL (usually IEEE single) DOUBLE PRECISION (usually IEEE single) FLOAT (n) (1-24: single, 25-53: double) |
| CHAR VARCHAR CLOB (maximum sizes not defined) | CHAR VARCHAR VARCHAR (max) (approx. 2GB max) | CHAR VARCHAR TEXT (approx. 1GB max) |

Table 1. Standard defined data types and their implementations

2. DESIGN ACTIVITIES

For the purposes of this paper, we categorized activities under *design* if they would be heavily involved in schema creation. In general, these activities do not directly affect the creation of SQL queries, but rather, decisions that would be made during the creation of conceptual and logical schema, and soon after they have been created.

2.1 Field Design

Although the specific data types used are generally considered to be a development activity, as they are used when the SQL code to implement a schema, they heavily influence field design. Therefore, we will consider the different data types available in MSSQL and Postgres as a design activity. The SQL standard defines three basic date and time types: DATE, TIME, and TIMESTAMP [1§2.4]. MSSQL implements the DATE and TIME types exactly as defined in the standard, with years ranging from 0001 to 9999 C.E., and the same precision available to the user as is defined in the standard. However, MSSQL's TIMESTAMP counterpart is named DATETIME. This is an important distinction because MSSQL does have a data type named TIMESTAMP, but it is used to refer to an internal row versioning system and is now deprecated [2§timestamp (T-SQL)]. Additionally, DATETIME is not completely equivalent to the standard's TIMESTAMP, as it can only store years from 1753-9999, and only allows up to 3 digits for fractional seconds (compared to 6 in both the SQL standard and Postgres). In addition to these three types, MSSQL also has other types available for storing date and time. These are SMALLDATETIME (years 1900-2079, 1 minute precision, 4 bytes), DATETIME2 (years 0001-9999, 6 fractional seconds, 6-8 bytes) and DATETIMEOFFSET, which is identical in precision and range to DATETIME2, but allows a UTC time offset (time zone) [2§Date and Time]. The other date and time types do not have a method of adding a time zone. In general, it is recommended to use DATETIME2 over DATETIME whenever possible, as it has an

expanded range and precision, and may use less storage space, depending on the precision specified.

In contrast, Postgres fully implements the three types, along with their WITH TIME ZONE counterparts, almost exactly as defined by the standard. As required, WITHOUT TIME ZONE is the default option. Postgres also provides TIMESTAMPTZ as an abbreviation for TIMESTAMP WITH TIME ZONE. One deviation, or perhaps, extension, from the standard is the range of years able to be stored in the DATE and TIMESTAMP types. The SQL standard states the year value is to be exactly 4 digits in length, with years ranging from 0001 to 9999. However, Postgres supports years ranging from 4713 B.C.E to 5874897 C.E. (294276 C.E in TIMESTAMP) [4§8.5]. See figure 2a and 2b for an implementation of a date and time type from the Babysitting schema in both MSSQL and Postgres.

The numeric types that are described in the SQL standard can be separated into two categories: *exact numerics* and *approximate numerics*. Exact numerics include INTEGER, SMALLINT, and BIGINT for integral numbers, and NUMERIC and DECIMAL for numbers with a fractional component, which are both given a precision and scale. Approximate numerics include REAL, DOUBLE PRECISION, and FLOAT [1§2.4]. These approximate numerics are floating-point numbers, where DOUBLE PRECISION is required to be of a greater precision than that of the REAL type. However, the standard does not provide a suggestion as to how much greater it should be. FLOAT allows the user to specify the desired precision. The standard allows the precision of any of these numeric types to be implementation-defined. The only restriction is that SMALLINT be less than or equal to INTEGER and that BIGINT be equal to or larger than INTEGER. It also states that NUMERIC must always be represented with the exact precision requested, while DECIMAL can be managed with a precision greater than what was specified.

Both MSSQL and Postgres follow the standard-defined exact numeric types and support the three integral types in a similar manner. MSSQL, however, also provides a `TINYINT` data type for integral values ranging from 0 to 255. Both DBMSs implementations treat the `NUMERIC` and `DECIMAL` data types as if they were synonyms, but they have a differing number of maximum digits available in each DBMS [2§Decimal and Numeric, 2§int, 3§8.5]. See Table 1 for the specific ranges and precision available for each type in both DBMSs.

For approximate numerics, MSSQL does not define a `DOUBLE PRECISION` data type, but does provide `REAL` and `FLOAT` types. This does not change the precision or range available since the `FLOAT` type provided by MSSQL has a maximum range identical to that of the `DOUBLE PRECISION` type provided by Postgres (when using the IEEE 754 standard in Postgres) [2§Float and Real]. Postgres follows the SQL standard and provides an implementation of all three approximate numeric types. However, the precision used depends on the environment that the DBMS is set up in. In most cases, `REAL` follows the single precision IEEE standard 754 Binary Floating-Point Arithmetic, while `DOUBLE PRECISION` follows the double precision section of that same standard. This is the expected behavior as long as "the underlying processor, operating system, and compiler support it". [4§8.1].

Two main character types are defined in the SQL standard: `CHAR` and `VARCHAR`, where `CHAR` values are fixed length (right-padded with spaces), and `VARCHAR` values have a variable length (up to a user specified maximum length, at which point the string is truncated). The standard also provides `CLOB` (character large object) as a type for storing large strings of characters without a maximum length. The character sets and maximum size of these types are left to be implementation defined. MSSQL and Postgres both provide `CHAR` and `VARCHAR` types, as expected. However, MSSQL does not accept `CLOB` as a data type, as it does not provide a separate type for large character objects. Instead, it uses the syntax `VARCHAR(max)` to provide similar functionality. The `CLOB` equivalent in Postgres goes under the type name `TEXT`, and Postgres does not accept `CLOB` as a synonym. Information on all data types described (including their ranges and size) is available in Table 1.

2.2 Indexes

Despite not being strictly defined in the SQL standard, indexes comprise a significant portion of the design stage of schema creation. They provide necessary optimizations and are frequently used by internal DBMS operations. However, this lack of a specification by the SQL standard does not necessarily mean that their implementations differ greatly. Rather, both DBMSs implement indexes in a relatively similar manner. Apart from some syntactical differences, the creation and behavior of indexes in both DBMSs is similar. Both MSSQL and Postgres allow the creation of clustered and non-clustered indexes. They both also allow the type of index to be specified. MSSQL does this through the characteristics of the index that was created, while Postgres allows this to be manually set. Changing the type of index affects the data structures and algorithms associated with each index [2§Types of Indexes; 4§11.2]. Since they have similar implementation, most indexes can be designed without needing much modification when moving from one DBMS to the other. Some issues arise when needing to create special kinds of indexes. The three kinds of indexes that we focus on are indexes with included columns, filtered indexes, and indexes on expressions.

Included Columns: Indexes with included columns are indexes where in addition to the key attributes (or expressions, as we discuss later), one or more columns are also included and stored with the index. However, these extra columns are not used to organize the index, making them non-key columns in relation to the index. By adding included columns, a well-designed index can eliminate the need for reading data pages for a significant portion of the workload, greatly improving performance for queries that benefit from this covering index. In MSSQL this is performed by adding the `INCLUDE` keyword after the table that the index is created on, followed by the desired included columns in parenthesis, as in figure 1a. [2§Index w Included Columns]. Adding a column in this manner is less computationally expensive than adding it as a key column for the index. Since the index is not sorted or managed in relation to these columns, queries that only involve included columns, and not the non-key columns, will not see a performance benefit due to the index. Although Postgres does support indexes with more than one column, it does not support adding included columns in this manner. Instead, they must be added as key columns for the index (figure 1b) [4§11.3]. This reduces the net benefit of indexes with multiple columns.

```
CREATE NONCLUSTERED INDEX
    IX_dog_arrivalDate
ON dog (arrival_date)
INCLUDE (name, breed)
WHERE arrival_date > '2010-01-01';
```

Figure 1a. Creating a filtered index with included columns (MSSQL)

```
CREATE INDEX IX_dog_arrivDate
ON dog (arrival_date, name, breed)
WHERE arrival_date > '2010-01-01';
```

Figure 1b. Creating a filtered multi-column index (Postgres)

Filtered Indexes: These indexes do not include all rows of the table that they are indexing. Instead, they only contain a portion of the table. This reduces the size and overhead of the index, since they can be designed to only include rows that are frequently targeted by queries. The rows in the index are selected through the value of a specified conditional statement. Both MSSQL [2§Create Filtered Indexes] and Postgres [4§11.8] implement filtered indexes in an identical manner. In both DBMSs, they are created by adding a `WHERE` keyword, followed by a conditional statement. Figure 1a and 1b show a filtered index being created.

Indexing on Expressions: The final kind of index that we identify are indexes on expressions. In addition to indexing on the columns of a table, indexes can also be created on expressions which involve the columns of a table. These are particularly useful for queries that involve sorting or grouping by an expression, especially if the expression in question is computationally expensive and frequently used. Although MSSQL supports indexes on expressions, they must be defined indirectly through computed columns (see section 2.3) in the base table [2§Indexes on Computed Columns]. After creating the computed column on the base table, the index should then be created or extended to include that computed column. Postgres instead allows expressions to be declared directly alongside regular columns when creating or altering the index [4§11.7].

2.3 Computed Columns

Computed columns are a way of representing the results of an expression as an attribute of a table, rather than needing to use the

expression in every related query. This process is not explicitly covered by the SQL standard. MSSQL offers this functionality, while Postgres does not. The simplest way to obtain similar, although not identical, functionality in Postgres is to use a view. If it is not possible or desirable to use a view, then there is also a method to perform this by using a row level trigger on a column which users do not have INSERT or UPDATE permissions of. A shortened example from the Babysitting schema where we implemented a computed column in both DBMSs (by using a view in Postgres) is provided in Figure 2a and Figure 2b.

In Postgres, any expression that would normally be permitted as a part of a SELECT statement on the underlying table can be used. MSSQL also allows any expression, so long as it is not a subquery. As a result, computed columns are only allowed to reference the columns of the table where it resides, and not those of other tables. In MSSQL, certain expressions may limit the ability to use the computed column in a similar manner to a regular (non-computed) column.

When using a view to replace a computed column, no special considerations are necessary and it functions like any other view. In contrast, while MSSQL's implementation may be easier to set up, since it does not require the use of a view, it carries more considerations compared to Postgres' implementation. These considerations are needed because the computed column cannot be used the same way that a regular column can in certain situations.

```
CREATE TABLE mssql_test (
    SID INTEGER PRIMARY KEY
    SStart DATETIME2,
    SFinish DATETIME2,
    SLength AS (ROUND(DATEDIFF(mi, SStart,
        SFinish)/ 60.0, 0)) );
```

Figure 2a. Implementing a computed column in MSSQL

```
CREATE TABLE pg_test_tab (
    SID INTEGER PRIMARY KEY,
    SStart TIMESTAMP,
    SFinish TIMESTAMP );

CREATE VIEW pg_test_view AS (
    SELECT SID, SStart, SFinish,
        (SFinish - SStart) as SLength
    FROM pg_test_tab );
```

Figure 2b. Implementing a computed column in Postgres

For instance, these computed columns cannot be modified directly though INSERT or UPDATE statements (though it will be updated as needed if the value of the expression changes). There are additional considerations when placing constraints on the column, or using it as a foreign key. It is also important to note that by default, the computed column is a virtual column, and as a result, the values are not stored. This can be changed by marking the column as PERSISTED [2§Specify Computed Columns].

2.4 Querying Metadata

Both DBMSs have at least partial support for the INFORMATION_SCHEMA. INFORMATION_SCHEMA is a set of views that contain metadata related to individual objects in the database. In our survey, we focused on views that contain metadata

about tables and columns. For example, the INFORMATION_SCHEMA.COLUMNS view includes the name, data type, and maximum allowed length of each column in every table (Figure 3). This query works in both T-SQL and pgSQL, as they both implement the view INFORMATION_SCHEMA.COLUMNS.

```
SELECT column_name, data_type,
    character_maximum_length
FROM INFORMATION_SCHEMA.COLUMNS
WHERE table_name = 'advertiser_t';
```

Figure 3. A simple INFORMATION_SCHEMA query (Advert)

A more complex query allows us to find the column name, table name, and constraint name of every foreign key constraint in the database (Figure 4). This query also works in both T-SQL and pgSQL, and is schema independent.

```
SELECT t.TABLE_NAME, c.COLUMN_NAME,
    c.CONSTRAINT_NAME
FROM
    INFORMATION_SCHEMA.TABLE_CONSTRAINTS t
JOIN
    INFORMATION_SCHEMA.CONSTRAINT_COLUMN_USAGE
    c
ON t.CONSTRAINT_NAME = c.CONSTRAINT_NAME
WHERE CONSTRAINT_TYPE = 'FOREIGN KEY';
```

Figure 4. A more complex INFORMATION_SCHEMA query

While both MSSQL and Postgres support the INFORMATION_SCHEMA, Postgres' support is much more complete. There are 63 views defined in the SQL standard [1§22]. MSSQL only implements 20 of these views, while Postgres implements all 63 [2§Information Schema; 4§35]. One specific example is that MSSQL lacks the INFORMATION_SCHEMA.USAGE_PRIVILEGES view. Instead, the sys.database_permissions table contains similar information. The documentation for both DBMSs notes that all DBMS specific metadata is stored in the system catalog. Additionally, Microsoft's documentation warns against using INFORMATION_SCHEMA as a way to reliably determine the schema of a table [2§COLUMNS].

2.5 Views

Materialized Views: Materialized views are the results of a query stored on the disk as an object in the database. This is in contrast with a non-materialized view, which is completely virtual and not stored. Another difference is that a materialized view is not necessarily kept up-to-date with the data that it originated from. MSSQL supports this indirectly, while Postgres uses a direct syntax. In order to implement what is similar to a materialized view in MSSQL, a unique clustered index must first be created on a view. These are referred to as Indexed Views [2§Create Indexed Views]. In Postgres, a materialized view is created with a CREATE MATERIALIZED VIEW clause, which is then followed by the appropriate subquery [4§39.3]. Along with being created in a different manner, the two differ in that the MSSQL implementation keeps the information up-to-date with the original data. In Postgres, materialized views need to be updated with REFRESH MATERIALIZED VIEW whenever necessary. If the information

should not be kept up to date, then it is always possible to create a new table in the database using the `CREATE TABLE AS` syntax.

Updateable Views: Both T-SQL and pgSQL support updateable views with some limitations. Views that only `SELECT` data from one source table and have no computed columns are updateable in both DBMSs [2§CREATE VIEW,3§VI.I]. For example, the view `ADVERTISER` in the `Advert` schema is updateable because it only selects data from the `ADVERTISER_T` table. The query in figure 5a will insert a new row into the `ADVERTISER_T` table, then update and delete the row through the `ADVERTISER` view.

Views defined using a `JOIN` have less ability to be updated. T-SQL is able to perform `UPDATE` statements on these views, while pgSQL will fail with an error message. Neither implementation is able to `DELETE` from these views.

```
INSERT INTO ADVERTISER_T VALUES (2,0,0);
UPDATE ADVERTISER
SET advertiser_id = 3
WHERE advertiser_id = 2;
DELETE FROM ADVERTISER
WHERE advertiser_id = 3;
```

Figure 5a. An example of using an updateable view (Advert)

```
UPDATE INVOICE
SET invoice_date = '2017-02-01';

DELETE FROM INVOICE
WHERE ad_id = 0;
```

Figure 5b. Example of a query updating the INVOICE view, defined with a JOIN statement (Advert)

Figure 5b demonstrates performing `UPDATE` and `DELETE` statements on the view `INVOICE`, which is defined using two `JOIN` statements. The `UPDATE` in this query will succeed in T-SQL, but fail in pgSQL. The `DELETE` will fail on both DBMSs.

The documentation for both DBMSs goes into additional detail on the limitations of updateable views. The limitations in T-SQL are based on how the column being updated is derived. Any `INSERT`, `UPDATE`, or `DELETE` statement on a view can only modify columns that are derived from a single base table. Additionally, the column definition cannot include any aggregate functions [2§CREATE VIEW]. For example, T-SQL is unable to update the `fully_paid` column in the `INVOICE` view (Figure 6).

```
UPDATE INVOICE
SET fully_paid = 0;
```

Figure 6. Example query that updates a column in INVOICE derived from multiple tables (Advert)

By comparison, pgSQL's updateable views are more limited. The same qualities that make a view not updateable in T-SQL apply to pgSQL. However, pgSQL makes the entire view not updateable, instead of just the offending column [4§VI.I].

2.6 Designing DML Triggers

Both DBMSs support the execution of triggers when DML statements are evaluated. MSSQL refers to these as DML triggers, while Postgres refers to them as regular triggers. Both MSSQL and Postgres execute these triggers in the context of a single database.

The trigger implementations in both DBMSs only support a subset of the standard. MSSQL does not support row-level triggers, which deviates from the standard [1§11.3; 2§CREATE TRIGGER]. Neither MSSQL nor Postgres support the `REFERENCING` clause for specifying an alias for new or old rows [1§11.3]. MSSQL provides two tables, `inserted` and `deleted`, which contain any rows that were inserted or deleted by the triggering statement [2§CREATE TRIGGER]. This also allows statement level triggers to act on a row level basis. Postgres provides the aliases `NEW` and `OLD`, which refer to the new and changed rows, respectively [3§I.]. Postgres also requires that the trigger only execute a single, user-defined function, which deviates from the standard [4§I.]. In practice, however, this is easily overcome by having the function execute any needed statements. Figures 7a and 7b present a DML trigger in each DBMS. Note that the MSSQL trigger is able to operate on all deleted rows in a statement-level trigger using the `deleted` table, and Figure 7b contains both the trigger and function definitions.

```
CREATE OR ALTER TRIGGER
delete_ad_runs_trigger
ON ad
INSTEAD OF DELETE
AS
BEGIN
    DELETE FROM ad_run
    WHERE ad_id = ANY(SELECT ad_id FROM
deleted);
    DELETE FROM payment
    WHERE ad_id = ANY(SELECT ad_id FROM
deleted);
    DELETE FROM invoice_t
    WHERE ad_id = ANY(SELECT ad_id FROM
deleted);
    DELETE FROM ad
    WHERE ad_id = ANY(SELECT ad_id FROM
deleted);
END
```

Figure 7a. DDL trigger example in MSSQL

```
CREATE OR REPLACE FUNCTION delete_ad_runs()
RETURNS trigger AS
$BODY$
BEGIN
    DELETE FROM ad_run WHERE ad_id =
OLD.ad_id;
    DELETE FROM payment WHERE ad_id =
OLD.ad_id;
    DELETE FROM invoice_t WHERE ad_id =
OLD.ad_id;
    RETURN OLD;
END;
$BODY$
LANGUAGE plpgsql;
```

```
CREATE TRIGGER delete_ad_runs_trigger
BEFORE DELETE
ON ad_t
FOR EACH ROW
EXECUTE PROCEDURE delete_ad_runs();
```

Figure 7b. Regular trigger example in Postgres

3. DEVELOPMENT ACTIVITIES

The development activities we identified concern the SQL implementation in each DBMS. T-SQL and pgSQL have many differences that require modified SQL code for the same effect in each implementation.

3.1 Common Table Expressions

Both T-SQL and pgSQL support common table expressions using the `WITH` clause. For non-recursive statements, the two implementations are functionally identical.

However, the syntax for recursive `WITH` statements differs. T-SQL will evaluate any `WITH` statement recursively, as long as the code is recursive. pgSQL will only evaluate a `WITH` statement recursively if the `RECURSIVE` clause is included. Requiring the `RECURSIVE` clause is consistent with the SQL standard [1§9.13]. Figures 8a and 8b demonstrate a recursive `WITH` statement in both implementations.

```
WITH expanded AS (
SELECT NEW.ad_id, NEW.start_date,
CAST(NEW.num_issues AS int) ni
UNION ALL
SELECT ad_id, start_date, ni - 1
FROM expanded
WHERE ni > 1)
```

Figure 8a. Recursive WITH example (T-SQL)

```
WITH RECURSIVE expanded AS (
SELECT NEW.ad_id, NEW.start_date,
CAST(NEW.num_issues AS int) ni
UNION ALL
SELECT ad_id, start_date, ni - 1
FROM expanded
WHERE ni > 1)
```

Figure 8b. Recursive WITH example (pgSQL)

3.2 Query Batch Execution

T-SQL and pgSQL interpret queries that have been sent through a client interface differently. T-SQL interprets incoming queries in batches. Microsoft defines a query batch as, “a group of two or more SQL statements or a single SQL statement that has the same effect as a group of two or more SQL statements,” [2§Batches]. Postgres does not have a similar construct, and all queries are essentially evaluated in their own batches.

Thus, when working in an interface such as MSSQL Management Studio, the DBMS interprets any script that results in the execution of two or more SQL statements as a query batch. T-SQL imposes several limitations on what groupings of statements can be in a single batch. The following statements must be executed in their own batch: `CREATE DEFAULT`, `CREATE FUNCTION`, `CREATE PROCEDURE`, `CREATE RULE`, `CREATE SCHEMA`,

`CREATE TRIGGER`, `CREATE VIEW`. Additionally, columns added or modified using an `ALTER TABLE` statement may not be referenced by other queries in the same batch [2§Batches].

T-SQL does not provide a native statement for explicitly separating a SQL script into multiple batches. To achieve this, Microsoft’s client programs implement the `GO` command [2§GO]. When the program encounters a `GO` command, it sends all preceding commands in their own batch, and begins sending all following queries in a new batch. This allows a single SQL script to execute multiple statements that would not be allowed in the same batch.

3.3 Text Matching

Despite being a common task, the SQL standard does not define advanced support for text matching beyond two simple wildcard characters and case sensitivity. Both T-SQL and pgSQL provide full support for the two wildcards, with the only difference between the two being that T-SQL is case insensitive when using the `LIKE` keyword, and does not provide a simple method to make the matching case sensitive. pgSQL instead defaults to being case sensitive, which can be disabled through the use of the `ILIKE` keyword. However, since these facilities are not sufficient for all purposes, both implementations provide extended functionality for text matching through the use of regular expressions. In T-SQL, these expressions still use the `LIKE` keyword. With these expressions, a single character can be matched to be in or not in a specific range or set of characters [2§Pattern Matching]. pgSQL provides different extensions to text matching. Additional metacharacters, for example “{n}” which marks the repetition of the previous character n times and |, which provides the ability to match either of two values, can be used with the `SIMILAR TO` and `NOT SIMILAR TO` keywords. Finally, pgSQL also provide full support of POSIX regular expressions with the `~`, `!~`, `~*`, and `!~*` operators, depending on whether it should be case sensitive or not, and whether it should be identifying a match or mis-match [3§9.7].

3.4 Performance Optimization

Both DBMSs use a cost based system for determining the best execution plan for a query [2§Hints ,3§I.]. The DBMS selects a set of operations that perform the requested query with the lowest calculated cost. The documentation for both states that the DBMS generally selects the best plan, and advise against manually making changes to the plan [2§Hints ,3§I.]. Despite this, both DBMSs provide facilities for optimizing query performance, however, their approaches differ significantly.

MSSQL provides query hints and table hints, which allow the developer to modify the behavior of the query optimizer. Query hints are added in an additional clause to a query, and are only applied to that query. There are several distinct areas of behavior that hints allow you to modify. The `JOIN`, `UNION`, and `GROUP` hints force the optimizer to generate a plan with a specific method of performing `JOINS`, `UNIONS`, and `GROUP BYs`. The `MAXDOP` hint forces the optimizer to generate a plan with a certain maximum degree of parallelism. Similarly, `MAXRECURSION` specifies the maximum number of recursive calls the query can perform. The `OPTIMIZE FOR` hint allows a value for one or more variables to be supplied to the optimizer. It will use these values to generate the query plan, instead of the values that will be used in the query execution. There are also several miscellaneous hints that allow certain query optimizer features to be forced on or disabled.

Query hints also include a subset called table hints, which are applied to a single table in a query. These can force a specific index

be used when accessing that table, or modify how the query plan will access the table.

MSSQL provides an additional tool for optimizing performance called Plan Guides. Plan guides force the query optimizer to behave a certain way when it encounters a specific query text [2§Plan Guides]. This is useful in a situation where the exact text of a query cannot be changed, such as when an external application is issuing the query. Plan guides are created using the `sp_create_plan_guide` stored procedure, which is provided the query text to match and the query hints that should be applied to it. Guides can only be scoped to a single database, so only plans from the current database a query is executing from are eligible to be applied to the query [2§Plan Guides].

MSSQL also provides an additional form of plan guides, template plan guide. These allow a plan guide to be applied to any query text that can be parameterized to a certain query, even if the text does not match exactly [2§Create a Plan Guide for Parameterized Queries]. Template plan guides are created by first using `sp_get_query_template` to get the template for the desired query, and then using `sp_create_plan_guide` with the parameterized template.

Postgres provides a very different method for performance optimization. There is no facility provided for changing the behavior of the planner on a query by query basis. Instead, Postgres exposes many parameters to change the overall behavior of the planner [4§19.7]. Two types of configuration options are exposed, method configurations and cost constants. Method configurations allow the user to disable certain query execution operations, similar to MSSQL's query hints. Unlike query hints, these options apply to all plans generated by the query planner. The Postgres documentation warns that these options are not intended to be permanent solutions, rather they should only be used for performance testing [4§19.7].

For permanent changes to the planner's behavior, Postgres provides cost constants. These allows the user to set the cost for different internal database operations, which can cause the planner to select different plans.

3.5 Dynamic SQL

Both DBMSs support executing a dynamically constructed string as a SQL query. MSSQL provides the `EXEC` statement and `sp_executesql` stored procedure to accomplish this. `EXEC` will compile and execute a statement string at runtime, while `sp_executesql` will take a parameterized query string and the relevant parameters, construct the final query, and then execute it.

```
DECLARE @query_text NVARCHAR(MAX);
SET @query_text = '';

SELECT @query_text += 'SELECT * FROM ' +
table_name + ';';
FROM INFORMATION_SCHEMA.TABLES;

EXEC(@query_text);
```

Figure 9. Example of dynamic SQL in MSSQL (Advert)

Postgres also supports executing dynamic SQL using the `EXECUTE` statement. Additionally, the `format()` function can be used to construct a parameterized query, similar to `sp_executesql`. `EXECUTE` can only be used to perform a dynamic query in a PL/pgSQL context. If the query is expected to

return a single value, the syntax `EXECUTE <query>; INTO <var>;` can be used to directly place the result of the query into a variable.

The requirement of executing dynamic SQL in PL/pgSQL contexts can complicate certain queries. For example, the query in figure 9 can be implemented in PL/pgSQL, as shown in figure 10. However, the output from the query cannot be easily displayed, because any output from a PL/pgSQL code block must be explicitly returned. Data cannot be arbitrarily `SELECT`d to show up in the console output. This query outputs the text of the generated query for demonstration purposes. Note that although the dynamic query is executed, the output is discarded.

```
DO $$
DECLARE
    query TEXT;
BEGIN
    SELECT string_agg('
        SELECT * FROM ' || table_name, ';' )
    INTO query
    FROM INFORMATION_SCHEMA.TABLES
    WHERE table_schema='public'
    AND NOT table_name = '';

    EXECUTE(query);

    RAISE NOTICE 'Query to select from all tables
in database: %I', query;
END$$;
```

Figure 10. Example of dynamic SQL in PL/pgSQL (Advert)

3.6 Miscellaneous Activities

We also identified several minor activities related to development. While these do not represent the most important differences, they should be kept in mind during a schema migration process.

Date Arithmetic: T-SQL and pgSQL provide different facilities for date arithmetic. T-SQL provides non-standard functions for performing date arithmetic, including `DATEADD()` and `DATEDIFF()` [2§Date and Time]. These functions take a date interval, such as day, and two `DATETIME` values and return the sum or difference of the two dates (Figure 11a). pgSQL follows the standard, and allows for date arithmetic using normal arithmetic operators. Figure 11b performs the same query as figure 11a in Postgres [4§8.5]. Note that `DATEDIFF` subtracts the first input value from the second, whereas pgSQL's arithmetic operator subtracts the second operand from the first.

```
SELECT DATEDIFF(day,
    (SELECT MIN(issue_date) first_issue
    FROM AD_RUN
    WHERE ad_id = 0),
    (SELECT MAX(issue_date) last_issue
    FROM AD_RUN
    WHERE ad_id = 0)) + 1 run_length;
```

Figure 11a. Example of DATEDIFF() (Advert)

```

SELECT
  (SELECT MAX(issue_date) first_issue
   FROM AD_RUN
   WHERE ad_id = 0) -
  (SELECT MIN(issue_date) last_issue
   FROM AD_RUN
   WHERE ad_id = 0) + 1 run_length;

```

Figure 11b. Example of pgSQL date arithmetic syntax (Advert)

Expressions in ORDER BY and GROUP BY: Both T-SQL and pgSQL allow an identical set of expressions to be a part of an ORDER BY or GROUP BY clause. If an expression uses a function, it must be a scalar function that performs an identical action to every value that is queried. As a part of the Babysitting schema, we were asked to query a list of birthdates and addresses, sorted by day of the year, in order to create a birthday mailing list. In order to perform the sorting, we used an expression in the ORDER BY clause that would sort the list by only the month and day parts of a date. Both the T-SQL and pgSQL implementations used a single function to extract these date parts. However, they used different functions due to differences in the functions available to manipulate dates.

TRIM Functions: Postgres provides a TRIM() function. T-SQL does not implement a function called TRIM(). Instead it implements LTRIM() and RTRIM(), which remove whitespace from the left and right sides of a string, respectively. When used together, they are effectively the same as TRIM().

T-SQL Stored Procedure Library: T-SQL provides several built-in stored procedures for retrieving metadata from the system catalog. In particular, we discovered sp_columns when looking for a replacement for Oracle's DESCRIBE statement. sp_columns returns metadata about a table's columns, similar to the INFORMATION_SCHEMA query in (Figure 3). Since T-SQL does not fully support INFORMATION_SCHEMA, sp_columns allows easy access to column metadata stored in the system catalog. Several other stored procedures with similar functionality are provided, such as sp_tables [2\$sp_columns].

SELECT Without FROM: Another development activity we identified was using a SELECT statement to select data not inside the database. This feature is commonly used as a way to output text from a query without necessarily accessing data inside the database. Both T-SQL and pgSQL accomplish this using SELECT statements without a WHERE clause. This allows a query to output data that is not inside the DBMS.

Type Casting and Conversion: Since SQL is a strongly typed language, both T-SQL and pgSQL provide facilities to convert between variable types. T-SQL provides the CAST and CONVERT statements for explicitly converting between data types. CAST provides the SQL standard facility for type conversion, using the syntax CAST(<var> AS <type>). T-SQL will try to convert the supplied value to the requested data type, and throw an exception if the types are incompatible. CONVERT behaves similarly, and provides additional facilities for how the cast should be performed. For example, CONVERT can cast a FLOAT number into a VARCHAR with commas and a fixed fractional precision. T-SQL also provides TRY_CAST and TRY_CONVERT, which return NULL if the cast cannot be performed, instead of an exception. Additionally, the MSDN documentation provides a table of which

data types can be implicitly converted, explicitly converted, or are incompatible [2\$CAST and CONVERT].

Postgres also provides the CAST statement for type conversion, with the same syntax. pgSQL will also attempt to implicitly convert types when necessary. It will first find if the operator or function has a version that matches the input type or types. If not, it will attempt to convert one or more of the input values to a compatible type. If one or more of the input values still does not match the required values, an exception is thrown. The same process is followed when attempting to insert values into a table [4\$10.1].

Grouping Sets: The final minor development activity we found was advanced grouping through the use of GROUPING SETS, including the two shorthands for common grouping sets: CUBE and ROLLUP. Grouping by a grouping set runs the SELECT expression on each column/expression in the grouping set, outputting the results for each element of the grouping set. This is an important feature because it allows this grouping to be performed with a single query, rather than relying on several UNION ALLs. Despite not being defined in the SQL standard, these are all implemented similarly in both T-SQL[2\$Using GROUP BY with ROLLUP...] and pgSQL[4\$7.2].

4. ADMINISTRATION ACTIVITIES

Administration activities are those which involve the operations and maintenance of the DBMS, rather than those which deal with data modeling or querying. As we were only dealing with a single user and did not need to perform any maintenance on the systems, our experience with administration activities is limited to those involved during the setup of both DBMSs on our machines. Other administration activities include those performed via the Data Control Language (DCL) component of SQL, and other management and optimization activities.

4.1 Environment Setup

Installation of both DBMSs was rather straightforward. Both DBMSs were installed on machines running Windows. (See section 1.2 for the specific versions of each DBMS used.) MSSQL only provides a single installer [3], whereas Postgres' website provides two installers. One is an "Interactive installer" provided by EnterpriseDB, and the other is a "Graphical installer" provided by BigSQL [6]. We found that the Interactive Installer required additional configuration if command line access using the included psql tool was desired. However, no other configuration was needed in either distribution if the graphical pgAdmin tool was used. Finally, since Postgres is open source, there is also the option to create an individual or custom build of the software.

While both DBMSs can have all administration activities performed via a command line interface, MSSQL's packaged graphical interface, SQL Server Management Studio (SSMS), is also able to perform all of these activities. However, the graphical interface that is usually packaged with Postgres (pgAdmin) cannot perform all available administration activities. This tool is a separate community project, not maintained by the same group that manages the Postgres DBMS. Additionally, it has recently undergone a complete rewrite, as such, some issues are bound to arise. However, these issues are actively being worked on, and the latest two versions (v1.3 and v1.4) contain over 60 combined bug fixes.

4.2 DDL and Server Level Triggers

Both DBMSs support triggers that execute when DDL statements are performed. MSSQL refers to these as DDL triggers, while

Postgres refers to them as event triggers. MSSQL can execute DDL triggers in the context of a single database, or the entire server. Event triggers can only be executed in the context of a database in Postgres.

Since these triggers are commonly used for logging, it is important that they can be executed with the correct permissions. MSSQL allows an `EXECUTE AS` clause in a DDL trigger definition. This causes the trigger procedure to be executed with different permissions than the user causing the trigger to execute. There are three permission types `EXECUTE AS` can use: `CALLER`, `SELF`, or `<user name> [2$EXECUTE AS]`. `CALLER` executes the trigger with the same permissions as the executing user. `SELF` executes the trigger with the same permissions as the trigger owner. Additionally, a login name of the user the trigger will execute as can be provided.

Postgres provides similar functionality with the `SECURITY` clause [4\$I.]. Since Postgres triggers always execute a user-defined function, the execution permissions are set on the function itself, not the trigger. There are two forms of the `SECURITY` clause, `SECURITY DEFINER` and `SECURITY CALLER`. `SECURITY DEFINER` executes the function with the permissions of the defining user, while `SECURITY CALLER` executes with the permissions of the executer.

MSSQL also supports logon triggers. These are similar to DDL triggers, but are only executed when a user logs on to the database, and can only be executed in the context of the whole server. Logon triggers support the same permissions mentioned previously. Postgres does not provide any functionality similar to a logon trigger.

4.3 Users and Roles

Although the SQL standard gives an outline of how a security and permissions system should be implemented, it leaves the separation between roles (groups) and users (authorization identifiers) up to be implementation defined. MSSQL provides a clear separation between groups and users, while Postgres merges them both into the same model (roles). As such, the concept of roles are different in the two DBMSs. In MSSQL, roles always refer to groups, whereas in Postgres, they may refer to either users or groups. MSSQL also provides integration with Windows accounts, allowing an easier infrastructure setup for organizations who already have a Microsoft Windows domain and organizational system in place. Another difference between the two is that MSSQL requires the creation of a login, which is based at the server level. Following that, logins can then be assigned to users (one login per user per database) [2\$Server and Database Roles...]. Postgres does not separate the two, instead, it uses a `LOGIN` attribute to allow a role to connect to the database. The presence or lack thereof can be seen as the equivalent of the separation between users and groups. Other role settings which are based at the server level (such as the maximum number of connections) are also done using attributes when creating or altering a role [4\$21.2]. The process of creating users is explored through the Classroom scenario. An example of creating a student and an instructor can be seen in figure 12a and 12b. In the actual implementation of this scenario, these processes can be performed using stored procedures, rather than the exact statements in these two examples.

4.4 Execution Permissions

Although a user with administrative or superuser rights is able to perform most management tasks without needing to switch roles, it is sometimes necessary to do so.

```
CREATE ROLE CS205F17Student;
CREATE ROLE CS205F17Instructor;

CREATE USER [WCSU\Students\Ramsey033];
ALTER ROLE CS205F17Student ADD MEMBER
[WCSU\Students\Ramsey033];

CREATE SCHEMA ramsey033 GRANT SELECT,
INSERT, DELETE, UPDATE;
GRANT SELECT ON SCHEMA ramsey033 TO
CS205F17Instructor;
```

Figure 12a. Creating a student user based on a windows account (MSSQL)

```
CREATE ROLE CS205F17Student;
CREATE ROLE CS205F17Instructor;

CREATE USER ramsey033 PASSWORD '50045123';
CREATE USER westP PASSWORD '123999888';

GRANT CS205F17Student TO ramsey003;
GRANT CS205F17Instructor TO westP;

CREATE SCHEMA ramsey003;
GRANT ALL PRIVILEGES ON SCHEMA ramsey003 TO
ramsey003;
GRANT USAGE ON SCHEMA ramsey003 TO
cs205f17instructor;
```

Figure 12b. Example of creating a student user (Postgres)

More frequently, different permissions or restrictions are needed when executing a procedure, or when a procedure needs to impersonate another role in the database. Another reason to switch execution permissions is to follow the least privilege principle, so users and applications will run with the minimum permissions necessary, and only switch to a role with greater permissions when needed. Both MSSQL and Postgres provide methods of doing so. In MSSQL, the `EXECUTE AS <user>` statement allows this [2\$EXECUTE AS], and Postgres permits this with the `SET SESSION AUTHORIZATION <role>` statement [4\$SET SESSION AUTHORIZATION]. Both implementations also provide methods of returning to the previous user, with the `REVERT` statement in MSSQL, and `RESET SESSION AUTHORIZATION` in Postgres. With Postgres, it is also possible to return to the default role rather than simply resetting by using `DEFAULT SESSION AUTHORIZATION`. This may or may not be the same role that was being used prior to changing the session authorization. Postgres also allows the ability to only change the current role, and not the current session, through the `SET ROLE <role>` statement, and its correspondent `RESET ROLE`. Different privilege checks are run depending on whether a session or a role is being switched. Also, switching sessions changes the available roles that can be switched to. This Postgres implementation is in line with the statements that the SQL standard recommends [1\$14.5]. Both implementations also allow switching sessions (along with roles in Postgres) during a transaction, despite being a restriction suggested by the SQL standard.

4.5 Stored Procedures

MSSQL supports separate stored procedures and functions, while Postgres implements stored procedures as a subset of functions [2§CREATE PROCEDURE, 4§4.1.1]. In MSSQL, functions are intended to perform an atomic set of operations on an input to provide some output, while stored procedures may execute several T-SQL statements in one or more transactions. Stored procedures do support input and output parameters, while functions support input parameters and return values. Stored procedures may call functions, or perform any other T-SQL statements. Functions may not call stored procedures, however, because a function must be an atomic operation, and a stored procedure may perform multiple transactions.

Postgres implements stored procedures as a special case of a function. Stored procedures are functions that have no return statement, and thus can't be used in an expression. Both are created using the CREATE FUNCTION statement. While both can contain many pgSQL statements, all functions are treated as atomic, so stored procedures can only use a single transaction.

Language Support: MSSQL currently only allows T-SQL statements, or Microsoft .NET Framework common runtime language methods to be run in stored procedures [2§Stored Procedures (DB Engine)], whereas Postgres allows the execution of any language that has been implemented to run in Postgres, including C and R. However, some support for the R programming language is available through an alternate framework [2§SQL Server R Services]. Additionally, it has been recently announced that a newer version of MSSQL (SQL Server 2017) adds support for the Python programming language [7].

4.6 Error Handling

The final administrative activity we identified was dealing with exceptional situations during the execution of stored procedures. MSSQL's implementation follows the TRY...CATCH and THROW convention familiar to most computer programmers. If any execution error with a severity that is greater than 10 occurs during the processing of statements in the try block, control is passed to the catch block. [2§TRY...CATCH]. Although Postgres does not implement these TRY...CATCH blocks, the EXCEPTION keyword provides similar functionality. The EXCEPTION keyword can be used once in each BEGIN block (typically towards the end of the block). If an error occurs during the execution of a stored procedure, execution is moved to the statements following the EXCEPTION keyword. Here, conditions can be checked, followed by statements that can appropriately handle the exceptional circumstances [4§33.8].

5. SUMMARY

Our survey found many similarities and differences between MSSQL and Postgres. Both DBMSs supported the majority of activities we identified. The most glaring incompatibilities we found between the two DBMSs were MSSQL's partial INFORMATION_SCHEMA support, and Postgres' lack of computed columns, advanced indexing, and per-query optimization.

Standards Compliance: MSSQL is clearly less standards compliant than Postgres. MSSQL showed major deviations, such as its lack of support for the complete INFORMATION_SCHEMA, and minor deviations, such as allowing recursive CTEs without explicit declaration. While Postgres is largely standards compliant, there are several areas where both DBMSs deviate. For example, both DBMSs deviate in their implementation of the CLOB data

type. MSSQL uses a different syntax for performing the same functionality, while Postgres uses a different name.

Despite being largely standards-compliant, we still identified many differences between both DBMSs. The SQL standard primarily dictates features a DBMS must support. It often does not place strict limitations on the behavior of such features. One example is the difference in fractional exact numerical data type ranges, as the standard does not define what they must be. For example, Postgres supported a greatly expanded range for date data types. Another example is that the SQL standard requires support for views, but it does not define any requirements for the behavior of updatable views [1§4.3]. This allows for the differences we observed between the MSSQL and Postgres implementations of updatable views.

This also allows both DBMSs to implement extended features that are not defined in the standard. Postgres' extensible native language support is an example of one such feature. Many of MSSQL's deviations from the standard are used to provide an extended feature set. For example, included columns and query hints are not defined in the standard, however these are features that are clearly useful for many applications. The clear disadvantage to these features is that they are not defined in the standard. Therefore, an application depending on them becomes locked to platforms that support the required non-standard features.

| Activity | MSSQL | Postgres |
|--------------------------------------|-----------|-----------|
| Design | | |
| Standard Field Types | 2 | 2 |
| Querying Metadata | 1 | 2 |
| Native Computed Columns | 2 | 0 |
| Updatable Views | 2 | 2 |
| Materialized Views | 1 | 2 |
| DML Triggers | 2 | 2 |
| Included Columns in Indexes | 2 | 0 |
| Filtered Indexes | 2 | 2 |
| Expressions in Indexes | 1 | 2 |
| Development | | |
| Common Table Expressions | 2 | 2 |
| Unrestricted Query Batches | 0 | 2 |
| Extended Text Matching | 1 | 2 |
| Dynamic SQL | 2 | 2 |
| Query Hints | 2 | 0 |
| Grouping Sets | 2 | 2 |
| Expressions in ORDER BY and GROUP BY | 2 | 2 |
| Standard Type Casting | 2 | 2 |
| Administration | | |
| DDL Triggers | 2 | 2 |
| Server Level Triggers | 2 | 0 |
| Role-Based Access Control | 2 | 2 |
| Execution Permissions | 2 | 2 |
| Full Linux Support | 0 | 2 |
| Stored Procedures | 2 | 1 |
| User Defined Exceptions | 2 | 2 |
| Plan Guides | 2 | 0 |
| Native Language Extensibility | 0 | 2 |
| Total | 42 | 41 |

Table 2. Summary of support for each identified activity

Conclusions: One conclusion that can be drawn from these differences is that standards compliant SQL code is not necessarily portable or optimal. While many of the differences shown may individually be minor, their sum can make schema migration difficult. For example, a schema that heavily relies on computed columns or updatable views may be difficult to migrate to Postgres, despite being otherwise standards-compliant. Likewise, a schema that relies on `INFORMATION_SCHEMA` may be difficult to migrate to MSSQL, and may require the use of non-standard features.

To help gauge the overall level of support both DBMSs showed for the activities we studied, we assigned a score for each activity based on the level of support the DBMS had for that activity. A score of two indicates complete, and, if possible, standards compliant support for that activity. A score of one indicates partial or non-standard support for that activity. A score of zero indicates no support for that activity. The score for each activity, as well as the total score for each DBMS can be seen in table 2.

The highest possible score was 52 points, a score of two in each of the 26 activities. MSSQL score slightly higher than Postgres, at 42 points compared to 41. This indicates that overall, both DBMSs had a high level of support for the activities we studied. When MSSQL did not have full support for an activity, it tended to have partial or non-standard support. This is shown by its four scores of one compared to only two of zero. Conversely, Postgres tended to have no support instead of partial support, as evidenced by five scores of zero and only a single score of one. This points to one of the fundamental differences between the two DBMSs. MSSQL is more likely to have support for a given activity, however this comes at the cost of standards compliance. Postgres has support for less activities, however those it does support are very likely to be standards compliant.

This also effects Postgres' technical suitability for enterprise applications. The activities Postgres does support function very well, and show that it is suitable for enterprise applications.

However, many enterprise applications require feature Postgres does not support, such as logon triggers or included columns in indexes. Therefore, we can conclude that Postgres is suitable for any enterprise applications that do not require features it does not support.

REFERENCES

- [1] Jim Melton and Alan R. Simon. 2002. *SQL:1999: Understanding Relational Language Components*. Academic Press, San Diego, CA, 32-42.
- [2] Microsoft Corporation. 2017. SQL Server Technical Documentation. MSDN Library. [https://msdn.microsoft.com/library/ms130214\(v=sql.130\).aspx](https://msdn.microsoft.com/library/ms130214(v=sql.130).aspx)
- [3] Microsoft Corporation. 2017. SQL Server 2016 SP1 Express Edition. SQL Server. <https://www.microsoft.com/en-us/sql-server/sql-server-editions-express/>
- [4] PostgreSQL Global Development Group. 2017. PostgreSQL 9.6.2 Documentation. <https://www.postgresql.org/files/documentation/pdf/9.6/postgresql-9.6-A4.pdf>
- [5] PostgreSQL Global Development Group. 2017. License. <https://www.postgresql.org/about/licence>
- [6] PostgreSQL Global Development Group. 2017. PostgreSQL: Windows Installers <https://www.postgresql.org/download/windows/>
- [7] Sumit Kumar and Nagesh Pabbisetty. Python in SQL Server 2017: enhanced in-database machine learning. <https://blogs.technet.microsoft.com/dataplatforminsider/2017/04/19/python-in-sql-server-2017-enhanced-in-database-machine-learning/>

APPENDIX

A. SQL CODE FOR SCHEMA

These schemas are also available digitally (as .sql files) at our respective drop off folders on the WCSU X: drive and publicly via Microsoft OneDrive. Additional working examples for each schema are located in their respective folders.

Base directories:

WCSU X Drive:

X:\Dropoff\CS\murthys\CS299\Section 03\figueroaA\Final\Appendix\

or

X:\Dropoff\CS\murthys\CS299\Section 03\rolloS\Final\Appendix\

Public:

[https://connectwcsu-](https://connectwcsu-my.sharepoint.com/personal/figueroa039_connect_wcsu_edu/_layouts/15/guestaccess.aspx?folderid=08d10fcfef42e459c82910824f020f40a&authkey=AWoOQgudYoguKM8dacnpf8Q)

[my.sharepoint.com/personal/figueroa039_connect_wcsu_edu/_layouts/15/guestaccess.aspx?folderid=08d10fcfef42e459c82910824f020f40a&authkey=AWoOQgudYoguKM8dacnpf8Q](https://connectwcsu-my.sharepoint.com/personal/figueroa039_connect_wcsu_edu/_layouts/15/guestaccess.aspx?folderid=08d10fcfef42e459c82910824f020f40a&authkey=AWoOQgudYoguKM8dacnpf8Q)

A.1 Advert

A.1.1 T-SQL

Schema File: Advert\MSSQL\3_createAdvertTSQL.sql

Additional working examples for this schema:

1_ddl-login-triggers.sql

4_dml-trigger.sql

5_opsTSQL.sql

6_dynamic-sql.sql

7_perfromance-optimization.sql

--The ADVERTISER entity is fully represented by the view ADVERTISER below

CREATE TABLE ADVERTISER_T

```
(
    advertiser_id NUMERIC(5, 0) CHECK(advertiser_id > -1) PRIMARY KEY,
    university_org NUMERIC(1, 0) CHECK(university_org = 0 OR university_org = 1),
    nonprofit_org NUMERIC(1, 0) CHECK(nonprofit_org = 0 OR nonprofit_org = 1)
    --outstanding_balance is in view ADVERTISER
);
```

CREATE TABLE CONTACT_INFO

```
(
    advertiser_id NUMERIC(5, 0) NOT NULL PRIMARY KEY REFERENCES ADVERTISER_T,
    name VARCHAR(50) NOT NULL,
    address VARCHAR(50) NOT NULL,
    city VARCHAR(30) NOT NULL,
    state CHAR(2) CHECK(LEN(LTRIM(RTRIM(state))) = 2),
    zip CHAR(5) CHECK(LEN(LTRIM(RTRIM(zip))) = 5),
    email VARCHAR(50) NOT NULL,
    phone CHAR(10) CHECK(LEN(LTRIM(RTRIM(phone))) = 10)
);
```

CREATE TABLE RATE_CARD

```
(
    rate_card_id NUMERIC(2, 0) NOT NULL CHECK(rate_card_id > -1) PRIMARY KEY,
    ad_size CHAR(5) NOT NULL CHECK(LEN(LTRIM(RTRIM(ad_size))) = 5),
    price_per_issue NUMERIC(8, 2) NOT NULL
);
```

```

);
CREATE TABLE PRICE_REQUEST
(
    rate_card_id NUMERIC(2, 0) NOT NULL REFERENCES RATE_CARD,
    advertiser_id NUMERIC(5, 0) NOT NULL REFERENCES ADVERTISER_T,
    PRIMARY KEY(rate_card_id, advertiser_id)
);
CREATE TABLE AD
(
    ad_id NUMERIC(10, 0) CHECK(ad_id > -1) PRIMARY KEY,
    name CHAR(20) CHECK(LEN(LTRIM(RTRIM(name))) = 20) UNIQUE,
    order_date DATE NOT NULL,
    start_date DATE NOT NULL,
    rate_card_id NUMERIC(2, 0) NOT NULL REFERENCES RATE_CARD,
    num_issues NUMERIC(5, 0) NOT NULL,
    prepaid NUMERIC(1, 0) CHECK(prepaid = 0 OR prepaid = 1),
    consec_disc AS (CASE WHEN num_issues > 4 THEN 1 ELSE 0 END),
    premium_place NUMERIC(1, 0) CHECK(premium_place = 0 OR premium_place = 1),
    color NUMERIC(1, 0) CHECK(color = 0 OR color = 1),
    edit NUMERIC(1, 0) CHECK(edit = 0 OR edit = 1),
    advertiser_id NUMERIC(5, 0) NOT NULL REFERENCES ADVERTISER_T
);

CREATE TABLE INVOICE_T
(
    ad_id NUMERIC(10, 0) NOT NULL PRIMARY KEY REFERENCES AD,
    invoice_date DATE NOT NULL,
    advertiser_id NUMERIC(5, 0) NOT NULL REFERENCES ADVERTISER_T
    --total_charge is in view INVOICE
    --fully_paid is in view INVOICE
    --run_complete is in view INVOICE
    --run_failed is in view INVOICE
);
CREATE TABLE PAYMENT
(
    payment_id NUMERIC(16, 0) CHECK(payment_id > -1) PRIMARY KEY,
    advertiser_id NUMERIC(5, 0) NOT NULL REFERENCES ADVERTISER_T,
    ad_id NUMERIC(10, 0) NOT NULL REFERENCES INVOICE_T,
    amount NUMERIC(8, 2) NOT NULL
);
CREATE TABLE AD_RUN
(
    ad_id NUMERIC(10, 0) NOT NULL REFERENCES INVOICE_T,
    issue_date DATE NOT NULL,
    proof_sent NUMERIC(1, 0) CHECK(proof_sent = 0 OR proof_sent = 1 OR proof_sent IS NULL),

```

```

PRIMARY KEY(ad_id, issue_date)
);
GO
CREATE VIEW AD_PRICE AS
SELECT a.ad_id ad_id, a.advertiser_id advertiser_id,
       (a.num_issues * r.price_per_issue) base_price,
       (a.num_issues * r.price_per_issue + 100 * a.edit + a.num_issues
        * r.price_per_issue * 0.30 * a.color + a.num_issues
        * r.price_per_issue * 0.20 * a.premium_place - a.num_issues
        * r.price_per_issue * 0.10 * a.prepaid - a.num_issues
        * r.price_per_issue * 0.10 * a.consec_disc - a.num_issues
        * r.price_per_issue * 0.25 * av.university_org - a.num_issues
        * r.price_per_issue * 0.50 * av.nonprofit_org) total_price
FROM AD a
JOIN RATE_CARD r ON r.rate_card_id = a.rate_card_id
JOIN ADVERTISER_T av ON av.advertiser_id = a.advertiser_id;
GO
CREATE VIEW ADVERTISER AS
SELECT a.advertiser_id advertiser_id, a.university_org university_org, a.nonprofit_org
nonprofit_org,
(
  SELECT SUM(ar.total_price)
  FROM AD_PRICE ar
  WHERE ar.advertiser_id = a.advertiser_id
) -
(
  SELECT SUM(p.amount)
  FROM PAYMENT p
  WHERE p.advertiser_id = a.advertiser_id
) outstanding_balance
FROM ADVERTISER_T a;
GO
CREATE VIEW INVOICE AS
SELECT i.ad_id ad_id, i.invoice_date invoice_date, ap.total_price total_price,
       CASE WHEN ap.total_price -
(
  SELECT SUM(p.amount)
  FROM Payment p
  WHERE p.ad_id = i.ad_id
) > 0 THEN 0 ELSE 1 END fully_paid,
CASE WHEN DATEADD(day, a.num_issues, a.start_date) < GETDATE() THEN 1 ELSE 0 END
run_complete,
CASE WHEN DATEADD(day, a.num_issues, a.start_date) > GETDATE() OR
(
  SELECT SUM(COALESCE(ar.proof_sent, 0))
  FROM AD_RUN ar

```

```

        WHERE ar.ad_id = i.ad_id
    ) = a.num_issues THEN 0 ELSE 1 END run_failed
FROM INVOICE_T i
JOIN AD a ON a.ad_id = i.ad_id
JOIN AD_PRICE ap ON ap.ad_id = i.ad_id;
GO

INSERT INTO RATE_CARD
VALUES(0, '01x01', 5);
INSERT INTO RATE_CARD
VALUES(1, '02x02', 10);
INSERT INTO RATE_CARD
VALUES(2, '03x03', 15);
INSERT INTO RATE_CARD
VALUES(3, '10x10', 40);
INSERT INTO RATE_CARD
VALUES(4, 'fullp', 100);
SELECT 'Price List' BASE_DATA;
SELECT *
FROM RATE_CARD;
INSERT INTO ADVERTISER_T
VALUES(0, 0, 0);
INSERT INTO CONTACT_INFO
VALUES(0, 'Robert's Discount Furniture', '000 Example Street', 'Danbury', 'CT',
'00000',
'robert@rdiscountfurniture.net', '5555555555');
INSERT INTO PRICE_REQUEST
VALUES(3, 0);
INSERT INTO PRICE_REQUEST
VALUES(4, 0);
INSERT INTO AD
(ad_id, name, order_date, start_date, rate_card_id, num_issues, prepaid, premium_place,
color,
    edit, advertiser_id
)
VALUES(0, 'RODISCFURN2016000000', GETDATE() - 1, GETDATE() + 7, 4, 10, 1, 0, 0, 0, 0);
INSERT INTO INVOICE_T
VALUES(0, GETDATE(), 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 7, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 8, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 9, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 10, 0);
INSERT INTO AD_RUN

```

```

VALUES(0, GETDATE() + 11, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 12, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 13, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 14, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 15, 0);
INSERT INTO AD_RUN
VALUES(0, GETDATE() + 16, 0

```

A.1.2 pgSQL

Schema File: Advert\Postgres\3_createAdvertpgSQL.sql

Additional working examples for this schema:

1_ddl-login-triggers.sql

4_dml-trigger.sql

5_opsTSQL.sql

6_dynamic-sql.sql

7_perfromance-optimization.sql

```

CREATE TABLE advertiser_t
(
    advertiser_id NUMERIC(5,0) CHECK(advertiser_id > -1) PRIMARY KEY,
    university_org NUMERIC(1,0) CHECK(university_org = 0 OR university_org = 1),
    nonprofit_org NUMERIC(1,0) CHECK(nonprofit_org = 0 OR nonprofit_org = 1)
);
CREATE TABLE contact_info
(
    advertiser_id NUMERIC(5,0) NOT NULL
    PRIMARY KEY REFERENCES advertiser_t,
    name VARCHAR(50) NOT NULL,
    address VARCHAR(50) NOT NULL,
    city VARCHAR(30) NOT NULL,
    state CHAR(2) CHECK(LENGTH(TRIM(state)) = 2),
    zip CHAR(5) CHECK(LENGTH(TRIM(zip)) = 5),
    email VARCHAR(50) NOT NULL,
    phone CHAR(10) CHECK(LENGTH(TRIM(phone)) = 10)
);
CREATE TABLE rate_card
(
    rate_card_id NUMERIC(2,0) NOT NULL CHECK(rate_card_id > -1) PRIMARY KEY,
    ad_size CHAR(5) NOT NULL CHECK(LENGTH(TRIM(ad_size)) = 5),
    price_per_issue NUMERIC(8,2) NOT NULL
);
CREATE TABLE price_request
(

```



```

    rate_card_id NUMERIC(2,0) NOT NULL REFERENCES rate_card,
    advertiser_id NUMERIC(5,0) NOT NULL REFERENCES advertiser_t,
    PRIMARY KEY(rate_card_id, advertiser_id)
);
CREATE TABLE ad_t
(
    ad_id NUMERIC(10,0) CHECK(ad_id > -1) PRIMARY KEY,
    name CHAR(20) CHECK(LENGTH(TRIM(name)) = 20) UNIQUE,
    order_date DATE NOT NULL,
    start_date DATE NOT NULL,
    rate_card_id NUMERIC(2,0) NOT NULL REFERENCES RATE_CARD,
    num_issues NUMERIC(5,0) NOT NULL,
    prepaid NUMERIC(1,0) CHECK(prepaid = 0 OR prepaid = 1),
    premium_place NUMERIC(1,0) CHECK(premium_place = 0 OR premium_place = 1),
    color NUMERIC(1,0) CHECK(color = 0 OR color = 1),
    edit NUMERIC(1,0) CHECK(edit = 0 OR edit = 1),
    advertiser_id NUMERIC(5,0) NOT NULL REFERENCES advertiser_t
);
CREATE VIEW ad AS
SELECT
    ad_id, name, order_date, start_date, rate_card_id, num_issues, prepaid,
    (CASE WHEN num_issues > 4 THEN 1 ELSE 0 END) AS consec_disc,
    premium_place, color, edit, advertiser_id
FROM ad_t;
CREATE TABLE invoice_t
(
    ad_id NUMERIC(10,0) NOT NULL PRIMARY KEY REFERENCES ad_t,
    invoice_date DATE NOT NULL,
    advertiser_id NUMERIC(5,0) NOT NULL REFERENCES advertiser_t
);
CREATE TABLE payment
(
    payment_id NUMERIC(16,0) CHECK(payment_id > -1) PRIMARY KEY,
    advertiser_id NUMERIC(5,0) NOT NULL REFERENCES advertiser_t,
    ad_id NUMERIC(10,0) NOT NULL REFERENCES invoice_t,
    amount NUMERIC(8,2) NOT NULL
);
CREATE TABLE ad_run(
    ad_id NUMERIC(10,0) NOT NULL REFERENCES invoice_t,
    issue_date DATE NOT NULL,
    proof_sent NUMERIC(1,0) CHECK(proof_sent = 0
    OR proof_sent = 1
    OR proof_sent IS NULL),
    PRIMARY KEY(ad_id, issue_date)
);

```

```

CREATE VIEW ad_price AS
SELECT a.ad_id ad_id, a.advertiser_id advertiser_id,
      (a.num_issues * r.price_per_issue)
      base_price,
      (a.num_issues * r.price_per_issue
      + 100 * a.edit
      + a.num_issues * r.price_per_issue * 0.30 * a.color
      + a.num_issues * r.price_per_issue * 0.20 * a.premium_place
      - a.num_issues * r.price_per_issue * 0.10 * a.prepaid
      - a.num_issues * r.price_per_issue * 0.10 * a.consec_disc
      - a.num_issues * r.price_per_issue * 0.25 * av.university_org
      - a.num_issues * r.price_per_issue * 0.50 * av.nonprofit_org) total_price
FROM ad a
JOIN rate_card r ON r.rate_card_id = a.rate_card_id
JOIN advertiser_t av ON av.advertiser_id = a.advertiser_id;
CREATE VIEW advertiser AS
SELECT a.advertiser_id advertiser_id, a.university_org university_org, a.nonprofit_org
nonprofit_org,
      (SELECT SUM(ar.total_price)
      FROM ad_price ar
      WHERE ar.advertiser_id = a.advertiser_id)
      - (SELECT SUM(p.amount)
      FROM payment p
      WHERE p.advertiser_id = a.advertiser_id) outstanding_balance
FROM advertiser_t a;
CREATE VIEW INVOICE AS
SELECT i.ad_id ad_id, i.invoice_date invoice_date, ap.total_price total_price,
      CASE WHEN ap.total_price
      - (SELECT SUM(p.amount)
      FROM Payment p
      WHERE p.ad_id = i.ad_id) > 0 THEN 0 ELSE 1 END fully_paid,
      CASE WHEN a.start_date + interval '1day' * a.num_issues < current_date THEN 1 ELSE 0
      END run_complete,
      CASE WHEN a.start_date + interval '1day' * a.num_issues > current_date OR
      (SELECT SUM(COALESCE(ar.proof_sent, 0))
      FROM ad_run ar
      WHERE ar.ad_id = i.ad_id) = a.num_issues THEN 0 ELSE 1 END run_failed
FROM invoice_t i
JOIN ad a ON a.ad_id = i.ad_id
JOIN ad_price ap ON ap.ad_id = i.ad_id;
INSERT INTO rate_card VALUES(0, '01x01', 5);
INSERT INTO rate_card VALUES(1, '02x02', 10);
INSERT INTO rate_card VALUES(2, '03x03', 15);
INSERT INTO rate_card VALUES(3, '10x10', 40);
INSERT INTO rate_card VALUES(4, 'fullp', 100);
INSERT INTO advertiser_t

```

```

VALUES(0, 0, 0);
INSERT INTO contact_info
VALUES(0, 'Robert's Discount Furniture', '000 Example Street', 'Danbury', 'CT',
'00000', 'robert@rdiscountfurniture.net', '5555555555');
INSERT INTO price_request
VALUES(3, 0);
INSERT INTO price_request
VALUES(4, 0);
INSERT INTO ad
(ad_id, name, order_date, start_date, rate_card_id, num_issues, prepaid,
premium_place, color, edit, advertiser_id)
VALUES(0, 'RODISCFURN2016000000', CURRENT_DATE - 1, CURRENT_DATE + 7, 4, 10, 1, 0,
0, 0, 0);
INSERT INTO invoice_t
VALUES(0, CURRENT_DATE, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 7, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 8, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 9, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 10, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 11, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 12, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 13, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 14, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 15, 0);
INSERT INTO ad_run
VALUES(0, CURRENT_DATE + 16, 0);

```

A.2 Shelter

A.2.1 T-SQL and pgSQL

Directory: Shelter\MSSQL\shelter_TSQL.sql or Shelter\Postgres\shelter_pgSQL.sql

```

CREATE TABLE dog
(
    dog_id          CHAR(3) NOT NULL,
    name            VARCHAR(15),
    arrival_date    DATE,
    breed           VARCHAR(20),
    date_of_birth   DATE,
    weight          NUMERIC(3),

```

```

        PRIMARY KEY(dog_id)
    );
CREATE TABLE adopter
(
    adopter_id CHAR(3),
    fname      VARCHAR(10),
    lname      VARCHAR(10) NOT NULL,
    address    VARCHAR(20),
    city       VARCHAR(15),
    state      CHAR(2),
    zip        CHAR(5),
    phone      CHAR(13),
    PRIMARY KEY(adopter_id)
);
CREATE TABLE volunteer
(
    vol_id CHAR(3),
    fname  VARCHAR(10),
    lname  VARCHAR(10) NOT NULL,
    phone  CHAR(13),
    email  VARCHAR(15),
    PRIMARY KEY(vol_id)
);
CREATE TABLE responsibility
(
    title VARCHAR(20),
    PRIMARY KEY(title)
);
(
    vet_id  CHAR(1),
    fname   VARCHAR(10),
    lname   VARCHAR(10) NOT NULL,
    address VARCHAR(20),
    city    VARCHAR(15),
    state   CHAR(2),
    zip     CHAR(5),
    phone   CHAR(13),
    PRIMARY KEY(vet_id)
);
CREATE TABLE adoption
(
    dog_id      CHAR(3),
    adopter_id  CHAR(3),
    vol_id      CHAR(3),
    adoption_date DATE,

```

```

    adoption_fee NUMERIC(5, 2),
    FOREIGN KEY(dog_id) REFERENCES dog(dog_id),
    FOREIGN KEY(adopter_id) REFERENCES adopter(adopter_id),
    FOREIGN KEY(vol_id) REFERENCES volunteer(vol_id),
    PRIMARY KEY(dog_id, adopter_id, vol_id)
);
CREATE TABLE treatment
(
    treatment_id CHAR(3),
    vet_id CHAR(1),
    dog_id CHAR(3),
    treatment_date DATE,
    description VARCHAR(20),
    fee NUMERIC(5, 2),
    discount_rate NUMERIC(4, 2),
    FOREIGN KEY(vet_id) REFERENCES vet(vet_id),
    FOREIGN KEY(dog_id) REFERENCES dog(dog_id),
    PRIMARY KEY(treatment_id)
);
CREATE TABLE "return"
(
    dog_id CHAR(3),
    adopter_id CHAR(3),
    return_date DATE,
    reason VARCHAR(30),
    FOREIGN KEY(dog_id) REFERENCES dog(dog_id),
    FOREIGN KEY(adopter_id) REFERENCES adopter(adopter_id),
    PRIMARY KEY(dog_id, adopter_id)
);
CREATE TABLE assignment
(
    vol_id CHAR(3),
    responsibility VARCHAR(20),
    FOREIGN KEY(vol_id) REFERENCES volunteer(vol_id),
    FOREIGN KEY(responsibility) REFERENCES responsibility(title),
    PRIMARY KEY(vol_id, responsibility)
);

```

A.3 Babysitting

A.3.1 T-SQL

Directory: Babysitting\MSSQL\babysitting_TSQL.sql

```

CREATE TABLE Family(
    FID INTEGER PRIMARY KEY CHECK (FID > 0),
    FName VARCHAR(50) NOT NULL,
    FAddress VARCHAR(100) NOT NULL
);

```

```

CREATE TABLE Family_Member(
    FID INTEGER,
    Member VARCHAR(50),
    CONSTRAINT pk_Family_Member PRIMARY KEY (FID, Member),
    CONSTRAINT fk_PartOfFamily FOREIGN KEY (FID)
        REFERENCES Family(FID)
);

CREATE TABLE Child(
    FID INTEGER NOT NULL,
    CName VARCHAR(50) NOT NULL,
    CBirthdate DATE NOT NULL,
    CONSTRAINT pk_Child PRIMARY KEY (FID, CName),
    CONSTRAINT fk_ChildOfFamily FOREIGN KEY (FID)
        REFERENCES Family(FID)
);

CREATE TABLE Sitting(
    SID INTEGER PRIMARY KEY CHECK (SID > 0),
    F_FID INTEGER NOT NULL,
    CName VARCHAR(50) NOT NULL,
    C_FID INTEGER NOT NULL,
    SDate DATE NOT NULL,
    SStart DATETIME2 NOT NULL,
    SFinish DATETIME2 NOT NULL,
    SLength AS (ROUND(DATEDIFF(mi, SStart, SFinish) / 60.0, 0)),
    CONSTRAINT fk_SittingFamily FOREIGN KEY (F_FID)
        REFERENCES Family(FID),
    CONSTRAINT fk_ChildSat FOREIGN KEY (C_FID, CName)
        REFERENCES Child(FID, CName),
    CONSTRAINT Sitting_DiffFam CHECK (F_FID <> C_FID),
    CONSTRAINT Sitting_SeqTimes CHECK (SStart < SFinish)
);

```

A.3.2 *PgSQL*

Directory: Babysitting\Postgres\babysitting_pgSQL.sql

```

CREATE TABLE Family(
    FID INTEGER PRIMARY KEY CHECK (FID > 0),
    FName VARCHAR(50) NOT NULL,
    FAddress VARCHAR(100) NOT NULL
);

CREATE TABLE Family_Member(
    FID INTEGER,
    Member VARCHAR(50),
    CONSTRAINT pk_Family_Member PRIMARY KEY (FID, Member),

```

```

        CONSTRAINT fk_PartOfFamily FOREIGN KEY (FID)
            REFERENCES Family(FID)
    );

CREATE TABLE Child(
    FID INTEGER NOT NULL,
    CName VARCHAR(50) NOT NULL,
    CBirthdate DATE NOT NULL,
    CONSTRAINT pk_Child PRIMARY KEY (FID, CName),
    CONSTRAINT fk_ChildOfFamily FOREIGN KEY (FID)
        REFERENCES Family(FID)
);

CREATE TABLE Sitting(
    SID INTEGER PRIMARY KEY CHECK (SID > 0),
    F_FID INTEGER NOT NULL,
    CName VARCHAR(50) NOT NULL,
    C_FID INTEGER NOT NULL,
    SDate DATE NOT NULL,
    SStart TIMESTAMP NOT NULL,
    SFinish TIMESTAMP NOT NULL,
    CONSTRAINT fk_SittingFamily FOREIGN KEY (F_FID)
        REFERENCES Family(FID),
    CONSTRAINT fk_ChildSat FOREIGN KEY (C_FID, CName)
        REFERENCES Child(FID, CName),
    CONSTRAINT Sitting_DiffFam CHECK (F_FID <> C_FID),
    CONSTRAINT Sitting_SeqTimes CHECK (SStart < SFinish)
);

CREATE VIEW Sitting_Comp AS (
    SELECT SID, F_FID, CName, C_FID SDate, SStart, SFinish,
        (SFinish - SStart) as SLength
    FROM Sitting );

```

A.4 Classroom

No schemas available as Classroom is only a hypothetical scenario, not a full implementation.

A.3.1 T-SQL

Directory: Classroom\MSSQL

```

--The following is specific example of creating a student
--Implementations with stored procedures will vary depending on the organization's
-- user and group structure.

```

```

CREATE ROLE CS205F17Student;
CREATE ROLE CS205F17Instructor;

CREATE USER [WCSU\Students\Ramsey033];

```

```
ALTER ROLE CS205F17Student ADD MEMBER [WCSU\Students\Ramsey033];
```

```
CREATE SCHEMA ramsey033 GRANT SELECT, INSERT, DELETE, UPDATE;  
GRANT SELECT ON SCHEMA ramsey033 TO CS205F17Instructor;
```

A.3.2 PgSQL

Directory: Classroom\Postgres

--Group equivalent for managing permissions for students

```
CREATE ROLE CS205F17Student;
```

--Group equivalent for managing permissions for instructors

```
CREATE ROLE CS205F17Instructor;
```

--Removes the ability for users to modify the "public" schema for the current database

```
REVOKE CREATE ON SCHEMA public FROM PUBLIC;
```

--Creates a role for a student given a username and password. This procedure also creates

-- a schema for each user and gives both the student and instructor appropriate

-- privileges.

```
CREATE OR REPLACE FUNCTION createCS205F17Student(userName VARCHAR(25), pw VARCHAR(25))  
RETURNS VOID AS
```

```
$$
```

```
BEGIN
```

```
    userName := lower(userName);
```

```
    EXECUTE format('CREATE USER %I PASSWORD %L', userName, pw);
```

```
    EXECUTE format('GRANT CS205F17Student TO %I', userName);
```

```
    EXECUTE format('CREATE SCHEMA %I', userName);
```

```
    EXECUTE format('GRANT ALL PRIVILEGES ON SCHEMA %I TO %I', userName, userName);
```

```
    EXECUTE format('GRANT USAGE ON SCHEMA %I TO cs205F17Instructor', userName);
```

```
    EXECUTE format('ALTER USER %I SET search_path = %I', userName, userName);
```

```
END
```

```
$$ LANGUAGE plpgsql;
```

--Creates a role for an instructor given a username and password. The procedure also

-- adds this new instructor to the appropriate group, but does not create any schemas.

```
CREATE OR REPLACE FUNCTION createCS205F17Instructor(userName VARCHAR(25), pw  
VARCHAR(25)) RETURNS VOID AS
```

```
$$
```

```
BEGIN
```

```
    userName := lower(userName);
```

```
    EXECUTE format('CREATE USER %I PASSWORD %L', userName, pw);
```

```
    EXECUTE format('GRANT CS205F17Instructor TO %I', userName);
```

```
END
```

```
$$ LANGUAGE plpgsql;
```

--Creates a sample student and instructor


```
SELECT createCS205F17Student('Ramsey033', '50045123');  
SELECT createCS205F17Instructor('WestP', '123999888');
```

```
--Note that in order to drop the roles, all objects belonging to the role must also be  
-- dropped before doing so.
```