Assembly Language for x86 Processors

Seventh Edition



Chapter 2

x86 Processor Architecture

Pearson

Chapter Overview

- General Concepts
- IA-32 Processor Architecture
- IA-32 Memory Management
- 64-bit Processors
- Components of an IA-32 Microcomputer
- Input-Output System

General Concepts

- Basic microcomputer design
- Instruction execution cycle
- Reading from memory
- How programs run

Basic Microcomputer Design

- clock synchronizes CPU operations
- control unit (CU) coordinates sequence of execution steps
- ALU performs arithmetic and bitwise processing



CPU vs GPU in ALU



Clock

- synchronizes all CPU and BUS operations
- machine (clock) cycle measures time of a single operation
- clock is used to trigger events



Instruction Execution Cycle

- Fetch
- Decode
- Fetch operands
- Execute
- Store output

Figure 2–2 Simplified Pentium CPU Block Diagram.



Reading from Memory

Multiple machine cycles are required when reading from memory, because it responds much more slowly than the C PU. The steps are:

1. Place the address of the value you want to read on the address bus.
2. Assert (changing the value of) the processor's RD (read) pin.
3. Wait one clock cycle for the memory chips to respond.
4. Copy the data from the data bus into the destination operand

Cache Memory

- High-speed expensive static RAM both inside and outside the CPU.
  - Level-1 cache: inside the CPU
  - Level-2 cache: outside the CPU
- Cache hit: when data to be read is already in cache memory
- Cache miss: when data to be read is not in cache memory.

How a Program Runs



Basic Execution Environment

- Addressable memory
- General-purpose registers
- Index and base registers
- Specialized register uses
- Status flags
- Floating-point, MMX, XMM registers

Addressable Memory

- Protected mode
  - 4 GB
  - 32-bit address
- Real-address and Virtual-8086 modes
  - 1 MB space
  - 20-bit address

General-Purpose Registers

- Named storage locations inside the CPU, optimized for speed.



Accessing Parts of Registers

- Use 8-bit name, 16-bit name, or 32-bit name
- Applies to EAX, EBX, ECX, and EDX



32-bit	16-bit	8-bit (high)	8-bit (low)
EAX	AX	AH	AL
EBX	BX	BH	BL
ECX	CX	CH	CL
EDX	DX	DH	DL

Index and Base Registers

- Some registers have only a 16-bit name for their lower half:

32-bit	16-bit
ESI	SI
EDI	DI
EBP	BP
ESP	SP

Some Specialized Register Uses (1 of 2)

- General-Purpose
  - EAX – accumulator
  - ECX – loop counter
  - ESP – stack pointer
  - ESI, EDI – index registers
  - EBP – extended frame pointer (stack)

Some Specialized Register Uses (2 of 2)

- Segment
  - CS – code segment
  - DS – data segment
  - SS – stack segment
  - ES, FS, GS - additional segments
- EIP- instruction pointer
- EFLAGS
  - status and control flags
  - each flag is a single binary bit

Status Flags

- Carry
  - unsigned arithmetic out of range
- Overflow
  - signed arithmetic out of range
- Sign
  - result is negative
- Zero
  - result is zero
- Auxiliary Carry
  - carry from bit 3 to bit 4
- Parity
  - sum of 1 bits is an even number

IA-32 Memory Management

- Real-address mode
- Calculating linear addresses
- Protected mode
- Multi-segment model
- Paging

Protected Mode (1 of 2)

- 4 GB addressable RAM
  - (00000000 to FFFFFFFFh)
- Each program assigned a memory partition which is protected from other programs
- Designed for multitasking
- Supported by Linux & MS-Windows

Components of an IA-32 Microcomputer

- Motherboard
- Video output
- Memory
- Input-output ports

Motherboard

- CPU socket
- External cache memory slots
- Main memory slots
- BIOS chips
- Sound synthesizer chip (optional)
- Video controller chip (optional)
- IDE, parallel, serial, USB, video, keyboard, joystick, network, and mouse connectors
- PCI bus connectors (expansion cards)

Intel 965 Express Chipset



Sample Video Controller (ATI Corp.)

- 128-bit 3D graphics performance powered by RAGE™ 128 PRO
- 3D graphics performance
- Intelligent TV-Tuner with Digital VCR
- TV-ON-DEMAND™
- Interactive Program Guide
- Still image and MPEG-2 motion video capture
- Video editing
- Hardware DVD video playback
- Video output to TV or VCR



Memory (1 of 2)

- ROM
  - read-only memory
- EPROM
  - erasable programmable read-only memory
- Dynamic RAM (DRAM)
  - inexpensive; must be refreshed constantly
- Static RAM (SRAM)
  - expensive; used for cache memory; no refresh required

Memory (2 of 2)

- Video RAM (VRAM)
  - dual ported; optimized for constant video refresh
- CMOSRAM
  - complimentary metal-oxide semiconductor
  - system setup information

Levels of Input-Output

- Level 3: High-level language function
  - examples: C++, Java
  - portable, convenient, not always the fastest
- Level 2: Operating system
  - Application Programming Interface (API)
  - extended capabilities, lots of details to master
- Level 1: BIOS
  - drivers that communicate directly with devices
  - OS security may prevent application-level code from working at this level

Displaying a String of Characters

When a program displays a string of characters, the following steps take place:



Programming levels

- Assembly language programs can perform input-output at each of the following levels: