Conservatoire National des Arts et Métiers
Équipement pour la Performance et le Numérique (EPN04)

Digital Twin & Reduced Order Modelling for Nonlinear Dynamics

Internship Report

March – September 2026

Author:
WEHBE Mumen

Supervisor:
Dr. Christophe Hoareau
EPN04, Cnam

2026

Abstract

This report presents the work conducted during a six-month internship at the Conservatoire National des Arts et Métiers (Cnam), within the Équipement pour la Performance et le Numérique (EPN04) department, under the supervision of Dr. Christophe Hoareau. The project addresses the development of a real-time pedagogical Digital Twin for nonlinear structural mechanics, combining Isogeometric Analysis (IGA) with projection-based Reduced Order Model (ROM) techniques.

The methodology relies on Non-Uniform Rational B-Splines (NURBS) basis functions for exact geometric representation and employs Proper Orthogonal Decomposition (POD) via Singular Value Decomposition (SVD) to extract dominant deformation modes from parametric snapshot databases. A Galerkin projection framework reduces the dimensionality of the governing equations, while hyper-reduction strategies (DEIM, ECSW) accelerate the evaluation of nonlinear terms.

The resulting web-based application enables real-time simulation of geometrically nonlinear 2D structures with parametric control, achieving solve times under 10 ms compared to several seconds for the full-order model. The platform serves as both a research validation tool and an interactive pedagogical environment for teaching advanced computational mechanics.

Keywords: Isogeometric Analysis, Reduced Order Modelling, Nonlinear Mechanics, Digital Twin, NURBS, Proper Orthogonal Decomposition, Hyper-reduction, Real-time Simulation.

Contents

Abstract **i**

Introduction **1**

1 State of the Art **4**

1.1 Isogeometric Analysis (IGA) 4

1.1.1 From FEM to IGA 4

1.1.2 B-Splines and NURBS 5

1.1.3 Refinement Strategies 5

1.1.4 Advantages of IGA for ROM 5

1.2 Linear and Nonlinear Elasticity 6

1.2.1 Linear Elasticity 6

1.2.2 Geometric Nonlinearity 6

1.2.3 Constitutive Model: Saint Venant–Kirchhoff 7

1.2.4 Newton–Raphson Solution Procedure 7

1.3 Projection-Based Reduced Order Modelling 7

1.3.1 The Offline–Online Paradigm 7

1.3.2 Proper Orthogonal Decomposition (POD) 7

1.3.3 Galerkin Projection 8

1.3.4 Hyper-Reduction 8

2 Geometrically Parameterized Nonlinear Mechanics in 2D **9**

2.1 Weak Formulation on a Reference Configuration 9

2.1.1 Total Lagrangian Formulation 9

2.1.2 Variation of the Green–Lagrange Strain 9

2.1.3 Parameterized Reference Domain 10

2.2 IGA Discretization 10

2.2.1 2D NURBS Approximation 10

2.2.2 Stiffness Matrix Assembly 10

2.2.3 Boundary Conditions 11

2.3 Offline Simulations . . . 11
2.3.1 Parameter Space Definition . . . 11
2.3.2 Latin Hypercube Sampling . . . 11
2.3.3 Snapshot Database Generation . . . 11
2.3.4 POD Basis Extraction . . . 12
2.4 Online Simulations . . . 12
2.4.1 Galerkin-Projected Nonlinear ROM . . . 12
2.4.2 Performance Targets . . . 12
2.4.3 Data Serialization . . . 13

3 Real-Time Pedagogical Application 14
3.1 Workflow with AI . . . 14
3.1.1 AI-Assisted Development Methodology . . . 14
3.1.2 Quality Assurance . . . 14
3.2 Presentation of the Project . . . 15
3.2.1 Architecture Overview . . . 15
3.2.2 Front-End . . . 15
3.2.3 Back-End (Computational Core) . . . 16
3.2.4 Simulation Hub . . . 16
3.3 Benchmarks . . . 16
3.3.1 Kirsch Plate with Hole . . . 16
3.3.2 ROM Accuracy . . . 17
3.3.3 Computational Speedup . . . 17
3.4 Examples of Use . . . 17
3.4.1 Interactive Parameter Exploration . . . 17
3.4.2 Pedagogical Scenarios . . . 17

4 Extension to 3D Applications 19
4.1 3D NURBS Volume Parameterization . . . 19
4.2 3D Nonlinear Assembly . . . 19
4.3 3D ROM and Visualization . . . 19

Conclusion and Perspectives 21

A Supplementary Material 23
A.1 Cox–de Boor Recursion: Detailed Derivation . . . 23
A.2 Gauss Quadrature Rules . . . 23
A.3 Project Repository Structure . . . 23

List of Figures

3.1 High-level architecture: Offline–Online workflow. 15

List of Tables

2.1 Parameter space definition for the 2D test cases. 11
2.2 Performance comparison: FOM vs. ROM. 12

3.1 Core JavaScript modules. 16

A.1 Gauss–Legendre quadrature points and weights for $n_g = 1, \ldots, 4$. 23

Introduction

Context

The rapid advancement of computational mechanics and the growing demand for interactive simulation tools have created a fertile ground for innovation at the intersection of numerical methods and digital engineering. This internship takes place within the Équipement pour la Performance et le Numérique (EPN04) department at the Conservatoire National des Arts et Métiers in Paris, under the supervision of Dr. Christophe Hoareau.

Who. The project is carried out by WEHBE Mumen, an engineering student, in collaboration with the EPN04 research team specializing in advanced numerical simulation and structural mechanics.

What. The objective is to develop a real-time Digital Twin (DT) platform that couples a physical 3D-printed structural model with a virtual simulation environment powered by Reduced Order Model (ROM) techniques built upon Isogeometric Analysis (IGA).

Where. The work is conducted at the Cnam campus (Paris), leveraging the department's computational infrastructure and pedagogical environment.

When. The internship spans six months, from March to September 2026, following a structured timeline that progresses from theoretical foundations through computational implementation to application deployment.

Why. Traditional high-fidelity simulations of nonlinear structural problems are computationally expensive, often requiring minutes to hours for a single parameter evaluation. This renders them impractical for real-time applications, interactive teaching, and rapid design exploration. The need for a methodology that preserves simulation fidelity while achieving real-time performance motivates this work.

Problematic and Research Gap

While Reduced Order Model techniques have been extensively studied for linear structural problems, their application to **geometrically nonlinear** problems with **parametric variations** remains an active area of research. The key challenges include:

- **Nonlinear operator dependence:** The tangent stiffness matrix $\mathbf{K}_T(\boldsymbol{u})$ changes at every Newton–Raphson iteration, requiring repeated projection onto the reduced basis—a computational bottleneck that standard Galerkin projection alone cannot resolve efficiently.
- **Geometric parameterization:** When the geometry itself is a parameter (e.g., varying aspect ratios or hole sizes), the physical domain $\Omega(\mu)$ changes, invalidating the fixed-mesh assumption of classical ROM approaches.
- **Hyper-reduction for nonlinear terms:** Even after projection, evaluating internal forces $\mathbf{F}_{\text{int}}(\boldsymbol{u})$ requires integration over the full mesh. Hyper-reduction techniques (DEIM, ECSW) are needed to reduce this cost, but their application to IGA-discretized nonlinear problems is not yet well established.
- **Pedagogical accessibility:** Existing ROM implementations are typically confined to research codes (Python/MATLAB) that are inaccessible to students without specialized software environments.

Objectives

The primary objectives of this internship are:

1. **Develop an IGA-based computational core** capable of solving 2D geometrically nonlinear elasticity problems with NURBS discretization, including stiffness assembly, Newton–Raphson iteration, and stress recovery.
2. **Construct a projection-based ROM framework** using POD/SVD for basis extraction and Galerkin projection for operator reduction, extended to handle nonlinear terms via hyper-reduction.
3. **Build a real-time web application** that serves as both a research validation tool and an interactive pedagogical platform, enabling students to explore IGA, ROM, and nonlinear mechanics concepts through live simulations.
4. **Validate the methodology** through benchmark problems (cantilever beam, plate with hole) and quantify the speedup and accuracy of the ROM against the full-order model.

5. **Explore 3D extensions** (time permitting) to assess the scalability of the approach to industrially relevant three-dimensional geometries.

Chapter 1

State of the Art

This chapter reviews the theoretical foundations underpinning the three pillars of the project: Isogeometric Analysis, continuum mechanics for linear and nonlinear elasticity, and projection-based reduced order modelling.

1.1 Isogeometric Analysis (IGA)

1.1.1 From FEM to IGA

The Finite Element Method (FEM) has been the dominant discretization method in computational mechanics for over half a century. However, a fundamental inefficiency persists in the traditional FEM workflow: the geometry created in Computer-Aided Design (CAD) systems using Non-Uniform Rational B-Splines (NURBS) must be re-approximated by polynomial meshes before analysis can begin. This mesh generation step introduces geometric errors, is labor-intensive, and often constitutes a significant portion of the total simulation time.

Isogeometric Analysis (IGA), introduced by Hughes, Cottrell, and Bazilevs in 2005 [3], resolves this gap by using the same NURBS basis functions for both geometry representation and solution approximation. The key principle is:

$$\boldsymbol{x}(\xi) = \sum_{i=1}^{n} R_{i,p}(\xi)\, \boldsymbol{P}_i \tag{1.1}$$

where $R_{i,p}$ are the rational basis functions and $\boldsymbol{P}_i$ are the control points. The displacement field is approximated using the same basis:

$$\boldsymbol{u}^h(\xi) = \sum_{i=1}^{n} R_{i,p}(\xi)\, \boldsymbol{d}_i \tag{1.2}$$

where $\boldsymbol{d}_i$ are the unknown displacement coefficients at control points.

1.1.2 B-Splines and NURBS

A B-spline of degree p is defined over a knot vector $\Xi = \{\xi_1, \xi_2, \ldots, \xi_{n+p+1}\}$ by the Cox–de Boor recursion:

$$N_{i,0}(\xi) = \begin{cases} 1 & \text{if } \xi_i \leq \xi < \xi_{i+1} \\ 0 & \text{otherwise} \end{cases} \tag{1.3}$$

$$N_{i,p}(\xi) = \frac{\xi - \xi_i}{\xi_{i+p} - \xi_i} N_{i,p-1}(\xi) + \frac{\xi_{i+p+1} - \xi}{\xi_{i+p+1} - \xi_{i+1}} N_{i+1,p-1}(\xi) \tag{1.4}$$

NURBS basis functions are obtained by introducing weights $w_i > 0$:

$$R_{i,p}(\xi) = \frac{N_{i,p}(\xi)\, w_i}{\sum_{j=1}^{n} N_{j,p}(\xi)\, w_j} \tag{1.5}$$

For 2D problems, tensor-product surfaces are constructed:

$$\boldsymbol{S}(\xi, \eta) = \sum_{i=1}^{n} \sum_{j=1}^{m} R_{i,j}^{p,q}(\xi, \eta)\, \boldsymbol{P}_{i,j} \tag{1.6}$$

1.1.3 Refinement Strategies

IGA supports three refinement mechanisms that preserve the exact geometry:

- **h-refinement (knot insertion):** Adds new knots to the knot vector, increasing the number of basis functions without changing the polynomial degree.
- **p-refinement (order elevation):** Increases the polynomial degree while maintaining the knot vector structure.
- **k-refinement:** A combination unique to IGA—order elevation followed by knot insertion—that produces basis functions with maximal continuity (C^{p-1}).

1.1.4 Advantages of IGA for ROM

Several properties make IGA particularly well-suited for reduced order modelling:

1. **Exact geometry:** No geometric approximation error, critical for parametric studies where the domain changes.

2. **Higher continuity:** C^{p-1} inter-element continuity (vs. C^0 in FEM) produces smoother solution fields, leading to better snapshot quality.

3. **Natural parameterization:** The mapping from the master domain $\hat{\Omega}$ to the physical domain $\Omega(\mu)$ is built into the NURBS framework, enabling parametric ROM on a fixed reference configuration.

1.2 Linear and Nonlinear Elasticity

1.2.1 Linear Elasticity

Under the assumption of infinitesimal strains, the linearized strain tensor is:

$$\boldsymbol{\varepsilon} = \frac{1}{2}\left(\nabla \boldsymbol{u} + \nabla \boldsymbol{u}^T\right) \tag{1.7}$$

The constitutive law for an isotropic material (generalized Hooke's law) in Voigt notation reads:

$$\boldsymbol{\sigma} = \mathbf{C}\,\boldsymbol{\varepsilon} \tag{1.8}$$

where $\mathbf{C}$ is the elasticity matrix depending on Young's modulus E and Poisson's ratio ν.

The weak form of the equilibrium equation leads to the standard stiffness system:

$$\mathbf{K}\,\boldsymbol{u} = \boldsymbol{F} \tag{1.9}$$

1.2.2 Geometric Nonlinearity

When displacements become large relative to the structural dimensions, the linear strain measure is no longer adequate. The deformation is described by the deformation gradient:

$$\mathbf{F} = \frac{\partial \boldsymbol{x}}{\partial \boldsymbol{X}} = \mathbf{I} + \nabla_{\boldsymbol{X}} \boldsymbol{u} \tag{1.10}$$

The **Green–Lagrange strain tensor** captures finite deformations without contamination by rigid-body rotations:

$$\mathbf{E} = \frac{1}{2}\left(\mathbf{F}^T\mathbf{F} - \mathbf{I}\right) = \frac{1}{2}\left(\nabla \boldsymbol{u} + \nabla \boldsymbol{u}^T + \nabla \boldsymbol{u}^T \nabla \boldsymbol{u}\right) \tag{1.11}$$

The quadratic term $\nabla \boldsymbol{u}^T \nabla \boldsymbol{u}$ is the source of geometric nonlinearity, producing the **geometric stiffening** effect.

1.2.3 Constitutive Model: Saint Venant–Kirchhoff

For this work, we adopt the Saint Venant–Kirchhoff (SVK) hyperelastic model, which relates the second Piola–Kirchhoff stress tensor $\mathbf{S}$ to the Green–Lagrange strain:

$$\mathbf{S} = \mathbf{C} : \mathbf{E} \tag{1.12}$$

This is the simplest hyperelastic model and is appropriate for large displacements with moderate strains.

1.2.4 Newton–Raphson Solution Procedure

The nonlinear equilibrium is expressed as a residual equation:

$$\boldsymbol{R}(\boldsymbol{u}) = \boldsymbol{F}_{\text{ext}} - \boldsymbol{F}_{\text{int}}(\boldsymbol{u}) = \mathbf{0} \tag{1.13}$$

Linearization yields the iterative correction:

$$\mathbf{K}_T(\boldsymbol{u}^{(k)})\,\Delta\boldsymbol{u} = \boldsymbol{R}(\boldsymbol{u}^{(k)}), \qquad \boldsymbol{u}^{(k+1)} = \boldsymbol{u}^{(k)} + \Delta\boldsymbol{u} \tag{1.14}$$

where the tangent stiffness $\mathbf{K}_T = \mathbf{K}_L + \mathbf{K}_G$ includes both the material (linear) and geometric contributions.

1.3 Projection-Based Reduced Order Modelling

1.3.1 The Offline–Online Paradigm

ROM follows a two-phase strategy:

- **Offline phase (expensive, done once):** Generate high-fidelity solutions (snapshots) for a training set of parameters, extract a reduced basis, and pre-compute projected operators.
- **Online phase (fast, repeated):** For any new parameter value, solve the reduced system of size $r \ll N$ in real time.

1.3.2 Proper Orthogonal Decomposition (POD)

Given a snapshot matrix $\mathbf{S} = [\boldsymbol{u}(\mu_1), \ldots, \boldsymbol{u}(\mu_{N_s})] \in \mathbb{R}^{N \times N_s}$, the POD basis is obtained via the Singular Value Decomposition:

$$\mathbf{S} = \mathbf{U}\,\boldsymbol{\Sigma}\,\mathbf{V}^T \tag{1.15}$$

The reduced basis $\mathbf{\Phi} \in \mathbb{R}^{N\times r}$ consists of the first r columns of $\mathbf{U}$, chosen such that the cumulative energy criterion is satisfied:

$$\eta(r) = \frac{\sum_{i=1}^{r} \sigma_i^2}{\sum_{i=1}^{N_s} \sigma_i^2} > 1 - \varepsilon, \qquad \text{typically } \varepsilon = 10^{-4} \tag{1.16}$$

1.3.3 Galerkin Projection

The displacement is approximated in the reduced subspace:

$$\boldsymbol{u} \approx \mathbf{\Phi}\, \boldsymbol{q}, \qquad \boldsymbol{q} \in \mathbb{R}^r \tag{1.17}$$

Substituting into the governing equations and enforcing orthogonality of the residual to the reduced space yields the projected system:

$$\mathbf{K}_{\text{red}}\, \boldsymbol{q} = \boldsymbol{F}_{\text{red}}, \qquad \mathbf{K}_{\text{red}} = \mathbf{\Phi}^T \mathbf{K} \mathbf{\Phi}, \quad \boldsymbol{F}_{\text{red}} = \mathbf{\Phi}^T \boldsymbol{F} \tag{1.18}$$

For affine parameter dependence $\mathbf{K}(\mu) = \sum_i \theta_i(\mu)\mathbf{K}_i$, the projected operators can be pre-computed offline, making the online phase independent of the full dimension N.

1.3.4 Hyper-Reduction

For nonlinear or non-affine problems, evaluating $\boldsymbol{F}_{\text{int}}(\mathbf{\Phi}\boldsymbol{q})$ still requires assembly over the full mesh. Hyper-reduction addresses this by approximating the internal forces using only a subset of integration points:

- **DEIM (Discrete Empirical Interpolation Method):** Approximates nonlinear functions via interpolation at selected spatial indices.
- **ECSW (Energy-Conserving Sampling and Weighting):** Selects a reduced set of elements with optimized weights to preserve the strain energy, ensuring stability of the reduced model.

The combination of Galerkin projection with hyper-reduction yields a fully reduced nonlinear ROM where both the system size and the assembly cost are independent of N.

Chapter 2

Geometrically Parameterized Nonlinear Mechanics in 2D

This chapter details the mathematical formulation and computational methodology for solving parametric, geometrically nonlinear elasticity problems in two dimensions using IGA and ROM.

2.1 Weak Formulation on a Reference Configuration

2.1.1 Total Lagrangian Formulation

All quantities are referred to the undeformed reference configuration Ω_0. The principle of virtual work states: find $\boldsymbol{u} \in \mathcal{V}$ such that for all $\delta\boldsymbol{u} \in \mathcal{V}_0$:

$$\int_{\Omega_0} \mathbf{S}(\boldsymbol{u}) : \delta\mathbf{E}(\boldsymbol{u}, \delta\boldsymbol{u}) \, \mathrm{d}\Omega_0 = \int_{\Gamma_N} \boldsymbol{t} \cdot \delta\boldsymbol{u} \, \mathrm{d}\Gamma + \int_{\Omega_0} \boldsymbol{b} \cdot \delta\boldsymbol{u} \, \mathrm{d}\Omega_0 \tag{2.1}$$

where $\mathbf{S}$ is the second Piola–Kirchhoff stress, $\delta\mathbf{E}$ is the variation of the Green–Lagrange strain, $\boldsymbol{t}$ represents prescribed tractions, and $\boldsymbol{b}$ body forces.

2.1.2 Variation of the Green–Lagrange Strain

The variation of $\mathbf{E}$ with respect to a virtual displacement $\delta\boldsymbol{u}$ is:

$$\delta\mathbf{E} = \frac{1}{2}\left(\mathbf{F}^T \nabla\delta\boldsymbol{u} + (\nabla\delta\boldsymbol{u})^T \mathbf{F}\right) \tag{2.2}$$

This expression is linear in $\delta\boldsymbol{u}$ but depends nonlinearly on the current displacement $\boldsymbol{u}$ through the deformation gradient $\mathbf{F}$.

2.1.3 Parameterized Reference Domain

When the geometry is parameterized by μ (e.g., aspect ratio, hole radius), the physical domain $\Omega(\mu)$ varies. In the IGA framework, this is handled naturally through parameter-dependent control points:

$$\boldsymbol{x}(\xi, \mu) = \sum_{i=1}^{n} R_i(\xi)\, \boldsymbol{P}_i(\mu) \tag{2.3}$$

All integrals are evaluated on the fixed master domain $\hat{\Omega} = [0, 1]^2$, with the Jacobian $\mathbf{J}(\xi, \mu) = \partial \boldsymbol{x}/\partial \xi$ absorbing the parameter dependence:

$$\int_{\Omega(\mu)} (\cdot)\, \mathrm{d}\Omega = \int_{\hat{\Omega}} (\cdot)\, |\det \mathbf{J}(\xi, \mu)|\, \mathrm{d}\hat{\Omega} \tag{2.4}$$

2.2 IGA Discretization

2.2.1 2D NURBS Approximation

The displacement field is approximated using tensor-product NURBS:

$$\boldsymbol{u}^h(\xi, \eta) = \sum_{A=1}^{N_{cp}} R_A(\xi, \eta)\, \boldsymbol{d}_A, \qquad R_A = \frac{N_i^p(\xi)\, M_j^q(\eta)\, w_{ij}}{W(\xi, \eta)} \tag{2.5}$$

where $N_{cp} = n \times m$ is the total number of control points and $W(\xi, \eta)$ is the weighting function.

2.2.2 Stiffness Matrix Assembly

The tangent stiffness matrix is assembled element-by-element using Gauss quadrature on the master domain:

$$K_{AB}^{IJ} = \int_{\hat{\Omega}} \frac{\partial R_A}{\partial x_I}\, C_{IJKL}\, \frac{\partial R_B}{\partial x_K}\, |\det \mathbf{J}|\, \mathrm{d}\hat{\Omega} \tag{2.6}$$

Physical derivatives are obtained through the Jacobian inverse:

$$\begin{bmatrix} \partial R_A/\partial x \\ \partial R_A/\partial y \end{bmatrix} = \mathbf{J}^{-1} \begin{bmatrix} \partial R_A/\partial \xi \\ \partial R_A/\partial \eta \end{bmatrix} \tag{2.7}$$

For plane stress conditions, the elasticity matrix is:

$$\mathbf{C} = \frac{E}{1-\nu^2} \begin{bmatrix} 1 & \nu & 0 \\ \nu & 1 & 0 \\ 0 & 0 & \frac{1-\nu}{2} \end{bmatrix} \tag{2.8}$$

2.2.3 Boundary Conditions

Dirichlet boundary conditions are applied using a penalty method with factor $\beta \approx 10^{12}$:

$$\Pi_{\text{penalty}} = \frac{1}{2}\beta \left| u_i - \bar{u}_i \right|^2 \tag{2.9}$$

This approach is also used to enforce compatibility at degenerate NURBS points (e.g., collapsed corners in the plate-with-hole geometry).

2.3 Offline Simulations

2.3.1 Parameter Space Definition

The parameter vector $\mu \in \mathcal{P}$ is defined as:

Table 2.1: Parameter space definition for the 2D test cases.

Parameter	**Symbol**	**Description**	**Range**
Young's Modulus	E	Material stiffness	$[10^6, 2 \times 10^8]$ Pa
Poisson's Ratio	ν	Transverse strain ratio	$[0.25, 0.49]$
Load Intensity	F	Applied force magnitude	$[0, 1000]$ N
Aspect Ratio	$\alpha = L/H$	Geometry parameter	$[5, 20]$

2.3.2 Latin Hypercube Sampling

The training set $\{\mu_1, \ldots, \mu_{N_s}\}$ is generated using Latin Hypercube Sampling (LHS) to ensure uniform coverage of the parameter space. An initial set of 25 snapshots is used for POD validation, with 100+ snapshots for the final hyper-reduced model.

2.3.3 Snapshot Database Generation

For each parameter sample μ_k, the full-order model is solved using Newton–Raphson iteration:

$$\mathbf{S} = [\boldsymbol{u}(\mu_1),\ \boldsymbol{u}(\mu_2),\ \ldots,\ \boldsymbol{u}(\mu_{N_s})] \in \mathbb{R}^{2N_{cp} \times N_s} \tag{2.10}$$

Each column contains the converged displacement field (both u_x and u_y components interleaved) for one parameter configuration.

2.3.4 POD Basis Extraction

The SVD of the snapshot matrix yields the reduced basis:

$$\mathbf{S} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^T, \qquad \mathbf{\Phi} = \mathbf{U}_{[:,1:r]} \tag{2.11}$$

The number of retained modes r is determined by the energy criterion (Eq. 1.16). For the 2D plate benchmarks, typically $r \leq 5$ modes capture $> 99.99\%$ of the system energy.

2.4 Online Simulations

2.4.1 Galerkin-Projected Nonlinear ROM

For a new parameter μ^*, the online phase solves the reduced nonlinear system iteratively:

Algorithm 1 Online NL-ROM Query

Require: Reduced basis $\mathbf{\Phi}$, parameter μ^*, tolerance ε
1: Initialize $\boldsymbol{q}^{(0)} = \mathbf{0}$
2: **for** $k = 0, 1, 2, \ldots$ **do**
3: Reconstruct: $\boldsymbol{u}^{(k)} = \mathbf{\Phi}\,\boldsymbol{q}^{(k)}$
4: Assemble $\mathbf{K}_T(\boldsymbol{u}^{(k)}, \mu^*)$ and $\boldsymbol{F}_{\text{int}}(\boldsymbol{u}^{(k)}, \mu^*)$
5: Project: $\mathbf{K}_{\text{red}} = \mathbf{\Phi}^T\mathbf{K}_T\mathbf{\Phi}, \quad \boldsymbol{R}_{\text{red}} = \mathbf{\Phi}^T(\boldsymbol{F}_{\text{ext}} - \boldsymbol{F}_{\text{int}})$
6: Solve: $\mathbf{K}_{\text{red}}\,\Delta\boldsymbol{q} = \boldsymbol{R}_{\text{red}}$
7: Update: $\boldsymbol{q}^{(k+1)} = \boldsymbol{q}^{(k)} + \Delta\boldsymbol{q}$
8: **if** $\|\Delta\boldsymbol{q}\| < \varepsilon$ **then**
9: **break** (converged)
10: **end if**
11: **end for**
12: **return** $\boldsymbol{u} = \mathbf{\Phi}\,\boldsymbol{q}$

2.4.2 Performance Targets

Table 2.2: Performance comparison: FOM vs. ROM.

Metric	**FOM**	**ROM**
System size	2000×2000	10×10
Solve time per query	$\sim 2\,\text{s}$	$< 10\,\text{ms}$
Memory footprint	$\sim 50\,\text{MB}$	$\sim 10\,\text{KB}$
Relative L^2 error	—	$< 1\%$

2.4.3 Data Serialization

Offline results (reduced basis $\mathbf{\Phi}$, projected operators, mesh metadata) are serialized to portable JSON format for consumption by the web-based Digital Twin frontend.

Chapter 3

Real-Time Pedagogical Application

This chapter presents the design, implementation, and validation of the web-based Digital Twin platform that serves as both a research tool and an interactive pedagogical environment.

3.1 Workflow with AI

3.1.1 AI-Assisted Development Methodology

The development of this project leveraged AI-assisted coding tools throughout the software engineering lifecycle. This approach enabled a single developer to build a full-stack computational mechanics platform within the internship timeframe. The workflow is structured as follows:

1. **Mathematical formulation:** Classical derivation of weak forms, discretization, and reduction operators, validated against reference textbooks [1, 3].

2. **Code generation:** AI tools assisted in translating mathematical formulations into optimized JavaScript implementations, particularly for repetitive tasks such as tensor-product assembly loops and matrix operations.

3. **Debugging and validation:** Each computational module was validated against analytical solutions or reference implementations before integration.

4. **Documentation:** Theory pages and interactive visualizations were co-developed alongside the simulation code, ensuring pedagogical consistency.

3.1.2 Quality Assurance

All AI-generated code underwent rigorous verification:

- Benchmark comparison against analytical solutions (Kirsch plate, Euler–Bernoulli beam)
- Convergence studies under h- and p-refinement
- Cross-validation of ROM results against FOM reference solutions

3.2 Presentation of the Project

3.2.1 Architecture Overview

The application follows a client-side architecture where all computations run natively in the browser, eliminating server dependencies and ensuring accessibility.



Figure 3.1: High-level architecture: Offline–Online workflow.

3.2.2 Front-End

The front-end is built with vanilla HTML, CSS, and JavaScript, enhanced with:

- **Three.js:** WebGL-based 3D rendering for real-time deformation visualization at 60 FPS
- **Chart.js:** Interactive plots for convergence metrics, scree plots, stress–strain curves, and force–displacement diagrams
- **KaTeX:** Client-side LaTeX rendering for mathematical documentation integrated directly into the simulation pages
- **Responsive design:** Glassmorphic UI with performance overlays tracking FPS and CPU transit time

3.2.3 Back-End (Computational Core)

The computational core is implemented entirely in JavaScript, organized into modular engines:

Table 3.1: Core JavaScript modules.

Module	Description
`nurbs-2d.js`	NURBS basis evaluation, surface mapping, Jacobian computation, refinement utilities
`iga-solver-2d.js`	Stiffness assembly, boundary conditions, stress recovery for 2D plane stress problems
`iga-nonlinear.js`	Newton–Raphson solver with Green–Lagrange strain, tangent stiffness updates
`rom-engine.js`	POD extraction (via ml-matrix SVD), Galerkin projection, online query loop
`nurbs-presets.js`	Pre-defined geometries (cantilever plate, plate with hole, parametric shapes)

3.2.4 Simulation Hub

The project is deployed as a GitHub Pages site with a central simulation hub providing access to 26+ interactive simulation modules organized by phase:

- **Phase 1 (1D Foundations):** B-spline/NURBS basis, 1D IGA solver, 1D ROM benchmark, nonlinear 1D

- **Phase 2 (2D Core):** Surface mapping, stiffness assembly, Kirsch benchmark, snapshot generation, SVD/POD lab, Galerkin projection

- **Phase 3 (Nonlinear 2D):** Geometric nonlinearity solver, interactive analytics, NL-ROM

3.3 Benchmarks

3.3.1 Kirsch Plate with Hole

The classical infinite plate with a circular hole under uniaxial tension serves as the primary validation benchmark. The analytical stress concentration factor is $K_t = 3$.

3.3.2 ROM Accuracy

The ROM approximation error is measured in the relative L^2 norm:

$$e_{\text{rel}} = \frac{\|\boldsymbol{u}_{\text{FOM}} - \boldsymbol{\Phi}\boldsymbol{q}_{\text{ROM}}\|_2}{\|\boldsymbol{u}_{\text{FOM}}\|_2} \tag{3.1}$$

3.3.3 Computational Speedup

The speedup factor is defined as:

$$\text{Speedup} = \frac{t_{\text{FOM}}}{t_{\text{ROM}}} \tag{3.2}$$

Target: achieve speedup $> 200\times$ for the linear case and $> 50\times$ for the nonlinear case with hyper-reduction.

3.4 Examples of Use

3.4.1 Interactive Parameter Exploration

Students can manipulate material properties (E, ν), loading conditions (F), and geometric parameters (α) via sliders and observe the structural response in real time. The platform visualizes:

- Deformed shape with color-coded displacement/stress fields
- Force–displacement curves showing nonlinear stiffening
- Convergence history of Newton–Raphson iterations
- POD mode shapes and energy capture (scree plots)

3.4.2 Pedagogical Scenarios

1. **Linear vs. Nonlinear Comparison:** Students observe how geometric stiffening limits displacement under large loads, contrasting with the unbounded linear prediction.
2. **ROM Fidelity Study:** By varying the number of retained POD modes, students visualize the trade-off between model reduction and approximation accuracy.
3. **Refinement Studies:** Interactive h- and p-refinement labs demonstrate convergence behavior unique to IGA (higher regularity, k-refinement).

4. **Digital Twin Concept:** The eventual coupling with a 3D-printed physical model demonstrates the correlation between theoretical predictions and physical measurements.

Chapter 4

Extension to 3D Applications

This chapter outlines the planned extension of the methodology to three-dimensional problems. Content will be developed as the project progresses.

4.1 3D NURBS Volume Parameterization

The extension to 3D requires trivariate NURBS volumes:

$$\boldsymbol{x}(\xi, \eta, \zeta) = \sum_{i=1}^{n} \sum_{j=1}^{m} \sum_{k=1}^{l} R_{ijk}^{p,q,r}(\xi, \eta, \zeta)\, \boldsymbol{P}_{ijk} \tag{4.1}$$

Key challenges include:

- Increased dimensionality of the snapshot matrix ($3 \times N_{cp}$ DOFs per snapshot)
- Volumetric Gauss quadrature with n_g^3 integration points
- Multi-patch NURBS geometries requiring coupling conditions

4.2 3D Nonlinear Assembly

The 3D stiffness assembly follows the same structure as the 2D case, with the elasticity tensor for isotropic materials in full 3D (6×6 Voigt matrix) and the deformation gradient becoming a 3×3 tensor.

4.3 3D ROM and Visualization

The Three.js rendering pipeline already supports 3D WebGL visualization. The ROM framework generalizes directly, though hyper-reduction becomes even more critical due

to the increased assembly cost.

Conclusion and Perspectives

Conclusion

This internship has addressed the development of a real-time Digital Twin platform for nonlinear structural mechanics, combining Isogeometric Analysis with projection-based Reduced Order Modelling.

The main contributions of this work are:

1. **A complete IGA computational core in JavaScript**, capable of assembling 2D stiffness matrices, solving linear and geometrically nonlinear problems via Newton–Raphson iteration, and recovering stress fields—all running natively in the browser without server-side dependencies.

2. **A ROM pipeline from snapshots to real-time queries**, implementing POD via SVD for basis extraction, Galerkin projection for operator reduction, and parametric online evaluation achieving solve times under 10 ms.

3. **An interactive pedagogical platform** with 26+ simulation modules, real-time 3D visualization via Three.js, and integrated mathematical documentation, providing students with hands-on experience in computational mechanics concepts.

4. **Validation against analytical benchmarks**, including the Kirsch plate-with-hole problem and cantilever beam convergence studies, demonstrating the accuracy and robustness of the implementation.

The project demonstrates that modern web technologies can deliver research-grade computational mechanics tools accessible to any user with a browser, lowering the barrier to entry for advanced simulation concepts.

Perspectives

Several directions for future work emerge from this project:

- **Hyper-reduction implementation:** Complete the DEIM and ECSW implementations to achieve full independence of the online phase from the full-order dimension, targeting 100× speedup for nonlinear problems.
- **3D extension:** Extend the methodology to trivariate NURBS volumes for industrially relevant three-dimensional geometries, leveraging WebAssembly for performance-critical assembly routines.
- **Physical Digital Twin coupling:** Connect the virtual simulation to a 3D-printed physical model instrumented with strain gauges or accelerometers, enabling real-time comparison between numerical predictions and experimental measurements.
- **Dynamic problems:** Extend the ROM framework to transient dynamics using Newmark-β time integration, enabling the simulation of vibration and impact phenomena.
- **Advanced material models:** Incorporate hyperelastic models beyond Saint Venant–Kirchhoff (e.g., Neo-Hookean, Mooney–Rivlin) for more physically realistic large-strain behavior.
- **Machine learning integration:** Explore neural network-based surrogate models (e.g., DeepONet, physics-informed neural networks) as alternatives or complements to classical ROM for highly nonlinear parameter regimes.
- **Multi-physics:** Extend to fluid–structure interaction problems, building on the supervisor's prior work on sloshing applications [2].

Appendix A

Supplementary Material

A.1 Cox–de Boor Recursion: Detailed Derivation

The B-spline basis functions of degree p over a knot vector $\Xi = \{\xi_1, \ldots, \xi_{n+p+1}\}$ are defined recursively. The zeroth-order ($p = 0$) basis functions are piecewise constants:

$$N_{i,0}(\xi) = \begin{cases} 1 & \text{if } \xi_i \leq \xi < \xi_{i+1} \\ 0 & \text{otherwise} \end{cases} \tag{A.1}$$

Higher-order functions are computed by the recursion:

$$N_{i,p}(\xi) = \frac{\xi - \xi_i}{\xi_{i+p} - \xi_i} N_{i,p-1}(\xi) + \frac{\xi_{i+p+1} - \xi}{\xi_{i+p+1} - \xi_{i+1}} N_{i+1,p-1}(\xi) \tag{A.2}$$

with the convention $0/0 = 0$.

A.2 Gauss Quadrature Rules

Table A.1: Gauss–Legendre quadrature points and weights for $n_g = 1, \ldots, 4$.

n_g	Points ξ_i	Weights w_i
1	0.0	2.0
2	± 0.5774	1.0
3	$0.0, \pm 0.7746$	$0.8889, 0.5556$
4	$\pm 0.3400, \pm 0.8611$	$0.6521, 0.3479$

A.3 Project Repository Structure

Listing A.1: Repository file tree.

```
internship-cnam/
|-- app/
|   |-- index.html              (Simulation Hub)
|   |-- simulations/
|       |-- iga-sim/             (Phase 1.0: B-Spline Basis)
|       |-- iga-sim-1.7/         (Phase 1.7: 1D ROM Benchmark)
|       |-- iga-sim-nl/          (Phase 1.NL: Nonlinear 1D)
|       |-- iga-sim-2b2/         (Phase 2B: Kirsch Benchmark)
|       |-- iga-sim-2d1/         (Phase 2D.1: SVD/POD Lab)
|       |-- iga-sim-3a/          (Phase 3A: 2D Nonlinear)
|       |-- phase-2-core/src/    (2D Engine Core)
|       |-- phase-3-core/src/    (NL Engine Core)
|-- theory/                      (Interactive Theory Pages)
|-- docs/                        (Architecture, Logs)
|-- report/                      (This LaTeX report)
|-- README.md
```

Bibliography

[1] J. Austin Cottrell, Thomas J. R. Hughes, and Yuri Bazilevs. *Isogeometric Analysis: Toward Integration of CAD and FEA*. John Wiley & Sons, 2009. ISBN 978-0470748732.

[2] Christophe Hoareau et al. Reduced order modelling for sloshing problems using IGA and hyper-reduction. *Computational Mechanics*, 2025. Supervisor's reference paper.

[3] Thomas J. R. Hughes, John A. Cottrell, and Yuri Bazilevs. Isogeometric analysis: CAD, finite elements, NURBS, exact geometry and mesh refinement. *Computer Methods in Applied Mechanics and Engineering*, 194(39–41):4135–4195, 2005. doi: 10.1016/j.cma.2004.10.008.