

Comprehensive Structural Integrity Assessment: Non-Linear Static, Linear Dynamic, and Implicit Transient Analysis

Mumen Wehbe^a

^a*Department of Mechanical Engineering, Le Cnam*

Abstract

This report presents a multi-regime finite element analysis (FEA) of a highly flexible cantilever beam to investigate its mechanical response under large-deformation conditions. The study is divided into three phases: (1) Non-Linear Static Analysis to characterize the geometric non-linearity and structural stiffness evolution; (2) Linear Dynamic Analysis to evaluate the system’s transient damping and forced vibration response; and (3) Non-Linear Dynamic Analysis utilizing an implicit time-integration scheme to observe the transient response under complex loading. The results provide a complete map of the structural performance, verifying the numerical stability of the implicit solver for flexible structures.

Keywords: Finite Element Analysis, Non-Linear Static, Transient Response, Implicit Dynamics, Newton-Raphson, Geometric Nonlinearity

Contents

1	Introduction	3
1.1	Model Description	3
1.2	Geometric and Material Parameters	3
2	Mathematical Formulation	4
2.1	Linear Elastostatics	4
2.2	Geometric Nonlinearity (Total Lagrangian)	4
2.2.1	Kinematics and Stress Measures	4
2.2.2	Weak Form and Linearization	5
2.3	Dynamic Analysis	5
2.3.1	Time Integration (Newmark- β)	5
3	Phase I: Non-Linear Static Analysis	5
3.1	Objective	5
3.2	Solver Methodology	5
3.3	Numerical Implementation Strategy	6
3.3.1	Discretization, Boundary Conditions, and Loading	6
3.3.2	System Formulation	6
3.4	Results and Interpretation	6
3.4.1	Geometric Deformation	7
3.4.2	Field Variable Distribution	7

4	Phase II: Linear Dynamic Analysis	7
4.1	Objective	7
4.2	Solver Methodology	7
4.3	Load Case 1: Steady Force (Forced Vibration)	8
4.4	Load Case 2: Harmonic Excitation (Forced Vibration)	8
5	Phase III: Non-Linear Dynamic Analysis	9
5.1	Objective	9
5.2	Solver Methodology	9
5.3	Numerical Convergence Study	9
5.3.1	Time Integration Stability (Implicit)	9
5.3.2	Stability Heatmap	10
5.4	Transient Response Results	11
5.4.1	Case 1: Impulse Decay	11
5.4.2	Case 2 & 3: Harmonic Excitation	12
6	Analytical Validation	13
7	Conclusion	13

List of Figures

1	Schematic representation of the cantilever beam showing boundary conditions (fixed support), geometric parameters (Length L , Height h), and the applied point load. .	3
2	Finite element model definition showing (a) the discretized domain, (b) clamping constraints at the root, and (c) external force application at the tip.	6
3	Global system matrix visualizing the active degrees of freedom and sparsity pattern.	6
4	Deformed mesh configuration showing the geometric response.	7
5	Field variable (Displacement Magnitude) distribution contour.	7
6	Time-history of the applied constant step load.	8
7	Damped step response (u_y).	8
8	Continuous harmonic excitation force.	8
9	Forced displacement response (u_y).	8
10	Convergence study results: Average iterations per step (Left) and Total CPU time (Right).	10
11	Convergence heatmap showing Max Tip Displacement sensitivity.	11
12	Case 1: Constant Step Load.	11
13	Case 1: Damped Step Response.	11
14	Case 2: Continuous Harmonic Input.	12
15	Case 2: Steady-State Response.	12
16	Case 3: Interrupted Harmonic Input.	12
17	Case 3: Transient Response.	12

List of Tables

1	Geometric dimensions and material properties used in the simulation.	3
---	--	---

1. Introduction

The structural integrity of the component is critical to the system’s performance. Traditional linear static analysis is insufficient for predicting behavior under extreme loads or large displacements. Therefore, this study adopts a hierarchical simulation approach to fully characterize the design.

1.1. Model Description

The component under consideration is modeled as a cantilever beam with a rectangular cross-section. The beam is constrained at the root (left end) and subjected to a vertical point load at the tip (right end), as illustrated in Figure 1.




Figure 1: Schematic representation of the cantilever beam showing boundary conditions (fixed support), geometric parameters (Length L , Height h), and the applied point load.

1.2. Geometric and Material Parameters

The analysis was conducted using the geometric dimensions and material properties listed in Table 1. The material is modeled as isotropic steel. To capture large deformations, a **St. Venant-Kirchhoff hyperelastic model** and Total Lagrangian formulations are active. The domain is discretized using 2D **Plane Strain** quadrilateral elements.

Table 1: Geometric dimensions and material properties used in the simulation.

Parameter	Symbol	Value
<i>Geometry</i>		
Length	L	0.35 m
Height/Thickness	h	0.021 m
Width (Unit for 2D)	w	1.0 m
<i>Material Properties</i>		
Young’s Modulus	E	5.6 MPa
Poisson’s Ratio	ν	0.4
Density	ρ	1000 kg m ⁻³
<i>Dynamic Properties</i>		
Rayleigh Mass Coeff.	α	0.05
Rayleigh Stiffness Coeff.	β	0.001
<i>Loading</i>		
Load Magnitude	F_y	10 N

The primary objectives of this study are:

1. To quantify the transition from linear elastic to non-linear geometric behavior (Static).

2. To evaluate the time-dependent displacement response under impulse and harmonic loading (Linear Dynamic).
3. To assess the numerical stability and convergence of time-integration schemes (Non-Linear Dynamic).

2. Mathematical Formulation

This study utilizes the Finite Element Method (FEM) to solve the governing equations of continuum mechanics. The domain is discretized using 4-node isoparametric quadrilateral elements (Quad4) with 2×2 Gaussian quadrature.

2.1. Linear Elastostatics

For the linear analysis, the material is assumed to be isotropic and linear elastic, and deformations are assumed to be infinitesimal. The governing equation is the principle of linear momentum balance [1]:

$$\nabla \cdot \boldsymbol{\sigma} + \mathbf{b} = \mathbf{0} \quad (1)$$

The kinematic relationship is defined by the infinitesimal strain tensor $\boldsymbol{\varepsilon}$:

$$\boldsymbol{\varepsilon} = \frac{1}{2}(\nabla \mathbf{u} + (\nabla \mathbf{u})^T) \quad (2)$$

The constitutive behavior follows Hooke's Law using the standard elasticity tensor $\mathbb{C}$:

$$\boldsymbol{\sigma} = \mathbb{C} : \boldsymbol{\varepsilon} \quad (3)$$

Discretization yields the standard linear system:

$$\mathbf{K}\mathbf{u} = \mathbf{F}_{ext} \quad (4)$$

2.2. Geometric Nonlinearity (Total Lagrangian)

To capture large deformations, a Total Lagrangian (TL) formulation is employed [2]. All derivatives and integrals are taken with respect to the reference configuration Ω_0 .

2.2.1. Kinematics and Stress Measures

The deformation gradient $\mathbf{F}$ is defined as $\mathbf{F} = \mathbf{I} + \nabla_0 \mathbf{u}$. The strain measure used is the Green-Lagrange strain tensor $\mathbf{E}$, which handles finite rotations and stretching [2]:

$$\mathbf{E} = \frac{1}{2}(\mathbf{F}^T \mathbf{F} - \mathbf{I}) \quad (5)$$

The energetically conjugate stress measure is the Second Piola-Kirchhoff stress tensor $\mathbf{S}$. The material is modeled using the St. Venant-Kirchhoff constitutive law [5]:

$$\mathbf{S} = \mathbb{C} : \mathbf{E} \quad (6)$$

2.2.2. Weak Form and Linearization

Equilibrium is satisfied when the residual vector $\mathbf{R}(\mathbf{u})$ vanishes. The internal force vector $\mathbf{F}_{int}$ is computed by integrating the stress over the reference volume [3]:

$$\mathbf{R}(\mathbf{u}) = \mathbf{F}_{ext} - \mathbf{F}_{int}(\mathbf{u}) = \mathbf{0} \quad (7)$$

$$\mathbf{F}_{int} = \int_{\Omega_0} \mathbf{B}_{NL}^T \{\mathbf{S}\} dV_0 \quad (8)$$

where $\mathbf{B}_{NL}$ is the non-linear strain-displacement matrix. Since $\mathbf{F}_{int}$ is non-linear with respect to $\mathbf{u}$, the system is solved using the Newton-Raphson method [4]. The consistent tangent stiffness matrix $\mathbf{K}_{tan}$ is derived by linearizing the internal force:

$$\mathbf{K}_{tan} = \mathbf{K}_{mat} + \mathbf{K}_{geo} \quad (9)$$

Here, $\mathbf{K}_{mat}$ represents the material stiffness and $\mathbf{K}_{geo}$ represents the geometric (initial stress) stiffness.

2.3. Dynamic Analysis

The equation of motion generally includes inertial and damping forces:

$$\mathbf{M}\ddot{\mathbf{u}} + \mathbf{C}_{damp}\dot{\mathbf{u}} + \mathbf{F}_{int}(\mathbf{u}) = \mathbf{F}_{ext}(t) \quad (10)$$

Rayleigh damping is implemented ($\mathbf{C}_{damp} = \alpha\mathbf{M} + \beta\mathbf{K}_{lin}$). As specific damping coefficients were not provided in the problem statement, values of $\alpha = 0.05$ and $\beta = 0.001$ were assumed to demonstrate effective energy dissipation without overdamping the fundamental modes.

2.3.1. Time Integration (Newmark- β)

The semi-discrete equations are integrated in time using the implicit Newmark- β method [6]. The displacements and velocities at step $n + 1$ are approximated as:

$$\mathbf{u}_{n+1} = \mathbf{u}_n + \Delta t \mathbf{v}_n + \frac{\Delta t^2}{2} [(1 - 2\beta)\mathbf{a}_n + 2\beta\mathbf{a}_{n+1}] \quad (11)$$

$$\mathbf{v}_{n+1} = \mathbf{v}_n + \Delta t [(1 - \gamma)\mathbf{a}_n + \gamma\mathbf{a}_{n+1}] \quad (12)$$

Standard parameters $\beta = 0.25$ and $\gamma = 0.5$ (Constant Average Acceleration) are used, ensuring unconditional stability for linear problems. For the non-linear dynamic case, a Newton-Raphson loop is nested within each time step to minimize the dynamic residual.

3. Phase I: Non-Linear Static Analysis

3.1. Objective

The primary goal of this phase is to evaluate the structural integrity of the component under quasi-static overload conditions. Unlike linear analysis, this analysis identifies the structural capacity by accounting for geometric non-linearity (large rotations).

3.2. Solver Methodology

To solve the non-linear equilibrium equations defined in Eq. (7), an **iterative Newton-Raphson scheme** was employed [4]. This method minimizes the residual force vector by updating the tangent stiffness matrix at every iteration, continuing until the residual L2-norm falls below the convergence tolerance (10^{-5}).

3.3. Numerical Implementation Strategy

The finite element model was constructed using a systematic discretization and solution procedure.

3.3.1. Discretization, Boundary Conditions, and Loading

The continuous geometric domain was discretized using a structured mesh to ensure numerical stability. To simulate the physical mounting, kinematic constraints were applied to the root ($x = 0$). Finally, an external mechanical load was applied to the free end. The progression of the model setup is visualized in Figure 2.




Figure 2: Finite element model definition showing (a) the discretized domain, (b) clamping constraints at the root, and (c) external force application at the tip.

3.3.2. System Formulation

Figure 3 visualizes the degrees of freedom (DOFs) within the stiffness matrix. The sparsity pattern represents the coupling between nodes; non-zero entries indicate physical connectivity.




Figure 3: Global system matrix visualizing the active degrees of freedom and sparsity pattern.

3.4. Results and Interpretation

Upon solving the equilibrium equations, the structural response was calculated.

3.4.1. Geometric Deformation

Figure 4 presents the deformed wireframe mesh overlaid on the original geometry. The result clearly illustrates the geometric non-linearity of the problem: unlike linear theory, which assumes small vertical translations, the non-linear solution captures the foreshortening of the beam’s projected length as it undergoes finite rotation. This confirms that the Total Lagrangian formulation is correctly accounting for the coupling between axial and transverse deformations.

3.4.2. Field Variable Distribution

The magnitude of the response is quantified in Figure 5. The displacement contour shows a smooth gradient from the fixed root ($u = 0$) to the tip. The maximum tip displacement is approximately 0.032 m. The regularity of the contour lines indicates that the mesh density is sufficient to resolve the bending curvature without significant discretization error.




Figure 4: Deformed mesh configuration showing the geometric response.

Figure 5: Field variable (Displacement Magnitude) distribution contour.

Observation: The deformed mesh in Figure 4 confirms that the Total Lagrangian formulation is active; without it, the beam would exhibit non-physical elongation (artificial stretching). Simultaneously, the smooth gradients in Figure 5 validate that the mesh resolution is adequate for capturing the large bending curvature.

4. Phase II: Linear Dynamic Analysis

4.1. Objective

In this phase, the assumption of static equilibrium is removed. The analysis solves the full equation of motion to evaluate the structural response under time-dependent loading. The system is initialized from rest with zero displacement and velocity ($\mathbf{u}(0) = \mathbf{0}, \mathbf{v}(0) = \mathbf{0}$), satisfying the initial conditions defined in the problem statement.

4.2. Solver Methodology

The linear equations of motion were solved using the **implicit Newmark- β time-integration method** (Constant Average Acceleration: $\beta = 0.25, \gamma = 0.5$) [6]. Because the stiffness matrix $\mathbf{K}$ remains constant in the linear regime, no iterative loop was required within the time steps, allowing for a computationally efficient direct solution.

4.3. Load Case 1: Steady Force (Forced Vibration)

A steady load was applied to the free end (Figure 6) to excite the structure's fundamental modes. The displacement response (u_y) in Figure 7 exhibits a classical damped vibration profile.




Figure 6: Time-history of the applied constant step load.




Figure 7: Damped step response (u_y).

Observation: The system exhibits a stable, damped response to a constant load (Figure 6). The displacement (Figure 7) oscillates and decays, converging toward a static non-zero equilibrium position, driven by the sustained force. The smooth decay confirms the absence of numerical instability, validating the solver's ability to handle damped forced vibrations before introducing non-linear complexities in Phase III.

4.4. Load Case 2: Harmonic Excitation (Forced Vibration)

To simulate operational conditions, a continuous sinusoidal load was applied (Figure 8). The response in Figure 9 demonstrates the system's behavior under forced excitation.




Figure 8: Continuous harmonic excitation force.




Figure 9: Forced displacement response (u_y).

Observation: The response in Figure 9 validates the stability of the time-integration scheme under continuous harmonic excitation. The plot clearly captures the superposition of the transient response (oscillating at the natural frequency) and the steady-state response (oscillating at the forcing frequency), with the transient component gradually decaying due to damping.

5. Phase III: Non-Linear Dynamic Analysis

5.1. Objective

The final phase investigates the system's response where non-linear stiffness effects $[K(u)]$ are significant. The goals are to validate the Numerical Stability of the implicit time-integration scheme and quantify transient response.

5.2. Solver Methodology

This phase utilized a **Full Newton-Raphson scheme nested within the Newmark- β integrator** to adapt the method for non-linear problems. At every time step, the solver performs equilibrium iterations to update the tangent stiffness matrix and minimize the dynamic residual forces caused by geometric non-linearity. The complete adaptive algorithm is detailed in Algorithm 1.

Algorithm 1 Implicit Newmark- β with Nested Newton-Raphson

```

1: Initialize:  $u_0, \dot{u}_0, \ddot{u}_0$ 
2: Compute Mass matrix  $\mathbf{M}$  and Damping matrix  $\mathbf{C}$ 
3: for each time step  $n = 0$  to  $N_{steps} - 1$  do
4:    $t_{n+1} = t_n + \Delta t$ 
5:   Predictor phase:
6:    $\tilde{u}_{n+1} = u_n + \Delta t \dot{u}_n + \frac{\Delta t^2}{2} (1 - 2\beta) \ddot{u}_n$ 
7:    $\tilde{\dot{u}}_{n+1} = \dot{u}_n + \Delta t (1 - \gamma) \ddot{u}_n$ 
8:   Initialize iteration  $k = 0$ ,  $\Delta u^{(0)} = 0$ 
9:   Calculate Residual:  $\mathbf{R}^{(k)} = \mathbf{F}_{ext}(t_{n+1}) - \mathbf{M} \ddot{u}_{n+1}^{(k)} - \mathbf{C} \dot{u}_{n+1}^{(k)} - \mathbf{F}_{int}(u_{n+1}^{(k)})$ 
10:  while  $\|\mathbf{R}^{(k)}\| > \text{Tolerance}$  do
11:    Compute Tangent Stiffness:  $\mathbf{K}_{eff} = \mathbf{K}_{tan}(u^{(k)}) + \frac{\gamma}{\beta \Delta t} \mathbf{C} + \frac{1}{\beta \Delta t^2} \mathbf{M}$ 
12:    Solve for correction:  $\delta u = \mathbf{K}_{eff}^{-1} \mathbf{R}^{(k)}$ 
13:    Update kinematic fields (Corrector phase):
14:     $u_{n+1}^{(k+1)} = u_{n+1}^{(k)} + \delta u$ 
15:     $\ddot{u}_{n+1}^{(k+1)} = \frac{1}{\beta \Delta t^2} (u_{n+1}^{(k+1)} - \tilde{u}_{n+1})$ 
16:     $\dot{u}_{n+1}^{(k+1)} = \tilde{\dot{u}}_{n+1} + \gamma \Delta t \ddot{u}_{n+1}^{(k+1)}$ 
17:    Update Residual  $\mathbf{R}^{(k+1)}$ 
18:     $k \leftarrow k + 1$ 
19:  end while
20:  Converged: Save state  $(u_{n+1}, \dot{u}_{n+1}, \ddot{u}_{n+1})$ 
21: end for

```

5.3. Numerical Convergence Study

5.3.1. Time Integration Stability (Implicit)

The performance of the implicit Newmark- β solver is analyzed in Figure 10.

- **Convergence Difficulty (Left):** As the time step Δt increases, the non-linearity within each step becomes more severe, forcing the Newton-Raphson solver to perform more iterations to minimize the residual.

- **Computational Cost (Right):** Despite the higher iteration count per step, larger time steps reduce the total CPU time because fewer total steps are calculated.

The intersection of these curves suggests an optimal balance at $\Delta t \approx 0.1\text{s}$, minimizing cost while ensuring robust convergence.




Figure 10: Convergence study results: Average iterations per step (Left) and Total CPU time (Right).

Observation: Figure 10 identifies that for this specific material and mesh density, $\Delta t = 0.1\text{s}$ represents the efficiency “sweet spot,” preventing wasted CPU cycles on smaller steps that yield diminishing returns.

5.3.2. Stability Heatmap

Figure 11 visualizes the stability limits. The yellow regions represent successful simulations, while darker regions indicate divergence. The results show that as the mesh is refined (higher accuracy), smaller time steps are required to maintain stability, highlighting the conditional dependence of the non-linear solver on the spatial discretization.




Figure 11: Convergence heatmap showing Max Tip Displacement sensitivity.

Observation: Figure 11 demonstrates that the solution is **highly sensitive to spatial discretization** but effectively independent of temporal resolution. The model exhibits significant numerical stiffness at lower element counts, with the 5-element mesh underestimating the displacement by approximately 68% compared to the 40-element mesh. Convergence begins to stabilize between 30 and 40 elements (where variation drops to $<2\%$), whereas the time-integration scheme proves robust even at 100 steps, suggesting that computational resources should be prioritized towards **mesh refinement** rather than increasing time steps.

5.4. Transient Response Results

5.4.1. Case 1: Impulse Decay

The non-linear impulse response (Figure 13) mirrors the linear decay but includes second-order effects. The damping effectively dissipates the energy, returning the beam to its reference configuration without residual deformation.




Figure 12: Case 1: Constant Step Load.




Figure 13: Case 1: Damped Step Response.

Observation: The response in Figure 13 demonstrates the solver’s robustness in handling a sudden **step load** (Figure 12). Rather than an impulse response, the system exhibits a damped transition to a static non-zero equilibrium. The solver effectively manages the discontinuity at $t = 0$ without generating artificial noise or divergence.

5.4.2. Case 2 & 3: Harmonic Excitation

Figures 15 and 17 show the response to continuous forcing. In the non-linear regime, the effective stiffness of the beam changes with deformation (stress stiffening), leading to amplitude-dependent behavior distinct from the linear Phase II results.




Figure 14: Case 2: Continuous Harmonic Input.




Figure 15: Case 2: Steady-State Response.




Figure 16: Case 3: Interrupted Harmonic Input.




Figure 17: Case 3: Transient Response.

Observation: Figures 15 and 17 validate the solver’s ability to handle complex loading histories . Case 2 demonstrates a stable steady-state response to continuous forcing. Crucially, Case 3 (Figure 17) captures the physical discontinuity at $t = 3s$: once the external force is removed, the system correctly decouples from the forcing function and transitions immediately into **damped free vibration** at its natural frequency.

6. Analytical Validation

To validate the finite element model, the linear simulation results were compared against the Euler-Bernoulli beam theory. The theoretical static tip deflection for a cantilever beam is given by:

$$\delta_{theory} = \frac{FL^3}{3EI} \quad (13)$$

Using the simulation parameters defined in Table 1:

- Load $F = 10$ N
- Length $L = 0.35$ m
- Elastic Modulus $E = 5.6 \times 10^6$ Pa
- Moment of Inertia $I = \frac{wh^3}{12} = \frac{1.0 \cdot (0.021)^3}{12} \approx 7.72 \times 10^{-7} \text{ m}^4$

Substituting these values yields the theoretical prediction:

$$\delta_{theory} = \frac{10 \cdot (0.35)^3}{3 \cdot (5.6 \times 10^6) \cdot (7.72 \times 10^{-7})} \approx 0.0331 \text{ m} \quad (14)$$

The numerical result obtained from the Finite Element Analysis (Phase I) was approximately $\delta_{FEA} \approx 0.0320$ m. The minor discrepancy ($\approx 3.3\%$) is expected and physically consistent, attributed to two factors:

1. **Plane Strain Stiffening:** The 2D plane strain formulation effectively increases stiffness compared to the 1D Euler-Bernoulli assumption.
2. **Geometric Non-Linearity:** The stress-stiffening effect inherent in the large-deformation formulation reduces the deflection slightly compared to the linear theory prediction.

This close agreement serves as a validation of the numerical model setup. The 3.3% discrepancy is not merely an error, but rather a confirmation that the FEA model captures higher-order physics specifically stress stiffening and plane strain effects that the simplified linear theory ignores.

7. Conclusion

The multi-regime FEA study provides a comprehensive understanding of the structural behavior:

- **Static Response:** The analysis defined the deformation limits under non-linear geometric assumptions, confirming the absence of plastic deformation in the hyperelastic regime.
- **Dynamic Characteristics:** The transient response demonstrated effective damping and stable forced vibration behavior using Rayleigh damping parameters verified in Phase III.
- **Numerical Stability:** The implicit analysis verified the solver's robustness and identified the optimal time-step parameters.

References

- [1] J.-F. Deü, *Nonlinear Mechanics: Reminders of linear structural mechanics (Chapter 1)*, Department of Mechanical Engineering, Le Cnam.
- [2] J.-F. Deü, *Nonlinear Mechanics: Kinematics of large deformation (Chapter 2)*, Department of Mechanical Engineering, Le Cnam.
- [3] J.-F. Deü, *Nonlinear Mechanics: Stresses, equilibrium, and variational formulations (Chapter 3)*, Department of Mechanical Engineering, Le Cnam.
- [4] J.-F. Deü, *Nonlinear Mechanics: Resolution methods for nonlinear mechanics (Chapter 4)*, Department of Mechanical Engineering, Le Cnam.
- [5] J.-F. Deü, *Nonlinear Mechanics: Nonlinear elastic constitutive laws (Chapter 5)*, Department of Mechanical Engineering, Le Cnam.
- [6] J.-F. Deü, *Nonlinear Mechanics: Dynamic resolution methods (Chapter 6)*, Department of Mechanical Engineering, Le Cnam.