Advanced Autonomous Navigation Technologies for UAVs: Challenges and Opportunities

Issam SENHAJI-MOUHADDIB
Lab of Advanced Systems Engineering
Ibn Tofail University, ENSA
Kenitra, Morocco
issam.senhaji-mouhaddib@uit.ac.ma

Samir BOUZAKRI
Lab of Advanced Systems Engineering
Ibn Tofail University, ENSA
Kenitra, Morocco
samir.bouzakri@uit.ac.ma

Ismail LAGRAT
Lab of Advanced Systems Engineering
Ibn Tofail University, ENSA
Kenitra, Morocco
Ismail.lagrat@uit.ac.ma

2024 4th International Conference on Innovative Research in Applied Science, Engineering and Technology (IRASET) | 979-8-3503-0950-8/24/$31.00 ©2024 IEEE | DOI: 10.1109/IRASET60544.2024.10548645

***Abstract*— The utilization of Unmanned Aerial Vehicles (UAVs) has revolutionized numerous industries, with navigation being a crucial factor in ensuring their operational success. This literature review examines the subject of UAV navigation, discussing fundamental concepts, GPS-denied challenges, and cutting-edge technologies. The review commences with an explanation of the basic principles of UAV navigation, including the employment of IMUs, GPS, LiDAR, and Stereo Vision Systems. A dedicated section then delves into the challenges posed by GPS-denied environments, emphasizing the importance of GPS in navigation and exploring alternative approaches. The subsequent sections investigate advanced navigation technologies, such as INS/IMU, Multi-sensor Fusion, and AI applications. These innovative research areas cover enhancements to sensors, the development of hybrid navigation systems, deep learning for sensor fusion, and other related topics. The conclusion emphasizes the transformative potential of emerging technologies, providing a roadmap for researchers and practitioners. The identified research directions aim to address current limitations and develop next-generation UAV navigation systems capable of precise navigation in complex and challenging environments.**

Keywords: UAVs, Navigation, GPS-denied, INS, Multi-Sensor Fusion, Artificial Intelligence

I- INTRODUCTION

In the realm of modern technology, Unmanned Aerial Vehicles (UAVs), commonly known as drones, have emerged as pivotal players across diverse sectors, reshaping the landscape of various industries and research domains. These versatile aerial platforms come in a spectrum of classes and types, each designed with specific functionalities and applications in mind. From the nimble quadcopters navigating urban landscapes to the sophisticated fixed-wing UAVs surveying vast terrains, the taxonomy of UAVs encompasses a rich diversity of forms and capabilities.

Classes and Types of UAVs

UAVs can be broadly categorized into classes such as fixed-wing, rotary-wing, and hybrid configurations, each tailored for distinct purposes. Fixed-wing UAVs, with their endurance and speed, are well suited for large-scale surveys and mapping tasks. In contrast, rotary-wing UAVs, including quadcopters and hexacopters, excel in dynamic and confined environments, offering agile maneuverability. Hybrid designs combine features of both, offering a versatile solution to address varied operational requirements.

Roles and Missions of UAVs

UAVs assume a myriad of roles and missions, spanning applications in agriculture, environmental monitoring, surveillance, and disaster response. In agriculture, UAVs are deployed for precision farming, optimizing crop health assessments, and yield predictions. In surveillance, they serve as eyes in the sky during Intelligence, Surveillance, and Reconnaissance (ISR) missions, providing real-time insights for defense and security applications. These aerial assets prove instrumental in Search and Rescue (SAR) operations, accessing hard-to-reach areas, surveying disaster-stricken regions, and aiding in locating and assisting individuals in distress. Moreover, in disaster response scenarios, UAVs offer rapid and efficient means for damage assessment, situational awareness, and coordination of emergency efforts.[1]

UAV Autonomy

Autonomy stands as a defining characteristic of UAVs, enabling them to execute tasks with minimal human intervention. Advances in Artificial Intelligence (AI) and sensor technologies contribute to the development of autonomous UAVs capable of navigating complex environments, avoiding obstacles, and adapting to changing conditions. Such autonomy not only enhances operational efficiency but also unlocks new possibilities for UAVs to function collaboratively in swarms, facilitating collective decision-making and distributed tasks.

As we explore the multifaceted world of UAVs and their evolving capabilities, a fundamental aspect that warrants closer examination is their navigation. The next section delves into the intricate domain of UAV navigation, unraveling the key challenges, methodologies, and innovations that propel these aerial systems through the skies with precision and purpose.

II- UAV NAVIGATION:

2.1 Fundamentals of UAV Navigation

2.1.1 Inertial Measurement Units (IMUs)

In the realm of UAV navigation, Inertial Measurement Units (IMUs) stand as foundational elements, providing essential data on acceleration, angular rates, and magnetic fields. These sensors play a pivotal role in determining the UAV's orientation, contributing significantly to flight stability. IMUs achieve this by precisely measuring changes in velocity and angular motion, allowing for real-time adjustments that ensure optimal control and navigation capabilities.

2.1.2 Global Positioning System (GPS)

Integral to UAV navigation, Global Positioning System (GPS) receivers serve as primary tools for accurate positioning data. However, challenges emerge when navigating in GPS-denied environments, necessitating the seamless integration of alternative sensor technologies. In such scenarios, UAVs may experience signal obstructions or complete signal loss, prompting the need for robust sensor

979-8-3503-0950-8/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

fusion techniques. Overcoming these challenges requires sophisticated algorithms and the incorporation of complementary sensors to maintain precise navigation.

2.1.3 Computer Vision Systems

Computer Vision Systems, encompassing advanced cameras and depth sensors, significantly enhance UAV navigation. These systems play a multifaceted role, facilitating obstacle detection, terrain mapping, and visual odometry. Particularly valuable in environments where GPS signals face interference or are compromised, computer vision systems offer a rich source of data for autonomous navigation. The cameras capture real-time images, enabling the UAV to interpret and respond to its surroundings dynamically. Depth sensors, utilizing technologies like LiDAR or stereo vision, contribute to accurate three-dimensional mapping and obstacle avoidance, ensuring robust navigation capabilities even in challenging conditions.[2]–[5]

LiDAR Technology

Within the realm of computer vision, Light Detection and Ranging (LiDAR) technology deserves special mention. LiDAR sensors utilize laser beams to measure distances with exceptional precision, providing detailed 3D mapping of the environment. This high-resolution data is invaluable for navigating complex terrains and avoiding obstacles with a level of granularity that traditional cameras may not achieve.[6], [7]

Stereo Vision Systems

Stereo vision systems, leveraging the principles of triangulation, enhance depth perception by capturing images from two or more cameras with slightly offset viewpoints. This approach allows UAVs to perceive depth accurately, crucial for tasks such as terrain mapping and obstacle avoidance in GPS-challenged scenarios.

2.2 Challenges and Considerations

Environmental Factors: Wind gusts, turbulence, and even strong magnetic fields can throw off sensor readings and disrupt planned trajectories.

Dynamic Obstacles: Birds, balloons, and even other UAVs can become unexpected obstacles, requiring quick reflexes and agile maneuvers.

Real-Time Decision-Making: UAVs often operate in time-sensitive situations, demanding split-second decisions. Algorithms need to analyze sensor data, assess risks, and choose the optimal course of action in a blink of an eye.

III- UAV NAVIGATION IN GPS-DENIED ENVIRONMENT:

3.1 Importance of GPS in UAV Navigation

Global Positioning System (GPS) serves as a foundational pillar in UAV navigation, furnishing precise global positioning data crucial for flight control. This section delves into the technical intricacies of GPS, exploring the signals, data delivery to UAV receivers, and the diverse types of GPS data.

3.1.1 GPS Signals and their Characteristics

GPS relies on signals transmitted from a constellation of satellites orbiting the Earth. These signals, primarily in the L-band frequency, carry essential information for navigation. The key characteristics of GPS signals include:

Carrier Frequency: GPS signals operate in the L1 (1575.42 MHz) and L2 (1227.60 MHz) bands, with the carrier frequency providing a reference for determining distance.

Modulation Schemes: Signals are modulated with navigation data using Binary Phase Shift Keying (BPSK) for the L1 signal and Quadrature Phase Shift Keying (QPSK) for the L2 signal.

Navigation Message: Each signal includes a navigation message containing information about satellite orbits, clock corrections, and system status[8].

3.1.2 Data Delivery to UAV Receivers

UAV receivers rely on the collected GPS signals to compute their precise position and navigate through the airspace. The process involves:

Signal Reception: UAV receivers capture signals from multiple satellites simultaneously.

Pseudorange Measurements: By measuring the time delay between the transmission and reception of signals, UAV receivers calculate pseudoranges, providing an estimate of the distance to each satellite.

Multilateration: Using the pseudoranges from at least four satellites, UAV receivers perform multilateration to determine the UAV's 3D position.[9]

3.1.3 Types of GPS Data

GPS delivers diverse data types crucial for accurate UAV navigation:

Positional Data: Latitude, longitude, and altitude information pinpointing the UAV's location.

Velocity Data: Speed and direction of UAV movement derived from Doppler shifts in the received signals.

Timing Data: Precise timing information enabling synchronization of onboard systems.

Satellite Ephemeris Data: Orbital parameters of satellites aiding in precise position calculation.[10]

3.2 Challenges in GPS-Denied Environments

While GPS serves as a fundamental navigation tool, certain operational environments present challenges that may restrict or entirely block GPS signals, leaving UAVs without this vital positioning data. Urban canyons, dense foliage, buildings, and indoor spaces are among the environments where GPS signals can be compromised. Additionally, intentional interference, such as jamming or spoofing, poses a growing threat. In GPS-denied scenarios, UAVs face difficulties in maintaining accurate positioning and must rely on alternative navigation strategies to overcome these challenges. The next sections will explore these alternative strategies and ongoing research endeavors aimed at mitigating the impact of GPS limitations on UAV navigation.

3.3 Alternative Navigation Strategies

Exploring alternative navigation strategies becomes imperative in GPS-denied environments. Leveraging a combination of sensor fusion, artificial intelligence (AI) algorithms [11], data from Inertial Measurement Units (IMUs), and other sensors allows UAVs to maintain accurate positioning and navigate effectively despite the absence of GPS signals. In the context of navigating without GPS, a summary table of key research papers, including many surveys, can provide insights into various alternative strategies employed in UAV navigation. The following table highlights some seminal studies:

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

STUDY & DOMAIN	RESULTS	METHODOLOGY	GAPS & COMMENTS
[12], [13] **MSF**	Improved Long-Term Navigation Precision: The suggested linear-complexity Extended Kalman Filter (EKF) is anticipated to exhibit enhanced precision over prolonged durations, particularly in demanding settings. This improvement can be attributed to its proficient integration of loop closures.	Incorporation of Loop Closure: Upon detecting a loop closure, the EKF is expected to systematically integrate supplementary constraints during the update step. This process aims to refine preceding state estimates, thereby mitigating accumulated errors.	Multisensor integration Opportunities: A notable gap lies in the exploration of integrating visual-inertial data with a broader spectru of sensor modalities, such as GPS and Lidar. Keyframe Selection Optimization : the absence of detailed discussions on adaptive keyframe selection strategies represents a gap to the current understanding.
[14]–[27] **Visual-Inertial Odometry (VIO), Sensor Fusion**	Visual-inertial Odemetry (VIO) : A technique that fuses data from cameras and Inertial Measurement Units (IMUs) to estimate a device's motion and position in 3D space.	Structureless Filter Update: Use feature tracks and IMU data to update state estimates and uncertainties. Integration with other sensor modalities (GPS, LiDAR).	Challenges in terms of improving the computational efficiency and robustness of the underlying algorithms for applications in autonomous flight with micro aerial vehicles. Difficulty in using high-quality sensors and powerful processors due to constraints on size and weight.
[28] **MSF** **AI**	The study evaluates three representative strategies for UAV navigation in simulated indoor environments. Metrics used for evaluation include path length, deviation rate, and exploration efficiency.	The taxonomy classifies navigation approaches into Mapless (Integrated, Direct, Indirect) and Map-based (Known Map/Spaces, Map-building). Evaluation involves testing three strategies: CNN-based Supervised Learning, Frontier-based navigation, and CNN-based Distance Estimation.	Limited Scope: The taxonomy primarily addresses map-based and mapless approaches, suggesting potential exploration of other hybrid or alternative strategies, such as sensor fusion. Evaluation Metric Limitations: While the proposed metrics are useful, the study acknowledges potential limitations in capturing all aspects of navigation performance, like robustness to sensor noise, adaptability to unforeseen obstacles, and energy efficiency.
[29] **MSF** **AI** **INS**	Improved depth estimation accuracy over existing monocular self-supervised methods on the KITTI dataset, achieving successful autonomous navigation in various 3D environments	The software architecture for UAV navigation adopts a modular approach with well-defined interfaces for reusability. It employs 6D localization based on visual odometry and Monte Carlo Localization, along with an adaptive Lazy Theta algorithm for efficient motion planning.	Validation and Applicability: While the paper reports successful testing, it lacks real-world validation beyond simulations and controlled tests. Computational requirements may limit its applicability on resource-constrained UAVs.
[30] **MSF** **AI**	The paper classifies systems into analytics-based and learning-based fusion, providing insights into their advantages and disadvantages. Discussion of application scenarios highlights diverse use cases in autonomous driving, IoT, UAVs, and smart cities.	Focus on analytics-based (Kalman filter, graph optimization) and learning-based fusion (ANN, fuzzy logic, SVM, random forest, deep learning). Evaluation includes accuracy assessment and error mitigation in complex environments.	The paper excels in classifying integrated systems but falls short in offering detailed insights into practical challenges faced during real-world implementation. While the paper touches on comparisons between analytics-based and learning-based approaches, it lacks a comprehensive framework for evaluating these methods, considering factors such as accuracy, reliability, and cost in practical scenarios.
[31] **SLAM** **MSF** **AI**	Advanced SLAM Algorithm for 3-D Mapping Efficient Wind Estimation with Machine Learning	Sensor Fusion and Algorithm Integration K-Nearest Neighbor Learning for Wind Estimation	The absence of extensive outdoor validation limits the generalizability of the proposed SLAM algorithm and wind estimation method in diverse real-world scenarios.

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

[32] MSF	The paper demonstrates the effectiveness of combining UWB ranging and vision-based techniques for both approach and landing phases in UAV navigation.	Recursive least-square optimization is utilized for relative position estimation using UWB measurements, showcasing accurate landing capabilities through sensor fusion.	While adaptation to dynamic environments and moving targets is mentioned, the paper lacks specific details on the challenges faced and the effectiveness of the proposed system under dynamic conditions.
[33] MSF	A framework enabling drones to navigate in partially known environments without reliable position references, encompassing hardware and software components Validation in simulation and real-world scenarios, including participation in the Leonardo Drone Contest, highlights the robustness of the system's design.	Use of the Robot Operating System (ROS) middleware facilitates seamless communication among software modules, contributing to the overall efficiency of the system Use of a topological graph enhances path planning, while real-time obstacle avoidance contributes to adaptability in dynamic environments.	Lack of LiDAR sensors restricts the drone's flight time and angular range for obstacle detection
[34] AI MSF INS	The paper conducts a thorough examination of conventional small Unmanned Aerial System (sUAS) navigation systems, encompassing system architecture, sensing modalities, and data-fusion algorithms.	The critical evaluation offers insights into the practical advantages and limitations of incorporating AI in sUAS navigation, guiding future research directions.	Further exploration of specific challenges and potential AI-driven solutions in addressing safety, efficiency, and sustainability concerns would enhance the paper's depth.

Table1. Summary of studies and identified gaps.

3.4 Limitations Analysis:

3.4.1 Inertial Navigation Systems:

Drift and Errors: INS/IMU primarily rely on accelerometers and gyroscopes to track position and orientation. However, these sensors are prone to drift over time due to internal biases, temperature fluctuations, and external factors like vibrations. This drift can lead to significant positional errors, especially during extended flights in GPS-denied environments.

Due to the inherent bias instability and noise commonly associated with low-quality MEMS-IMUs (Micro-Electro-Mechanical Systems Inertial Measurement Units) utilized in small Unmanned Aerial Systems (sUAS), the absence of Global Navigation Satellite System (GNSS) signals results in a divergence of the estimated states of the UAV. This phenomenon is depicted in Figure 1, considering various sensor grades and employing the error parameters detailed in Table 2 [34].

Sensors	**IMU grade**			
	Error Source	**Consumer**	**Tactical**	**Aviation**
Gyroscope	**Bias** (rad/s)	0.0013	$5x10^{-5}$	$5x10^{-8}$
	Noise PSD (rad^2/s)	0.000291	10^{-9}	10^{-12}
Accelerometer	**Bias** (m/s^2)	0.127	0.01	0.001
	Noise PSD (m^2/s^3)	0.0098	10^{-6}	10^{-7}

Table2. Inertial sensor grades and corresponding error sources.

Accumulated errors from sensor noise, calibration inaccuracies, and environmental factors can further compound the issue, making long-term navigation unreliable without external correction.

Limited Environmental Awareness: INS/IMU rely solely on internal sensor data and lack the ability to directly perceive the surrounding environment. This makes them blind to obstacles, sudden terrain changes, or dynamic elements like moving objects or wind gusts, potentially leading to collisions or unsafe flight paths. Integration with other sensors like LiDAR or cameras can improve environmental awareness but adds complexity and computational cost.

Calibration and Maintenance: Accurate INS/IMU performance relies heavily on precise calibration and regular maintenance. This can be challenging, especially for smaller UAVs with limited resources and accessibility.

Environmental factors like temperature changes can also affect sensor accuracy, requiring recalibration at regular intervals, adding operational complexity and potentially delaying missions.

Integration Challenges: Integrating INS/IMU data with other navigation systems like magnetometers or barometers can improve accuracy and compensate for drift. However, this requires sophisticated algorithms and careful calibration to avoid introducing additional errors. Efficient data fusion between INS/IMU and other sensors remains a challenge, particularly when dealing with diverse data formats and real-time processing requirements.

3.4.2 MSF:

While Multi-Sensor Fusion systems offer significant advantages in terms of accurate and robust navigation, they

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

also have some limitations. Here are several common challenges associated with Multi-Sensor Fusion:

Initialization and Drift: Multi-Sensor Fusion systems often require an accurate initialization to establish the initial pose. Errors in the initial estimation can lead to drift over time. Additionally, even with good initialization, Multi-Sensor Fusion systems may experience drift over long durations due to cumulative errors in sensor measurements.

Sensitivity to Lighting Conditions: Sensor fusion involving visual sensors, such as cameras, can be sensitive to changes in lighting conditions. Variations in lighting, shadows, or abrupt changes in illumination can affect the performance of sensor fusion algorithms, leading to pose estimation errors.

Feature Ambiguity and Occlusions: Multi-Sensor Fusion systems rely on detecting and tracking distinct features in the environment. When these features become ambiguous or are occluded, the system may struggle to accurately track them, affecting pose estimation accuracy.

Scale Ambiguity: Multi-Sensor Fusion systems often face challenges in determining scale, especially in environments with limited visual cues. This can result in errors in estimating the true size and distance of objects in the environment.

Computational Requirements: Implementing Multi-Sensor Fusion algorithms can be computationally intensive, particularly when using advanced filtering or optimization techniques. This can be a limitation in resource-constrained devices or systems with real-time processing requirements.

Sensor Calibration: Accurate calibration of both visual and inertial sensors is crucial for the proper functioning of Multi-Sensor Fusion. Any misalignment or calibration errors can lead to inaccurate pose estimates.

Limited Coverage in GPS-Denied Environments: While Multi-Sensor Fusion is designed to operate in GPS-denied environments, it may still face challenges in areas with extremely limited sensor features, making it difficult to establish and maintain a reliable navigation solution.

Hardware Limitations: The quality and precision of the sensors used in Multi-Sensor Fusion play a significant role in system performance. Low-quality sensors or sensors with high noise levels can impact the accuracy of pose estimates."

3.4.3 Artificial Intelligence:

Data Dependence: AI algorithms rely heavily on training data to learn efficient navigation strategies. Lack of diverse training data in GPS-denied scenarios can lead to poor performance and unexpected errors. Limited data acquisition in these environments due to signal issues further hinders training and improvement of AI models.

Sensor Fusion Challenges: Effectively fusing data from multiple sensors like LiDAR, cameras, and IMUs remains a challenge. Inconsistencies and noise in sensor data can confuse AI algorithms, leading to misinterpretations and unreliable navigation. Integrating the temporal dynamics of the environment, such as moving obstacles or changing weather conditions, into AI models poses another hurdle.

Computational Limitations: Running complex AI algorithms onboard resource-constrained UAVs often requires significant computational power and memory. This limits the sophistication of AI models that can be deployed on smaller UAVs. Trade-offs between accuracy and computational efficiency need to be carefully considered, especially in real-time decision-making scenarios.

IV- PERSPECTIVES AND FUTURE RESEARCH DIRECTIONS:

4.1 INS/IMU:

Sensor Improvement and Calibration:

- Develop miniaturized, low-power, and more accurate IMUs
- Explore innovative calibration techniques, including in-situ calibration under various environmental conditions
- Investigate sensor drift reduction methods using advanced algorithms and machine learning

Hybrid Navigation Systems:

- Combine INS/IMU with other sensors like GNSS, LiDAR, cameras, and magnetometers for improved accuracy and robustness in GPS-denied environments
- Develop intelligent sensor selection and switching algorithms based on environmental context and mission requirements
- Explore tightly coupled and loosely coupled integration techniques for optimal performance

Fault Detection and Diagnosis:

- Design AI-powered algorithms for real-time sensor fault detection and isolation in IMUs
- Investigate fault-tolerant navigation strategies that maintain operation even with sensor malfunctions

4.2 Multi-sensor Fusion:

Deep Learning for Sensor Fusion:

- Develop deep learning models for robust and efficient fusion of data from diverse sensors, considering uncertainty and noise
- Explore unsupervised and semi-supervised learning techniques for handling limited labeled training data in real-world scenarios
- Focus on scene understanding and context awareness to interpret sensor data accurately

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

Temporal and Dynamic Fusion:

- Incorporate temporal dynamics into sensor fusion models to account for changes in the environment and UAV motion
- Develop adaptive fusion algorithms that adjust to varying environmental conditions and mission objectives
- Investigate the integration of predictive models based on weather forecasts or terrain maps

4.3 AI for UAV Navigation:

Adaptive Path Planning:

- Develop AI algorithms that can dynamically plan and adjust UAV paths in real-time based on sensor data, obstacles, and weather conditions
- Consider reinforcement learning approaches for continuous learning and adaptation in unknown or changing environments
- Address collision avoidance and safety concerns through intelligent decision-making and path optimization

Autonomous Decision-Making:

- Train AI models to make autonomous decisions for UAV mission execution, including obstacle avoidance, emergency landing, and route optimization
- Explore explainable AI techniques to ensure transparency and trust in AI-driven decisions
- Integrate ethical considerations into AI algorithms for responsible and safe UAV operation

Swarm Intelligence and Collaboration:

- Develop algorithms for collaborative navigation and decision-making among multiple UAVs using swarm intelligence principles
- Investigate communication protocols and resource allocation strategies for efficient collaborative missions
- Address security and privacy concerns in multi-UAV systems with AI-powered decision-making

IV- CONCLUSION

In this comprehensive review, we have navigated through the diverse landscape of UAV navigation, addressing fundamental principles, challenges in GPS-denied environments, and potential avenues for future research. The synthesis of literature pertaining to INS/IMU, Multi-sensor Fusion, and AI technologies has provided a holistic understanding of the current state of UAV navigation and has illuminated promising pathways for advancements in the field.

As we chart the course for the future of UAV navigation, the synthesis of insights and research directions presented in this paper aims to inspire and guide researchers, engineers, and decision-makers. The collaborative efforts of the research community are instrumental in realizing the full potential of UAVs, propelling us toward a future where autonomous aerial systems navigate with precision and efficiency.

In conclusion, the journey through the intricacies of UAV navigation has revealed not only the existing challenges but also the transformative potential embedded in emerging technologies. The road ahead invites collaborative exploration, innovation, and the pursuit of knowledge as we continue to push the boundaries of what is achievable in the realm of unmanned aerial vehicle navigation.

REFERENCES

[1] « Systems | A Comprehensive Review of Recent Research Trends on Unmanned Aerial Vehicles (UAVs) ». https://www.mdpi.com/2079-8954/11/8/400

[2] O. Araar, N. Aouf, et I. Vitanov, « Vision Based Autonomous Landing of Multirotor UAV on Moving Platform », *J. Intell. Robot. Syst.*, vol. 85, p. 369-384, 2017, doi: 10.1007/s10846-016-0399-z.

[3] S. Gaglione, S. Del Pizzo, S. Troisi, et A. Angrisano, « POSITION ACCURACY ANALYSIS OF A ROBUST VISION-BASED NAVIGATION », *Int. Arch. Photogramm. Remote Sens. Spat. Inf. Sci.*, vol. XLII-2, p. 355-361, mai 2018, doi: 10.5194/isprs-archives-XLII-2-355-2018.

[4] Y. Lu, Z. Xue, G.-S. Xia, et L. Zhang, « A survey on vision-based UAV navigation », *Geo-Spat. Inf. Sci.*, vol. 21, nº 1, p. 21-32, janv. 2018, doi: 10.1080/10095020.2017.1420509.

[5] « Drones | Vision-Based Navigation Techniques for Unmanned Aerial Vehicles: Review and Challenges ».https://www.mdpi.com/2504-446X/7/2/89

[6] I. Cortés, J. Beltrán, A. de la Escalera, et F. Q. García, « DALi: Domain Adaptation in LiDAR Point Clouds for 3D Obstacle Detection », *2022 IEEE 25th Int. Conf. Intell. Transp. Syst. ITSC*, vol. null, p. 3837-3842, 2022, doi: 10.1109/ITSC55140.2022.9922408.

[7] J. C. Ho, S. K. Phang, et H. K. Mun, « 2-D UAV navigation solution with LIDAR sensor under GPS-denied environment », *J. Phys. Conf. Ser.*, vol. 2120, nº 1, p. 012026, déc. 2021, doi: 10.1088/1742-6596/2120/1/012026.

[8] M. Tamazin, M. Karaim, A. Noureldin, M. Tamazin, M. Karaim, et A. Noureldin, « GNSSs, Signals, and Receivers », in *Multifunctional Operation and Application of GPS*, IntechOpen, 2018. doi: 10.5772/intechopen.74677.

[9] S. Z. Khan, M. Mohsin, et W. Iqbal, « On GPS spoofing of aerial platforms: a review of threats, challenges, methodologies, and future research directions », *PeerJ Comput. Sci.*, vol. 7, p. e507, mai 2021, doi: 10.7717/peerj-cs.507.

[10] M. F. F. Rahman, « Research on Multi-sensor Fusion for UAV Localization », 2022. doi: 10.13140/RG.2.2.22570.80327.

[11] S. Rezwan et W. Choi, « Artificial Intelligence Approaches for UAV Navigation: Recent Advances and Future Challenges », *IEEE Access*, vol. PP, p. 1-1, 2022, doi: 10.1109/ACCESS.2022.3157626.

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.

[12] P. Geneva, K. Eckenhoff, et G. Huang, « A Linear-Complexity EKF for Visual-Inertial Navigation with Loop Closures », *2019 Int. Conf. Robot. Autom. ICRA*, vol. null, p. 3535-3541, 2019, doi: 10.1109/ICRA.2019.8793836.

[13] P. Geneva, J. Maley, et G. Huang, « An Efficient Schmidt-EKF for 3D Visual-Inertial SLAM », *2019 IEEECVF Conf. Comput. Vis. Pattern Recognit. CVPR*, vol. null, p. 12097-12107, 2019, doi: 10.1109/CVPR.2019.01238.

[14] J. Huai, Y. Lin, C. Toth, Y. Zhuang, et D. Chen, « A Versatile Keyframe-Based Structureless Filter for Visual Inertial Odometry », *ArXiv*, vol. abs/2012.15170, p. null, 2020.

[15] D. Scaramuzza et Z. Zhang, « Aerial Robots, Visual-Inertial Odometry of », *Encycl. Robot.*, vol. null, p. null, 2020, doi: 10.1007/978-3-642-41610-1_71-1.

[16] Y. Yang et G. Huang, « Aided Inertial Navigation with Geometric Features: Observability Analysis », *2018 IEEE Int. Conf. Robot. Autom. ICRA*, vol. null, p. 2334-2340, 2018, doi: 10.1109/ICRA.2018.8460670.

[17] Y. Yang et G. Huang, « Aided Inertial Navigation: Unified Feature Representations and Observability Analysis », *2019 Int. Conf. Robot. Autom. ICRA*, vol. null, p. 3528-3534, 2019, doi: 10.1109/ICRA.2019.8793507.

[18] Y. Liu, Z. Li, S. Zheng, P. Cai, et X. Zou, « An Evaluation of MEMS-IMU Performance on the Absolute Trajectory Error of Visual-Inertial Navigation System », *Micromachines*, vol. 13, p. null, 2022, doi: 10.3390/mi13040602.

[19] K. Eckenhoff, P. Geneva, et G. Huang, « Closed-form preintegration methods for graph-based visual–inertial navigation », *Int. J. Robot. Res.*, vol. 38, p. 563-586, 2018, doi: 10.1177/0278364919835021.

[20] J. Hesch, D. G. Kottas, S. L. Bowman, et S. Roumeliotis, « Consistency Analysis and Improvement of Vision-aided Inertial Navigation », *IEEE Trans. Robot.*, vol. 30, p. 158-176, 2014, doi: 10.1109/TRO.2013.2277549.

[21] K. Eckenhoff, P. Geneva, et G. Huang, « Continuous Preintegration Theory for Graph-based Visual-Inertial Navigation », *ArXiv*, vol. abs/1805.02774, p. null, 2018.

[22] Y. Yang, C. Chen, W. Lee, et G. Huang, « Decoupled Right Invariant Error States for Consistent Visual-Inertial Navigation », *IEEE Robot. Autom Lett*, vol. 7, p. 1627-1634, 2022, doi: 10.1109/lra.2021.3140054.

[23] C. Forster, L. Carlone, F. Dellaert, et D. Scaramuzza, « On-Manifold Preintegration for Real-Time Visual–Inertial Odometry », *IEEE Trans. Robot.*, vol. 33, p. 1-21, 2015, doi: 10.1109/TRO.2016.2597321.

[24] Y. Yang, P. Geneva, X. Zuo, et G. Huang, « Online IMU Intrinsic Calibration: Is It Necessary? », *Robot. Sci. Syst. XVI*, vol. null, p. null, 2020, doi: 10.15607/rss.2020.xvi.026.

[25] W. Huang, W. Wan, et H. Liu, « Optimization-Based Online Initialization and Calibration of Monocular Visual-Inertial Odometry Considering Spatial-Temporal Constraints », *Sensors*, vol. 21, p. null, 2021, doi: 10.3390/s21082673.

[26] K. Sun *et al.*, « Robust Stereo Visual Inertial Odometry for Fast Autonomous Flight », *IEEE Robot. Autom. Lett.*, vol. 3, p. 965-972, 2017, doi: 10.1109/LRA.2018.2793349.

[27] A. Flores-Abad, N. Habib, D. Aponte-Roa, A. Espinoza, et J. Martinez-Martinez, « Unmanned Autonomous Aerial Navigation in GPS-Denied Environments », in *Proceedings of the 18th LACCEI International Multi-Conference for Engineering, Education, and Technology: Engineering, Integration, And Alliances for A Sustainable Development" "Hemispheric Cooperation for Competitiveness and Prosperity on A Knowledge-Based Economy"*, Latin American and Caribbean Consortium of Engineering Institutions, 2020. doi: 10.18687/LACCEI2020.1.1.349.

[28] Y. Chang, Y. Cheng, U. Manzoor, et J. Murray, « A review of UAV autonomous navigation in GPS-denied environments », *Robot. Auton. Syst.*, vol. null, p. null, 2023, doi: 10.1016/j.robot.2023.104533.

[29] F. J. Pérez-Grau, R. Ragel, F. Caballero, A. Viguria, et A. Ollero, « An architecture for robust UAV navigation in GPS-denied areas », *J. Field Robot.*, vol. 35, p. 121-145, 2018, doi: 10.1002/rob.21757.

[30] Y. Zhuang *et al.*, « Multi-sensor integrated navigation/positioning systems using data fusion: From analytics-based to learning-based approaches », *Inf. Fusion*, vol. 95, p. 62-90, juill. 2023, doi: 10.1016/j.inffus.2023.01.025.

[31] L. Wang, « Advanced guidance and navigation of small UAVs under GPS-denied environment with experimental validations », 2019, doi: 10.7282/T3-VEZP-4547.

[32] T.-M. Nguyen, T. Nguyen, M. Cao, Z. Qiu, et L. Xie, « Integrated UWB-Vision Approach for Autonomous Docking of UAVs in GPS-denied Environments », *2019 Int. Conf. Robot. Autom. ICRA*, vol. null, p. 9603-9609, 2019, doi: 10.1109/ICRA.2019.8793851.

[33] M. Mugnai, M. Teppati Losé, E. P. Herrera-Alarcón, G. Baris, M. Satler, et C. A. Avizzano, « An Efficient Framework for Autonomous UAV Missions in Partially-Unknown GNSS-Denied Environments », *Drones*, vol. 7, nº 7, Art. nº 7, juill. 2023, doi: 10.3390/drones7070471.

[34] S. Bijjahalli, R. Sabatini, et A. Gardi, « Advances in intelligent and autonomous navigation systems for small UAS », *Prog. Aerosp. Sci.*, vol. 115, p. 100617, mai 2020, doi: 10.1016/j.paerosci.2020.100617.

Authorized licensed use limited to: University of Chinese Academy of SciencesCAS. Downloaded on October 27,2024 at 03:37:02 UTC from IEEE Xplore. Restrictions apply.