
AgnianeStealer Write-up by Wh0isG0TH4M


Sherlock Scenario

> SecureTech Solutions recently detected unusual activity on its employee workstations. Upon investigation, they found that sensitive customer information, including email addresses and passwords, has been compromised. The company suspects that a stealer malware might be responsible for the breach.

Task 0 : What is the decoded hostname that is used by the stealer?

I initiated basic static analysis by loading the stealer binary into Detect It Easy. After checking the **Strings** tab for IoCs, I identified a **Base64-encoded** string and successfully decoded it.






Answer: https://central-cee-doja[.]ru/

Task 1 : What is the API used by the stealer to detect debuggers?


After Detect It Easy flagged the executable as a .NET application, I opened it in **dotPeek**. I then used the search bar to query `debugger`



Answer: CheckRemoteDebuggerPresent

Task 2 : What is the number of the process names that are used by stealer to detect malware analysts?


Heading over to the `AntiAnalysis` class, I found a method that checks running processes to detect malware analysts. This technique verifies whether the binary is running inside an analysis environment or sandbox, as analysts frequently use these tools to inspect malware.



Answer: 8

Task 4 : What is the number of the functions that are used by the stealer as anti-analysis?


Based on the code, if any of the `AntiAnalysis` functions (`Debugger`, `Emulator`, `Processes`, or `VirtualBox`) return `true`, or if `HostingAsync()` returns `false`, the program executes `Environment.Exit(0)` and terminates immediately.



Answer: 5

Task 4 : What is the first DLL name that was downloaded by the malware?


Heading over to the `DynamicLinkLibrary` class, I found a method named `Download()` that uses `WebClient` to download `System.Data.SQLite.dll`.



Answer: SQLite.dll

Task 5 : What is the name of the project advertised by the malware?


In the `Archive` class, the `Compile()` method contains a hardcoded string referencing the project name, **Cinoshi**.



Answer: Cinoshi

Task 6 : What is the user of the bot in Telegram?


Inspecting the hardcoded strings, I found the Telegram username of the bot owner/operator mentioned in the code.



Answer: @agnianebot

Task 7 : What is the first regex that is used by the malware to find tokens?


Inspecting the `FindTokens()` method within the `Discord` class reveals that the malware uses regular expressions to collect Discord tokens from local database files.




Answer: [a-zA-Z0-9]{24}\\.[a-zA-Z0-9]{6}\\.[a-zA-Z0-9_\\-]{27}

Task 8 : What is the build version?

Inspecting the `Silk` class reveals a static string field named `buildversion` with a value of **"0.1.1 beta"**






Answer: 0.1.1 beta

Task 9 : How many domains are targeted by the Stealer to collect passwords and login credentials?


In the `DomainDetection` class under the `Silk` namespace, the `Start()` method defines a pipe-delimited string containing target domains: **vk.com**, **facebook.com**, **instagram.com**, and **mail.ru**.



Answer: 4

Task 10 : Which specific registry key is targeted by the malware to collect Hostname, username, and password information from all sessions of WinSCP?


In the `WinSCP` class, the `GetCredentials()` method queries the Windows Registry key `Software\\Martin Prikryl\\WinSCP 2\\Sessions` to steal saved WinSCP login credentials (HostName, UserName, and Password).



Answer: Software\\Martin Prikryl\\WinSCP 2\\Sessions

Task 11 : What is the file name that is used by the stealer to save the information about the system?

String inspection shows that the stealer writes harvested system details into `PC Information.txt`



Answer: PC Information.txt

In conclusion, AgnianeStealer begins by checking its environment for debuggers, emulators, suspicious analysis processes, and VirtualBox. If its anti-analysis checks detect a possible analysis environment, the malware terminates. Otherwise, it proceeds to download the required SQLite DLL and continues its operations. It then collects sensitive information by extracting Discord tokens, targeting login credentials from specific domains, and accessing saved WinSCP session credentials from the Windows Registry. It also gathers system information and saves it in a file named PC information.txt. Overall, its behavior focuses on avoiding analysis and stealing sensitive user information.