



Job Fair For Students Trending Now DSA Data Structures Algorithms Interview Preparation Data Sci

Reverse a string in C/C++ using Client Server model

Read

Discuss

Courses

Practice

Video

This article describes a Client and Server setup where a Client connects, sends a string to server and the server shows the original string and sends reversed string to client using socket connection.

Prerequisite : [Socket Programming](#)

Examples:

Input : welcome

Output :emoclew

Input :geeks for geeks

Output :skeeg rof skeeg

Explanation

In this, first setup client-server connection. When connection will setup, client will send user input string to server by send system call. At server side, server will wait for string sent by client. Server read string by read system call. After this, server will reverse the string and send back to client.

Compiling :

1. First run the server program as

```
gcc Server.c -o server
```

2. Run the client program on another terminal

```
gcc Client.c -o client
```

3. Server program is waiting for string sent by client.
4. Input the string in client side.
5. Server program will print original string.
6. Client program will print reversed string.

Recommended: Please try your approach on *{IDE}* first, before moving on to the solution.

Client.c

C

```
// C client code to send string to reverse
#include <arpa/inet.h>
#include <netinet/in.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <unistd.h>

#define PORT 8090

// Driver code
int main()
{
    struct sockaddr_in address;
    int sock = 0, valread;
    struct sockaddr_in serv_addr;
    char str[100];

    printf("\nInput the string:");
    scanf("%[^\n]s", str);

    char buffer[1024] = { 0 };

    // Creating socket file descriptor
    if ((sock = socket(AF_INET,
```

```

        SOCK_STREAM, 0))

    < 0) {
        printf("\n Socket creation error \n");
        return -1;
    }

    memset(&serv_addr, '0', sizeof(serv_addr));
    serv_addr.sin_family = AF_INET;
    serv_addr.sin_port = htons(PORT);

    // Convert IPv4 and IPv6 addresses from
    // text to binary form 127.0.0.1 is local
    // host IP address, this address should be
    // your system local host IP address
    if (inet_pton(AF_INET, "127.0.0.1",
                  &serv_addr.sin_addr)
        <= 0) {
        printf("\nAddress not supported \n");
        return -1;
    }

    // connect the socket
    if (connect(sock, (struct sockaddr*)&serv_addr,
                sizeof(serv_addr))
        < 0) {
        printf("\nConnection Failed \n");
        return -1;
    }

    int l = strlen(str);

    // send string to server side
    send(sock, str, sizeof(str), 0);

    // read string sent by server
    valread = read(sock, str, l);

    printf("%s\n", str);

    return 0;
}

```

Server.c

C

```

// Server C code to reverse a
// string by sent from client
#include <netinet/in.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <unistd.h>

```

```
#define PORT 8090

// Driver code
int main()
{
    int server_fd, new_socket, valread;
    struct sockaddr_in address;
    char str[100];
    int addrlen = sizeof(address);
    char buffer[1024] = { 0 };
    char* hello = "Hello from server";

    // Creating socket file descriptor
    if ((server_fd = socket(AF_INET,
                           SOCK_STREAM, 0)) == 0) {
        perror("socket failed");
        exit(EXIT_FAILURE);
    }

    address.sin_family = AF_INET;
    address.sin_addr.s_addr = INADDR_ANY;
    address.sin_port = htons(PORT);

    // Forcefully attaching socket to
    // the port 8090
    if (bind(server_fd, (struct sockaddr*)&address,
              sizeof(address)) < 0) {
        perror("bind failed");
        exit(EXIT_FAILURE);
    }

    // puts the server socket in passive mode
    if (listen(server_fd, 3) < 0) {
        perror("listen");
        exit(EXIT_FAILURE);
    }
    if ((new_socket = accept(server_fd,
                            (struct sockaddr*)&address,
                            (socklen_t*)&addrlen)) < 0) {
        perror("accept");
        exit(EXIT_FAILURE);
    }

    // read string send by client
    valread = read(new_socket, str,
                   sizeof(str));

    int i, j, temp;
    int l = strlen(str);

    printf("\nString sent by client:%s\n", str);

    // loop to reverse the string
    for (i = 0, j = l - 1; i < j; i++, j--) {
        temp = str[i];
        str[i] = str[j];
        str[j] = temp;
    }
}
```

```
}

// send reversed string to client
// by send system call
send(new_socket, str, sizeof(str), 0);
printf("\nModified string sent to client\n");

return 0;
}
```

Last Updated : 26 Jan, 2018

2

[Previous](#)[Next](#)

Article Contributed By :

**GeeksforGeeks**

Vote for difficulty

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)**Article Tags :** [system-programming](#), [C Language](#)[Improve Article](#)[Report Issue](#)

A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)[Careers](#)

Trending @GfG

[Job Fair For Students](#)[GfG Weekly #100](#)

[In Media](#)[POTD: Revamped](#)[Contact Us](#)[Python Backend LIVE](#)[Terms and Conditions](#)[Android App Development](#)[Privacy Policy](#)[DevOps LIVE](#)[Copyright Policy](#)[DSA in JavaScript](#)[Third-Party Copyright Notices](#)[Advertise with us](#)

Languages

[Python](#)[Java](#)[C++](#)[GoLang](#)[SQL](#)[R Language](#)[Android Tutorial](#)

Data Structures

[Array](#)[String](#)[Linked List](#)[Stack](#)[Queue](#)[Tree](#)[Graph](#)

Algorithms

[Sorting](#)[Searching](#)[Greedy](#)[Dynamic Programming](#)[Pattern Searching](#)[Recursion](#)[Backtracking](#)

Web Development

[HTML](#)[CSS](#)[JavaScript](#)[Bootstrap](#)[ReactJS](#)[AngularJS](#)[NodeJS](#)

Data Science & ML

[Data Science With Python](#)[Data Science For Beginner](#)[Machine Learning Tutorial](#)[Maths For Machine Learning](#)[Pandas Tutorial](#)[NumPy Tutorial](#)[NLP Tutorial](#)

Interview Corner

[Company Preparation](#)[Preparation for SDE](#)[Company Interview Corner](#)[Experienced Interview](#)[Internship Interview](#)[Competitive Programming](#)[Aptitude](#)

Python

[Python Tutorial](#)

GfG School

[CBSE Notes for Class 8](#)

[Python Programming Examples](#)[Django Tutorial](#)[Python Projects](#)[Python Tkinter](#)[OpenCV Python Tutorial](#)[CBSE Notes for Class 9](#)[CBSE Notes for Class 10](#)[CBSE Notes for Class 11](#)[CBSE Notes for Class 12](#)[English Grammar](#)

UPSC/SSC/BANKING

[SSC CGL Syllabus](#)[SBI PO Syllabus](#)[IBPS PO Syllabus](#)[UPSC Ethics Notes](#)[UPSC Economics Notes](#)[UPSC History Notes](#)

Write & Earn

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Write Interview Experience](#)[Internships](#)[Video Internship](#)

@geeksforgeeks , Some rights reserved