


TCP Client-Server Program to Check if a Given String is Palindrome



Read Discuss Courses Practice Video

Prerequisites:

- Socket Programming in C/C++,
- TCP and UDP server using select,
- <u>UDP Server-Client implementation in C</u>
- TCP Client-Server Implementation in C

This article describes a Client and Server setup where a Client connects, sends a string to the server and the server shows the original string and sends confirmation whether the string is a palindrome or not, to the client using socket connection.

Examples:

Input: naman

Output: Palindrome

Input: geek

Output: Not Palindrome

Recommended: Please try your approach on <u>{IDE}</u> first, before moving on to the solution.

Approach:

- In this, first set up a client-server connection.
- When the connection will setup, the client will send the user input string to the server by the send system call.
- At the server-side, the server will wait for a string sent by the client.
- Server reads the string by the reading system call.
- After this, the server will <u>check if the string is a palindrome or not</u> and sends the confirmation back to the client.

Compiling:

1. First, run the server program as

```
gcc server.c -o server
./server
```

2. Run the client program on another terminal

```
gcc client.c -o client
./client
```

- 3. Server program is waiting for the string sent by the client.
- 4. Input the string in client-side.
- 5. Server program will print original string.
- 6. Client program will print result.

Below is the implementation of the above approach:

TCP Server

```
// defines in_addr structure
#include <arpa/inet.h>

// contains constants and structures
// needed for internet domain addresses
```

```
#include <netinet/in.h>
// standard input and output library
#include <stdio.h>
// contains string functions
#include <string.h>
// for socket creation
#include <sys/socket.h>
// contains constructs that facilitate getting
// information about files attributes.
#include <sys/stat.h>
// contains a number of basic derived types
// that should be used whenever appropriate
#include <sys/types.h>
main()
{
    struct sockaddr in client, server;
    int s, n, sock, g, j, left, right, flag;
    char b1[20], b2[10], b3[10], b4[10];
    // creating socket
    s = socket(AF_INET, SOCK_STREAM, 0);
    // assign IP, PORT
    server.sin_family = AF_INET;
    // this is the port number of running server
    server.sin port = 2000;
    server.sin_addr.s_addr = inet_addr("127.0.0.1");
    // Binding newly created socket
    // to given IP and verification
    bind(s, (struct sockaddr*)&server, sizeof server);
    listen(s, 1);
    n = sizeof client;
    sock = accept(s, (struct sockaddr*)&client, &n);
    for (;;) {
        recv(sock, b1, sizeof(b1), 0);
        // whenever a request from a client came.
        // It will be processed here.
        printf("\nThe string received is:%s\n", b1);
        if (strlen(b1) == 0)
            flag = 1;
        else {
            left = 0;
            right = strlen(b1) - 1;
            flag = 1;
            while (left < right && flag) {</pre>
                if (b1[left] != b1[right])
                    flag = 0;
```

Job Fair For Students Trending Now DSA Data Structures Algorithms Interview Preparation Data Sci

```
// defines in_addr structure
#include <arpa/inet.h>
// contains constants and structures
// needed for internet domain addresses
#include <netinet/in.h>
// standard input and output library
#include <stdio.h>
// contains string functions
#include <string.h>
// for socket creation
#include <sys/socket.h>
// contains constructs that facilitate getting
// information about files attributes.
#include <sys/stat.h>
// contains a number of basic derived types
// that should be used whenever appropriate
#include <sys/types.h>
main()
{
    struct sockaddr_in client;
    int s, flag;
    char buffer[20];
    // socket create
    s = socket(AF_INET, SOCK_STREAM, 0);
    // assign IP, PORT
    client.sin family = AF INET;
    client.sin_port = 2000;
    client.sin_addr.s_addr = inet_addr("127.0.0.1");
```

```
// connect the client socket to server socket
    connect(s, (struct sockaddr*)&client, sizeof client);
   for (;;) {
        printf("\nEnter a string to check palindrome: ");
        scanf("%s", buffer);
        printf("\nClient: %s", buffer);
        send(s, buffer, sizeof(buffer), 0);
        recv(s, &flag, sizeof(int), 0);
        if (flag == 1) {
            printf("\nServer: The string is a Palindrome.\n");
        }
        else {
            printf("\nServer: The string is not a palindrome.\n");
            break:
        }
   }
   // close the socket
   close(s);
}
```

Output:

• Server Side:

```
thakur@thakur-VirtualBox: ~/Documents/new$

thakur@thakur-VirtualBox: ~/Documents/new$ ./client

Enter a string to check palindrome: naman

Client: naman

Server: The string is a Palindrome.

thakur@thakur-VirtualBox: ~/Documents/new$ ./client

Enter a string to check palindrome: aman

Client: aman

Server: The string is not a palindrome.

thakur@thakur-VirtualBox: ~/Documents/new$
```

• Client Side:

3

Last Updated: 02 Aug, 2019

Similar Reads

- 1. TCP Server-Client implementation in C
- 2. Setting up local DNS server between client-server machines
- 3. TCP Tahoe and TCP Reno
- 4. TCP with explicit link failure notification (TCP-ELFN)
- 5. UDP Client Server using connect | C implementation
- 6. Java Implementation of Diffie-Hellman Algorithm between Client and Server
- 7. Two way communication between Client and Server using Win32 Threads
- 8. Distributed Objects Computing: The next generation of client-server computing
- 9. Difference between Server OS and Client OS
- 10. Difference between Client /Server and Distributed DBMS

Previous

Article Contributed By:



Vote for difficulty

Current difficulty: Hard

Easy

Normal

Medium

Hard

Expert

Article Tags: cpp-multithreading, palindrome, C Programs, Computer Networks

Practice Tags: Computer Networks, palindrome, Palindrome

Improve Article

Report Issue



A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

About Us

Careers

In Media

Contact Us

Terms and Conditions

Privacy Policy

Copyright Policy

Third-Party Copyright Notices

Advertise with us

Languages

Python

Trending @GfG

Job Fair For Students

GfG Weekly #100

POTD: Revamped

Python Backend LIVE

Android App Development

DevOps LIVE

DSA in JavaScript

Data Structures

Array

Web Development

Interview Corner

GfG School

Java String

C++ Linked List

GoLang Stack

SQL Queue

R Language Tree

Android Tutorial Graph

Algorithms

Sorting HTML

Searching CSS

Greedy JavaScript

Dynamic Programming Bootstrap

Pattern Searching ReactJS

Recursion AngularJS

Backtracking NodeJS

Data Science & ML

Data Science With Python Company Preparation

Data Science For Beginner Preparation for SDE

Machine Learning Tutorial Company Interview Corner

Maths For Machine Learning Experienced Interview

Pandas Tutorial Internship Interview

NumPy Tutorial Competitive Programming

NLP Tutorial Aptitude

Python

Python Tutorial CBSE Notes for Class 8

Python Programming Examples CBSE Notes for Class 9

Django Tutorial CBSE Notes for Class 10

Python Projects CBSE Notes for Class 11

Python Tkinter CBSE Notes for Class 12

OpenCV Python Tutorial English Grammar

UPSC/SSC/BANKING

IBPS PO Syllabus

SSC CGL Syllabus Write an Article

SBI PO Syllabus Improve an Article

Pick Topics to Write

Write & Earn

UPSC Ethics Notes

Write Interview Experience

UPSC Economics Notes

Internships

UPSC History Notes

Video Internship

@geeksforgeeks, Some rights reserved