

CINIC10 Cross-Source Transfer Results

Config C (out-basis adapter, RC-on) — 200 epochs, 1W1A shared backbone

Generated 2026-06-25 | accuracy = Final Best Top-1 (%)

Notes: M=number of adapter branches (multi-adapter, 1-bit). Bit-sweep varies the adapter/net bit-width at a single branch (M=1). The M1 and 1-bit columns are the same single-branch configuration (identical values, a consistency check). All cells use the same CINIC10/source backbones trained by the shared `run_xx_pretrain.py` pipeline.

A. Source backbone → CINIC10

Table 1: Multi-adapter (Config C, 1-bit), target = CINIC10.

Source backbone	M1	M2	M3	M4
SVHN	32.76	34.47	36.84	39.70
STL10	56.07	56.74	57.39	57.36
FashionMNIST	24.82	25.33	27.28	26.34

Table 2: Bit-sweep (Config C), target = CINIC10.

Source backbone	1-bit	2-bit	4-bit	8-bit
SVHN	32.76	64.96	69.04	69.75
STL10	56.07	70.59	73.56	73.99
FashionMNIST	24.82	60.31	67.65	68.84

B. CINIC10 → other datasets

Table 3: Multi-adapter (Config C, 1-bit), source backbone = CINIC10.

Target	M1	M2	M3	M4
CIFAR10	78.05	78.08	78.47	78.59
SVHN	67.43	70.60	71.12	72.30
STL10	66.42	66.86	67.33	67.83
FashionMNIST	79.81	80.89	81.26	81.59

Table 4: Bit-sweep (Config C), source backbone = CINIC10.

Target	1-bit	2-bit	4-bit	8-bit
CIFAR10	78.05	88.42	90.46	90.54
SVHN	67.43	95.49	95.94	95.72
STL10	66.42	74.90	76.62	74.19
FashionMNIST	79.81	93.38	94.00	93.77