

THE EPPLEY LABORATORY, INC.

12 Sheffield Avenue, PO Box 419, Newport, Rhode Island USA 02840 Phone: 401.847.1020 Fax: 401.847.1031 Email: info@eppleylab.com

Calibration Certificate

Instrument:

Standard Precision Pyranometer, Model SPP, Serial Number 38214F3

Procedure:

This pyranometer was compared in Eppley's Integrating Hemisphere according to procedures described in ISO 9847 Section 5.3.1 and Technical Procedure, TP01 of

The Eppley Laboratory, Inc.'s Quality Assurance Manual on Calibrations.

Transfer Standard: Eppley Standard Precision Pyranometer, Model SPP, Serial Number 37501F3

Results:

Sensitivity:

 $S = 7.85 \ \mu V \ / \ Wm^{-2}$

Uncertainty:

 $U_{95} = \pm 0.91\%$ (95% confidence level, k=2)

Resistance:

 697Ω at 23° C

Date of Test:

March 10, 2021

Traceability:

This calibration is traceable to the World Radiation Reference (WRR) through comparisons with Eppley's AHF standard self-calibrating cavity pyrheliometers which participated in the Twelfth International Pyrheliometric Comparisons (IPC XII) at Davos, Switzerland in September-October 2015. Unless otherwise stated in the remarks section below or on the Sales Order, the results of this calibration are

"AS FOUND / AS LEFT".

Due Date:

Eppley recommends a minimum calibration cycle of five (5) years but encourages

annual calibrations for highest measurement accuracy.

Customer:

WHOI

Woods Hole, MA

In Charge of Test:

65916

Eppley SO:

Date of Certificate March 12, 2021

Remarks: