Payment provider API readiness

Status: STAGING CONTRACT - DO NOT USE AS A PRODUCTION ACTIVATION NOTICE

The target production origin remains:

https://billing.superoptic.net

The pre-production acceptance origin is:

https://mgt.superoptic.net

The payment API routes described in this directory become production routes only after SuperOptic sends a written activation notice. A DNS record, login page, or successful TLS handshake alone is not an activation notice.

Credential model

Each provider receives its own:

- public key ID;
- one-time private secret used in the bearer credential and HMAC-SHA256 signature;
- production source-IP allowlist;
- test and production activation dates.

Emanat and United Payment credentials are not interchangeable. No credential is stored in this repository or embedded in the documentation.

The public key ID is an identifier, not an RSA/ECDSA public key. The private secret is shown once and only its Argon2id hash is retained by SuperOptic. If a provider requires asymmetric RSA/ECDSA exchange, that is a different authentication profile and must be agreed before activation.

Required provider information

Before production activation, each provider must return:

- legal provider name and technical contact;
- test and production source IP addresses;
- maximum timeout and retry policy;
- confirmation that custom HTTP headers are supported;
- confirmation that HMAC-SHA256 is supported;
- confirmation that the same transaction ID is reused on retries;
- planned test window.

Operational contract

- TLS 1.2 or newer is required.
- Requests time out after 15 seconds on the provider side.
- Payment retries must reuse the same transaction ID and idempotency key.
- A successful payment response means the payment was durably recorded.
- RADIUS/service activation is asynchronous and is exposed through

payment_state.

- Every response returns X-Correlation-ID and a JSON correlation_id.

- Provider credentials must be exchanged through an approved secure channel,

never through email body, chat, source code, or a ticket comment.

SuperOptic United Payment kiosk and wallet API v1

Status: staging contract

Base URL after written activation:

https://billing.superoptic.net/api/provider/up

Acceptance-test base URL before activation:

https://mgt.superoptic.net/api/provider/up

Authentication

All requests include:

```
Authorization: Bearer <PUBLIC_KEY_ID>.<PRIVATE_SECRET>
X-Provider-Name: unitedpayment
X-Superoptic-Timestamp: <Unix time in seconds>
X-Superoptic-Signature: <lowercase hex HMAC-SHA256>
X-Correlation-ID: <provider request correlation id>
```

The signature input is:

```
<timestamp>\n<raw HTTP request body>
```

PUBLIC_KEY_ID identifies United Payment's credential and may be shown in operational logs. PRIVATE_SECRET is shown only once and must remain in United Payment's secret manager. The HMAC signing key is the same PRIVATE_SECRET. For GET requests the raw body is empty. The timestamp must be within 300 seconds of SuperOptic server time. Production source IPs are allowlisted in addition to credential and HMAC validation.

1. Member lookup

```
GET /api/provider/up/?memberId=2320025
```

Success:

```
{
  "StatusCode": "00",
  "StatusDesc": "APPROVED",
  "memberInfo": "Example",
  "additionalInfo": "Customer",
  "description": "2320025",
  "balance": "25",
  "customer": {},
  "correlation_id": "req-..."
}
```

2. Insert payment

```
POST /api/provider/up/insert-payment/
Content-Type: application/x-www-form-urlencoded
Idempotency-Key: unitedpayment:<toProcessId>
```

Exact body example:

```
memberId=2320025&toProcessId=UP-20260728-000001&amount=25.00&channelId=1&channelDesc=Kiosk-001
```

Success:

```
{
  "StatusCode": "00",
  "StatusDesc": "APPROVED",
  "paymentState": "service_action_pending",
  "correlationId": "req-...",
  "correlation_id": "req-..."
}
```

The exact request can be retried safely with the same toProcessId and Idempotency-Key. A duplicate already recorded by the legacy UP contract can return E209; the status endpoint must then be queried.

3. Payment status

```
GET /api/provider/up/payment-status/?toProcessId=UP-20260728-000001
```

Success returns StatusCode=00 plus paymentState and correlationId.

UP status codes

StatusCode	Meaning
00	Approved or transaction exists
E000	Customer or transaction not found
E202	Invalid request
E209	Duplicate transaction

Authentication and transport failures use HTTP 401, 403, or 503 with a JSON code value as described in EMANAT_API_V1.md.

Payment provider production cutover checklist

SuperOptic

[ ] billing.superoptic.net routes /api/provider/ to the unified portal.

[ ] /api/health.php returns HTTP 200 through the public TLS origin.

[ ] Emanat and United Payment have separate public key IDs and private secrets.

[ ] Shared legacy provider credentials are disabled.

[ ] Provider production source IPs are configured.

[ ] TLS certificate has at least 14 days remaining.

[ ] Database backup and rollback point are verified.

[ ] Payment outbox worker and timer are active.

[ ] RADIUS action worker is active or deliberately isolated for the test.

[ ] Duplicate payment, payload mismatch, retry, and status tests pass.

[ ] Failed RADIUS action reaches retry/manual reconciliation without losing

the payment.

[ ] Audit records include provider, transaction ID, state, and correlation ID.

[ ] No credential appears in source, documentation, logs, screenshots, or support tickets.

Provider

[ ] Test and production source IPs supplied.

[ ] Custom auth/signature/idempotency headers confirmed.

[ ] Clock is NTP synchronized.

[ ] Retry reuses the same transaction ID and idempotency key.

[ ] Provider has tested customer not found, invalid signature, timeout, duplicate, and payment status flows.

[ ] Provider technical and incident contacts supplied.

Activation gate

Production traffic starts only after both sides sign a test result containing:

- test customer code;
- provider transaction ID;
- SuperOptic correlation ID;
- payment amount;
- final payment state;
- UTC and Asia/Baku timestamps;
- explicit rollback owner.