Team TBL # 2: High-Resolution Magnetic Survey in Locating Abandoned Brine Wells in Hutchinson, Kansas: Xia and Williams

TA: Dom Fournier
  e-mail: dfournie@eos.ubc.ca
  office: ESB 4021

DUE: Monday, September 26, 2016

Overview

Many improperly abandoned wells exist in Canada and the US. They are difficult to find as they are often covered by soil so they are not visible by eye. Their small diameter makes them difficult to locate by direct probing of the ground. In this case study, the authors use magnetic surveys to locate abandoned wells.

Instructions

Answer the following questions within the context of the 7 step framework. Your answers should be brief, and point form can be used where appropriate.

  Team exercise:

- Discuss the case history amongst yourselves

- As a team, answer the following questions

- You will hand this in at the end of the class

Resources

- GPG: Magnetics

- Jupyter Notebook App

- Instructions for downloading and using the Jupyter Notebook: here

Q1. Orientation of Earth's field: The following questions make use of the Mag App.

a. In Hutchinson, Kansas, the inducing field has an inclination of 66° and a declination of $\sim 4°$ (found using the Natural Resources Canada Magnetic field calculator). Using the default parameters for the geometry of the pipe (dx=0.08m, dy=0.08m, dz=100m, depth=1, pinc=0, pdec=0). Describe the differences in the character of the anomaly due to having a vertically oriented inducing field (inclination of 90°) and an inducing field with an inclination of 66°

b. Using the inclination in Kansas, what happens to the anomaly as you move the well deeper?

Q2. Characterizing susceptibility and remanence: Consider the well identified in Figure 6. To answer the following questions, use the app to simulate the expected response over the pipe. Assume that it has a susceptibility of $\kappa = 100$, the cross-sectional area for the steel is $60cm^2$. Use the parameters for the inducing field in Hutchinson, with magnitude: 53,600nT, inclination of 66°, and a declination of 4°

a. From your work in the individual TBL, what was the estimated depth of burial from your half-width calculation?

b. Using the depth and sensor height reported in the paper, what is the maximum expected total field anomaly amplitude? and half-width?

c. Adjust the magnetic susceptibility until the maximum simulated amplitude is similar to that of the maximum anomaly amplitude. What did you have to use for the susceptibility?

d. Our synthetically evaluated amplitude seems much smaller than what is observed. This might be explained by having pipes that are remanently magnetized. Let's assume that the susceptibility of the pipe is known to be 100, and that it is remanently magnetized. Using the app, return the value of the susceptibility to 100. Select which direction you expect the remanence is in, and increase Q, the Koenigsberg ratio (ratio of remnant to induced magnetization). What value of Q fits the maximum observed anomaly amplitude? What was your final choice of direction of remanence?

e. Would you expect the remanence to be vertically up or down? Why?

Q3. Survey design: Just like the researchers in the case study, you are given the task of finding all of the brine wells within a 100ft x 100ft area. Assume the following:

- Inducing field is the same as in Hutchinson, KS (magnitude: $53,600$nT, inclination of $66°$, and a declination of $4°$)

- Magnetization is induced

- Susceptibility of steel is $\kappa = 100$

- Cross-sectional area for the steel is $60cm^2$

    a. What information should be used to determine an adequate station spacing?

    b. Using the second part of the app, determine whether or not the acquisition strategy used in the case history was satisfactory to characterize a pipe buried within 20m of the surface.

- Simulate the survey for a pipe buried at several depths between 0 and 20m and observe how the anomaly changes as a function of depth.

- Will a shallow target or a deep target require a smaller station spacing to characterize?

- Is the line spacing of 3ft sufficient to characterize the perspective brine well targets? If not provide your recommendation for a minimum line/station spacing.

c. If we assume the same data acquisition efficiency that you displayed on the beach, one reading (3 repeats but no re-occupancy of a base station) then one datum can be collected every 30 seconds. How many stations and how long would it take you to acquire the data over the 100ft x 100ft grid at the spacing you decided upon above?

d. How long did it take the contractors to collect their data over this 100ft x 100ft grid? Supposing they halved their line spacing approximately how long would it have taken for them to complete their survey?

Q4. Accuracy: Suppose you want to find and estimate the depth of any pipe whose top lies within 20 m of the surface. What is the data accuracy that you need to capture this anomaly?