

# Class of Property Toolset Guide

The *Class of Property Toolset* consists of three separate tools, each designed to translate some of the most common formats that Class of Property is maintained as within Wisconsin tax rolls or county land information systems. Each tool will handle a specific format of class of property data and create an output that adheres to V2 schema definitions from Appendix F in the V2 Submission Documentation.

Use this guide if your class of property information exists in one of the formats outlined in Figure 1 and you wish to reformat this information so as to meet the requirements of the V2 schema definitions of **PROPCCLASS** and **AUXCLASS**.

**Tool 1 Format:** A feature class is required to run tool 1. In the attribute table of the feature class, class of property is separated into field(s) associated with that particular class. For example, a general property class might have a field for class 1 acres and class 1 land value. Auxiliary classes are structured the same way, but that might have fewer fields associated with each class. For an example, see the Input Table graphic for Tool 1 in Figure 1.

**Tool 2 Format:** A table (usually a tax roll) is the input format required to run tool 2. The structure for class of property in the input table follows the relational model. Each record in the table will have a unique parcel id and class of property. For example, see the Input Table graphic for Tool 2 in Figure 1, parcel 100 has three records and three distinct classes of property (1, 4, and 6).

**Tool 3 Format:** The input of tool 3 can be either a table or feature class. In this case, class of property is maintained in multiple fields with one class per field. For example, see the Input Table graphic for Tool 3 in Figure 1, parcel 300 has two classes versus parcel 200 with three classes.




Figure 1. Class of Property Tool workflow overview

The tool follows the State of Wisconsin Assessment Codes.

### **General Real Estate Property Code Descriptions**

- 1 – Residential
- 2 – Commercial
- 3 – Manufacturing
- 4 – Agricultural (Assessment values based on use in agriculture)
- 5 – Undeveloped (Assessed at 50% of full value)
- 5M – Agricultural Forest (Assessed at 50% of full value)
- 6 – Productive Forest Land
- 7 – Other

### **Special Code Descriptions (Formerly “Woodland”)**

- W1 – Private Forest Crop Pre 1972
- W2 – Private Forest Crop Post 1971
- W3 – Private Forest Crop Special
- W4 – County Forest Crop
- W5 – MFL Open Post 2004
- W6 – MFL Closed Post 2004
- W7 – MFL Open Pre 2005
- W8 – MFL Closed Pre 2005
- W9 – MFL Ferrous Mining

### **Exempt Code Descriptions**

- X1 – Federal
- X2 – State
- X3 – County
- X4 – Other

## **❶ Step 1: Install the Tool**

---

### **1.1 Download and unzip the tool**

Download the zipped package with the *Class of Property Toolset*, an ArcPy script tool, from <http://www.sco.wisc.edu/images/stories/publications/V2/tools>.

Unzip to the directory of your choice. Then open ArcCatalog and navigate to the new directory. You should see toolboxes, labeled with their respective ArcGIS version compatibility. Choose the toolbox that fits your ArcGIS install. If you do not see any toolboxes, hit F5 to refresh the directory. Once the tools are visible, move on to the next step.

The remaining sections describe the three tools individually. Please review Figure 1 to select the appropriate tool. If class of property is not maintained in a similar way to any of the tools, please contact the State Cartographer’s Office (contact information included in *Troubleshooting* Section) for additional support.

## ② Step 2: Select Appropriate Tool

### 1.2 Tool1 Overview

Tool 1 uses ancillary fields for each class of property to determine the classes of property that exist for a given record. The existence of a class of property is made by checking if the value in a field is greater than 0. The output is a duplicate feature class with a record's classes of property separated into COP and COP\_ALT fields.

The screenshot shows the 'Tool1' dialog box with the following parameters:

- 1 In FC (Required)
- 2 Out Directory (Required)
- 3 Out FC (Required)
- 4 1 - Res. (Optional)
- 5 2 - Com. (Optional)
- 6 3 - Manu. (Optional)
- 7 4 - Ag. (Optional)
- 8 5 - Undev. (Optional)
- 9 6 - Prod. For. (Optional)
- 10 7 - Other (Optional)
- 11 5M - Ag. For. (Optional)
- 12 W1 (optional) (Optional)
- 13 W2 (optional) (Optional)
- 14 W3 (optional) (Optional)
- 15 W4 (optional) (Optional)
- 16 W5 (optional) (Optional)
- 17 W6 (optional) (Optional)
- 18 W7 (optional) (Optional)
- 19 W8 (optional) (Optional)
- 20 X1 (optional) (Optional)
- 21 X2 (optional) (Optional)
- 22 X3 (optional) (Optional)
- 23 X4 (optional) (Optional)

Buttons at the bottom: OK, Cancel, Environments..., Show Help >>

Figure 2. Class of Property Tool1 parameters

Class of Property Tool1 Parameter Definitions		
1	In FC	The feature class containing class of property.
2	Out Directory	The path specified for the output feature class. This must be a path to a file geodatabase, or file geodatabase feature dataset.
3	Output FC	The name of the output feature class.
4-11	General Property Class	Select the acreage field associated with a given property class. If the acreage field does not exist, please use the land value field.
11-23	Auxiliary Class of Property (optional)	Select the acreage field associate with a given auxiliary property class.

### 1.3 Tool2 Overview

Tool 2 uses a table in a many-to-one structure, where each record contains a unique id and class of property, to generate a table with unique ids and class of property separated into COP and COP\_ALT fields. The output table can be joined to a parcel layer via the id.

The screenshot shows the 'Tool2' dialog box with the following parameters:

- 1 In Table: [Text field]
- 2 Out Table Name: [Text field]
- 3 Out GDB: [Text field]
- 4 In COP Field: [Dropdown menu]
- 5 In PIN Field: [Dropdown menu]
- 6 Native COP Domains: [Text field with value '1,2,3,4,5,5M,6,7']
- 7 Native ALT Domains (optional): [Text field]
- 8 Mapped ALT Domains (optional): [Text field]

Buttons at the bottom: OK, Cancel, Environments..., Show Help >>

Figure 3. Class of Property Tool2 parameters

Class of Property Tool2 Parameter Definitions		
1	In Table	The table containing class of property data.
2	Out Table Name	The name of the output table.
3	Out GDB	The path specified for the output table.
4	In COP Field	The field containing class of property data.
5	In PIN Field	The field containing the id. A value can exist multiple times in the table depending on the number of classes of property for a record.
6	Native COP Domains	The general class of property domains that exist for your county. Use a comma as the delimiter without spaces. By default, the output domains are listed. <b>NOTE:</b> Order does matter. The first value is mapped to 1, the second to 2...
7	Native ALT Domains (optional)	Any additional auxiliary classes of property domains for your county should be listed here. Use a comma as the delimiter without spaces. <b>NOTE:</b> Order does matter. The first value will be mapped to the first value of the Mapped ALT Domains parameter.
8	Mapped ALT Domains (optional)	The State of Wisconsin auxiliary classes of property corresponding to the domains listed in the previous parameter. Use a comma as the delimiter without spaces. <b>NOTE:</b> Order does matter. The first value of Native ALT Domains parameter will be mapped to this parameter's first value.

## 1.4 Tool3 Overview

Tool ingests a feature class or table with multiple fields used to describe class of property. The output is a duplicate feature class or table with class of property divided into two new fields, COP and COP\_ALT.




Figure 4. Class of Property Tool3 parameter

Class of Property Tool3 Parameter Definitions		
1	In Table	The table containing class of property data.
2	Out Table	The name of the output table.
3	Out GDB	The path specified for the output table.
4	In COP Fields	Select all fields in the table that contain class of property data.
5	Native COP Domains	The general class of property domains that exist for your county. Use a comma as the delimiter without spaces. By default, the output domains are listed. <b>NOTE:</b> Order does matter. The first value is mapped to 1, the second to 2...
6	Native ALT Domains (optional)	Any additional auxiliary classes of property domains for your county should be listed here. Use a comma as the delimiter without spaces. <b>NOTE:</b> Order does matter. The first value will be mapped to the first value of the Mapped ALT Domains parameter.
7	Mapped ALT Domains (optional)	The State of Wisconsin auxiliary classes of property corresponding to the domains listed in the previous parameter. Use a comma as the delimiter without spaces. <b>NOTE:</b> Order does matter. The first value of Native ALT Domains parameter will be mapped to this parameter's first value.

## ③ Step 3: Configure and Run Tool

### 1.5 Sample configurations of each tool

This zipped package includes three sample sets of data, each specific to the tool that would appropriately process it. There are feature class and table examples included for Tool3. The following images depict how the provided sample data would be used within the Class of Property Toolset.




Figure 5. Tool1 sample configuration

**Tool2**

In Table  
Z:\PROJECTS\V2\_Parcels\V2\_Parsing\_Tools\COPDissolve\_Dist\test\_data\test\_data.gdb\COPDissolveTool2\_Example

Out Table Name  
COPDissolveTool2\_Example\_COP

Out GDB  
Z:\PROJECTS\V2\_Parcels\V2\_Parsing\_Tools\COPDissolve\_Dist\test\_data\test\_data.gdb

In COP Field  
ASSMT\_CD

In PIN Field  
GISPIN

Native COP Domains  
A,B,C,D,E,5M,F,G

Native ALT Domains (optional)  
M5,M6,M7,M8,X1,X2,X3,X4,X5

Mapped ALT Domains (optional)  
M5,M6,M7,M8,X1,X2,X3,X4,X5

OK Cancel Environments... Show Help >>

Figure 6. Tool2 sample configuration

**Tool3**

In Table  
Z:\PROJECTS\V2\_Parcels\V2\_Parsing\_Tools\COPDissolve\_Dist\test\_data\test\_data.gdb\COPDissolveTool3\_FeatureClassExample

Out Table  
COPDissolveTool3\_Example\_COP\_FeatureClass

Out GDB  
Z:\PROJECTS\V2\_Parcels\V2\_Parsing\_Tools\COPDissolve\_Dist\test\_data\test\_data.gdb

In COP Fields

<input type="checkbox"/>	TXKEY
<input checked="" type="checkbox"/>	VLCO01
<input checked="" type="checkbox"/>	VLCO02
<input checked="" type="checkbox"/>	VLCO03
<input checked="" type="checkbox"/>	VLCO04
<input checked="" type="checkbox"/>	VLCO05
<input checked="" type="checkbox"/>	VLCO06
<input checked="" type="checkbox"/>	VLCO07
<input checked="" type="checkbox"/>	VLCO08

Select All Unselect All Add Field

Native COP Domains  
G1,G2,G3,G4,G5,5M,G6,G7

Native ALT Domains (optional)  
X1,X2,X3,X4,W1,W5,W6,W7,W8,4A,4B,4C,3,2,1

Mapped ALT Domains (optional)  
X-1,X-2,X-3,X-4,W-1,W-5,W-6,W-7,W-8,4-A,4-B,4-C,Z-3,Z-2,Z-1

OK Cancel Environments... Show Help >>

Figure 7. Tool3 sample configuration

# Troubleshooting for Class of Property Toolset

---

## **My tool does not show-up in the directory I have unpacked to.**

If the tool does not appear in the directory you have unpacked it to, first try refreshing the directory in ArcCatalog (Right click directory » Refresh...). If the problem continues, it may be because you are using a legacy version of ArcGIS (ArcGIS 9.0 – ArcGIS 10.0).

## **I get an error when attempting to run the tool.**

If running the tool results in an error, first ensure that the tool runs correctly on the test data provided in the zipped package.

- If the tool does not run successfully over the test data, try to interpret the error message in finding a solution and submit the error message (via screen capture or cut and paste) to Codie See at [csee@wisc.edu](mailto:csee@wisc.edu).

## **I get a properties dialogue instead of a tool input dialogue when opening the tool.**

Refresh the directory in ArcCatalog (hit F5 to refresh).

## **Who can I contact for help?**

Codie See, State Cartographer's Office, 608-890-3793, [csee@wisc.edu](mailto:csee@wisc.edu)

## **Credits**

Developed by the State Cartographers Office:

Chris Scheele  
David Vogel  
Codie See