

山东大学 计算机科学与技术 学院

大数据分析与实践 课程实验报告

学号： 202300130242		姓名：王启源		班级：数据 23	
实验题目：实验 4					
实验学时： 2			实验日期： 2025.12.18		
实验目的： 训练 bert 模型，使其适用于句子一致性判断问题					
硬件环境： 计算机一台					
软件环境： Linux 或 Windows					
实验步骤与内容：					
1.自定义一个数据集，这个数据集适用于 MRPC 数据集					
<pre>class MRPCStructuredDataset(Dataset): def __init__(self, df, tokenizer, max_length=128): self.df = df.reset_index(drop=True) # 过滤空值行和无效标签行（确保Quality是0或1） self.df = self.df.dropna(subset=['#1 String', '#2 String', 'Quality']) self.df = self.df[self.df['Quality'].isin([0, 1])] # 只保留标签为0或1的行 self.tokenizer = tokenizer self.max_length = max_length def __len__(self): return len(self.df) def __getitem__(self, idx): row = self.df.iloc[idx] sentence1 = str(row['#1 String']) sentence2 = str(row['#2 String']) label = int(row['Quality']) encoding = self.tokenizer(sentence1, sentence2, truncation=True, padding='max_length', max_length=self.max_length, return_tensors='pt') item = {key: val.squeeze(0) for key, val in encoding.items()} item['labels'] = torch.tensor(label, dtype=torch.long) return item</pre>					
2.					
导入预训练好的分词器和 bert 模型					

```
model_name = "bert-base-uncased"
tokenizer = AutoTokenizer.from_pretrained(model_name)
model = AutoModelForSequenceClassification.from_pretrained(model_name, num_labels=2)
```

3.将 MRPC 数据集导入，然后划分为训练集和验证集

```
) from google.colab import drive
from sklearn.model_selection import train_test_split
drive.mount('/content/drive')

train_path = f"/content/drive/MyDrive/datasets/msr_paraphrase_train.txt"
test_path = f"/content/drive/MyDrive/datasets/msr_paraphrase_test.txt"

full_train_df = pd.read_csv(
    train_path,
    sep="\t",
    header=0,
    names=['Quality', '#1 ID', '#2 ID', '#1 String', '#2 String'],
    on_bad_lines='skip'
)

full_train_df = full_train_df.dropna(
    subset=['#1 String', '#2 String', 'Quality']
)
full_train_df = full_train_df[full_train_df['Quality'].isin([0, 1])]

train_df, dev_df = train_test_split(
    full_train_df,
    test_size=0.2,
    random_state=42,
    stratify=full_train_df['Quality']
)

try:
    train_dataset = MRPCStructuredDataset(train_df, tokenizer)
    dev_dataset = MRPCStructuredDataset(dev_df, tokenizer)
    print(f"训练集加载成功，共 {len(train_dataset)} 条数据")
    print(f"验证集加载成功，共 {len(dev_dataset)} 条数据")
except Exception as e:
    print(f"数据集加载失败: {e}")
    exit()
```

4.导入测试集

```
) test_df = pd.read_csv(
    test_path,
    sep="\t",
    header=0,
    names=['Quality', '#1 ID', '#2 ID', '#1 String', '#2 String'],
    on_bad_lines='skip'
)

test_df = test_df.dropna(
    subset=['#1 String', '#2 String', 'Quality']
)
test_df = test_df[test_df['Quality'].isin([0, 1])]

test_dataset = MRPCStructuredDataset(test_df, tokenizer)
```

5.该函数指定了在模型训练过程中会计算哪一些指标的分数

```
def compute_metrics(pred):
    labels = pred.label_ids
    preds = pred.predictions.argmax(-1)
    precision, recall, f1, _ = precision_recall_fscore_support(labels, preds, average='binary')
    acc = accuracy_score(labels, preds)
    return {'accuracy': acc, 'f1': f1, 'precision': precision, 'recall': recall}
```

6. 设定训练参数并开始训练

```
training_args = TrainingArguments(
    output_dir="./mrpc_results",
    num_train_epochs=3,
    per_device_train_batch_size=2,
    per_device_eval_batch_size=2,
    eval_strategy="epoch",
    save_strategy="epoch",
    logging_dir="./logs",
    learning_rate=2e-5,
    load_best_model_at_end=True,
    no_cuda=False # 若没有GPU, 设为True
)

# 初始化Trainer
trainer = Trainer(
    model=model,
    args=training_args,
    train_dataset=train_dataset,
    eval_dataset=dev_dataset,
    compute_metrics=compute_metrics
)

# 开始训练
trainer.train()
```

[4701/4701 06:54, Epoch 3/3]

Epoch	Training Loss	Validation Loss	Accuracy	F1	Precision	Recall
1	0.822100	0.654303	0.798469	0.853160	0.840659	0.866038
2	0.502800	0.907340	0.823980	0.875899	0.836770	0.918868
3	0.212500	0.993345	0.836735	0.880150	0.873606	0.886792

TrainOutput(global_step=4701, training_loss=0.4851495563869805, metrics={'train_runtime': 415.2342, 'train_samples_per_second': 22.635, 'train_steps_per_second': 11.321, 'total_flos': 618245202332160.0, 'train_loss': 0.4851495563869805, 'epoch': 3.0})

7. 对测试集进行测试，得到最后的测试分数

```
test_metrics = trainer.evaluate(test_dataset)
print("Test set results:", test_metrics)
```

[815/815 00:13]

Test set results: {'eval_loss': 0.6624998450279236, 'eval_accuracy': 0.803680981595092, 'eval_f1': 0.8579040852575488, 'eval_precision': 0.8256410256410256, 'eval_recall': 0.8927911275415896, 'eval_runtime':

结论分析与体会：

掌握了如何对 bert 模型进行一个微调，使其适用于其他的任务