Problem Chosen	2020 MCM/ICM Summary Sheet	Team Control Number
C		7391856

From Review Signals to Reliable Launch Decisions

Summary

Sunshine can use review data to monitor dissatisfied experiences and investigate design problems, provided that review activity is not confused with sales. We analyze all 32,024 supplied reviews using rating distributions, transparent text descriptors, exposure-aware helpfulness measures and a calendar-based reputation model.

The microwave file has 31.8% one–two-star reviews, compared with 14.6% in the dryer file and 11.3% in the pacifier file. A conservative title cohort retains 10,475 of 18,939 pacifier-file rows and has 9.1% low-star reviewing, exposing a material scope mismatch. Reliability words strongly accompany low ratings in the electrical categories, and the association persists within product families and after explicitly excluding accessory titles. This is our strongest basis for prioritizing durability investigation. In contrast, the apparent pacifier material signal largely disappears within families; it does not establish a universal material preference.

Our dashboard combines a rolling ninety-day low-star fraction, a Beta posterior interval, issue counts, verified-review strata and vote coverage. Calendar comparisons reveal composition effects: pooled reputation trends can hide changes within existing families. Cumulative helpful votes are useful for retrospective review reception but excluded from forecasting because their historical availability is unknown.

To compare rating-only, text-only and combined warning measures, we train through 2013, select on 2014, and test complete ninety-day windows in 2015. In the primary reviewer-rich test of 3901 future reviews, the combined model has log loss 0.32368 versus 0.32402 for ratings alone. Its tiny incremental gain has a product-cluster interval spanning zero. Scoring all positive future windows eligible from past information raises its loss to 0.33104, exposing harder sparse-review outcomes. We recommend a simple rating warning baseline with text for interpretable triage, pending prospective calibration.

Product/time-adjusted review-flow associations do not clearly differ from zero. More fundamentally, missing purchases, impressions and observed rating exposure prevent identification of whether seeing low stars *causes* reviewing. We give a constructive counterexample and a practical data requirement rather than infer causality from sequence. The resulting strategy carries explicit sample, time and measurement limits and 11 independently reconstructed computational checks.

Keywords: review reputation; product reliability; temporal validation; text measurement; causal identification

Contents

Letter to the Marketing Director **3**

1 From review evidence to launch decisions **4**

2 Assumptions and measurement boundaries **4**

3 What the supplied records actually contain. **5**

3.1 Reviewer and listing composition 6

3.2 Helpfulness is conditional on receiving votes 7

4 Text that distinguishes praise, complaints and design topics **8**

4.1 Descriptor associations with rating levels 8

4.2 Design topics and family-adjusted comparisons 9

5 Tracking reviewer reputation **11**

5.1 A dashboard with uncertainty and denominators 11

5.2 Calendar trends and composition effects. 12

6 Which text–rating combination provides a useful warning? **13**

6.1 A measurable target and a fair time test 13

6.2 Likelihood, selection and uncertainty 14

6.3 A secondary target-cohort check. 16

7 Do prior stars incite subsequent reviews? **17**

8 A launch strategy matched to the evidence **18**

9 Verification, robustness and remaining limits **19**

10 Conclusion **20**

A Reproducibility and full model parameters **21**

Report on Use of AI **23**

Letter to the Marketing Director

Dear Marketing Director,

The most defensible first step is to prioritize reliability investigation for the new hair dryer and microwave. In the supplied reviews, 51.3% of target-title dryer reviews mentioning breakage or stoppage and 80.0% of corresponding microwave reviews carry one or two stars. Within-family comparisons still show roughly 38 and 41 percentage points of excess dissatisfied reviewing. These signals survive an explicit sensitivity excluding accessory titles. They justify examining durability and returned-unit failure modes; they do not yet quantify the sales benefit of redesign.

Keep the dryer easy to handle and quick to dry, and tell microwave buyers the usable capacity and plate fit. The evidence for simply reducing noise or enlarging every microwave is weaker. For the pacifier, separate genuine pacifiers from clips, cases and novelty products, publish clear age/size and cleaning information, and test acceptance in the intended use group. A pooled material-word association vanishes within product families, so it should not dictate a universal material choice.

Once products launch, track the last ninety days of ratings with the number of reviews, low-star share, full star distribution and uncertainty interval. Add counts of specific reliability, fit and cleaning complaints, verified-review strata, and vote coverage. Treat a high-probability rise of ten percentage points above a disclosed category reference as an investigation trigger, subject to prior sensitivity and actual text review. Sparse launches require more evidence before a reputation label. Set an acceptable own-product risk tolerance separately: absence of an alert above a poor historical reference does not certify acceptable quality.

We tested combinations of text and stars against future ninety-day reviews. The combined model was nominally best, but its gain over rating-only prediction was small and statistically uncertain; use text to explain and route complaints rather than claim a major predictive improvement. Cumulative helpful votes show how existing reviews are received and must be kept separate from a contemporaneous quality score.

Finally, these records do not show whether a sequence of low ratings incites new reviews. Our adjusted associations are inconclusive, and purchases, impressions and each customer's displayed review history are absent. Review counts can change because sales change or because willingness to review changes. Avoid designing rating campaigns around an unsupported causal story.

We recommend a reliability-first engineering investigation and a transparent, uncertainty-aware review dashboard. This recommendation rests on observed associations and explicit checks, while sales effects, defect incidence and performance on your brand-new listings require additional evidence.

Sincerely,
Team 7391856

1 From review evidence to launch decisions

Sunshine needs a way to decide which product problems to address, which public-facing signals to monitor, and when deteriorating feedback deserves investigation. The supplied files allow us to measure *dissatisfied reviewing*, expressed demand for design features, and review reception. They do not observe sales, profit, page impressions, non-reviewers, or which reviews any buyer saw. Our analysis therefore follows a chain: define a measurable reputation proxy, establish descriptive evidence, validate a future-warning model, and translate only supported signals into actions.

Requirement 1 is addressed by Sections 3–4; 2(a) and 2(b) by Section 5; 2(c) by Section 6; 2(d) by Section 7; and 2(e) by Section 4. The preceding letter addresses requirement 3. We use all three supplied files and their glossary [1]. Mathematical formulas below specify our own estimation and comparison choices; the only external online material consulted is generic software documentation, not product data or another solution.

Let a review have star rating $r \in \{1, 2, 3, 4, 5\}$ and define the low-star indicator $b = \mathbf{1}\{r \leq 2\}$. Its product family is the supplied `product_parent`; the glossary explicitly permits aggregation by that field. For a set of n reviews, $k = \sum b$, $q = k/n$, and $\bar{r} = \sum r/n$. The denominator for q is *reviews*, never purchases. A higher q indicates a worse observed reviewer reputation under this definition. A commercially failing product could have favorable reviews but insufficient margins or sales; such failure is not measurable here.

2 Assumptions and measurement boundaries

1. **Observed reviewers define the estimation population.** The extraction and willingness to review are unknown. We describe these records without assuming random purchasers. This restricts all prevalence statements and prevents conversion of review volume into sales.

2. **Family aggregation follows the supplied identity.** Variants can share a parent while differing in material or design. We therefore compare both pooled and within-family issue associations; family-level alarms require inspecting the actual variant before action.

3. **One–two stars operationalize dissatisfied reviewing.** This is an explicit measurement choice, supported by the supplied scale, rather than a learned definition of market success. A category-level one–three-star summary records descriptive label sensitivity, and verified-only summaries describe reviewer mix. Robustness of downstream forecasts and family issue effects to the one–three-star label is not established.

4. **A category prior stabilizes sparse windows.** Its strength of ten pseudo-reviews is a modeling choice, not an observed fact. We also examine strengths two and thirty. Probabilities from this model are conditional calculations; they are not calibrated guarantees for new Sunshine products.

5. **Text describes mentions.** A transparent dictionary measures words about enthusiasm, disappointment, and design topics. Local negation reduces some errors but does not re-

solve sarcasm, quotations or multiple product experiences. A mention is not a certified defect or a safety event.

6. **Historical information must exist at its cutoff.** Stars, text and review dates enter forecasting. Helpful votes are cumulative at extraction and lack a vote date, so they do not enter historical models. Validation covers the same 90-day horizon as the proposed warning model.

7. **Panel adjustment is associative.** Family and calendar effects remove stable listing differences and common time changes only. Exposure, purchases, selective reviewing and unobserved quality remain. We do not assume away these mechanisms to claim that ratings incite reviews.

3 What the supplied records actually contain

Table 1. Complete supplied samples. Low-star means one or two stars.

Category	Reviews	Families	Mean stars	Low-star	Voted
Hair dryer	11,470	473	4.116	14.6%	37.7%
Microwave	1,615	55	3.445	31.8%	66.9%
Pacifier	18,939	5,432	4.305	11.3%	28.0%

All 32,024 supplied rows have usable dates and integer stars in the stated range; no review ID repeats within its category. Helpful votes are nonnegative and never exceed total votes. We preserve the input files and all valid observations, including extreme votes and unpopular ratings. The earliest dates differ by category, and all files end on August 31, 2015. Inter-category comparisons consequently refer to these unequal extraction samples, not an equal market experiment.




Figure 1. Star-rating profiles. Each denominator is its complete supplied category; connecting lines guide comparison of five discrete levels.

The microwave sample has the lowest mean and the largest low-star fraction (31.8%), compared with 14.6% for hair dryers and 11.3% for pacifiers. Five-star reviews dominate each file. Thus a mean alone hides a substantial dissatisfied tail, particularly for microwave listings; a five-star share alone obscures its size. Retaining the full histogram alongside low-star risk gives an actionable picture without compressing all information into an arbitrary composite score.

3.1 Reviewer and listing composition

Purchase and Vine indicators have uppercase and lowercase forms in the supplied files. We retain their original counts and normalize case before grouping. This matters especially in the pacifier file: treating lowercase "y" as unverified would misclassify thousands of records.

Table 2. Purchase-verification sensitivity after case normalization.

Category	Verified n	Verified low	Other n	Other low
Hair dryer	9811	12.7%	1659	25.5%
Microwave	1095	15.7%	520	65.8%
Pacifier	16261	10.3%	2678	17.2%

Verified microwave reviewers have a much lower low-star fraction than unverified reviewers. This is an association, not evidence that verification improves products or that unverified complaints are false. Different products, review timing, return experiences and reviewer selection could create it. We retain both strata and advise Sunshine to show them separately. Vine samples are small and more favorable in several categories; their favorable ratings cannot be treated as unbiased launch predictions.

The files also contain surrounding and unrelated products. For example, microwave cavity paint and a magnetron/diode kit appear in the microwave file; pacifier storage boxes, a baby-shower game and a thermometer appear in the pacifier file. Concordances also expose baby cups and video monitors; the hair-dryer file contains some unrelated beauty products. Deleting them silently would change the question's provided samples. Instead, our main results retain every row and a separate sensitivity excludes titles matching declared accessory words.

Table 3. Title-exclusion sensitivity; excluded records remain in every main result.

Category	Excluded n	Retained n	Retained low
Hair dryer	69	11401	14.5%
Microwave	136	1479	34.3%
Pacifier	842	18097	11.1%

This transparent exclusion is imperfect: a combined pacifier-and-clip title may be removed, while an unusual accessory without those words may remain. It is a sensitivity, not a manually verified ontology. After exclusion, the low-star fractions for reliability-mention reviews are Hair dryer: 50.9%; Microwave: 79.7%. The reliability signal survives this direct challenge; its exact prevalence should still be checked on Sunshine's own product variants. Tables and frozen results retain the words, excluded titles and counts.

A stronger scope challenge adds positive title words: hair dryer/hairdryer/blow dryer/blowdryer; microwave/microwaves; and pacifier/pacifiers/paci/soothie/soothies. It then excludes the declared accessory words. Genuine hood dryers are retained even if the title says stand; pure holders are excluded. This conservative lexical rule can miss genuine products and include combined packages, so it is a target-title sensitivity rather than certified product labels.

Table 4. A stricter positive-title cohort for transfer to the three intended products.

Category	Target reviews	Families	Mean stars	Low-star
Hair dryer	11035	123	4.122	14.4%
Microwave	1467	39	3.337	34.4%
Pacifier	10475	286	4.419	9.1%

The pacifier file is particularly heterogeneous: only 10,475 of 18,939 rows meet this narrow scope, and their low-star fraction is 9.1% instead of 11.3%. Target-cohort design comparisons below use that explicit membership. This scope correction was made after the first complete paper and original final-test results were inspected, in response to the observed title/concordance mismatch. Its predictive comparison is transparently secondary; it does not restore an untouched test set.

3.2 Helpfulness is conditional on receiving votes

For review i, define $u = h/v$ when $v > 0$, where h and v are helpful and total votes. When $v = 0$, u is undefined. We report both vote coverage $\Pr(v > 0)$ and aggregate helpfulness $\sum h / \sum v$. The latter is a vote-weighted fraction and gives more influence to highly exposed reviews; it is not the mean usefulness of every review.

Table 5. Cumulative voting and text length.

Category	Helpful/votes	Age–votes ρ	Length–votes ρ
Hair dryer	85.0%	0.31	0.37
Microwave	84.3%	0.45	0.46
Pacifier	73.1%	0.23	0.36

Vote coverage is 66.9% for microwave reviews, 37.7% for hair dryers and 28.0% for pacifiers. Many pacifier and hair-dryer reviews therefore provide no measured helpfulness judgment. Zero votes must not be interpreted as zero usefulness. Time since the latest recorded review is positively correlated with total votes, as is text length. Length–vote correlations remain positive within age quartiles in all categories. This supports an exposure-aware presentation, but longer writing could also reflect severe problems, product complexity or selection.

For launch monitoring, Sunshine should show issue prevalence among *all* reviews and helpfulness only among voted reviews, always displaying both denominators. A vivid, heavily voted complaint warrants examination, but weighting every reputation estimate by votes would con-

found product quality with exposure and aging. This is why our forecasting model deliberately uses no helpfulness field.

Table 6. Extreme ratings and vote reception in the supplied files.

Category	1-star voted	5-star voted	1-star helpful	5-star helpful
Hair dryer	67.9%	31.7%	78.2%	89.0%
Microwave	79.1%	56.8%	80.0%	90.2%
Pacifier	64.3%	21.5%	61.3%	79.8%

One-star reviews are more likely than five-star reviews to receive any votes, yet their conditional helpful-vote fractions are lower. Their text is also longer on average in all three files. This distinguishes attention from endorsement: a complaint can attract votes without every voter endorsing it. Neither difference certifies a true defect or proves that readers change purchases. Age, listing and reviewer selection are unresolved.

4 Text that distinguishes praise, complaints and design topics

We normalize case, replace HTML markup with spaces, and use letter tokens from headline plus body. Enthusiasm is operationalized by love/loves/loved, excellent, perfect, great and amazing; recommendation is tracked separately and also enters the positive bundle. Disappointment includes disappointed/disappointing/disappointment, terrible/horrible/awful, broken/broke/breaks/defective, stopped and return/refund variants. A positive match is suppressed if a negator occurs among the preceding three tokens, including cannot and contracted would-not/could-not forms. Curly apostrophes are normalized. Recommendation intensification such as cannot recommend enough is retained only without a following not/no/never; could-not-be-more-perfect is retained. These are scoped heuristics rather than complete sentiment parsing. This dictionary is declared in executable source; no external sentiment corpus or pretrained sentiment labeler is used.

4.1 Descriptor associations with rating levels

For a descriptor, let a, b count low/non-low reviews with a mention and c, d those without. We report the corrected odds ratio

$$O = \frac{(a + 1/2)(d + 1/2)}{(b + 1/2)(c + 1/2)}. \tag{1}$$

An approximate log-odds interval is $\log O \pm 1.96\sqrt{V}$, where

$$V = \sum_{z \in \{a,b,c,d\}} \frac{1}{z + 1/2}. \tag{2}$$

It describes count-based association and ignores within-family clustering. Fisher tests and Benjamini–Hochberg adjusted values for all 33 declared category–descriptor comparisons are retained in the results; they are exploratory under the usual dependence conditions, not product-effect tests.

Table 7. Declared descriptors and low-star associations. OR compares a mention with no mention.

Cat.	Descriptor	n	Low-star	OR	95% interval
H	love	2668	3.9%	0.19	[0.16, 0.23]
H	perfect	617	3.6%	0.21	[0.14, 0.32]
H	disappointed	345	57.1%	8.71	[6.99, 10.85]
H	broken	434	48.6%	6.20	[5.10, 7.55]
H	return	447	68.9%	15.67	[12.73, 19.29]
M	love	183	13.1%	0.30	[0.19, 0.46]
M	perfect	155	3.2%	0.07	[0.03, 0.16]
M	disappointed	49	65.3%	4.17	[2.31, 7.54]
M	broken	105	82.9%	11.99	[7.17, 20.04]
M	return	99	70.7%	5.77	[3.70, 8.99]
P	love	6846	2.8%	0.15	[0.13, 0.18]
P	perfect	1453	1.6%	0.12	[0.08, 0.18]
P	disappointed	400	59.8%	13.00	[10.59, 15.96]
P	broken	237	50.6%	8.48	[6.55, 10.98]
P	return	312	67.0%	17.53	[13.79, 22.29]

Expressions of love and perfection associate with higher ratings, whereas disappointment, breakage and returns associate with low ratings in each supplied category. The full one–five-star distributions are retained in the machine-readable results, so the analysis does not force all text into two sentiments. The pattern answers question 2(e), but does not prove that changing review wording changes the star rating. Stars and text are jointly produced by an author's experience, and their disagreement is itself useful for triage.

We inspect deterministic concordances for broken, disappointed, perfect and recommend: three matching review IDs per category and descriptor. These examples expose ambiguity, such as praising a replacement while mentioning an earlier break or saying a feature is perfect for only one use. They are neither a random accuracy sample nor human labels. A frozen-first-draft review found RJ9VV71726BA2 (would not recommend) and R12R4SUKX7I6OY (cannot recommend this product) incorrectly positive. The repaired lexer and independent validator now suppress them, retain positive enough-intensification examples, and suppress RLCG35UOS05E8, which recommends not buying. Six targeted original-text cases pass; the prior lexer and results remain preserved. This correction follows first-test inspection and is not a global semantic-accuracy certification. The dictionary therefore remains a measured *mention* system. A customer-service analyst should read flagged text before identifying a root cause.

4.2 Design topics and family-adjusted comparisons

Each target-title cohort has a small declared topic dictionary. Reliability uses words such as broke, broken, stopped or defective; dryer topics also include noise, weight, heat and power/speed. Microwave topics include size/capacity, heating, noise and controls. Pacifier topics include acceptance, cleaning, size/fit, material and attachment. Positive and negative

topic words are both retained: a "quiet" mention is not a noise complaint.

Table 8. Target-title issue mentions. Within-family differences are percentage points.

Cat.	Mention	n	Low-star	OR	Within	Families
H	reliability	959	51.3%	8.58	+38.1	81
H	noise	1136	14.6%	1.02	+0.2	89
H	weight	1932	9.7%	0.59	-5.5	102
H	heat	2307	17.2%	1.31	+3.8	114
H	power/speed	3275	8.1%	0.43	-8.3	120
M	reliability	255	80.0%	12.00	+41.1	33
M	size/capacity	480	17.1%	0.28	-17.3	24
M	heating	394	34.5%	1.01	-2.3	34
M	noise	142	32.4%	0.91	-6.2	16
M	controls	295	35.6%	1.07	-0.9	30
P	acceptance	1465	9.8%	1.10	-0.1	134
P	cleaning	957	7.3%	0.78	-0.8	75
P	size/fit	2069	11.8%	1.47	+3.2	149
P	material	548	14.8%	1.81	+0.2	62
P	attachment	494	9.1%	1.01	+0.4	42

Here OR compares the low-star odds with versus without a topic. "Within" is a family-adjusted risk difference: for families having at least three mentioning and three non-mentioning reviews, calculate the difference in their low-star fractions and average it with weights $n_1 n_0/(n_1+n_0)$. This reduces stable listing-mix confounding without making a causal claim. The number of eligible families is reported to expose sparse comparisons.

Reliability mentions have large negative-review associations for dryers and microwaves, and these persist within families. We therefore most confidently recommend prioritizing durability investigation for both electrical products: inspect returned units, separate early failures from later wear, and validate control and motor/heating-system endurance before promoting extra features. The data identify complaint themes, not the physical failure mechanism or a quantified return on investment.

For pacifiers, the material-topic pooled association largely disappears within families, showing how a plausible-looking aggregate result can be driven by listing composition. Acceptance words also mix a baby's refusal with successful acceptance. We do not claim that one material or pacifier shape is universally preferred. The usable recommendation is to present clear age/size and cleaning information and test acceptance on the intended age range; use actual text to distinguish rejection, fit, cleaning and accessory issues. For dryers, power/speed and weight mentions often occur in favorable reviews; preserve portability and quick drying while investigating reliability. For microwaves, size/capacity is frequently discussed favorably, so a small footprint alone should not be read as a defect: communicate actual usable capacity and plate compatibility.

5 Tracking reviewer reputation

5.1 A dashboard with uncertainty and denominators

At cutoff t, collect reviews in $[t-90, t)$ using real calendar days. Track n, k/n, mean stars and the histogram; positive/negative and reliability-mention fractions; verified-review strata; vote coverage and conditional helpfulness separately. The window highlights current feedback while cumulative averages serve as context. A new listing with few reviews is visibly uncertain rather than automatically praised or condemned.

For current low-star risk, use the category's pre-2014 low-star mean p_0 as a disclosed reference and strength $s = 10$:

$$p \mid k, n \sim \text{Beta}(k + sp_0,\ n - k + s(1 - p_0)), \qquad E[p \mid k, n] = \frac{k + sp_0}{n + s}. \tag{3}$$

This follows by multiplying the binomial likelihood $p^k(1-p)^{n-k}$ by the Beta prior density. The 95% interval is given by its 2.5% and 97.5% quantiles, computed using SciPy [3]. The interval quantifies uncertainty inside this model, including its fixed prior choice, rather than selection bias or variant mixing.

An *investigation alert* requires at least ten recent reviews and

$$\Pr(p > p_0 + 0.10 \mid k, n) \geq 0.95. \tag{4}$$

The ten-percentage-point margin is an illustrative managerial tolerance. It is not optimized from unobserved business costs. Alerts prompt reading complaints and inspecting batches; they do not alone authorize withdrawing a product. For each alert, the saved results repeat its probability with strengths two and thirty. A decision that changes under these values receives the label "prior-sensitive" and requests more evidence.

Table 9. Target-title monitoring at August 31, 2015; alerts are relative to a historical reference.

Category	Baseline low	Eligible families	Alerts
Hair dryer	17.2%	30	0
Microwave	44.1%	3	0
Pacifier	9.8%	35	0

The last dashboard uses the target-title cohort and June 3–August 31, 2015, inclusive; its category baseline and eligible-family counts are explicit. No family crosses the 95% relative-alert rule, and this status is unchanged at prior strengths two and thirty. This is not evidence that all products are acceptable: the historical microwave reference itself has 44.1% low-star reviewing, and absence of an alert means only insufficient evidence of a further ten-point excess. For Sunshine's cold-start launches, using a competitor prior is provisional. Publish the counts, retain all genuine complaints and gather enough own-product history to replace it. Before deployment, management must choose an acceptable reviewer-risk tolerance u separately from a competitor reference. If the cost of a false investigation is A and the cost of missing a genuinely excessive-risk product is D, investigating has lower expected binary decision loss

when $\Pr(p > u \mid k, n) > A/(A + D)$. This follows by comparing $A(1 - P)$ with DP, for $P = \Pr(p > u \mid k, n)$. The illustrative 95% threshold is an evidence convention, not a cost-optimal threshold; the files supply neither u nor those costs. A historically poor category must not normalize an unacceptable product. Serious individual complaints still require ordinary investigation even before the statistical threshold is met; a frequency alarm and an engineering incident are different objects.

5.2 Calendar trends and composition effects




Figure 2. Quarterly reviewer risk. Points summarize calendar quarters with at least ten reviews; 2015 Q3 stops on August 31. Listing composition may change between points.

A fall in q or rise in mean stars suggests improving reviewer reputation; rising issue prevalence or a low-star burst suggests deterioration. Growth in the number of reviews is ambiguous: it may accompany popular sales, a review campaign or controversy. Figure 2 consequently plots reputation proportions rather than treating the volume trend as success.

We compare full-year 2014 with January–August 2015. To distinguish changing products from changing responses, restrict to families with at least twenty reviews in each period and standardize both periods using their 2014 review counts:

$$Q_{\text{old}} = \frac{\sum w_j q_{j,\text{old}}}{\sum w_j}, \qquad Q_{\text{new}} = \frac{\sum w_j q_{j,\text{new}}}{\sum w_j}, \quad w_j = n_{j,\text{old}}. \tag{5}$$

The family weights are fixed for both quantities; results cannot be explained simply by larger later weights on popular families. This comparison still mixes seasonal differences and limits itself to established families, so it is not a universal annual trend.

The pooled microwave low-star share declines much more than its matched-family standardized share. The pacifier matched-family risk increases even though its pooled fraction changes little. These are useful cautions against reading a file-wide average as a product's own reputation. The microwave matched subset includes an accessory; the exact family list is retained, and the title sensitivity should be applied before transferring the comparison to an oven launch.

Table 10. Pooled and fixed-composition reputation changes.

Category	2014 low	2015 low	Families	Fixed 2014	Fixed 2015
Hair dryer	13.1%	11.9%	28	12.0%	11.0%
Microwave	30.3%	22.0%	3	16.0%	13.9%
Pacifier	10.5%	10.7%	33	7.3%	9.6%

Table 11. Fixed-composition changes inside the target-title cohort.

Category	2014 low	2015 low	Families	Fixed 2014	Fixed 2015
Hair dryer	13.0%	11.7%	28	12.0%	11.0%
Microwave	33.4%	24.1%	2	16.8%	16.0%
Pacifier	8.2%	9.2%	30	6.6%	9.3%

Within the stricter cohort the established microwave comparison has only two families and changes from 16.8% to 16.0%, while the pooled cohort changes from 33.4% to 24.1%. Pacifier fixed-composition risk rises from 6.6% to 9.3%. These differences demonstrate the practical need to track an actual listing and product scope, while avoiding a general causal explanation of the temporal change.

Table 12. Selected family changes (percentage points); not discovery tests.

Category	Parent ID	Old/new n	Change	Posterior interval
Hair dryer	195677102	23/102	+7.8	[-7.1, +11.4]
Microwave	423421857	126/259	+0.7	[-8.4, +7.3]
Pacifier	277493012	20/33	+18.2	[-0.7, +26.2]

Intervals for selected family changes are computed by subtracting independent draws from the two Beta posteriors (10,000 draws, fixed seed 2020). They include substantial uncertainty; selecting the largest observed change does not make it statistically confirmed. For example, an apparent pacifier-family deterioration merits a closer read but is not evidence of a production change. Sunshine should monitor its own family and variant history, review growth, rating tail and topic counts together.

6 Which text–rating combination provides a useful warning?

6.1 A measurable target and a fair time test

To answer 2(c), define success in the limited sense of *favorable future reviewer reputation*, and failure risk as the probability that a future review is one or two stars. At each calendar-quarter cutoff from January 2010 through April 2015, use the preceding 90 days for predictors and the following 90 days for outcomes. Prediction windows require at least five reviews on each side; the forecast therefore concerns active reviewed families. The broader flow analysis in Section 7 retains zero future counts.

Training cutoffs end in 2013; all their outcomes precede 2014. The 2014 cutoffs select model complexity and the model family. Final evaluation uses January 1 and April 1, 2015, whose complete future windows end before the supplied cutoff. No partial third-quarter outcome is invented. The fixed 90-day windows leave small gaps between adjacent quarters instead of pretending every quarter has ninety days. Product identity may repeat across time, which is appropriate for updating an existing listing; entirely new-product launch transfer is a different problem.

Let m and y be the future review count and its low-star count. A constant category model estimates its low-star rate from training outcomes. A recent-risk baseline predicts $(k+10p_0)/(n+10)$, where this forecast prior uses the training *eligible-window* outcome mean. Its different sampling denominator from the dashboard prior is explicit. We then compare three regularized logistic candidates [2]:

- Ratings: recent low-star fraction, scaled mean $(\bar{r}-3)/2$, $\log(1+n)/5$, and category indicators.
- Text: negative, positive and defect/return mention fractions, the same recent-count transform, and category indicators.
- Combined: all rating and text predictors with the same count and category terms.

"Text-only" here means no rating predictors; the shared volume and category terms keep structural information equal. The defect bundle is overlapping with negative text by design, so coefficient signs cannot be read as independent effects. We do not include vote snapshots, future review dates, or learned text parameters from the final test.

6.2 Likelihood, selection and uncertainty

For predictor vector x, $p(x) = 1/(1+\exp(-a-x^T b))$. Fit the binomial log likelihood with an ℓ_2 penalty on b; the intercept is unpenalized:

$$\min_{a,b} \; -\sum \{y \log p + (m-y)\log(1-p)\} + \frac{\|b\|^2}{2C}. \tag{6}$$

We implement each window as two weighted observations, with weights y and $m-y$, which gives this exact aggregate likelihood. Each candidate selects $C \in \{0.1, 1, 10\}$ by 2014 review-weighted log loss; all selected C values equal 0.1. Their parameters remain fitted to the training prefix: no final-test refit or threshold tuning is performed.

The main loss is

$$L = -\frac{\sum\{y\log p + (m-y)\log(1-p)\}}{\sum m}; \qquad B = \frac{\sum\{y(1-p)^2 + (m-y)p^2\}}{\sum m}. \tag{7}$$

The Brier loss B provides a second probability score. Both operate at the future-review level and preserve the binomial denominator; a tiny window is not given the same precision as a large one. This choice favors high-volume families, so the results should not be represented as an equal-weight guarantee for every listing.

Table 13. Prediction comparison on identical calendar windows. Lower loss is better.

Model	2014 log loss	2015 log loss	2015 Brier
Category	0.34352	0.34850	0.10000
Recent	0.33200	0.33129	0.09140
Ratings	0.32722	0.32402	0.09008
Text	0.33223	0.32969	0.09217
Combined	0.32685	0.32368	0.09012

The final test contains 3901 future reviews in 222 windows and 138 families. Development contains 262 eligible windows. The combined model wins nominally on development and final-test log loss. Its gain over ratings alone is only 0.000342 nats per review, and ratings alone has a slightly better final Brier score. Therefore the evidence supports a rating-based warning baseline with text as interpretable triage; it does *not* establish that text makes prediction materially better.

Table 14. Final-test losses by category. Combined was selected on 2014 data.

Category	Reviews	Families	Ratings	Text	Combined
Hair dryer	1892	63	0.32598	0.33107	0.32636
Microwave	259	8	0.47397	0.53170	0.47922
Pacifier	1750	67	0.29971	0.29829	0.29777

Microwave validation rests on eight final-test families and 259 reviews. Its uncertainty and distribution shift are more consequential than a fifth decimal place. Pacifier and dryer samples are larger, but their active-family restriction still prevents unqualified transfer to a brand-new listing. Of 138 test families, 84 do not occur in the training snapshots, yet each supplies at least five recent reviews at prediction time; this is not a zero-history cold-start experiment.

We resample entire test families 1,000 times, retaining all their windows, and recompute the review-weighted loss difference. Intervals below are percentile product-cluster bootstrap intervals conditional on this test sample and fixed fitted models. They address clustering of losses, not model selection uncertainty or selection of reviewed families.

Table 15. Combined-model improvement in final-test log loss.

Comparator	Gain	95% product-cluster interval
Category	0.024817	[0.007557, 0.049701]
Recent	0.007607	[0.001813, 0.013766]
Ratings	0.000342	[-0.000597, 0.001410]
Text	0.006006	[0.002083, 0.010725]

The combined model beats category and recent-risk baselines in this observed test, while the interval for its gain over ratings includes zero. It is unjustified to label the complex combination decisively best. That negative result answers the requested comparison more usefully

than asserting a gain because a model contains both stars and text.




Figure 3. Held-out calibration. Points use fixed risk bins and review-weighted means from the combined model; the diagonal denotes agreement. Some bins have few reviews, so this is a diagnostic rather than a calibration guarantee.

Figure 3 shows imperfect calibration, especially for microwaves and sparse upper-risk bins. We therefore do not translate forecast probabilities directly into an automatic launch/no-launch decision. A warning score may rank investigation needs, but financial costs, recall thresholds, sales response and a prospective calibration test are absent. Rechecking these on Sunshine's own reviewed products is a condition for deployment.

6.3 A secondary target-cohort check

The stricter title cohort repeats every candidate with the same predictors, 90-day calendar definition, training years and 2014 selection rule. It has 3771 test reviews in 211 windows and 131 families.

Table 16. Secondary target-cohort sensitivity with the same algorithms and calendar split.

Model	2014 log loss	2015 log loss	2015 Brier
Category	0.33551	0.34486	0.09845
Recent	0.32606	0.33032	0.09085
Ratings	0.32120	0.32352	0.08985
Text	0.32562	0.32759	0.09135
Combined	0.32081	0.32308	0.08986

The combined model again wins nominally, but its gain over ratings is 0.000437 with a product-cluster interval [-0.000535, 0.001544]. The conclusion is unchanged: text is valuable for complaint routing, while its incremental forecast improvement is not established. Because this cohort definition followed inspection of the original test and concordances, these numbers are a scope robustness check rather than a second untouched confirmation.

Coverage at prediction time. Eligibility for a real dashboard depends on past reviews alone, while the original future-at-least-five filter selects an evaluation population. It is a coverage limitation, not use of future values as predictors. We preserve that primary comparison and additionally score all 300 2015 past-eligible windows: 298 have observed future reviews and 2 have none. Zero-review windows retain predictions but missing observed risk, never a fictitious zero-risk label. The original primary comparison covers 74.0% of these windows.

Table 17. Secondary coverage check: every 2015 window eligible from its past.

Model	Primary loss	All positive loss	Small-future loss
Category	0.34850	0.35607	0.49159
Recent	0.33129	0.33832	0.46419
Ratings	0.32402	0.33154	0.46599
Text	0.32969	0.33702	0.46829
Combined	0.32368	0.33104	0.46272

All positive windows contain 4119 reviews. The omitted small-future windows contain 218 reviews, including 39 low-star reviews (17.9%), and are more difficult than the primary reviewer-rich subset. The combined all-positive log loss is 0.33104 versus 0.33154 for ratings. This is another post-first-review sensitivity with the original training/development eligibility retained, not a new untouched test. The lexical repair is also carried through the revised historical comparisons; no updated result is represented as the immutable first complete draft.

7 Do prior stars incite subsequent reviews?

A sequence of poor ratings could attract complaint reviews, discourage purchases and hence reduce reviews, or reflect an underlying product problem that affects both earlier and later authors. The files observe neither what prospective customers read nor the non-reviewers. We first test an association that the available information can actually support.

For every eligible past-quarter window with at least five recent reviews, retain the next ninety-day review count m, including $m = 0$. Restrict to families with at least three such windows so a within-family comparison exists. Estimate separately in each category:

$$\log(1 + m) = \alpha_j + \tau_t + \beta q + \gamma \log(1 + n) + e. \tag{8}$$

Family effects α_j adjust persistent differences; calendar-cutoff effects τ_t adjust common shocks; prior count controls review-flow persistence. Least squares gives a transparent descriptive benchmark. Standard errors cluster by family, with a finite-sample correction. The intervals use a normal approximation; eight microwave families are too few for strong inferential assurance.

All three coefficient intervals cross zero. Repeating the panel on the target-title subset gives dryer $\beta = -0.159$, microwave -0.133 and pacifier -0.096; all three intervals still cross zero. The target microwave comparison has only seven families. This scope check does not remove unmeasured exposure or selection. We find no clear adjusted association between prior low-star

Table 18. Past low-star share and subsequent review flow.

Category	Windows	Families	β	Approx. 95% interval
Hair dryer	461	63	-0.159	[-0.634, 0.316]
Microwave	50	8	-0.055	[-1.060, 0.949]
Pacifier	353	58	-0.134	[-0.712, 0.445]

share and subsequent review volume in these eligible windows. A ten-point rise in q corresponds to $\exp(0.1\beta) - 1$ in the fitted $1 + m$ scale, not a causal percent change in purchases. Including zero-count future windows avoids selecting only products that continued attracting reviews.

The rank correlations between prior and subsequent low-star proportions are positive (approximately 0.12 for dryers, 0.52 for microwaves and 0.37 for pacifiers among positive-count windows). That is consistent with persistent dissatisfied experiences, reviewer selection or contagion, and cannot distinguish them. It provides a reason to inspect repeat complaints, not to claim that preceding reviewers persuaded later authors to complain.

Why causal incitement is not identified. Even in the simple expectation $E[m] = S\pi$, sales S and review propensity π are both unobserved. Counts changing from one to two can arise with sales changing from ten to twenty at unchanged $\pi = 0.1$, or unchanged sales of one hundred with π changing from 0.01 to 0.02. Both worlds can have the same prior stars and observed subsequent reviews. A further unobserved variable can determine which prior stars were displayed. Thus a fixed-effect fit cannot identify how seeing ratings changes reviewing behavior.

Sunshine should not solicit a string of particular ratings to stimulate review volume on the basis of these files. To test incitement, it would need a separately authorized design recording impressions, displayed rating histories, purchases and review opportunities, with random or defensible quasi-random variation. Such new data are outside this problem; the current answer is a tested association plus a constructive identification limit, rather than a causal yes/no invented from correlations.

8 A launch strategy matched to the evidence

Our most confident recommendation is a reliability-first investigation program for dryers and microwaves. It is supported by large low-star associations, persistence within product families, and a sensitivity that excludes explicit accessory titles. This evidence ranks an investigation priority; it does not measure how much revenue a durability redesign will earn. The engineering team should code actual failure modes from returned units and complaints before deciding which component to alter.

For the hair dryer, preserve the favorably described quick drying and manageable weight, communicate intended use, and monitor repeated stoppage/breakage alongside heat-related text. Noise mentions alone show little excess low-star risk; a blanket "make it quieter" priority is weaker than the reliability recommendation. For the microwave, preserve clearly communicated usable capacity and plate fit while auditing early failures and controls; do not interpret favorable size discussion as proof that every buyer wants a larger oven. For the pacifier, avoid deriving

a universal material preference from the pooled data. Separate core pacifiers from clips, cases, novelty items and unrelated baby goods in Sunshine's dashboard, publish size/age and cleaning information, and test the intended use with a correctly scoped product cohort.

After launch, use the past ninety-day dashboard as a compact weekly view, updating counts without changing its calendar definition. Show the low-star posterior with its interval, actual issue count, verified strata, review volume and time since launch. A new listing starts as "insufficient own history." An alert leads to a named product-family investigation, variant check and review of new batches; a cleared investigation remains in the record rather than disappearing because a cumulative mean recovered.

The predictive rating baseline can supplement this process once at least five recent reviews exist. Text remains valuable because it names why a review may be unfavorable, even where its incremental forecast loss is indistinguishable from zero. Display helpfulness as reception of already visible reviews, with vote coverage and age context, rather than letting a highly voted early review dominate a supposed quality score. The recommended workflow has observable inputs and an explicit action boundary; it requires neither unobserved sales nor fabricated customer histories.

9 Verification, robustness and remaining limits

The numerical result is bound to run `20261012T092912-46b2850a`. 11 automatic checks pass, each supporting a limited claim: independent CSV/Counter reconciliation of rows, star histograms and votes; independent regex/contingency reconstruction of descriptor odds ratios; exact-rational posterior means and numerical integration of Beta tails; every saved calendar window rescanned against raw rows; saved final predictions scored with independent rowwise summation; the panel focal coefficient verified by residualizing the outcome and predictor; a constructive sales–review-propensity counterexample; exact target-title membership, reliability counts, rational within-family effects and fixed-composition trend reconstruction; secondary subset-window/final-loss reconstruction; all past-eligible outcome coverage with zero-label checks; and six targeted original-text negation cases. None of these checks is a human semantic audit, a causal experiment or an award judgment.

The validator uses a different computation path from the model: standard-library parsing instead of pandas summaries, exact cross-products instead of log-odds evaluation, density integration instead of a distribution survival call, and Frisch–Waugh–Lovell residualization rather than trusting a full fitted coefficient. Data and measurement definitions are shared intentionally. Model and validator therefore can agree on an incorrect interpretation of a word; that remaining semantic risk is stated, not hidden behind a passed check.

Robustness checks have different purposes. Verified-only and category-level one–three-star summaries describe reviewer and label sensitivity without certifying all downstream robustness; title exclusions challenge category scope; within-family comparisons challenge listing mix; prior strengths challenge sparse-data monitoring; temporal holdout challenges a 90-day forecast; and product-cluster resampling challenges independence of forecast losses. No parameter perturbation alone certifies selection-free population quality. The source preserves uncompetitive forecast candidates and both failed initial workflow attempts; no failed receipt is

relabeled as a successful run.

The principal unresolved quantities are sales and profit, exposure and selective reviewing, true defect incidence, latent sentiment accuracy, zero-history launch performance, and prospective calibration. A broad extracted category includes accessories, unrelated products and many short-lived families; a future Sunshine product is not exchangeable with all of them merely because its name is similar. The 2015 horizon is a historical test, not validation of later markets or a multi-year forecast. These limits restrict deployment while leaving the observed relationships and monitoring formulas useful.

10 Conclusion

The three files support an evidence-based launch dashboard and a concrete design investigation priority. Track dissatisfied reviewing with its count and uncertainty, retain the rating distribution and verified strata, and read reliability complaints before drawing engineering conclusions. Product and reviewer composition materially affect category averages. Combined text and ratings give a competitive historical warning baseline, but the observed incremental gain over ratings alone is too small and uncertain to justify a strong superiority claim. Prior low ratings do not show a clear adjusted review-volume association here, and their causal incitement effect is not identified. Sunshine can act on the measured complaint themes while collecting the additional evidence needed for sales, causality and prospective decisions.

References

[1] COMAP. *2020 MCM Weekend 2, Problem C: A Wealth of Data*. Original three-page problem, glossary and supplied `hair_dryer.tsv`, `microwave.tsv`, `pacifier.tsv`. Data periods end August 31, 2015. All numerical product evidence derives from these supplied records.

[2] scikit-learn developers. *Linear Models: Logistic Regression*, version 1.9.1 documentation. https://scikit-learn.org/stable/modules/linear_model.html. Generic method/software documentation consulted October 12, 2026.

[3] SciPy developers. *scipy.stats.beta*, online manual. https://docs.scipy.org/doc/scipy/reference/generated/scipy.stats.beta.html. Consulted October 12, 2026; local execution version 1.18.1. Used for the explicitly derived Beta posterior quantiles and tails.

A Reproducibility and full model parameters

The preserved run receipt records Python 3.12.0, pandas 2.3.3, NumPy 2.5.3, SciPy 1.18.1 and scikit-learn 1.9.1, the exact argv, raw-input hashes, code snapshot and output hashes. The case contains executable `code/model.py` and `code/validate.py`, saved predictions, every calendar snapshot, the complete descriptor/aspect tables and concordance candidates. The plotting and paper generator uses those saved results, not fresh model fits. No external product data, learned sentiment corpus or same-topic solution is used.

The two initial failed attempts remain retained: one failed in concordance serialization after an incorrect pandas Series accessor; the next computed all checks but the workflow rejected a checks-evidence field of the wrong schema type. The accepted rerun uses the corrected source and records those failures without upgrading their status.

Receipt SHA256 (join the two lines):

```
8dd15ad1a42dc190a9f8e75f3c741436
48e05fa1ca139045d2ae247704600679
```

All raw data are unchanged; example team identity and original year are explicit. A4 and 12pt are elected project house style, not asserted as official 2020 requirements. The original problem's twenty-page solution and twenty-four-page total limit are used; references and appendices appear after the solution and are excluded according to that problem. Historical general AI/font rules are not asserted as verified.

Table 19. Combined-model parameters fitted only on the training prefix.

Term	Coefficient
Intercept	-0.96532
risk	0.30523
mean scaled	-0.80545
logn	-0.39433
negative	0.05887
positive	-0.39416
defect	-0.04124
microwave	0.68260
pacifier	-0.49926

Report on Use of AI

This is autonomous AI historical practice, with example team number 7391856 and no actual contest submission. The author AI formed definitions, wrote and executed model and validator source, inspected results, wrote the English paper and letter, generated vector figures and performed visual/code checks. The coordinating AI fixed the execution contract, input identity and budget before author work, then independently inspected the frozen first complete draft and returned formatting, prediction-scope and lexical counterexample findings. These findings led to repair of long formula/hash lines and appendix/AI page boundaries, a scoped negation repair, and an all-past-eligible evaluation. All revised historical checks disclose their post-first-test identity. Any final qualitative evaluation belongs to the accompanying review record; no award is claimed by the author. No human participant's independent mathematical work or semantic verification is claimed.

The accessible runtime identifies this service as Codex based on GPT-6; an exact provider model identifier and actual model token/cost metering are unavailable and remain unknown. The transcript provided to this task and retained technical events are not a complete provider chat export. We do not fabricate a complete prompt/response log. Program stdout, stderr, timestamps, hashes and source snapshots are technical records, not full AI conversations.

The permitted generic Praxis resources and three frozen lessons were read before route selection: measure the actual proxy and selection mechanism; preserve real calendar intervals and a matching forecast horizon; and validate task performance rather than representation fit. These do not provide answers to this problem. No same-topic paper, author code or targeted human feedback was accessed before this autonomous version.