Problem Chosen	2016	Team Control Number
A	**MCM/ICM**	**7391856**
	Summary Sheet	

A Hot Bath: Conserving Water Without Losing Uniformity

Summary

Conserving bath water requires two decisions: when to replace lost heat, and whether that heat can reach the coldest region in time. Our strategy uses stored warmth first, replenishes before a remote cold region loses its reserve, and reduces inflow only while a feasible continuation remains.

We prove coast-then-hold optimal for a perfectly mixed bath. A conservative three-dimensional thermal network then resolves the temperature differences hidden by that benchmark. Coefficients have correlation-based anchors and explicit scenario ranges. Comfort is represented by a floor in every cell and ceiling/spread limits outside a 0.15 m inlet zone; this does not resolve jet or skin-film safety.

For 164.25 L initially at 40°C, a 30-minute bath with a 39°C floor needs **24.14 L** under the best accepted constant trickle. The buffered six-stage policy waits five minutes, replenishes for fifteen and coasts for ten, using **21.48 L** (11% less). Independent continuous-time checks qualify it on three networks. The mixed optimum is 16.01 L and the spatial energy lower bound 15.41 L; the searched spatial policy is not a global optimum.

Transport changes the value of waiting. A local sensitivity criterion compares the extra rate needed after a delay with the water saved while the faucet is off. Stronger mixing permits a qualified 780 s wait followed by a pulse; at least 790 s is impossible for any allowed common inflow on that fixed network. Weak mixing has a separate all-control obstruction. An axial model reproduces the timing change, while cooler-than-mean overflow rules out excess outlet heat loss as its explanation in the tested baselines.

Geometry and body contact change heat storage, exposed area and delivery distance. Motion improves transport but can raise surface loss; an assumed foam layer lowers constant-flow demand to 10.4 L. These are conditional mechanisms, not measured human or additive effects. Under parameter ambiguity, the controller retains only models consistent with two probe histories and waits or reduces inflow only if all survivors retain a checked continuation. Inconsistent readings trigger reassessment; tested recovery may cost more water. The one-page guide translates these findings into actions and states their measurement and execution conditions.

Keywords: thermal network; energy balance; lower bound; optimal control; sensitivity analysis

Contents

1 Problem formulation 3

2 Assumptions and parameterization 4

3 Well-mixed thermal model 5

4 Mixed-model optimum and spatial energy bound 7

5 Spatial heat-network formulation 8

6 Numerical solution and control search 9

7 Replenishment policies 10

7.1 Piecewise-constant control optimization 11

7.2 Temperature–water trade-off 12

7.3 Delivery-error sensitivity 12

7.4 Supply decisions from temperature probes 13

8 Geometry and body-parameter sensitivity 15

9 Transport, heat loss and replenishment timing 16

10 Numerical verification 17

11 Structural uncertainty and model limitations 17

11.1 Common-reserve structural comparison 18

11.2 Observation-updated control 19

11.3 Parameter changes and fixed-policy bounds 20

11.4 Transport comparison and network infeasibility 21

12 Recourse after model rejection 22

13 Practical guidance 23

14 References and reproducible algorithm 24

Appendix A. Scenario definitions 25

Report on Use of AI 26

1 Problem formulation

The task is to preserve both warmth and spatial uniformity in an overflowing, unheated tub, and to examine geometry, the bather and motion, and a bubble-bath layer [1]. The report separates physical requirements from preference assumptions. There is no supplied temperature record or measured heat-transfer coefficient to fit.

The decision variables are an inlet flow rate and the time at which a constant trickle begins. The tub is already full: added water displaces an equal volume through the overflow. The horizon is 1,800 s. Our baseline requires every cell average to stay at or above 39°C, and requires the cell averages outside a 0.15 m jet-mixing zone around the inlet to stay at or below 41°C and within an instantaneous spread of 1.5°C. These choices operationalize comfort; they are not medical limits or numbers specified by the problem, and the jet zone is an assumption justified in Section 2.

$$J = 1000 \int_0^{t_f} q(t)\, dt \tag{1}$$

$$T_i(t) \geq T_{\min} \ \ (\forall i), \qquad T_i(t) \leq T_{\max}, \quad \max_{i\in\Omega} T_i(t) - \min_{i\in\Omega} T_i(t) \leq \Delta \ \ (i \in \Omega) \tag{2}$$

Here Ω is the set of cells outside the inlet jet zone, q is in m³/s and J is in litres. We prioritize the least water within the constraints, rather than assigning arbitrary weights to unlike units. Tightening the temperature tolerance is a separate scenario. Zero flow is admitted: if the initial stored heat suffices, using no added water is globally water-minimal.

Table 1 maps each requirement to its answer.

Table 1. Where each requirement is answered

Requirement	Where answered
Temperature in space and time	Sections 3, 5–7; Figures 1–2
Water-use strategy and its scope	Sections 4, 6–7 and 12
Tub/body geometry, size and temperature	Section 8
Motion and bubble-bath additive	Section 9
Validation and sensitivity	Sections 8–11
One-page non-technical explanation	Section 13

Spatial temperature means a control-volume average. It does not bound the unresolved temperature of a faucet jet or a skin-contact film. This distinction determines which practical conclusions the simulation can support.

Modeling options. The lumped model supplies a proved benchmark; the conservative network resolves cold regions with an explicit mixing parameter [5]. A velocity solver needs jet and turbulence data unavailable here. Table 2 compares their roles.

Table 2 contrasts spatial resolution and data requirements.

Table 2. Modeling options compared

Option	Resolves	Evidence it needs	Role here
Lumped (Newton)	Mean temperature	Two loss coefficients	Proved benchmark
Thermal network	Cells, heat paths, overflow	Loss, body and mixing coefficients	Decision model
Flow solver	Velocity and buoyancy	Turbulence closure, jet data	Not used

2 Assumptions and parameterization

The problem supplies no calibrated coefficients. Section 2 separates external anchors from assumptions; scenarios test the important ones.

Table 3 separates assumed inputs from anchored coefficients.

Table 3. Baseline inputs

Quantity	Baseline / units	Status
Tub L × W × H	1.50 × 0.65 × 0.23 m	Assumed geometry
Displaced body volume / area	0.060 m³ / 1.15 m²	Assumed
Water density / heat capacity	1000 kg/m³ / 4180 J/(kg K)	Rounded constants
Air / skin / inlet temperature	22 / 34 / 50°C	Fixed reservoirs
Surface / wall / body coefficient	25 / 6.5 / 25 W/(m² K)	Correlation-based (next page)
Mixing diffusivity D	0.001 m²/s	Uncalibrated closure; range tested
Initial / lower / upper limit	40 / 39 / 41°C	Preference scenario
Time / allowed spread	1800 s / 1.5°C	Preference scenario

A1. Constant density and heat capacity. Water properties change by under 1% between 39 and 41°C, and the constants are rounded values, not an evaluated IAPWS table [3]. *Reason:* the resulting capacity error is small next to the loss coefficients.

A2. Linear exchange. Newton's law [2] approximates the narrow temperature span. Surface loss includes convection, radiation and evaporation once; evaporative volume change is neglected. Room-temperature linearization understates near-40°C sensitivity by about 7% of total loss in an independent estimate, within the tested coefficient range.

A3. Skin held at a fixed temperature. *Reason:* thermoregulation is outside the problem; skin temperature is varied (32 and 36°C) instead of resolved.

A4. Prescribed surface stream. Water traverses the top row nearest the centre line (half

a cell off it for even row counts). Alternative paths and whole-section flow are tested in Section 11; the route is assumed, not measured.

A5. Mixing as one effective diffusivity D. Motion enters through D, with a separate surface-loss scenario. *Reason:* molecular diffusion alone would not represent circulation; D is anchored only by an order-of-magnitude scaling (Section 2) and is tested over a range; vertical mixing is tested separately in Section 9.

Parameter provenance.

No temperature record exists to fit, so each coefficient is derived from a textbook relation or tied to a published measurement where one exists, and given a range; where nothing exists (mixing, the exposed fraction, the air and skin temperatures) the value is an assumption and is labelled as one. Surface loss sums natural convection above a hot horizontal surface ($\mathrm{Nu} = 0.15\,\mathrm{Ra}^{1/3}$ for $10^7 < \mathrm{Ra} < 10^{11}$, length A/P [5]; here $\mathrm{Ra} = 1.9 \times 10^7$), linearized radiation (emissivity 0.96) and evaporation by the Lewis analogy. For open water at 40°C in 22°C air at 50% humidity the parts are 4.7, 6.1 and 24.6 W/(m² K) (0.66 kg/m² h evaporated), 35.4 in total. A bather covers part of the surface; with an assumed exposed fraction of 0.7 the central value is 24.8, and we use 25 within the range 17–37, which spans exposed fractions of 0.5 to 1.0. Evaporation correlations differ by tens of percent, so this is a scenario range, not a measured one.

A 5 mm shell (0.19 W/(m K)), with inside/outside films 300/8 W/(m² K), gives a series coefficient 6.5, with range 4.7–8.4; these are typical inputs. Menzies et al. observed rectal rise 0.9 ± 0.3°C after 30 min shoulder-depth immersion at 40°C [6]. For mass 73 kg and heat capacity 3470 J/(kg K), an assumed mean rise 1–2°C implies uptake 141–281 W and equivalent exchange 20–41 W/(m² K) at fixed 34°C skin. We use 25. Mean rise and driving difference are assumptions: this is a scale anchor, not calibration. Body capacity is about 37% of water capacity; its delayed warming is tested in Section 11.1.

The assumed scaling $D \approx 0.1u'\ell$ gives $1 \times 10^{-4}/1 \times 10^{-3}/6 \times 10^{-3}$ m²/s for velocity/eddy-length pairs (0.02 m/s, 0.05 m), (0.1, 0.1) and (0.3, 0.2). We use 0.001 and test 0.0003–0.003; these are circulation scenarios, not measured diffusivities.

The 39–41°C window is a preference, not a safety standard [6]. Inlet-cell maxima increase 40.55/40.76/41.00°C on the three meshes: the point source heats less water per cell. Ceiling/spread therefore exclude a 0.15 m inlet zone, assuming no bather occupies the jet; the floor covers every cell, as required by Section 4. Section 11 checks constrained quantities.

Table 4 summarizes the coefficient anchors and scenario ranges.

3 Well-mixed thermal model

Table 5 defines storage, transport and exchange symbols.

Let C be total water heat capacity, H_a the air/shell conductance and H_b the body conductance. A well-mixed overflow has the same temperature as the bath. Integrating the physical energy balance gives

$$C\dot{T} = H_a(T_a - T) + H_b(T_b - T) + \rho c_p q(T_{\mathrm{in}} - T) \tag{3}$$

Table 4. Coefficient anchors and the values used

Coefficient	Relation or anchor	Derived value	Used (range tested)
Surface, W/(m² K)	Convection + radiation + evaporation [5]	35.4 open; 24.8 at 70%	25 (17–37)
Shell, W/(m² K)	Series resistance, typical shell values	6.5 (4.7–8.4)	6.5 (4.5–8.5)
Body, W/(m² K)	Uptake implied by core rise [6]	20–41 at fixed skin	25 (12–40)
Mixing D, m²/s	Mixing-length scaling	1×10^{-4} to 6×10^{-3}	0.001 (0.0003–0.003)

Table 5. Symbols

Symbol	Meaning
C	Heat capacity of the water, J/K
H_a, H_b	Air/shell and body conductance, W/K
T_a, T_b, T_{in}	Room, skin and inlet temperature, °C
T_{min}, T_{max}	Lower and upper limit, °C
q, J	Inlet flow, m³/s; added water, L
D	Effective mixing diffusivity, m²/s

$$C = \rho c_p(LWH - V_b), \quad H_b = h_b A_b \tag{4}$$

$$H_a = h_s f LW + h_w\{LW + 2H(L + W)\} \tag{5}$$

The foam multiplier f equals one without a layer. Setting $q = 0$, define $H = H_a + H_b$ and $T_e = (H_a T_a + H_b T_b)/H$. The cooling solution and first time to reach the lower limit are

$$T(t) = T_e + (T_0 - T_e)e^{-Ht/C} \tag{6}$$

$$t_c = \frac{C}{H} \log \frac{T_0 - T_e}{T_{\min} - T_e} \tag{7}$$

Baseline conductances are H_a = 37.14 W/K and H_b = 28.75 W/K, and C = 686,565 J/K. Thus T_e = 27.24°C and t_c = 14.17 min.

A heat-loss model must approach an environmental equilibrium rather than zero Celsius. This analytic boundary also supplies a direct check on signs and units. The benchmark describes mixing perfectly; the spatial model will test the cost of departing from that assumption.

4 Mixed-model optimum and spatial energy bound

Let $\ell(T) = H_a(T - T_a) + H_b(T - T_b)$ be the heat loss of the mixed bath, and let the inlet be hotter than every temperature considered. **Proposition 1.** Coasting to the lower limit and then holding it uses the least water, provided the holding rate is within the faucet bound. The proof has four steps.

Proof. **Step 1, an identity.** Dividing the balance by $T_{\text{in}} - T$ and integrating over the horizon gives

$$\int q\, dt = \frac{C}{\rho c_p} \log \frac{T_{in} - T_0}{T_{in} - T_f} + \int \frac{\ell(T)}{\rho c_p (T_{in} - T)}\, dt \tag{8}$$

Step 2, monotonicity. The integrand $\ell(T)/(T_{\text{in}} - T)$ has derivative $[H_a(T_{\text{in}} - T_a) + H_b(T_{\text{in}} - T_b)]/(T_{\text{in}} - T)^2 > 0$, so it increases with T, and the logarithmic term increases with the final temperature. Water use is therefore an increasing functional of the temperature path.

Step 3, the lowest admissible path. Because $q \geq 0$, comparison with the no-flow solution gives $T(t) \geq T_c(t)$, the cooling curve of Section 3, and feasibility requires $T(t) \geq T_{\min}$. The pointwise lowest admissible path is $\max(T_c(t), T_{\min})$: coast until T_c reaches $T_{\min}$, then hold.

Step 4, attainability. Holding $T = T_{\min}$ means $\dot{T} = 0$, which needs the rate

$$q_{hold} = \frac{\ell(T_{\min})}{\rho c_p (T_{in} - T_{\min})} \tag{9}$$

When this rate is within the bound, the path is feasible and, by Step 2, optimal.

□

For the baseline, the mixed-model optimum adds 16.01 L: wait 14.17 min, then supply 1.012 L/min. Optimality is established for the mixed model; spatial policies are assessed separately.

Proposition 2 (energy lower bound). In the spatial model, suppose every cell satisfies $T_i(t) \geq T_{\min}$. Summing the cell balances gives $\sum_i C_i T_i(t_f) - CT_0 = -\int L\,dt + \rho c_p \int q(T_{\text{in}} - T_{\text{out}})\,dt$, with L the total loss. Each loss term increases with its cell temperature, and H_a and H_b are the sums of the cell conductances, so $L(t) \geq \ell(T_{\min})$. The outlet cell satisfies $T_{\text{out}} \geq T_{\min}$, so $T_{\text{in}} - T_{\text{out}} \leq T_{\text{in}} - T_{\min}$, and the left side is at least $C(T_{\min} - T_0)$. Combining these three facts,

$$J \geq \max\left(0, \frac{1000[\ell(T_{\min})t_f - C(T_0 - T_{\min})]}{\rho c_p (T_{in} - T_{\min})}\right) \tag{10}$$

The resulting 15.41 L is a genuine conditional lower bound, valid for any control, but it is not tight: the initial water is hotter than the floor and loses more heat, and limited mixing adds further cost. Section 7.1 shows how much of the gap an optimized schedule recovers.

5 Spatial heat-network formulation

The rectangular water envelope is divided into 8 × 4 × 3 cells. Each has a capacity C_i and exchanges heat only across common faces. The cells whose centres lie within 0.15 m of the inlet cell form the jet zone (2, 9 and 22 cells on the 8 × 4 × 3, 12 × 6 × 4 and 16 × 8 × 6 meshes); Ω is the rest. Top cells lose heat to the room; bottom and side faces lose heat through the shell. The bather is represented by a smooth, three-dimensional displacement field and a distributed skin contact term.

$$C_i \dot{T}_i = \sum_j g_{ij}(T_j - T_i) + H_{a,i}(T_a - T_i) + H_{b,i}(T_b - T_i) + S_i \tag{11}$$

$$g_{ij} = \rho c_p D \frac{A_{ij}}{d_{ij}} \min(\phi_i, \phi_j), \quad C_i = \rho c_p V_i \tag{12}$$

Here ϕ is fluid fraction, A_{ij} a face area and d_{ij} the center separation. Symmetric g_{ij} guarantees that internal heat exchange cancels when the equations are summed. D is an effective mixing closure; molecular diffusion alone would not represent motion or buoyant circulation.

$$w_i \propto \exp\left[-\frac{1}{2}\sum_{k=1}^{3}\left(\frac{x_{ik} - b_k}{s_k}\right)^2\right], \quad \sum_i w_i = 1 \tag{13}$$

$$V_i = V_{cell} - V_b w_i, \quad H_{b,i} = h_b A_b w_i \tag{14}$$

Baseline $\mathbf{b} = (0.55L,\ W/2,\ 0.45H)$, with widths $\mathbf{s} = (0.40, 0.16, 0.12)$ m. Fluid fraction is $\phi_i = V_i/V_{\text{cell}}$. The center $\mathbf{b}$ and widths $\mathbf{s}$ set the spatial distribution of body effects. Body volume and contact area remain independent inputs: shape is varied through $\mathbf{s}$ at fixed volume and area. This is a homogenized immersed-body representation, not an anatomically resolved obstruction. A cell whose occupied fraction reaches 0.95 is rejected rather than assigned a negative capacity.

A fixed envelope volume is preserved by balancing inlet and overflow. In the baseline the exact displaced-water volume is 164.25 L. Shape scenarios preserve envelope volume when isolating aspect-ratio effects. Volume scenarios deliberately change water depth and hence both storage and side-wall area.

Spatial temperature distribution.

Figure 1 locates cold regions across layers on one scale.




Figure 1. Final cell-average temperatures. The three layers share a color scale; distances are in metres.

The heat map and Figure 2 use the same archived trajectory. Exchange couples the horizontal layers into one three-dimensional network. The cold-region locations explain information lost by a mean or range; the mesh table tests resolution. These are homogenized cell averages, not resolved anatomy, recirculation or a faucet jet.

6 Numerical solution and control search

One surface stream carries the common q: hot water enters its first cell, upstream exchange transfers heat along the path, and its last cell overflows.

$$S_1 = \rho c_p q(T_{\text{in}} - T_1), \quad S_i = \rho c_p q(T_{i-1} - T_i) \tag{15}$$

$$\sum_i C_i \dot{T}_i = -\sum_i H_{a,i}(T_i - T_a) - \sum_i H_{b,i}(T_i - T_b) + \rho c_p q(T_{\text{in}} - T_{\text{out}}) \tag{16}$$

This prescribed stream permits short circuit but does not establish excess outlet heat loss. Section 11.4 diagnoses its sign against a distinct whole-section closure; Section 11.1 changes the internal path at fixed inlet and overflow. Neither route is an inferred velocity field.

For a fixed flow, the network is affine linear. Augmenting the state by a constant one permits matrix-exponential propagation, avoiding a large forward-Euler step restriction [4]. A delayed-start policy has two exact constant-control segments.

$$\dot{\mathbf{T}} = A(q)\mathbf{T} + \mathbf{b}(q), \quad \mathbf{z}(t+\tau) = e^{\widetilde{A}(q)\tau}\mathbf{z}(t) \tag{17}$$

Starts are tested at 0, 120, …, 1200 seconds. For each, rates from 0 to 3 L/min are bracketed on a 0.2 L/min grid; the first crossing of the lower-temperature requirement is refined by Brent's root method. The search targets $T_{\min}$ + 0.03°C as numerical reserve, then checks the upper-temperature and spread limits at 5-second output intervals. Starts that already violate the floor are rejected.

This is a reproducible candidate search. Nonmonotone flow responses, untested delays, pulsed inputs, inlet relocation and feedback are not excluded by the calculation. A failed search means no candidate was accepted, not that every possible action is infeasible. The independent checks further examine the chosen trajectory between samples.

7 Replenishment policies

Figure 2 contrasts the mean, coldest cell and spatial range.




Figure 2. Temperature evolution under constant replenishment. Shading spans the coldest cell to the hottest cell outside the inlet jet zone.

Table 6 reports the constant-rate trajectory and water use.

Table 6. Baseline result under the best constant rate

Result	Baseline
Rate / start	0.805 L/min / 0.0 min
Added water	24.14 L
Minimum / maximum	39.030 / 40.318°C
Maximum simultaneous spread	0.967°C
Final volume-weighted mean	39.418°C

Within the constant-rate family, starting the trickle immediately ranks ahead of delayed starts here, even though waiting is optimal in the ideal mixed model. The distant water needs time to receive heat; larger late rates create a warmer inlet region before they solve the cold-region constraint. This is a concrete consequence of resolving space.

Holding a perfectly mixed bath at 40°C throughout would use 36.22 L. This is a stricter reference service, not a like-for-like optimum. Our accepted 1°C cooling allowance uses less water partly because it provides a different service. The comparable mixed model with the same lower limit uses 16.01 L. The gap also reflects our restricted control family and 0.03°C numerical reserve; it cannot be attributed purely to imperfect mixing.

7.1 Piecewise-constant control optimization

Constant-rate policies are a narrow family. We therefore optimize piecewise-constant inlet flow in K equal segments (K = 3, 6, 12) by sequential quadratic programming, minimizing added water under the same floor and outside-jet limits (with the 0.03°C floor reserve), sampled every 5 s, from four starting schedules. The problem is non-convex: each result is the best local optimum found, with no global claim.

Table 7 separates candidates from proved bounds.

Table 7. Constant rate, scheduled flow and the bounds

Policy	Water (L)	Change	Min / max (°C)	Spread (°C)
Best constant rate	24.14	—	39.03 / 40.32	0.97
3 segments, coarse candidate	19.75	-18.2%	39.03 / 40.74	1.50
6 segments, coarse candidate	19.50	-19.2%	39.03 / 40.73	1.50
12 segments, coarse candidate	19.35	-19.9%	39.03 / 40.80	1.50
6 segments, accepted	21.48	-11.0%	39.13 / 40.79	1.42
Perfect-mixing optimum	16.01			
Energy lower bound	15.41			

```
Input: network, limits, K, starting schedules
for each starting schedule x0:
  minimize sum(x)*segment_time  over 0 <= x <= 3 L/min
  subject to  min_i T_i(t) >= Tmin+reserve,
              max_{i in Omega} T_i(t) <= Tmax,
              spread over Omega <= span   (every 5 s)
retain coarse candidates and buffered alternatives;
replay on three meshes with independent integration;
accept only if continuous bounds meet all limits
```

Figure 3 shows flow timing and temperature constraints.

The accepted 6-segment policy is off for the first 5.0 minutes and last 10.0 minutes, with a peak flow of 1.67 L/min. For consecutive 5-minute intervals the rates, rounded to nine decimals, are 0, 1.668107192, 1.343440056, 1.283871597, 0, 0 L/min; the interval duration times their sum is 21.477094 L. It adds 21.48 L, 11.0% below the constant rate. Its 0.1°C design margin sacrifices some water savings to protect the stated constraints. The remaining 6.06 L gap to the energy bound is not an optimality certificate.

The unbuffered 12-segment candidate uses 19.35 L but reaches a spread of 1.531°C on the finest mesh, above the 1.5°C limit, so it is rejected. Among the tested buffered alternatives, the accepted 6-segment policy gives spreads of 1.400, 1.395 and 1.416°C on the 8 × 4 × 3, 12 × 6 × 4 and 16 × 8 × 6 meshes. Independently integrated continuous-time bounds also pass on each




Figure 3. Buffered 6-segment replenishment. Flow rates (top) and temperatures outside the inlet jet zone (bottom); dotted lines mark the limits.

mesh. This establishes numerical feasibility for these tested networks, not mesh-independent physics or a global minimum.

7.2 Temperature–water trade-off

The task asks for a bath close to its initial temperature without wasting much water, which is a trade-off rather than a single optimum. Figure 4 repeats the search while the allowed fall below 40°C changes from 0.25 to 3°C; the 1°C case is the baseline. With a fall of 2.5°C or more the stored heat suffices and no water is added. At 2°C the best constant rate adds 1.9 L, at 1.5°C 12.9 L, at 1°C 24.1 L and at 0.75°C 29.8 L. Between 2°C and 0.75°C each further 0.5°C of tolerance is therefore worth roughly 11 L, almost linearly. At 0.5°C the best constant rate adds 36.3 L; for a fall of 0.25°C no constant-rate policy was accepted, while the perfectly mixed bath would still need 30.7 L.

Figure 4 compares searched spatial policies with analytical benchmarks.

The spatial-minus-mixed gap increases from 1.5 L at a 2°C fall to 9.2 L at 0.75°C. Scheduling lowers the baseline by 11%; schedules at other tolerances were not optimized.

7.3 Delivery-error sensitivity

We distinguish fixed tap bias from random segment errors. For the unbuffered 12-segment candidate, multiplying every rate by 0.9 or 1.1 crosses a limit by 0.076 and 0.126°C. Independently drawing each multiplier from a normal distribution of mean 1 and standard deviation 0.1, clipped below zero, gives median and 5th-percentile slacks of -0.070 and -0.217°C (200 draws, seed 11). Standard deviation 0.1 does not mean an error bounded within ±10%. Negative slack is a violation, however small.

The error is not symmetric. The most sensitive segment is segment 4 (2.81 L/min), where raising the flow by 20% breaks the limits by 0.245°C and lowering it by 20% by 0.047°C: extra hot water overheats the inlet region and widens the spread. Over-delivery in a high-flow segment




Figure 4. Water use versus temperature tolerance. Crosses denote unsuccessful searches; the dotted line marks the baseline.

is the error to guard against. 1 of the 5 active segments tolerates a 20% error in either direction.

The price of a margin is measured on a 6-segment version. Requiring all three limits to hold with a buffer b gives 19.50 L at b = 0, 21.48 L (+10%) at 0.1°C, 23.81 L (+22%) at 0.2°C and 26.83 L (+38%) at 0.3°C. With the 0.1°C buffer, 74% of 200 draws with independent Gaussian multiplier standard deviation 0.1 stay within the limits. The 0.1°C policy is selected here for its independently checked numerical margin. Its 74% acceptance under the stated random error model does not make it a reliable manual prescription; a real bath needs temperature feedback and separate calibration.

7.4 Supply decisions from temperature probes

Mixing changes timing: the weaker-mixing candidate starts immediately. Two probes miss violations in two of nine cases. We now propagate observation ambiguity into the supply decision.

A separate synthetic trial applies (0, 0, 1.2, 0, 0, 0) L/min in five-minute stages. Known geometry starts uniformly at 40°C; cells 89 and 6 are read every 30 s. Assumed reading errors and constant probe biases are each bounded by ±0.02°C; these are not instrument specifications.

For parameters θ and probe j, let $d_j(t;\theta) = T_j(t;\theta) - y_j(t)$. At observed times $\mathcal{T} = \{0, 30, \ldots, 1800\}$ s, a model is compatible when a constant correction a_j exists such that

$$\min_{|a_j| \le 0.02} \max_{t \in \mathcal{T}} |d_j(t;\theta) - a_j| \le 0.02 \quad (j = 1, 2). \tag{18}$$

The extreme-discrepancy midpoint clipped to the bias bound is the minimax correction, with physical bias $b_j = -a_j$. A trace from -0.04 to +0.04°C fails: bias cannot vary between readings.

Our grid has 7 mixing values (0.00085–0.00115 m²/s), 9 surface and 9 body coefficients (20–30 and 15–35 W/(m² K)), and 5 delivery multipliers (0.95–1.05). Of 2835 models, 178 fit. This finite decision ambiguity set is neither a confidence region nor a probability distribution.

Table 8 compares archived policies with a replacement optimized on ten extreme/failing models, using a 2 L/min bound, 0.1°C target and 0.03°C extra floor reserve. All 178 pass three-grid envelopes; the tightest spread bound is 1.496828°C. The selected target is not an all-model margin or global optimum.

Table 8. Policies on the same measurement-compatible set

Policy	Command (L)	Delivered (L)	Sampled pass
Constant	24.14	22.94–25.35	130/178
Nominal six-stage	21.48	20.40–22.55	174/178
Ambiguity-set six-stage	23.48	22.31–24.66	178/178

The table uses the same 178 models and five-second sampling; archived policies were not re-optimized. Only the replacement has 534 three-grid envelopes. Its five-minute rates are 0.892820, 1.473786, 1.179268, 1.150408, 0.000000, 0.000000 L/min; envelope extrema are 39.1297/40.9238°C.

The replacement costs 9.33% more than the nominal policy. A separate zero-inlet trial with the same prior, probes and errors retains 510 models, including unidentified delivery bias; its candidate passes 1530 three-grid envelopes. The two observation sets intersect in 167 models; they are not nested or probabilistic.

Table 9 separates control and trial water. Both candidates restart at uniform 40°C with the same control family and design targets.

Table 9. Observation-conditioned trial and control costs

Observation / trial	Models	Control (L)	Trial (L)
Nominal / passive	510	24.39	0.00
Nominal / pulse	178	23.48	6.00
Strong mixing / passive	60	16.51	0.00
Strong mixing / pulse	14	15.37	6.00
Weak mixing / passive	70	Not accepted	0.00
Weak mixing / pulse	11	35.05*	6.00

Passive rates are 1.419252, 1.083923, 1.055204, 1.044908, 0.274962, 0.000000 L/min. Initial filling and reset are not free; these conditional candidates do not establish expected information value or global optimality.

Let n unchanged baths share one trial; let $\alpha \in [0.95, 1.05]$ be the common delivery multiplier and R_0, R_1 the actual reset litres for passive and pulse designs. The difference between their total actual-water costs is

$$C_0 - C_1 = \alpha\big(n\Delta - 6\big) + R_0 - R_1, \qquad \Delta = 0.909836\ \text{L}. \tag{19}$$

At nominal delivery, passive costs less for one bath if $R_0 - R_1 < 5.0902$ L. Equal reset costs give a crossover at 6.59 baths: passive is cheaper through six, pulse from seven. Reuse requires

unchanged geometry, heat transfer, probes and delivery bias; otherwise remeasure. This is not online feedback or a real-bath guarantee.

Two additional observations use (D, surface/body coefficients)=(0.00115,20/15) and (0.00085,30/35), in m²/s and W/(m² K), with nominal delivery. Separate trials retain the same prior/errors. Strong mixing gives a 1.1406 L control-cost gap, so equal-reset pulse reuse pays from six. The three accepted candidates pass 255 distinct three-grid envelopes.

*The weak-mixing pulse passes physical limits but fails the optimizer and extra design margin. No passive candidate was accepted within two starts and three constraint-generation rounds; neither failure proves infeasibility. These are observation-conditioned outcomes, not ex ante experiment values or sequential inference.

8 Geometry and body-parameter sensitivity

Table 10 isolates geometry, storage and body changes.

Table 10. Geometry, size and body scenarios

Change from baseline	Water (L)	Interpretation
Shallow Wide	No candidate	Same envelope volume
Deep Narrow	17.48	Same envelope volume
Small Bath	27.05	Lower water depth
Large Bath	20.39	Higher water depth
Deep Bath	13.05	Depth 0.35 m, like a bath filled to the shoulders
Larger Body	28.11	More displacement/contact
Long Body	23.85	Shape only; fixed volume/area
Warmer Skin	21.08	Skin at 36°C
Cooler Skin	27.18	Skin at 32°C

At equal volume, the wide, shallow tub has a larger exposed top area and a changed diffusion length; it has no accepted candidate. The deep, narrow tub needs 17.48 L against 24.14 L, because a deep, narrow envelope reduces top-area heat loss, although a real deep bath may stratify, which Section 9 tests with a separate vertical-mixing scenario. Geometry is therefore more than an interchangeable cooling coefficient.

Changing depth changes storage and shell area. The large bath needs 20.39 L replenishment; the small bath needs 27.05 L. At 0.23 m the baseline is shallow: its surface-to-volume ratio is about 1.7 times that at shoulder depth; a 0.35 m bath needs 13.05 L. Initial filling is excluded from J, so lower replenishment does not establish lower total water use.

The larger-body case combines displacement and contact-area changes and needs 28.11 L; the long-body case changes distribution at fixed volume/area. Warmer skin reduces the exchange driving difference. These are conditional scenarios, not measured human responses.

To transfer the model to a real tub, measure water volume after entry, submerged contact geometry, temperatures at several depths and distances, and no-inlet cooling. Shape and

temperature should not be inferred from a single mean cooling curve.

9 Transport, heat loss and replenishment timing

Table 11 separates transport benefits from boundary losses.

Table 11. Conditional strategy map

Scenario	Water (L)	Action and evidence
Weak Mixing	—	Change conditions (E96)
Strong Mixing	19.40	Wait 10 min; supply (S)
Moving With Added Surface Loss	23.04	Wait 8 min; supply (S)
Stratified	24.42	Supply now (S)
Convective Surface Layer	24.10	Supply now (S)
Foam	10.37	Supply now (S)
Tight Comfort	36.32	Supply now (S)
Loose Comfort	1.87	Supply now (S)
Low Loss	8.60	Supply now (S)
High Loss	—	Unresolved
Cool Supply	44.80	Wait 4 min; supply (S)

S means five-second sampled qualification; E96 is the matched 96-cell all-control exclusion (Section 11.4). Delays precede constant flow; high loss is unresolved. No interpolation follows. Section 7 separately qualifies the baseline by three-grid continuous envelopes.

When does waiting save water? For constant q after delay d, set $F = T_{89}(H) - 39.03$, $H = 1800$ s, q in L/min. On a feasible branch with that terminal target uniquely binding, other limits slack, $q, F_q > 0$, $q' = -F_d/F_q$. Hence $J = q(H - d)/60$ gives $J' = q(\eta - 1)/60$, $\eta = -(H - d)F_d/(qF_q)$. Waiting saves water locally if $\eta < 1$: shorter supply outweighs the compensating rate increase. At $d = 0$, $\eta = 1.071/0.900$ for D=0.001/0.003: waiting costs/saves water. Independent sensitivities/envelopes agree. F includes transport and loss; this is not a global mixing threshold or pulse-optimality theorem.

Strong mixing uses 19.40 L against 24.14 L. Raising its surface coefficient by 20% to 30 W/(m² K) raises water to 23.04 L; transport improvement and boundary loss remain distinct.

Assumed $\ell = 0.077$ m, $\Delta T = 1$ K, $u = 0.02$ m/s and $\beta = 3.8 \times 10^{-4}$ K^{-1} give Ri $= g\beta\Delta T\ell/u^2 \approx 0.7$. The Munk–Anderson factor $(1 + 3.33\text{Ri})^{-3/2} \approx 0.15$ [8] motivates vertical/horizontal diffusivity ratio 0.2: water rises from 24.14 to 24.42 L, spread from 0.97 to 1.07°C. These are unmeasured stratification scales. Surface-cooling convection instead motivates ratio 3, giving 24.10 L.

Foam scales only surface loss by 0.4, reducing the accepted constant-flow amount to 10.37 L. The assumed 60% reduction is unmeasured; layer breakup or increased evaporation requires recomputation.

Weak-mixing, high-loss and wide-shallow sampled rates 0.8–2.5 L/min violate spread when inflow meets the floor. This finite search is inconclusive. Section 11.4 separately cer-

tifies a fixed-network obstruction; changed circulation, inlet layout, duration or tolerance needs new evidence.

At D=0.003, the 700 s delayed constant policy qualifies; 720 s ends at 39.03°C but dips to 38.9918°C. The pulse waits 780 s, supplies 3 L/min for 90 s, then 0.952428 L/min through 1800 s: 19.26 L. Independent 0.1 s chord bounds give floor ≥39.0043°C, ceiling ≤40.000004°C, spread ≤0.790423°C, assuming 2×10^{-6}°C error per phase accumulated across switches.

A sufficient waiting cutoff. On the archived network, no common measurable $q(t) \in [0, 3]$ L/min preserves the 39°C floor through 1800 s after waiting ≥790 s. For $T' = AT + v + q(BT + h)$, optimistic $g(T) = AT + v + 3\max(BT + h, 0)$ dominates every control. Metzler Jacobians with nonpositive row sums give comparison/contraction. Flux replay bounds cell 89 at 876.5 s by 38.9980°C, including <0.004439°C SSP2/Euler/IEEE64 error. Stable maps preserve [21,51]; induction closes the arithmetic domain. Later starts are colder; prefixes ≥900 s fail passively. The ten-second gap remains unresolved, without PDE/experimental claims.

Common-loss transfer. Keep D=0.003 and scale ambient/contact conductances together by λ. For $T_i \geq 39 > 34$, $\partial_\lambda f_i = [h_{a,i}(22 - T_i) + h_{b,i}(34 - T_i)]/C_i < 0$. First-exit cooperative comparison traps intermediate paths between endpoint trajectories across both switches. The same 780 s policy qualifies every $\lambda \in [0.5, 1]$: warm-endpoint ceiling minus cool-endpoint floor bounds spread by 1.330205°C. A supposed feasible path with $\lambda \geq 1$ lies below the original optimistic path, so the 790 s exclusion transfers. This does not order diffusion or arbitrary physical changes.

10 Numerical verification

17 baseline checks pass: energy residual $\leq 2.46 \times 10^{-10}$ W; independent RHS/RK45 difference $\leq 3.12 \times 10^{-07}$°C. Uniform cooling/conservative-sink tests verify signs and energy, not physical validity.

For $|\dot{T}_i| \leq L$, half-second cell/spread allowances are $L/4/L/2$. Including integration allowance, baseline floor/ceiling/spread bounds are 39.0144/40.3340/0.9980°C. Schedule bounds 39.1297/40.8304/1.4964°C use RK45 restarts, contraction, switch endpoints and finest-mesh bisection of unresolved one-second intervals. With assumed 2×10^{-6}°C integration error, both meet 39/41/1.5°C; neither is interval or experimental certification.

11 Structural uncertainty and model limitations

Table 12 compares constrained temperatures and the excluded inlet peak.

Table 12. Mesh replay: constrained temperatures

Mesh (cells)	Max outside jet zone	Spread outside zone	Inlet-cell max
8 × 4 × 3 (96)	40.318°C	0.967°C	40.553°C
12 × 6 × 4 (288)	40.315°C	0.960°C	40.757°C
16 × 8 × 6 (768)	40.330°C	0.973°C	40.995°C

Three meshes give outside-zone ceiling/spread differences 0.015/0.013°C; excluded inlet peaks range 40.55–41.00°C. The 96/288-cell searches select 24.142/24.117 L (0.11% apart). These sampled passes diagnose mesh sensitivity; the moving cell-centered mask prevents a fixed-domain convergence claim (Section 11.4).

41/64 Sobol scenarios admit constant rates. Ranges: surface/wall/body coefficients 17–37/4.5–8.5/12–40 W/(m² K), D=0.0003–0.003 m²/s, air/skin=20–26/32–36°C. D is log-uniform, others uniform (scrambled seed 7); accepted-only quantiles are not population estimates.

At uniform T_0, passive initial cooling is $\dot{T}_i(0) = [H_{a,i}(T_a - T_0) + H_{b,i}(T_b - T_0)]/C_i$, independent of D. Later spatial differences inform mixing, but cannot excite absent delivery bias or inlet route. Contact storage changes curvature; fitted loss can compensate. Check transport/overflow in a separate inlet experiment, and distinguish mixing from loss in matched motion/foam trials.

Four grids recover second-order cosine diffusion (finest order 1.98); a zero-diffusion cascade matches its independent step response within 4.3×10^{-14}°C. These test empty-domain implementation, not the mixing closure or real baths [9].

11.1 Common-reserve structural comparison

The alternatives replace fixed skin by $C_b\dot{B} = \sum_i H_{b,i}(T_i - B)$ (253.31 kJ/K, initially 34°C), or route the inlet stream down, across the bottom and back to the same overflow. Contact storage is not physiology; the fixed-skin energy bound does not transfer.

Eight alternative-mechanism observation sets fit the original structure; six policies pass sampled checks with min/max/spread/final-body summary differences below 1.85×10^{-08}°C. Screen surface/fixed, deep/fixed and surface/finite hypotheses jointly: passive/pulse banks retain 1465/467 pairs. Trials restart uniformly, not sequentially.

Base-grid success hid two finest-grid ceiling failures (41.0010/41.0007°C). A 1% passive-flow reduction repairs those sampled cases, without common reserves or full fine-grid coverage. New six-stage candidates instead target 39.13°C floor, 40.9°C outside-zone ceiling and 1.4°C spread across all three grids. These extra reserves leave the physical 39/41/1.5°C limits unchanged.

Table 13 compares structure-specific banks at the same reserves.

Table 13. Common-reserve structural decisions

Structure / trial	Pairs	Control (L)	Floor / ceiling (°C)	Spread (°C)
Surface/fixed / passive	510	26.09	39.132 / 40.857	1.374
Surface/fixed / pulse	178	23.63	39.132 / 40.900	1.400
Deep/fixed / passive	510	26.09	39.132 / 40.900	1.400
Deep/fixed / pulse	149	23.63	39.133 / 40.900	1.400
Surface/storage / passive	445	26.09	39.141 / 40.848	1.374
Surface/storage / pulse	140	23.63	39.145 / 40.895	1.400

Two base-grid candidates fail the common floor. Adding their active-cell constraints yields Table 13, with five-minute rates 1.303664, 1.053753, 1.011697, 0.988372, 0.860138, 0.000000

L/min (passive), and 1.126406, 1.318679, 1.149624, 1.130662, 0.000000, 0.000000 L/min (pulse); calculations retain unrounded values.

All 5796 model-grid objects pass conditional continuous-time envelopes. Dynamic $U = (T_1, \ldots, T_N, B)$ excludes the constant coordinate. Metzler matrices with nonpositive row sums contract per stage; chord error is $\|U''(t_0)\|_\infty h^2/8$, supplemented by a first-derivative enclosure. Unresolved one-second intervals bisect to 0.0625 s. The assumed 2×10^{-6}°C error doubles for spread; Table 13 rounds outward. Independent RK45/energy checks cover 54 extremal identities, not all models.

Section 7.4's cost identity now has $\Delta = 2.461267$ L, giving $n > 2.43777$: pulse beats the fixed passive candidate from use 3, if one 6 L trial is reused, delivery bias stays positive and fixed, and total reset costs match. The seven-use result was conditional on the original structure. This expanded-bank comparison establishes neither global optimality nor expected experiment value.

11.2 Observation-updated control

Starting from 1,465 passive-compatible pairs on the 96-cell grid, read probes 89 and 6 every minute. Given prediction $\widehat{T}_{mj,k}$ and reading $z_{j,k}$, retain each model's constant-bias intervals:

$$I_{mj,k} = [-0.02, 0.02] \cap \bigcap_{\ell=0}^{k} [z_{j,\ell} - \widehat{T}_{mj,\ell} - 0.020002,\ z_{j,\ell} - \widehat{T}_{mj,\ell} + 0.020002]. \tag{20}$$

Exclude a model if either interval is empty. Choose the least of 0, 0.8, 0.9 and 1 times the current backup rate whose next minute and remaining backup satisfy all survivors' common targets. Chord bounds include the dynamic body state, refine unresolved five-second intervals to 0.0390625 s, and assume the same 2×10^{-6}°C allowance.

Conditional feasibility and water cap. Each accepted minute is checked with the original remaining backup. Subsequent observations only shrink the set, preserving that feasible tail. Induction applies if the truth stays in the static bank and propagators are valid. For L/min commands $0 \le q_k \le q_k^{\text{backup}}$, a completed service has $J_{\text{cmd}} = \sum_k q_k \Delta t \le \sum_k q_k^{\text{backup}} \Delta t \le 26.09$ L ($\Delta t = 1$ minute). A shared $\alpha > 0$ gives $J_{\text{act}} = \alpha J_{\text{cmd}} \le \alpha \times 26.09$ L. This proves neither minimum water nor fault or timeout recovery.

Fixed probe biases (+0.013, -0.011)°C give 23.59 L with zero reading noise and 23.16 L with one bounded-noise sequence (seed 20261010); 114/1 models remain. Both start from 1,465 hypotheses and the 26.09 L backup. Figure 5 shows action changes before unique identification. These nominal cases do not estimate population performance.

A separate matched 12-model ablation uses 26.00 L without observations versus 22.86, 22.86 and 22.08 L with them in three structures. Six feedback trajectories pass 18 independent half-second three-grid RHS/energy replays; realized actions do not certify fine-grid feedback throughout the bank.

Minute-10 shifts to 45°C supply or 40 W/(m² K) surface loss empty the set at minute 11; terminal bias intervals independently exclude all 23 preceding survivors. Neither partial service counts as savings. An empty set invalidates reuse, without identifying the cause or certifying




Figure 5. Observation-dependent replenishment. Retained-model counts use a logarithmic scale.

recovery.

11.3 Parameter changes and fixed-policy bounds

Six predeclared bank-external truths give two complete services (22.59/22.80 L commands). Changed storage, dimensions, supply or loss empties the bank after 28/5/11/9 minutes, before a checked temperature violation. Partial services are not savings; Section 12 separately tests limited recourse.

Fix those commands, baseline geometry, uniform 40°C initial water, 34°C contact, 50°C inlet and 22°C air. Static (D, h_s, h_b, α) center is $(0.001025, 24.375, 26.25, 1.0125)$; halfwidths 6.25×10^{-06} m²/s, 0.15625/0.3125 W/(m² K), 0.003125. These mathematical neighborhoods are not measured tolerances.

Fixed-command perturbation bound. Write $U' = M_\theta U + c_\theta$, affine in the four parameters. For halfwidths w_j, set $K_j = w_j \partial_j M$, $f_j = w_j \partial_j c$, and $\theta = \theta_0 + w \odot z$ with $|z_j| \le 1$. Nominal variations satisfy $S_j' = M_0 S_j + K_j U_0 + f_j$, $S_j(0) = 0$.

Proof. The exact remainder $r = U_\theta - U_0 - \sum_j z_j S_j$ satisfies

$$r' = M_\theta r + \sum_{j,k} z_j z_k K_j S_k, \qquad r(0) = 0. \tag{21}$$

Positive parameters give nonnegative off-diagonals and nonpositive row sums at every vertex, hence throughout the affine box. Contraction [10] and variation of constants give

$$\|r(t)\|_\infty \le R(t), \qquad R(t) = \sum_{j,k} \int_0^t \|K_j S_k(u)\|_\infty \, du. \tag{22}$$

The cellwise radius is $\sum_j |S_j| + R$: subtract it for the floor, add it for the ceiling, and twice for spread. States are continuous at flow switches; R accumulates across them.

□

Half-second derivative/chord bounds assume 2×10^{-6}°C, 2×10^{-6}°C/s and 2×10^{-6}°C/s² errors. Of halfwidth scales 4/2/1/0.4, the displayed box is the largest passing both fixed paths on all three meshes: floor ≥39.0759°C, ceiling ≤40.7769°C, spread ≤1.1746°C; extra planning reserves do not all pass. Independent RHS/energy checks cover 102 corners/centers, not the continuum. A prior defect bound certified none. This exact-remainder box assumes numerical accuracy and covers fixed commands, not all feedback branches or real baths.

11.4 Transport comparison and network infeasibility

A separate axial closure matches volume, storage and total conductances, with uniform/localized-body losses but different anatomy. With v=qL/V, loss per length λ and capacity per length c,

$$T_t = DT_{xx} - vT_x - \lambda(x,T)/c, \qquad vT(0) - DT_x(0) = vT_{in}, \quad T_x(L) = 0. \tag{23}$$

The flux inlet [11] conserves enthalpy. Both policies replay two loss profiles on 40/80/160 meshes at D=0.0003/0.001/0.003 m²/s. Under constant flow, weak-mixing mean/outlet ends at 39.444/38.581°C. N80 searches choose start 0 min at D=0.001 (22.71/22.68 L, uniform/local loss), or 10 min at D=0.003 (18.87/18.86 L); all selected candidates pass three-mesh sampled checks.

Starts 0:120:1200 s and first roots 0:0.2:3 L/min use floor 39.03°C. Neither weak-mixing profile accepts a root; this finite search is inconclusive.

An arbitrary-control obstruction. Fix $D = 0.0003$ m²/s, 34°C contact, 40°C initial water, the original route and 30 minutes. No measurable $q(t) \in [0, 3]$ L/min satisfies the 39°C all-cell floor, 41°C ceiling outside the inlet jet zone and 1.5°C spread on the 96-cell network.

Let $\theta = T - 39 \in P$, with P enforcing the floor, ceiling, jet barrier and spread. Write $\theta' = K\theta + b + q(S\theta + a)$. For signed ω, define $E = \omega^T\theta$, $E_{\min} = \min_P E$ and $R = \max_{q\in\{0,3\},\theta\in P} \omega^T\theta'$. Then

$$E_{\min} \le E(t) \le E(0) + tR, \qquad t \le \frac{E(0) - E_{\min}}{-R} \quad (R < 0). \tag{24}$$

The derivative is affine in the common q: endpoints bound every measurable policy, and integration gives the inequality. Frozen weights contrast inlet-near warmth with the remote end; E is not heat. Exact rational support bounds give safety time <1717 s. Timing alone cannot reach 1800 s. The tested stronger-diffusion cases lose this obstruction, without proving feasibility.

Frozen-dual box corrections give a concave piecewise-affine gap $g = E_{\min}^{\text{lower}} - E(0) - 1800R_{\text{upper}}$: $s = D/0.0003$, ℓ scales both losses, z limits spread. Positive g certifies convex exclusion. Exact roots give $0.00029047 < D < 0.00030957$ m²/s at original loss and 1.5°C spread. At D=0.0003, separately, loss scales 0.97894–1.2 or spreads 0.75–1.53242°C remain excluded with other inputs fixed. These inward-rounded boundaries do not establish feasibility. Original 288-cell relaxations remain inconclusive.

A fixed 0.15 m ball at $(0, W/2, H)$ gives residual bounds >0.115/0.217/0.179°C on 96/288/768 cells; time limits <1619/<1481/<1533 s. Only the mask changes: non-nested on

96, stricter on 288. The source lane still follows the grid. These are finite-network obstructions, not a continuum limit or a verdict for the original 288-cell target.

$$E_{excess} = \rho c_p \int q(T_{out} - \overline{T})\, dt. \tag{25}$$

Positive excess is extra overflow loss relative to the mean. Original/matched-axial values are $-31.51/-26.28$ kJ. Both outlets are cooler: a permitted short circuit does not establish the cause of the water penalty.

For uniform loss, $k = (H_a + H_b)/C$, $w = T_x$ obeys $w_t = Dw_{xx} - vw_x - kw$, $w(L) = 0$, $w(0) = v[T(0) - T_{\text{in}}]/D \le 0$ when $T \le T_{\text{in}}$. Uniform initial water and inherited gradients at switches permit the maximum principle: $w \le 0$, hence $T_{\text{out}} \le \overline{T}$. Localized loss adds gradient forcing.

Steady/Robin tests show first-order convergence (N160 error $\le$0.002614°C); six independent flux/RK45 differences $\le 3.30 \times 10^{-07}$°C and energy errors $\le$0.00213 J verify this closure, not real baths or PDE-wide feasibility.

12 Recourse after model rejection

Over the remaining horizon, for every compatible model: **wait** only with a qualified zero-flow bridge and backup; **replenish** with a checked continuation or backup; otherwise **reassess**.

Reconstruct 54 exposed static hypotheses from 40°C/34°C and all actions/readings: six structures × D factors 0.975/1/1.025 × surface-loss offsets -0.625/0/0.625 W/(m² K). Intersect shared-bias intervals without using truth states. With prior parallel maintenance, pre-reading sets 1/15/6/7 qualify a 60 s bridge; the last reading leaves 1/8/4/6. Tail search: 0:0.05:2 L/min (Table 14).

Table 14. Recourse after a one-minute bridge

Changed condition	Alarm (min)	Tail (L/min)	Total command (L)
Contact storage	28	0.00	22.17
Longer geometry	5	0.80	25.72
Cooler inlet	11	0.80	25.86
Higher loss	9	1.05	30.76

Chord bounds cover bridge/tail; 57 independent three-grid sampled paths cover 19 survivors at physical 39/41/1.5°C limits without old reserves. Prior 0.70 L/min fails all meshes; higher-loss completion exceeds 26.09 L. Empty sets, failed bridges or timeouts refuse action in this offline study.

13 Practical guidance

A guide for the person in the bathtub

Choose your tolerance. Allowing some cooling uses stored heat before replacement water. Our example needs about 24 L with a 1°C allowance, but 1.9 L with 2°C. These are model scenarios; your comfort and health needs determine the acceptable range.

Redistribute warmth. Water near the faucet may warm while distant water stays cool. Gentle movement can help; stronger motion can increase surface loss. Extra inflow can widen temperature differences. In the certified weak-mixing network, timing alone cannot meet all limits; circulation or tolerance must change and be rechecked. A cooler overflow can retain heat while a distant cold patch persists; measure both before attributing poor performance to hot-water short circuit.

Wait only while a checked plan remains. The baseline schedule waits 5 minutes, supplies water for 15 minutes and stops for 10 minutes. It uses 21.48 L against 24.14 L for a constant trickle. Waiting helps only while delayed heat can reach cold regions without requiring excessive inflow; Section 9 explains this balance and transfers a plan only within a specified common-loss family. The axial comparison selects zero or ten minutes under different mixing. Only 74% of the specified random tap-error trials stayed within limits; this is not a reliable manual prescription.

Follow the three decisions. Our modeled controller reads two temperatures every minute. Wait or reduce inflow only when that change and the remaining backup pass for every compatible model; otherwise keep the checked backup. If no model explains the readings or the backup loses its support, reassess supply, motion and heat loss rather than treating refusal as recovery. Two specified shifts were detected after one minute. In four static mismatch studies, a prechecked one-minute pause allowed replacement plans, but some required extra water; planning reserves were reduced; unknown changes have no such guarantee. Spatial bounds come from the model: two probes can miss an unmodeled cold corner.

Count preparation as well as use. Across the broader model bank, cooling-only and hot-water trials lead to 26.09/23.63 L during a bath. For those fixed schedules, a reusable 6 L hot-water trial pays back from use 3 when conditions and reset costs match. Both trials need 30 minutes and a fresh uniform start. The online cases reduce the passive backup to 23.59/23.16 L under specified sensor errors; their repeated-use crossover with pulse is untested; trial/reset costs remain.

Keep the practical limits in view. An intact bubble layer may reduce heat loss, but the calculation does not measure a particular additive. Changed geometry, body position, motion, supply or foam needs reassessment. Use stored warmth, keep it distributed and avoid unnecessary overflow; the figures explain these tradeoffs rather than certifying bathing or hot-jet safety.

14 References and reproducible algorithm

[1] COMAP. 2016 MCM Problem A: A Hot Bath. 2016. Official problem PDF: https://contest.comap.com/undergraduate/contests/mcm/contests/2016/problems/2016_MCM_Problem_A.pdf.

[2] U.S. Department of Energy. DOE Fundamentals Handbook: Thermodynamics, Heat Transfer, and Fluid Flow. DOE-HDBK-1012/2-92, June 1992. Convection heat transfer, Eq. (2-9).

[3] IAPWS. Revised Release on the IAPWS Formulation 1995 for the Thermodynamic Properties of Ordinary Water Substance for General and Scientific Use. R6-95(2018). https://iapws.org/technical-guidance/release/IAPWS-95.

[4] SciPy developers. scipy.sparse.linalg.expm_multiply and scipy.integrate.solve_ivp, API documentation. https://docs.scipy.org/doc/scipy/reference/. Accessed 7 October 2026.

[5] Bergman, T. L., Lavine, A. S., Incropera, F. P., DeWitt, D. P. Fundamentals of Heat and Mass Transfer, 7th ed. Wiley, 2011. Natural convection above a heated horizontal surface (characteristic length A/P); heat and mass transfer analogy.

[6] Menzies, C., Clarke, N., Steward, C. J., Thake, C. D., Pugh, C. J. A., Cullen, T. Vascular, inflammatory and perceptual responses to hot water immersion: impacts of water depth and temperature in young healthy adults. Experimental Physiology, 2025. doi:10.1113/EP092761.

[7] OpenAI, Codex (GPT-6-based assistant), and Anthropic, Claude Sonnet 5.5 in Claude Code. Used during 7–10 October 2026 for modeling, code, validation and report composition; exact builds not independently established. See Report on Use of AI.

[8] Munk, W. H., Anderson, E. R. Notes on a theory of the thermocline. Journal of Marine Research, 7(3), 276–295, 1948.

[9] NASA/NPARC Alliance. Verification Assessment and Validation Assessment, CFD tutorial. https://www.grc.nasa.gov/WWW/wind/valid/tutorial/. Accessed 9 October 2026.

[10] Higham, N. J. What Is the Logarithmic Norm? 18 January 2022. https://nhigham.com/2022/01/18/what-is-the-logarithmic-norm/. Theorems 3 and 6. Accessed 10 October 2026.

[11] COMSOL. Theory for the Inflow Boundary Condition. Heat Transfer Module documentation, version 6.3. https://doc.comsol.com/6.3/doc/com.comsol.help.heat/heat_ug_theory.07.009.html. Accessed 10 October 2026.

Algorithm and computational record

Assemble valid capacities, symmetric exchange and conservative inlet/overflow; compute mixed benchmarks; search floor crossings, reject ceiling/spread failures and rank water costs. Qualify buffered schedules on three meshes; repeat searches at Sobol draws. Independent RHS/RK45 uses rtol 2×10^{-9}, atol 2×10^{-10}°C, steps ≤5 s and energy/analytic checks. Axial tests and AI use: Section 11.4 and [7].

Predeclared diagnostic: D=0.00101225 m²/s, surface loss 31.50 W/(m² K), nine-minute prefix retained without a new alarm; seven bridge hypotheses, five survivors. Tail 1.05 L/min

costs 30.76/31.14 L commanded/delivered. Survivors/truth pass 18 three-grid sampled paths. Truth never initializes decisions; unlisted mechanisms remain untested.

Appendix A. Scenario definitions

Each row changes only the listed baseline inputs. All unspecified inputs remain as stated in Section 2; geometry and conductance are then rebuilt. The equal-volume aspect-ratio cases retain the envelope volume of 0.22425 m³. Widths s describe a smooth displacement distribution, not measured anatomical semiaxes.

Accepted candidates are independently replayed on their scenario network at intervals of no more than five seconds. These scenario checks are sampled checks; continuous-time envelopes are reported for the baseline constant rate and the selected scheduled policy; the latter uses additional interval refinement when necessary. "None accepted" refers to the documented finite search and is not an infeasibility theorem.

Table 15 lists the changes defining each scenario.

Table 15. Scenario definitions

Scenario	Changed input(s)
Weak Mixing	D (m²/s) = 0.0003
Strong Mixing	D (m²/s) = 0.003
Moving With Added Surface Loss	D (m²/s) = 0.003; surface coefficient (W/m²K) = 30
Loose Comfort	lower limit (°C) = 38
Tight Comfort	lower limit (°C) = 39.5
Foam	surface multiplier = 0.4
Shallow Wide	length (m) = 1.7; width (m) = 0.75; depth (m) = 0.175882
Deep Narrow	length (m) = 1.3; width (m) = 0.6; depth (m) = 0.2875
Small Bath	depth (m) = 0.2
Large Bath	depth (m) = 0.27
Deep Bath	depth (m) = 0.35
Larger Body	body displacement (m³) = 0.075; body contact area (m²) = 1.35
Long Body	body widths s (m) = [0.48, 0.12, 0.1]
Warmer Skin	skin temperature (°C) = 36
Cooler Skin	skin temperature (°C) = 32
High Loss	surface coefficient (W/m²K) = 36; wall coefficient (W/m²K) = 8.5; body coefficient (W/m²K) = 40
Low Loss	surface coefficient (W/m²K) = 17; wall coefficient (W/m²K) = 4.5; body coefficient (W/m²K) = 12
Stratified	vertical/horizontal D ratio = 0.2
Convective Surface Layer	vertical/horizontal D ratio = 3
Cool Supply	inlet temperature (°C) = 45

Report on Use of AI

Tool, task and scope

Codex (GPT-6-based) and Claude Sonnet 5.5 via Claude Code assisted modeling, computation, validation, figures and writing, 7–10 October 2026; exact builds are unverified. Post-seal learning used Outstanding papers 44845/54164 and COMAP commentary, without copying data/figures. This is not unseen-problem testing. AI sub-agents independently checked RHS/probes.

Outputs, corrections and verification

Independent integration rejected 19.35 L and accepted a buffered schedule; archived corrections and baseline optimization remain. Sources [1]–[4]/[6] and [10] Theorems 3/6 were read; [5]/[8] relations were checked indirectly. AI produced derivations/report from actual results.

AI compared schedules, trials, structures and failures: 5796 common-reserve model-grid objects, 54 independent extremal replays. Two reserve failures were repaired and preserved. Diffusion/inlet checks test discretization; producer versions and synthetic observation identities remain.

Finite-bank feedback gave nine complete services/18 replays; two shifts stopped at 660 s. Six external-bank truths gave two services/four refusals and ten envelope replays. Stored empty intervals were audited without inventing missing predictions. Exact-remainder bounds qualified narrow fixed-action boxes with 102 independent replays; the failed loose bound remains.

An exposed 54-point static catalog reconstructs four refusal histories from known initial states. A prequalified 60 s zero-flow bridge precedes constant tails; 57 three-grid sampled replays passed. The 0.70 L/min failure, increased costs and reduced reserves remain. Controlled tests/frozen-candidate replay verify late-result rejection and timeout preservation; revised code is not attributed to historic runs.

AI checked arbitrary-control certificates; the original windowed proof remains. Original 288-cell relaxations and three feedback failures give no verdict. Fixed-region certificates cover three networks. Signed functionals certify time limits and continuous parameter exclusion; variational checks test local timing; pulse qualification permits 780 s, while an archived-flux IEEE64 enclosure excludes waits $\geq$790 s at D=0.003; common-loss comparison extends both statements. Constant exclusion retains 125 centers/six analytic tests; a diagnostic passed 18 sampled paths. Feasible-control LP timed out; independent moments satisfy its matrix. No PDE or empirical claim follows.

AI derived/tested an axial closure with continuum solutions, independent flux integration and unchanged controls; outlet diagnostics revised the short-circuit interpretation. Source [11] was read; COMSOL was not run. This is a counterfactual, not an experiment.

Record limitations

Task/tool/scope records, code and numerical receipts remain; the complete transcript is unavailable. Human verification, live control, experiments and feedback-wide certification were not performed.