

Claude Code Router (CCR) Cheat Sheet

Quick Start

```
# Install CCR (one-time)
npm install -g @musistudio/claude-code-router

# Start router service
ccr start

# Use Claude Code through router
ccr code "your prompt here"
```

Essential Commands

Command	Description
ccr start	Start the router service
ccr stop	Stop the router service
ccr restart	Restart service (after config changes)
ccr status	Check service status
ccr code "prompt"	Run Claude Code with routing
ccr ui	Open web UI for config
ccr -v	Show version

Dynamic Model Switching

Inside Claude Code, use `/model` command:

```
/model provider,model_name

# Examples:
/model xai,grok-4-fast           # XAI's 2M context model
/model xai,grok-fast-code-1      # Coding optimized
/model gemini,gemini-2.5-pro     # Gemini Pro
/model openrouter,x-ai/grok-4-fast:free # Free tier
```

Direct Model Selection

```
# Specify model directly in command
ccr code "xai,grok-4-fast" "analyze this codebase"
ccr code "openrouter,deepseek/deepseek-r1-0528" "solve this"
```

Configuration Location

- Config file: `~/.claude-code-router/config.json`
- Logs: `~/.claude-code-router/logs/`
- Edit config → `ccr restart` to apply

Default Routing (Your Setup)

Task Type	Model	Context
Default	gemini-2.5-flash	General tasks
Background	gemini-2.5-flash	Low-priority
Thinking	grok-4-0709	Reasoning
Long Context	grok-4-fast	>1.5M tokens (2M max)
Coding	grok-fast-code-1	Code-specific

Pro Tips

- **Auto-start:** `ccr code` starts router if not running
- **Free models:** `openrouter,x-ai/grok-4-fast:free` (limited time)
- **Web UI:** `ccr ui` for visual config editing
- **Multiple prompts:** Use quotes for complex prompts

Troubleshooting

```
# Service won't start?
ccr stop && ccr start

# Config not loading?
ccr restart

# Check if running
ccr status

# View logs
tail -f ~/.claude-code-router/logs/app.log
```

CCR v1.0.47 | Config: `~/.claude-code-router/config.json`