

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,1}(size(IDs,1))  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.3/10  
  
/home/nicole/Jupyter/Jpaper/Data/0.3/10
```

```
In [4]: ;ls  
  
G1.Genotype.ID  
G1.ID  
G1.noGenotype.ID  
G2.Genotype.ID  
G2.ID  
G2.noGenotype.ID  
G3.Genotype.ID  
G3.ID  
G3.noGenotype.ID  
G4.Genotype.ID  
G4.ID  
G4.noGenotype.ID  
G5.Genotype.ID  
G5.ID  
G5.noGenotype.ID  
GenNF.txt  
PedAll.txt  
Phe.txt  
PheAll.txt  
all.ID  
genotype.ID  
noGenotype.ID  
sim.bv  
sim.phenotype
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```

In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv

In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G1.ID

In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G2.ID

In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G3.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G4.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G5.ID

In [15]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [16]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [17]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [18]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [19]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [20]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [21]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [22]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [23]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [24]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID

In [25]: ;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID

In [26]: ;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G5.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID

```

```
In [27]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding,
nothing
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
nothing
```

```
In [28]: vRes    = 1.478
vG       = 0.633
aHat3=SSBR.PBLUP(y_Vecs,Z_Mats,A_Mats,numSSBayes,vRes,vG);
```

```
In [29]: using DataFrames
```

```
In [30]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=1,
a = Array{Float64,2}(undef,numSSBayes,num_ped)
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [31]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat3[posAi])[1,1]
reg1 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with all
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.770
```

```
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.998
```

```
Out[31]: 0.7703166201819893
```

```
In [32]: IDs = readtable("genotype.ID", eltypes=[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat3[posAi])[1,1]
reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # with all
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.476
```

```
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.009
```

```
Out[32]: 0.4756742050559272
```

```
In [33]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat3[posAi])[1,1]
reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3 ) ;
JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.745
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.996
```

```
Out[33]: 0.7452335534218748
```

```
In [34]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", reg4 ) ;
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.636
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.980
```

```
Out[34]: 0.6360229166930508
```

```
In [35]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", reg5 ) ;
JCall = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.671
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.006
```

```
Out[35]: 0.6712480092521932
```

```
In [36]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", reg6 ) ;
JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.678
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.999
```

```
Out[36]: 0.6783809049503469
```

```
In [37]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat3[posAi])[1,1]
reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.642
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 0.980
```

```
Out[37]: 0.6416621365112952
```

```
In [38]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat3[posAi])[1,1]
reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.410
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.030
```

```
Out[38]: 0.40968987829963915
```

```
In [39]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',hea
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
#TBV = a[posAi]
#GEBV = aHat3[posAi]
#reg = linreg(X,Y)
#reg = linreg(GEBV, TBV)[2,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6
JCall = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.846
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 0.970
```

```
Out[39]: 0.8461005269790888
```

```
In [40]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',hea
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6
JCall = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.856
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.951
```

```
Out[40]: 0.8556057957363418
```

```
In [41]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat3[posAi])[1,1]
reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.843
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.971
```

```
Out[41]: 0.8427212661771298
```

```
In [42]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat3[posAi])[1,1]
reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCA12 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.524
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.136
```

```
Out[42]: 0.5241403985054396
```

```
In [43]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat3[posAi])[1,1]
reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCA13 = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.410
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.030
```

```
Out[43]: 0.40968987829963915
```

```
In [44]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCA14 = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.615
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.974
```

```
Out[44]: 0.6152970932654314
```

```
In [45]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat3[posAi])[1,1]
reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCA11 = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.657
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.008
```

```
Out[45]: 0.6572211012607437
```

```
In [46]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat3[posAi])[1,1]
reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.665
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.001
```

```
Out[46]: 0.6645816003612635
```

```
In [47]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat3[posAi])[1,1]
reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCA11 = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.629
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.976
```

```
Out[47]: 0.6293759022808671
```

```
In [48]: numSSBayes
```

```
Out[48]: SSBR.NumSSBayes(44200,35400,8800,32000,31200,800,0)
```