

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,1}(size(IDs,1))  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5/G/8  
  
/home/nicole/Jupyter/JG3/Data/0.5/G/8
```

In [4]: ;ls

```
Correlation.G5.G.J.txt
Correlation.G5.G.JC.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.J.txt
Regression.G5.G.JC.txt
all.ID
alphaEstimates
genotype.ID
meanOfSNPGA11
meanOfSNPGG0
meanOfSNPGG1
meanOfSNPGG2
meanOfSNPGG3
meanOfSNPGG4
meanOfSNPGG5
noGenotype.ID
sim.bv
sim.phenotype
```

In [5]: ;awk '{print \$1}' PedAll.txt | sort -b > all.ID

In [6]: ;awk '{print \$1}' GenNF.txt | sort -b > genotype.ID

In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID

In [8]: ;awk '{print \$1,\$2}' Phe.txt > sim.phenotype

In [9]: ;awk '{print \$1,\$3}' PheAll.txt > sim.bv

In [10]: ; awk 'NR >=1 && NR <=8000 {print \$1}' PedAll.txt | sort -b > G0.ID

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc (
    200  200 1200 G0.Genotype.ID
    200  200 1200 G1.Genotype.ID
    200  200 1200 G2.Genotype.ID
    200  200 1200 G3.Genotype.ID
    200  200 1200 G4.Genotype.ID
    8000  8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding
nothing
df      = read_genotypes("GenNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped);           # with
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes);
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(Z_Mats,M_Mats,numSSBayes)      # no
nothing
```

```
In [31]: vRes      = 0.627
vG       = 0.627
nIter    = 50000
@time aHat1,alphaHat,betaHat,epsHat =
ssGibbs(M_Mats,y_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,nIter,
nothing

This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
3518.911387 seconds (23.08 G allocations: 724.667 GB, 7.06% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 1-element Array{Float64,1}:
 9.75751
```

```
In [33]: using DataFrames
```

```
In [34]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',head
a      = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [35]: IDs = readtable("all.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.912
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.974
```

```
Out[35]: 0.9118869461243357
```

```
In [36]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[36]: 1.3940512411353638
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat1[posAi])[1,1]
reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) #
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n",
JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.964
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.046
```

```
Out[37]: 0.9638245520866165
```

```
In [38]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[38]: 2.5124855827672152
```

```
In [39]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat1[posAi])[1,1]
reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n",
JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.873
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.957
```

```
Out[39]: 0.8726406728074824
```

```
In [40]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[40]: 1.1359510084510902
```

```
In [41]: IDs = readtable("G0.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.697
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.845
```

```
Out[41]: 0.6966514183497877
```

```
In [42]: GEBV = aHat1[posAi]
G0GEBV=mean(GEBV)
```

```
Out[42]: 0.11278638425927204
```

```
In [43]: IDs = readtable("G1.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.771
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.980
```

```
Out[43]: 0.770829076669968
```

```
In [44]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[44]: 0.6943638697008355
```

```
In [45]: IDs = readtable("G2.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.770
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.010
```

```
Out[45]: 0.7700092744671889
```

```
In [46]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[46]: 1.2033151760944811
```

```
In [47]: IDs = readtable("G3.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.770
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.986
```

```
Out[47]: 0.7699474504796829
```

```
In [48]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[48]: 1.677856630010408
```

```
In [49]: IDs = readtable("G4.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.787
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.000
```

```
Out[49]: 0.7872676127134177
```

```
In [50]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[50]: 2.1191128694635912
```

```
In [51]: IDs = readtable("G5.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.958
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.036
```

```
Out[51]: 0.9578266087954421
```

```
In [52]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[52]: 2.5568725172835944
```

```
In [53]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
#TBV = a[posAi]
#GEBV = aHat1[posAi]
#reg = linreg(X,Y)
#reg = linreg(GEBV, TBV)[2,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.963

SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.052

Out[53]: 0.9631570344279852

```
In [54]: GEBV = aHat1[posAi]
mean(GEBV)
```

Out[54]: 1.310611002753263

```
In [55]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
#TBV = a[posAi]
#GEBV = aHat1[posAi]
#reg = linreg(X,Y)
#reg = linreg(GEBV, TBV)[2,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.957

SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.064

Out[55]: 0.9570617198874436

```
In [56]: GEBV = aHat1[posAi]
mean(GEBV)
```

Out[56]: 1.7712144193066441

```
In [57]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 )
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.964

SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.047

Out[57]: 0.9636623955697015


```
In [58]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[58]: 2.1967566607847084
```

```
In [59]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor11 = cor(a[posAi],aHat1[posAi])[1,1]
         reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
         JCall = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.957
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.017
```

```
Out[59]: 0.9570182631900881
```

```
In [60]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[60]: 2.5631562309205673
```

```
In [61]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor12 = cor(a[posAi],aHat1[posAi])[1,1]
         reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
         JCall = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.936
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.013
```

```
Out[61]: 0.9356789325307429
```

```
In [62]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[62]: 2.945212219415727
```

```
In [63]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor13 = cor(a[posAi],aHat1[posAi])[1,1]
         reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
         JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.958
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.036
```

```
Out[63]: 0.9578266087954421
```

```
In [64]: writedlm("Correlation.G5.G.N.txt",cor13)
```

```
In [65]: writedlm("Regression.G5.G.N.txt",reg13)
```

```
In [66]: TBVG5Gall = a[posAi]
         TBVG5G=mean(TBVG5Gall)
```

```
Out[66]: 12.309573500000003
```

```
In [67]: GEBVG5Gall = aHat1[posAi]
         GEBVG5G=mean(GEBVG5Gall)
```

```
Out[67]: 2.5568725172835944
```

```
In [68]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.677
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.843
```

```
Out[68]: 0.6767451231039903
```

```
In [69]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[69]: 0.0820729325030159
```

```
In [70]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.754
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.982
```

```
Out[70]: 0.7542510850535575
```

```
In [71]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[71]: 0.6667523171468405
```

```
In [72]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat1[posAi])[1,1]
reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCA11 = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.752
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.009
```

```
Out[72]: 0.7520717162174188
```

```
In [73]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[73]: 1.1778423175126804
```

```
In [74]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.754
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.982
```

```
Out[74]: 0.7542142747407377
```

```
In [75]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[75]: 1.6551566402434812
```

```
In [76]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCA11 = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.774
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.996
```

```
Out[76]: 0.7739915306905492
```

```
In [77]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[77]: 2.097930834849434
```

```
In [78]: numSSBayes
```

```
Out[78]: SSBR.NumSSBayes(54971,45971,9000,40000,39000,1000,200)
```