

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,1}(size(IDs,1))  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5a0/G/4  
  
/home/nicole/Jupyter/JG3/Data/0.5a0/G/4
```

In [4]: ;ls

```
Correlation.G5.G.C.txt
Correlation.G5.G.J.txt
Correlation.G5.G.JC.txt
Correlation.G5.G.N.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.C.txt
Regression.G5.G.J.txt
Regression.G5.G.JC.txt
Regression.G5.G.N.txt
all.ID
alphaEstimates
genotype.ID
meanOfSNPGAll
meanOfSNPGG0
meanOfSNPGG1
meanOfSNPGG2
meanOfSNPGG3
meanOfSNPGG4
meanOfSNPGG5
noGenotype.ID
sim.bv
sim.phenotype
```

In [5]: ;awk '{print \$1}' PedAll.txt | sort -b > all.ID

In [6]: ;awk '{print \$1}' GenNF.txt | sort -b > genotype.ID

In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID

In [8]: ;awk '{print \$1,\$2}' Phe.txt > sim.phenotype

```

In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv

In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID

In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID

In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID

In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID

In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID

In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID

In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID

In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID

```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID
          7800 7800 46800 G0.noGenotype.ID
          7800 7800 46800 G1.noGenotype.ID
          7800 7800 46800 G2.noGenotype.ID
          7800 7800 46800 G3.noGenotype.ID
          7800 7800 46800 G4.noGenotype.ID
          0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreedingCoefficients,
          nothing
          y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
          Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
          nothing
```

```
In [31]: vRes = 1.991
          vG = 1.991
          aHat3=SSBR.PBLUP(y_Vecs,Z_Mats,A_Mats,numSSBayes,vRes,vG);
```

```
In [32]: using DataFrames
```

```
In [33]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',header=false)
          a = Array{Float64,1}(zeros(numSSBayes,num_ped))
          for (i,ID) in enumerate(df[:,1])
              j = ped.idMap[ID].seqID
              a[j] = df[i,2]
          end
```

```
In [34]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
          posAi = getPos(ped,IDs)
          cor1 = cor(a[posAi],aHat3[posAi])[1,1]
          reg1 = linreg(aHat3[posAi], a[posAi])[2,1]
          @printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
          @printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n", reg1)
          JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.900
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 1.006
```

```
Out[34]: 0.9002014382082102
```

```
In [35]: TBV = a[posAi]
          mean(TBV)
```

```
Out[35]: 14.033610145833334
```

```
In [36]: EBV = aHat3[posAi]
          mean(EBV)
```

```
Out[36]: 2.4546547060549195
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat3[posAi])[1,1]
reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3:
JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.553
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 0.948
```

```
Out[37]: 0.5534445268810628
```

```
In [38]: TBV = a[posAi]
mean(TBV)
```

```
Out[38]: 16.113595555555556
```

```
In [39]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[39]: 4.5873606710598285
```

```
In [40]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat3[posAi])[1,1]
reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6
JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.892
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 1.023
```

```
Out[40]: 0.8924688580609966
```

```
In [41]: TBV = a[posAi]
mean(TBV)
```

```
Out[41]: 13.553613512820514
```

```
In [42]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[42]: 1.9624917910537871
```

```
In [43]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.826
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 1.184
```

```
Out[43]: 0.8256081489904908
```

```
In [44]: TBV = a[posAi]
mean(TBV)
```

```
Out[44]: 11.54259725
```

```
In [45]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[45]: 0.004624725712304371
```

```
In [46]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.764
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 1.000
```

```
Out[46]: 0.7644214769053899
```

```
In [47]: TBV = a[posAi]
mean(TBV)
```

```
Out[47]: 12.770068125
```

```
In [48]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[48]: 1.1551512533902037
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.765
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.023
```

```
Out[49]: 0.7645968055407741
```

```
In [50]: TBV = a[posAi]
mean(TBV)
```

```
Out[50]: 13.672560125
```

```
In [51]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[51]: 2.081772166342695
```

```
In [52]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.754
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.991
```

```
Out[52]: 0.7535046983604734
```

```
In [53]: TBV = a[posAi]
mean(TBV)
```

```
Out[53]: 14.580887250000002
```

```
In [54]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[54]: 2.9719967185131146
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat3[posAi])[1,1]
reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation =  0.724
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV =  0.965
```

```
Out[55]: 0.7239335715137626
```

```
In [56]: TBV = a[posAi]
mean(TBV)
```

```
Out[56]: 15.439914125
```

```
In [57]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[57]: 3.837485972107859
```

```
In [58]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat3[posAi])[1,1]
reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation =  0.421
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV =  0.963
```

```
Out[58]: 0.42115961685139663
```

```
In [59]: TBV = a[posAi]
mean(TBV)
```

```
Out[59]: 16.195634
```

```
In [60]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[60]: 4.676897400263341
```



```
In [61]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.878
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 0.913
```

```
Out[61]: 0.8783577865197609
```

```
In [62]: TBV = a[posAi]
mean(TBV)
```

```
Out[62]: 14.014219999999998
```

```
In [63]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[63]: 2.27357119691467
```

```
In [64]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.899
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.022
```

```
Out[64]: 0.8986049329467142
```

```
In [65]: TBV = a[posAi]
mean(TBV)
```

```
Out[65]: 14.530675
```

```
In [66]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[66]: 2.9965451868411823
```

```
In [67]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.862
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.969
```

```
Out[67]: 0.8622087915577527
```

```
In [68]: TBV = a[posAi]
mean(TBV)
```

```
Out[68]: 15.507835
```

```
In [69]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[69]: 3.8612307336737284
```

```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat3[posAi])[1,1]
reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.889
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.990
```

```
Out[70]: 0.8893951825484661
```

```
In [71]: TBV = a[posAi]
mean(TBV)
```

```
Out[71]: 16.290675000000004
```

```
In [72]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[72]: 4.7093295226991305
```

```
In [73]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head = 1000)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat3[posAi])[1,1]
reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCall = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.443
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.822
```

```
Out[73]: 0.4432696768106561
```

```
In [74]: TBV = a[posAi]
mean(TBV)
```

```
Out[74]: 16.943035000000002
```

```
In [75]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[75]: 5.5146575470298735
```

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head = 1000)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat3[posAi])[1,1]
reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.421
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.963
```

```
Out[76]: 0.42115961685139663
```

```
In [77]: writedlm("Correlation.G5.G.PBLUP.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.G.PBLUP.txt",reg13)
```

```
In [79]: TBV = a[posAi]
mean(TBV)
```

```
Out[79]: 16.195634
```

```
In [80]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[80]: 4.676897400263341
```

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.809
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 1.206
```

```
Out[81]: 0.8091317618079803
```

```
In [82]: TBV = a[posAi]
mean(TBV)
```

```
Out[82]: 11.479222307692309
```

```
In [83]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[83]: -0.05355338893391012
```

```
In [84]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.749
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 1.004
```

```
Out[84]: 0.7488405950132855
```

```
In [85]: TBV = a[posAi]
mean(TBV)
```

```
Out[85]: 12.72492435897436
```

```
In [86]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[86]: 1.107936024327358
```

```
In [87]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat3[posAi])[1,1]
reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.748
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.023
```

```
Out[87]: 0.7484335677772721
```

```
In [88]: TBV = a[posAi]
mean(TBV)
```

```
Out[88]: 13.625501794871795
```

```
In [89]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[89]: 2.0361450235906173
```

```
In [90]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat3[posAi])[1,1]
reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.736
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.991
```

```
Out[90]: 0.7364489254585425
```

```
In [91]: TBV = a[posAi]
mean(TBV)
```

```
Out[91]: 14.53704653846154
```

```
In [92]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[92]: 2.9274497235339854
```

```
In [93]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat3[posAi])[1,1]
reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.714
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.972
```

```
Out[93]: 0.714285804363806
```

```
In [94]: TBV = a[posAi]
mean(TBV)
```

```
Out[94]: 15.40137256410256
```

```
In [95]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[95]: 3.794481572750884
```

```
In [96]: numSSBayes
```

```
Out[96]: SSBR.NumSSBayes(54900,45900,9000,40000,39000,1000,0)
```