

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
        using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,size(IDs,1)}  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
    end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5/G/3  
        /home/nicole/Jupyter/JG3/Data/0.5/G/3
```

In [4]: ;ls

```
Correlation.G5.G.C.txt
Correlation.G5.G.J.txt
Correlation.G5.G.JC.txt
Correlation.G5.G.N.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.C.txt
Regression.G5.G.J.txt
Regression.G5.G.JC.txt
Regression.G5.G.N.txt
all.ID
alphaEstimates
genotype.ID
meanOfSNPGAll
meanOfSNPGG0
meanOfSNPGG1
meanOfSNPGG2
meanOfSNPGG3
meanOfSNPGG4
meanOfSNPGG5
noGenotype.ID
sim.bv
sim.phenotype
```

In [5]: ;awk '{print \$1}' PedAll.txt | sort -b > all.ID

In [6]: ;awk '{print \$1}' GenNF.txt | sort -b > genotype.ID

In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID

In [8]: ;awk '{print \$1,\$2}' Phe.txt > sim.phenotype

```

In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv

In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID

In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID

In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID

In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID

In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID

In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID

In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID

In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID

```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID
          7800 7800 46800 G0.noGenotype.ID
          7800 7800 46800 G1.noGenotype.ID
          7800 7800 46800 G2.noGenotype.ID
          7800 7800 46800 G3.noGenotype.ID
          7800 7800 46800 G4.noGenotype.ID
          0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding)
          nothing
          y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
          Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
          nothing
```

```
In [31]: vRes = 0.664
          vG = 0.664
          aHat3=SSBR.PBLUP(y_Vecs,Z_Mats,A_Mats,numSSBayes,vRes,vG);
```

```
In [32]: using DataFrames
```

```
In [33]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',header=false)
          a = Array{Float64,1}(zeros(numSSBayes,num_ped))
          for (i,ID) in enumerate(df[:,1])
              j = ped.idMap[ID].seqID
              a[j] = df[i,2]
          end
```

```
In [34]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
          posAi = getPos(ped,IDs)
          cor1 = cor(a[posAi],aHat3[posAi])[1,1]
          reg1 = linreg(aHat3[posAi], a[posAi])[2,1]
          @printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
          @printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n", reg1)
          JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.882
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.978
```

```
Out[34]: 0.8824953881456271
```

```
In [35]: TBV = a[posAi]
          mean(TBV)
```

```
Out[35]: 11.135083416666665
```

```
In [36]: EBV = aHat3[posAi]
          mean(EBV)
```

```
Out[36]: 1.2976544212425094
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat3[posAi])[1,1]
reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3:
JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.549
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 0.951
```

```
Out[37]: 0.5493480005956689
```

```
In [38]: TBV = a[posAi]
mean(TBV)
```

```
Out[38]: 12.273038222222223
```

```
In [39]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[39]: 2.463378187392464
```

```
In [40]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat3[posAi])[1,1]
reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6
JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.868
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.980
```

```
Out[40]: 0.8679961320422401
```

```
In [41]: TBV = a[posAi]
mean(TBV)
```

```
Out[41]: 10.872478461538462
```

```
In [42]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[42]: 1.0286412444386737
```

```
In [43]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation =  0.700
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV =  0.877
```

```
Out[43]: 0.6995711216889441
```

```
In [44]: TBV = a[posAi]
mean(TBV)
```

```
Out[44]: 9.84533075
```

```
In [45]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[45]: 0.00151502395740011
```

```
In [46]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation =  0.773
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV =  0.984
```

```
Out[46]: 0.7725871354461374
```

```
In [47]: TBV = a[posAi]
mean(TBV)
```

```
Out[47]: 10.40474075
```

```
In [48]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[48]: 0.5736346558759015
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.750
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 0.979
```

```
Out[49]: 0.7496561352919332
```

```
In [50]: TBV = a[posAi]
mean(TBV)
```

```
Out[50]: 10.945704874999999
```

```
In [51]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[51]: 1.0959091680294455
```

```
In [52]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.738
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.972
```

```
Out[52]: 0.7382760419479034
```

```
In [53]: TBV = a[posAi]
mean(TBV)
```

```
Out[53]: 11.422414125000001
```

```
In [54]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[54]: 1.5744754256824816
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat3[posAi])[1,1]
reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.712
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 0.935
```

```
Out[55]: 0.7115018929422184
```

```
In [56]: TBV = a[posAi]
mean(TBV)
```

```
Out[56]: 11.871169375
```

```
In [57]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[57]: 2.0280087925129235
```

```
In [58]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat3[posAi])[1,1]
reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.398
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 0.905
```

```
Out[58]: 0.3984199348489252
```

```
In [59]: TBV = a[posAi]
mean(TBV)
```

```
Out[59]: 12.321140625
```

```
In [60]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[60]: 2.512383461396904
```



```
In [61]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCall = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.900
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.084
```

```
Out[61]: 0.8998236346247229
```

```
In [62]: TBV = a[posAi]
mean(TBV)
```

```
Out[62]: 10.961675
```

```
In [63]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[63]: 1.1557836474378849
```

```
In [64]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCall = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.879
```

```
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.014
```

```
Out[64]: 0.8793293474424341
```

```
In [65]: TBV = a[posAi]
mean(TBV)
```

```
Out[65]: 11.464300000000001
```

```
In [66]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[66]: 1.6351374369606535
```

```
In [67]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.851
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.952
```

```
Out[67]: 0.8514746133453182
```

```
In [68]: TBV = a[posAi]
mean(TBV)
```

```
Out[68]: 11.912560000000003
```

```
In [69]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[69]: 2.0660397984886765
```

```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat3[posAi])[1,1]
reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.896
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.026
```

```
Out[70]: 0.8964757382936054
```

```
In [71]: TBV = a[posAi]
mean(TBV)
```

```
Out[71]: 12.34098
```

```
In [72]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[72]: 2.5054662192726234
```

```
In [73]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat3[posAi])[1,1]
reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCall = cor12
```

SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.465

SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.929

Out[73]: 0.46531491648031875

```
In [74]: TBV = a[posAi]
mean(TBV)
```

Out[74]: 12.761580000000002

```
In [75]: EBV = aHat3[posAi]
mean(EBV)
```

Out[75]: 2.9942528746248795

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat3[posAi])[1,1]
reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCall = cor13
```

SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.398

SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.905

Out[76]: 0.3984199348489252

```
In [77]: writedlm("Correlation.G5.G.PBLUP.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.G.PBLUP.txt",reg13)
```

```
In [79]: TBV = a[posAi]
mean(TBV)
```

Out[79]: 12.321140625

```
In [80]: EBV = aHat3[posAi]
mean(EBV)
```

Out[80]: 2.512383461396904

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.677
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.865
```

```
Out[81]: 0.6774609051804127
```

```
In [82]: TBV = a[posAi]
mean(TBV)
```

```
Out[82]: 9.81670653846154
```

```
In [83]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[83]: -0.02808160741389438
```

```
In [84]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.757
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.982
```

```
Out[84]: 0.7565074097241409
```

```
In [85]: TBV = a[posAi]
mean(TBV)
```

```
Out[85]: 10.377572564102563
```

```
In [86]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[86]: 0.5464166358480872
```

```
In [87]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat3[posAi])[1,1]
reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.734
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 0.978
```

```
Out[87]: 0.7339185879850127
```

```
In [88]: TBV = a[posAi]
mean(TBV)
```

```
Out[88]: 10.92091371794872
```

```
In [89]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[89]: 1.0710340236586962
```

```
In [90]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat3[posAi])[1,1]
reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.721
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.970
```

```
Out[90]: 0.7213941215088447
```

```
In [91]: TBV = a[posAi]
mean(TBV)
```

```
Out[91]: 11.398861153846154
```

```
In [92]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[92]: 1.550603866872478
```

```
In [93]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat3[posAi])[1,1]
reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.699
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.936
```

```
Out[93]: 0.6990894082914335
```

```
In [94]: TBV = a[posAi]
mean(TBV)
```

```
Out[94]: 11.848338333333334
```

```
In [95]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[95]: 2.0032333032280016
```

```
In [96]: numSSBayes
```

```
Out[96]: SSBR.NumSSBayes(54866,45866,9000,40000,39000,1000,0)
```