

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,1}(size(IDs,1))
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

```
Out[2]: getPos (generic function with 1 method)
```

```
In [3]: ; cd Data/0.5/Q/10

        /home/nicole/Jupyter/JG3/Data/0.5/Q/10
```

```
In [4]: ;ls

Correlation.G5.Q.JC.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' QTLNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding
nothing
df      = read_genotypes("QTLNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped);           # with
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes)      # with
nothing
```

```
In [31]: vRes      = 0.583
vG       = 0.583
nIter    = 50000
@time aHat1,alphaHat,betaHat,epsHat =
ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,
nothing

This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
2324.030226 seconds (22.99 G allocations: 723.049 GB, 8.56% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
 8.35519
 7.24532
```

```
In [33]: mu  = betaHat[1]
mug = betaHat[2]
```

```
Out[33]: 7.245316976701568
```

```
In [34]: (mu+mug)/2
```

```
Out[34]: 7.800251559790468
```

```
In [35]: alphaHat
```

```
Out[35]: 50-element Array{Float64,1}:
 0.153326
 0.150042
 0.190862
 0.198819
 0.185889
 0.187883
 0.173184
 0.176612
 0.182091
 0.18248
 0.176025
 0.199977
 0.165389
  ⋮
 0.190385
 0.197189
 0.21124
 0.201885
 0.203666
 0.212299
 0.190262
 0.178801
 0.199455
 0.215888
 0.200694
 0.173321
```

```
In [36]: writedlm("alphaEstimates",alphaHat)
```

```
In [37]: using DataFrames
```

```
In [38]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=:ID,
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [39]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ', header=:ID,
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.921
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.978
```

```
Out[39]: 0.9214718960961563
```

```
In [40]: TBV = a[posAi]
         mean(TBV)
```

```
Out[40]: 9.817296166666667
```

```
In [41]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[41]: 1.4687265957887194
```

```
In [42]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor2 = cor(a[posAi],aHat1[posAi])[1,1]
         reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
         @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
         JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.995
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.071
```

```
Out[42]: 0.9953628107751346
```

```
In [43]: TBV = a[posAi]
         mean(TBV)
```

```
Out[43]: 10.998993111111111
```

```
In [44]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[44]: 2.666731641945136
```

```
In [45]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat1[posAi])[1,1]
         reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.881
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.963
```

```
Out[45]: 0.880675914503669
```

```
In [46]: TBV = a[posAi]
         mean(TBV)
```

```
Out[46]: 9.544596871794871
```

```
In [47]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[47]: 1.1922638928295461
```

```
In [48]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.682
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.814
```

```
Out[48]: 0.68205867252802
```

```
In [49]: TBV = a[posAi]
G0TBV=mean(TBV)
```

```
Out[49]: 8.537600375
```

```
In [50]: GEBV = aHat1[posAi]
G0GEBV=mean(GEBV)
```

```
Out[50]: 0.1141619554889302
```

```
In [51]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.777
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.969
```

```
Out[51]: 0.7767572796707034
```

```
In [52]: TBV = a[posAi]
G1TBV=mean(TBV)
```

```
Out[52]: 9.044070624999998
```

```
In [53]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[53]: 0.7025489695685524
```

```
In [54]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.769
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.016
```

```
Out[54]: 0.769061994030617
```

```
In [55]: TBV = a[posAi]
G2TBV=mean(TBV)
```

```
Out[55]: 9.610254000000001
```

```
In [56]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[56]: 1.2814384441864448
```

```
In [57]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.783
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.054
```

```
Out[57]: 0.7825960255429413
```

```
In [58]: TBV = a[posAi]
G3TBV=mean(TBV)
```

```
Out[58]: 10.094816125000001
```

```
In [59]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[59]: 1.7681043589546666
```

```
In [60]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.796
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.059
```

```
Out[60]: 0.7957804989913134
```

```
In [61]: TBV = a[posAi]
G4TBV=mean(TBV)
```

```
Out[61]: 10.564574125
```

```
In [62]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[62]: 2.2295817604144545
```

```
In [63]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.995
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.071
```

```
Out[63]: 0.9947888990962024
```

```
In [64]: TBV = a[posAi]
G5TBV=mean(TBV)
```

```
Out[64]: 11.052461749999999
```

```
In [65]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[65]: 2.716524086119267
```



```
In [66]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.993
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.054
```

```
Out[66]: 0.9925308661021697
```

```
In [67]: TBV = a[posAi]
mean(TBV)
```

```
Out[67]: 9.537889999999999
```

```
In [68]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[68]: 1.2990775862893833
```

```
In [69]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.991
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.068
```

```
Out[69]: 0.9907590920421561
```

```
In [70]: TBV = a[posAi]
mean(TBV)
```

```
Out[70]: 10.16994
```

```
In [71]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[71]: 1.9022603295463474
```

```
In [72]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.993
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.079
```

```
Out[72]: 0.9932769963314694
```

```
In [73]: TBV = a[posAi]
mean(TBV)
```

```
Out[73]: 10.58867
```

```
In [74]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[74]: 2.2903227400808
```

```
In [75]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat1[posAi])[1,1]
reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.992
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.079
```

```
Out[75]: 0.9915251602406189
```

```
In [76]: TBV = a[posAi]
mean(TBV)
```

```
Out[76]: 11.03682
```

```
In [77]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[77]: 2.69513346352258
```

```
In [78]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat1[posAi])[1,1]
reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6
JCall = cor12
```

SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.990

SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.071

Out[78]: 0.9902589710070689

```
In [79]: TBV = a[posAi]
mean(TBV)
```

Out[79]: 11.5229

```
In [80]: GEBV = aHat1[posAi]
mean(GEBV)
```

Out[80]: 3.155166323321331

```
In [81]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat1[posAi])[1,1]
reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6
JCall = cor13
```

SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.995

SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.071

Out[81]: 0.9947888990962024

```
In [82]: writedlm("Correlation.G5.Q.J.txt",cor13)
```

```
In [83]: writedlm("Regression.G5.Q.J.txt",reg13)
```

```
In [84]: TBVG5Gall = a[posAi]
TBVG5G=mean(TBVG5Gall)
```

Out[84]: 11.052461749999999

```
In [85]: GEBVG5Gall = aHat1[posAi]
GEBVG5G=mean(GEBVG5Gall)
```

Out[85]: 2.716524086119267

```
In [86]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.658
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.806
```

```
Out[86]: 0.6580909329795177
```

```
In [87]: TBV = a[posAi]
mean(TBV)
```

```
Out[87]: 8.511951923076923
```

```
In [88]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[88]: 0.0837795034171237
```

```
In [89]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.756
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.972
```

```
Out[89]: 0.7562230206818708
```

```
In [90]: TBV = a[posAi]
mean(TBV)
```

```
Out[90]: 9.01520217948718
```

```
In [91]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[91]: 0.6717871398255318
```

```
In [92]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat1[posAi])[1,1]
reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.751
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.019
```

```
Out[92]: 0.7505305230874094
```

```
In [93]: TBV = a[posAi]
mean(TBV)
```

```
Out[93]: 9.585166410256411
```

```
In [94]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[94]: 1.2555696160865895
```

```
In [95]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.767
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.056
```

```
Out[95]: 0.7674732218383538
```

```
In [96]: TBV = a[posAi]
mean(TBV)
```

```
Out[96]: 10.07066217948718
```

```
In [97]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[97]: 1.7443343819144637
```

```
In [98]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.782
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 1.061
```

```
Out[98]: 0.7819669337745921
```

```
In [99]: TBV = a[posAi]
mean(TBV)
```

```
Out[99]: 10.540001666666667
```

```
In [100]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[100]: 2.2058488229040214
```

```
In [101]: numSSBayes
```

```
Out[101]: SSBR.NumSSBayes(54932,45932,9000,40000,39000,1000,50)
```

```
In [102]: J_Vecs.J1
```

```
Out[102]: 45932x1 Array{Float64,2}:
-0.00117028
0.0
-0.897397
-0.504674
-0.501177
-0.00234399
-0.752046
-0.753565
-0.752047
1.49432e-18
-0.751765
-0.975067
-0.543029
⋮
-0.965907
-0.00117096
-0.756882
-0.751902
-0.768544
1.99782e-18
-0.963525
-0.537651
-0.887654
-0.879173
-0.00351084
-0.0241544
```

```
In [103]: sortrows(J_Vecs.J1[end-8000:end,:])
```

```
Out[103]: 8001x1 Array{Float64,2}:  
  -0.985316  
  -0.983749  
  -0.98286  
  -0.98127  
  -0.981231  
  -0.981152  
  -0.981143  
  -0.981092  
  -0.980863  
  -0.980849  
  -0.980809  
  -0.980475  
  -0.979826  
  ⋮  
  5.55355e-17  
  5.55837e-17  
  5.55842e-17  
  5.56411e-17  
  5.56488e-17  
  5.5714e-17  
  5.57303e-17  
  5.5942e-17  
  5.71723e-17  
  6.07752e-17  
  6.66221e-17  
  7.12178e-17
```

```
In [104]: J1 = sortrows(J_Vecs.J1)
```

```
Out[104]: 45932x1 Array{Float64,2}:  
  -0.999967  
  -0.987231  
  -0.986975  
  -0.986214  
  -0.98601  
  -0.985787  
  -0.985511  
  -0.985316  
  -0.985246  
  -0.985205  
  -0.983749  
  -0.983608  
  -0.983471  
  ⋮  
  6.52796e-17  
  6.53185e-17  
  6.66221e-17  
  7.12178e-17  
  7.14e-17  
  7.3991e-17  
  8.73907e-17  
  8.88254e-17  
  8.90717e-17  
  1.02696e-16  
  1.11298e-16  
  1.16024e-16
```



```
In [105]: J1[J1 .< 0.0,:]
```

```
Out[105]: 43949x1 Array{Float64,2}:  
  -0.999967  
  -0.987231  
  -0.986975  
  -0.986214  
  -0.98601  
  -0.985787  
  -0.985511  
  -0.985316  
  -0.985246  
  -0.985205  
  -0.983749  
  -0.983608  
  -0.983471  
  ⋮  
  -7.22083e-36  
  -7.22083e-36  
  -7.22083e-36  
  -7.22083e-36  
  -7.2166e-36  
  -7.2166e-36  
  -7.20809e-36  
  -7.16816e-36  
  -5.41404e-36  
  -1.78007e-67  
  -1.78007e-67  
  -8.90036e-68
```

```
In [106]: J1[J1 .> 0.0,:]
```

```
Out[106]: 1281x1 Array{Float64,2}:
 1.97628e-83
 8.01673e-52
 8.01673e-52
 1.59165e-51
 1.60052e-51
 1.60241e-51
 1.60335e-51
 1.60335e-51
 1.60335e-51
 1.60335e-51
 2.1823e-51
 6.41485e-51
 1.24261e-50
 ⋮
 6.52796e-17
 6.53185e-17
 6.66221e-17
 7.12178e-17
 7.14e-17
 7.3991e-17
 8.73907e-17
 8.88254e-17
 8.90717e-17
 1.02696e-16
 1.11298e-16
 1.16024e-16
```

```
In [107]: G = convert(Array,readtable("QTLNF.txt", separator = ' ',header=false));
```

```
In [108]: GAll=mean(G[:,2:end],1)
```

```
Out[108]: 1x50 Array{Float64,2}:
 1.646  0.744111  1.21744  1.09822  ...  1.68444  1.48689  0.383333  1.2188
 9
```

```
In [109]: GG0=mean(G[1:200,2:end],1)
```

```
Out[109]: 1x50 Array{Float64,2}:
 1.71  0.35  0.73  1.205  0.905  0.92  ...  0.56  1.305  1.11  0.455  0.97
```

```
In [110]: GG1=mean(G[201:400,2:end],1)
```

```
Out[110]: 1x50 Array{Float64,2}:
 1.675  0.495  0.9  1.135  1.025  1.0  ...  0.56  1.495  1.27  0.455  1.115
```

```
In [111]: GG2=mean(G[401:600,2:end],1)
```

```
Out[111]: 1x50 Array{Float64,2}:
 1.585  0.63  1.125  1.115  1.055  1.09  ...  0.545  1.585  1.42  0.4  1.18
 5
```

```
In [112]: GG3=mean(G[601:800,2:end],1)
```

```
Out[112]: 1x50 Array{Float64,2}:  
 1.645  0.75  1.145  1.09  1.105  1.19  ...  0.595  1.7  1.49  0.325  1.275
```

```
In [113]: GG4=mean(G[801:1000,2:end],1)
```

```
Out[113]: 1x50 Array{Float64,2}:  
 1.65  0.885  1.415  1.1  1.185  1.29  ...  0.545  1.825  1.63  0.38  1.295
```

```
In [114]: GG5=mean(G[1001:9000,2:end],1)
```

```
Out[114]: 1x50 Array{Float64,2}:  
 1.64512  0.759375  1.23675  1.09438  ...  1.69725  1.49975  0.380875  1.22  
525
```

```
In [115]: writedlm("meanOfSNPQAll",GAll)
```

```
In [116]: writedlm("meanOfSNPQG0",GG0)
```

```
In [117]: writedlm("meanOfSNPQG1",GG1)
```

```
In [118]: writedlm("meanOfSNPQG2",GG2)
```

```
In [119]: writedlm("meanOfSNPQG3",GG3)
```

```
In [120]: writedlm("meanOfSNPQG4",GG4)
```

```
In [121]: writedlm("meanOfSNPQG5",GG5)
```