

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,size(IDs,1)}  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.3/G/3  
  
/home/nicole/Jupyter/JG3/Data/0.3/G/3
```

```
In [4]: ;ls
```

```
Correlation.G5.G.PBLUP.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.PBLUP.txt
all.ID
alphaEstimates
genotype.ID
meanOfSNPGAll
meanOfSNPGG0
meanOfSNPGG1
meanOfSNPGG2
meanOfSNPGG3
meanOfSNPGG4
meanOfSNPGG5
noGenotype.ID
sim.bv
sim.phenotype
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding=false)
nothing
df      = read_genotypes("GenNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped,center=true);           # with centering
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes) # with J
nothing
```

```
In [31]: vG      = 0.505
         vRes    = 1.180
         nIter   = 50000
         @time aHat1,alphaHat,betaHat,epsiHat =
         ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,nIter, outFreq=5000);
         nothing

         This is iteration 5000
         This is iteration 10000
         This is iteration 15000
         This is iteration 20000
         This is iteration 25000
         This is iteration 30000
         This is iteration 35000
         This is iteration 40000
         This is iteration 45000
         This is iteration 50000
         2498.528402 seconds (23.05 G allocations: 723.882 GB, 7.63% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
          14.0571
           4.45947
```

```
In [33]: using DataFrames
```

```
In [34]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',header=false)
         a  = Array{Float64,numSSBayes.num_ped}
         for (i,ID) in enumerate(df[:,1])
             j = ped.idMap[ID].seqID
             a[j] = df[i,2]
         end
```

```
In [35]: IDs = readtable("all.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with epsilon
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n", reg1)
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.879
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.978
```

```
Out[35]: 0.8785445256439066
```

```
In [36]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[36]: -2.652861620371028
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat1[posAi])[1,1]
reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # with epsilon
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
JCA11 = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.974
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.085
```

```
Out[37]: 0.9735296217941309
```

```
In [38]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[38]: -1.698910894196221
```

```
In [39]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat1[posAi])[1,1]
reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) # with epsilon
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
JCA11 = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.824
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.966
```

```
Out[39]: 0.82374730569899
```

```
In [40]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[40]: -2.873004095642137
```

```
In [41]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with epsilon
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
JCA11 = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.641
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 1.022
```

```
Out[41]: 0.641220077672954
```

```
In [42]: GEBV = aHat1[posAi]
G0GEBV=mean(GEBV)
```

```
Out[42]: -3.7776241955479013
```

```
In [43]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", reg4)
JCA11 = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.690
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 1.021
```

```
Out[43]: 0.6895235679731075
```

```
In [44]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[44]: -3.2443827270317165
```

```
In [45]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", reg5)
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.700
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.022
```

```
Out[45]: 0.6998045937425779
```

```
In [46]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[46]: -2.8103522103255303
```



```
In [47]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with epsilon
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", reg6)
JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.699
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.039
```

```
Out[47]: 0.6989558757685801
```

```
In [48]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[48]: -2.4158836898917535
```

```
In [49]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with epsilon
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", reg7)
JCall = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.735
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.071
```

```
Out[49]: 0.7352687608511845
```

```
In [50]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[50]: -2.00781159888919
```

```
In [51]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with epsilon
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", reg8)
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.971
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.085
```

```
Out[51]: 0.971344585777327
```

```
In [52]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[52]: -1.6611153005400747
```

```
In [53]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.964
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.065
```

```
Out[53]: 0.9637382720744384
```

```
In [54]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[54]: -2.686102389997046
```

```
In [55]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation =  0.963
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV =  1.051
```

```
Out[55]: 0.963456501902377
```

```
In [56]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[56]: -2.3663936747019685
```

```
In [57]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation =  0.967
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV =  1.072
```

```
Out[57]: 0.9670121044638078
```

```
In [58]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[58]: -2.0111642513998174
```

```
In [59]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat1[posAi])[1,1]
reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11 ) # with epsilon
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation =  0.966
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV =  1.074
```

```
Out[59]: 0.9663640707051968
```

```
In [60]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[60]: -1.5953771372970933
```

```
In [61]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat1[posAi])[1,1]
reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12 ) # with epsilon
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCA11 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation =  0.969
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV =  1.079
```

```
Out[61]: 0.9685923148397221
```

```
In [62]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[62]: -1.3473407638310457
```

```
In [63]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat1[posAi])[1,1]
reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13 ) # with epsilon
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCA11 = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.971
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.085
```

```
Out[63]: 0.971344585777327
```

```
In [64]: writedlm("Correlation.G5.G.JC.txt",cor13)
```

```
In [65]: writedlm("Regression.G5.G.JC.txt",reg13)
```

```
In [66]: TBVG5Gall = a[posAi]
TBVG5G=mean(TBVG5Gall)
```

```
Out[66]: 12.3666555
```

```
In [67]: GEBVG5Gall = aHat1[posAi]
GEBVG5G=mean(GEBVG5Gall)
```

```
Out[67]: -1.6611153005400747
```

```
In [68]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCA11 = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.620
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 1.067
```

```
Out[68]: 0.620211192056283
```

```
In [69]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[69]: -3.805611934151769
```

```
In [70]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation =  0.669
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV =  1.032
```

```
Out[70]: 0.6688546404448568
```

```
In [71]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[71]: -3.2668952668350433
```

```
In [72]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor15 = cor(a[posAi],aHat1[posAi])[1,1]
         reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15 ) # with epsilon
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
         JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation =  0.681
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV =  1.026
```

```
Out[72]: 0.6807927064636158
```

```
In [73]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[73]: -2.8308442092723434
```

```
In [74]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16 ) # with epsilon
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation =  0.678
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV =  1.039
```

```
Out[74]: 0.6782258317109611
```

```
In [75]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[75]: -2.436922319445462
```

```
In [76]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17 ) # with epsilon
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCA11 = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation =  0.722
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV =  1.072
```

```
Out[76]: 0.7221326158958599
```

```
In [77]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[77]: -2.0247467485060655
```

```
In [78]: numSSBayes
```

```
Out[78]: SSBR.NumSSBayes(54913,45913,9000,40000,39000,1000,200)
```

```
In [79]: J1 = sortrows(J_Vecs.J1)
```

```
Out[79]: 45913x1 Array{Float64,2}:
```

```
-0.987848  
-0.98775  
-0.986976  
-0.986972  
-0.985598  
-0.985569  
-0.985307  
-0.984234  
-0.984219  
-0.984073  
-0.983729  
-0.983606  
-0.983122  
:  
6.67104e-17  
6.70633e-17  
7.24466e-17  
7.40484e-17  
7.47331e-17  
7.59165e-17  
7.86776e-17  
8.84953e-17  
8.85164e-17  
8.85362e-17  
8.88309e-17  
1.11342e-16
```



```
In [80]: J1[J1 .< 0.0,:]
```

```
Out[80]: 43908x1 Array{Float64,2}:
```

```
-0.987848  
-0.98775  
-0.986976  
-0.986972  
-0.985598  
-0.985569  
-0.985307  
-0.984234  
-0.984219  
-0.984073  
-0.983729  
-0.983606  
-0.983122  
:  
-7.21449e-36  
-7.21449e-36  
-7.21238e-36  
-7.21238e-36  
-7.21235e-36  
-7.20816e-36  
-7.11812e-36  
-6.75383e-36  
-4.91411e-36  
-3.55911e-67  
-1.77955e-67  
-1.77799e-67
```