

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,size(IDs,1)}
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

```
Out[2]: getPos (generic function with 1 method)
```

```
In [3]: ; cd Data/0.5a0/G/1

/home/nicole/Jupyter/JG3/Data/0.5a0/G/1
```

```
In [4]: ;ls

Correlation.G5.G.JC.txt
Correlation.G5.G.N.txt
Correlation.G5.G.PBLUP.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding
nothing
df      = read_genotypes("GenNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped,center=true);           # with
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes);
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(Z_Mats,M_Mats,numSSBayes)    # no
nothing
```

```
In [31]: vRes      = 1.408
vG       = 1.408
nIter    = 50000
@time aHat1,alphaHat,betaHat,epsHat =
ssGibbs(M_Mats,y_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,nIter,
nothing

This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
4658.954923 seconds (23.07 G allocations: 724.377 GB, 6.61% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 1-element Array{Float64,1}:
2.45743
```

```
In [33]: using DataFrames
```

```
In [34]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',head
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [35]: IDs = readtable("all.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.916
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.972
```

```
Out[35]: 0.9160191043465035
```

```
In [36]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[36]: 0.20092527197126842
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat1[posAi])[1,1]
reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) #
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.976
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.010
```

```
Out[37]: 0.9761750954987127
```

```
In [38]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[38]: 1.7449094558030687
```

```
In [39]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat1[posAi])[1,1]
reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.884
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.978
```

```
Out[39]: 0.8837100374424888
```

```
In [40]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[40]: -0.15537877045145485
```

```
In [41]: IDs = readtable("G0.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.799
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 1.105
```

```
Out[41]: 0.7987100684918621
```

```
In [42]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[42]: -1.689636681048176
```

```
In [43]: IDs = readtable("G1.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.783
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 1.003
```

```
Out[43]: 0.7826369763485335
```

```
In [44]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[44]: -0.7570742449360627
```

```
In [45]: IDs = readtable("G2.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.754
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 0.961
```

```
Out[45]: 0.7543105814265777
```

```
In [46]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[46]: -0.013227900330218518
```

```
In [47]: IDs = readtable("G3.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.749
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.954
```

```
Out[47]: 0.7491069399811771
```

```
In [48]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[48]: 0.6421376986365798
```

```
In [49]: IDs = readtable("G4.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.773
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 0.940
```

```
Out[49]: 0.7729218592537522
```

```
In [50]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[50]: 1.2237997583266798
```

```
In [51]: IDs = readtable("G5.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.973
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.010
```

```
Out[51]: 0.9732092481792368
```

```
In [52]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[52]: 1.7995530011788072
```

```
In [53]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.974
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 0.999
```

```
Out[53]: 0.9741397677038982
```

```
In [54]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[54]: 0.2181670632627978
```

```
In [55]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.978
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.000
```

```
Out[55]: 0.9778656373930116
```

```
In [56]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[56]: 0.7821616127757626
```

```
In [57]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 )
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10 )
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.974
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.002
```

```
Out[57]: 0.9735959289370003
```

```
In [58]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[58]: 1.343444680402232
```

```
In [59]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat1[posAi])[1,1]
reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.975
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.022
```

```
Out[59]: 0.9751184436446213
```

```
In [60]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[60]: 1.843461994813797
```

```
In [61]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat1[posAi])[1,1]
reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCA12 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.955
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.994
```

```
Out[61]: 0.9547921449704302
```

```
In [62]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[62]: 2.3515701127312125
```

```
In [63]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat1[posAi])[1,1]
reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCA13 = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.973
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.010
```

```
Out[63]: 0.9732092481792368
```

```
In [64]: writedlm("Correlation.G5.G.C.txt",cor13)
```

```
In [65]: writedlm("Regression.G5.G.C.txt",reg13)
```



```
In [66]: GEBVG5Gall = aHat1[posAi]
         GEBVG5G=mean(GEBVG5Gall)
```

```
Out[66]: 1.7995530011788072
```

```
In [67]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.785
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 1.138
```

```
Out[67]: 0.7854493964887527
```

```
In [68]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[68]: -1.738554725774098
```

```
In [69]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.767
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 1.010
```

```
Out[69]: 0.7674645458357734
```

```
In [70]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[70]: -0.7965418310312377
```

```
In [71]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor15 = cor(a[posAi],aHat1[posAi])[1,1]
         reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
         JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.738
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 0.962
```

```
Out[71]: 0.7382373080049426
```

```
In [72]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[72]: -0.04801437675925567
```

```
In [73]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor16 = cor(a[posAi],aHat1[posAi])[1,1]
         reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
         JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.734
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.952
```

```
Out[73]: 0.7340052904757195
```

```
In [74]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[74]: 0.6113345115551128
```

```
In [75]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor17 = cor(a[posAi],aHat1[posAi])[1,1]
         reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
         JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.761
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.938
```

```
Out[75]: 0.7606700763354177
```

```
In [76]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[76]: 1.1948825697522043
```

```
In [77]: numSSBayes
```

```
Out[77]: SSBR.NumSSBayes(54950,45950,9000,40000,39000,1000,200)
```