

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,1}(size(IDs,1))
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5a0/M/2

/home/nicole/Jupyter/JG3/Data/0.5a0/M/2
```

```
In [4]: ;ls

MarNF.txt
PedAll.txt
Phe.txt
PheAll.txt
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' MarNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G5.noGenotype.ID
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreedingCoefficients)
nothing
df      = read_genotypes("MarNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped,center=true); # with centering
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes) # with W_Mats
nothing
```

```
In [31]: vRes    = 0.323
         vG      = 0.323
         nIter   = 50000
         @time aHat1,alphaHat,betaHat,epsiHat =
         ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,
         nothing
```

```
This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
3039.174296 seconds (23.05 G allocations: 724.081 GB, 7.30% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
          3.40688
         -0.201813
```

```
In [33]: mu    = betaHat[1]
         mug    = betaHat[2]
```

```
Out[33]: -0.2018132256257097
```

```
In [34]: (mu+mug)/2
```

```
Out[34]: 1.602535174374645
```

```
In [35]: alphaHat
```

```
Out[35]: 150-element Array{Float64,1}:
 0.0542393
 0.0753227
 0.0345492
 0.0592516
 0.235556
-0.00594425
-0.01593
-0.0615966
-0.110545
 0.0597823
-0.0276026
-0.0344578
 0.00984042
  ⋮
-0.187435
-0.0439532
 0.0468822
 0.0923935
 0.0760766
 0.056042
-0.000958604
-0.0333981
 0.0395975
 0.0231357
 0.0112027
 0.00201097
```

```
In [36]: writedlm("alphaEstimatesJC",alphaHat)
```

```
In [37]: epsiHat
```

```
Out[37]: 45954-element Array{Float64,1}:
 0.0921049
-0.241817
-0.262838
-0.280258
-0.102677
-0.195313
 0.106993
-0.231056
-0.0669534
-0.0371943
 1.27924
 0.285005
-0.0852341
  ⋮
 0.590447
-0.223408
 0.064255
-0.277746
 0.473359
-0.0981396
-0.0902777
-0.0539236
 0.174434
 0.26793
-0.264318
-0.269307
```

```
In [38]: writedlm("epsiEstimatesJC",epsiHat)
```

```
In [39]: using DataFrames
```

```
In [40]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=:a
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [41]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.893
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.962
```

```
Out[41]: 0.8925668411847673
```

```
In [42]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[42]: 0.22470585614448063
```

```
In [43]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor2 = cor(a[posAi],aHat1[posAi])[1,1]
         reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
         @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
         JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.893
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.097
```

```
Out[43]: 0.8933144825442717
```

```
In [44]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[44]: 1.0483018269379367
```

```
In [45]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat1[posAi])[1,1]
         reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.851
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.914
```

```
Out[45]: 0.8511950444633994
```

```
In [46]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[46]: 0.03464524749983689
```

```
In [47]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat1[posAi])[1,1]
         reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
         @printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
         JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.574
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.579
```

```
Out[47]: 0.57368020832058
```

```
In [48]: GEBV = aHat1[posAi]
         G1GEBV=mean(GEBV)
```

```
Out[48]: -0.758889572722274
```

```
In [49]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat1[posAi])[1,1]
         reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
         @printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation =  0.766
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV =  0.952
```

```
Out[49]: 0.7660712054165186
```

```
In [50]: GEBV = aHat1[posAi]
         G1GEBV=mean(GEBV)
```

```
Out[50]: -0.29615381306985444
```

```
In [51]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor5 = cor(a[posAi],aHat1[posAi])[1,1]
         reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
         @printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation =  0.774
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV =  1.022
```

```
Out[51]: 0.7736732919917594
```

```
In [52]: GEBV = aHat1[posAi]
         G2GEBV=mean(GEBV)
```

```
Out[52]: 0.10856869740656115
```

```
In [53]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor6 = cor(a[posAi],aHat1[posAi])[1,1]
         reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
         @printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation =  0.764
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV =  1.050
```

```
Out[53]: 0.7644065309930304
```

```
In [54]: GEBV = aHat1[posAi]
         G3GEBV=mean(GEBV)
```

```
Out[54]: 0.4356160245113664
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor7 = cor(a[posAi],aHat1[posAi])[1,1]
         reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
         @printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
         JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.772
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.067
```

```
Out[55]: 0.7719476550537515
```

```
In [56]: GEBV = aHat1[posAi]
         G4GEBV=mean(GEBV)
```

```
Out[56]: 0.7802304025631752
```

```
In [57]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor8 = cor(a[posAi],aHat1[posAi])[1,1]
         reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
         @printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
         JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.878
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.070
```

```
Out[57]: 0.8782986769169564
```

```
In [58]: reg8 = linreg(aHat1[posAi], a[posAi])
```

```
Out[58]: 2-element Array{Float64,1}:
         3.40142
         1.07049
```

```
In [59]: VarGEBV=var(aHat1[posAi])
```

```
Out[59]: 0.18109617575487547
```

```
In [60]: VarTBV=var(a[posAi])
```

```
Out[60]: 0.2690228966395174
```

```
In [61]: Cov=cov(aHat1[posAi], a[posAi])
```

```
Out[61]: 0.19386146504715046
```



```
In [62]: b=Cov/VarGEBV
```

```
Out[62]: 1.070489005298232
```

```
In [63]: GEBV = aHat1[posAi]
         G5GEBV=mean(GEBV)
```

```
Out[63]: 1.0788633981779094
```

```
In [64]: GEBVG5G1=G5GEBV-G1GEBV
```

```
Out[64]: 1.3750172112477639
```

```
In [65]: GEBVG1G5=[G1GEBV;G2GEBV;G3GEBV;G4GEBV;G5GEBV]
```

```
Out[65]: 5-element Array{Float64,1}:
          -0.296154
           0.108569
           0.435616
           0.78023
           1.07886
```

```
In [66]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
         posAi = getPos(ped,IDs)
         cor9 = cor(a[posAi],aHat1[posAi])[1,1]
         reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
         @printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
         JCall = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.886
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.054
```

```
Out[66]: 0.8860490649549754
```

```
In [67]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[67]: 0.22328743393026232
```

```
In [68]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
         posAi = getPos(ped,IDs)
         cor9 = cor(a[posAi],aHat1[posAi])[1,1]
         reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
         @printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
         JCall = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.873
```

```
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 0.993
```

```
Out[68]: 0.8733822211289328
```

```
In [69]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[69]: 0.5719695320470085
```

```
In [70]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor10 = cor(a[posAi],aHat1[posAi])[1,1]
         reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
         @printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
         JCall = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.893
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.998
```

```
Out[70]: 0.8929081519427655
```

```
In [71]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[71]: 0.7789455070167862
```

```
In [72]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor11 = cor(a[posAi],aHat1[posAi])[1,1]
         reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
         JCall = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.871
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.980
```

```
Out[72]: 0.8706015192223044
```

```
In [73]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[73]: 1.100358668544467
```

```
In [74]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor12 = cor(a[posAi],aHat1[posAi])[1,1]
         reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
         JCall = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.831
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.929
```

```
Out[74]: 0.8310948071559361
```

```
In [75]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[75]: 1.344485143552261
```

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor13 = cor(a[posAi],aHat1[posAi])[1,1]
         reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
         JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.878
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.070
```

```
Out[76]: 0.8782986769169564
```

```
In [77]: writedlm("Correlation.G5.M.JC.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.M.JC.txt",reg13)
```

```
In [79]: TBVG5Gall = a[posAi]
         TBVG5G=mean(TBVG5Gall)
```

```
Out[79]: 4.55633275
```

```
In [80]: GEBVG5Gall = aHat1[posAi]
         GEBVG5G=mean(GEBVG5Gall)
```

```
Out[80]: 1.0788633981779094
```

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.549
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.567
```

```
Out[81]: 0.5489236930174197
```

```
In [82]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[82]: -0.7840735985338777
```

```
In [83]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.747
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.952
```

```
Out[83]: 0.747270542101785
```

```
In [84]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[84]: -0.31841338602156893
```

```
In [85]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat1[posAi])[1,1]
reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.759
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.020
```

```
Out[85]: 0.7592581308659965
```

```
In [86]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[86]: 0.09137954844219638
```

```
In [87]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.748
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.045
```

```
Out[87]: 0.7481505062639341
```

```
In [88]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[88]: 0.4185713413310306
```

```
In [89]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.759
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 1.059
```

```
Out[89]: 0.7593958222028617
```

```
In [90]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[90]: 0.7657623322814039
```

```
In [91]: numSSBayes
```

```
Out[91]: SSBR.NumSSBayes(54954,45954,9000,40000,39000,1000,150)
```

```
In [92]: J1 = sortrows(J_Vecs.J1)
```

```
Out[92]: 45954x1 Array{Float64,2}:
-0.990207
-0.987007
-0.985912
-0.985806
-0.985626
-0.985577
-0.985452
-0.985448
-0.98531
-0.985263
-0.984879
-0.98461
-0.984436
⋮
5.6874e-17
6.32693e-17
6.33331e-17
6.6688e-17
7.0995e-17
7.41042e-17
7.42296e-17
7.52177e-17
7.52508e-17
8.53373e-17
8.54678e-17
8.89738e-17
```

```
In [93]: J1[J1 .< 0.0,:]
```

```
Out[93]: 43889x1 Array{Float64,2}:  
  -0.990207  
  -0.987007  
  -0.985912  
  -0.985806  
  -0.985626  
  -0.985577  
  -0.985452  
  -0.985448  
  -0.98531  
  -0.985263  
  -0.984879  
  -0.98461  
  -0.984436  
  ⋮  
  -7.2166e-36  
  -7.2166e-36  
  -7.2166e-36  
  -7.2166e-36  
  -7.21238e-36  
  -7.21237e-36  
  -7.17242e-36  
  -6.64565e-36  
  -5.93075e-36  
  -5.78073e-36  
  -5.45576e-52  
  -1.36439e-65
```

```
In [94]: J1[J1 .> 0.0,:]
```

```
Out[94]: 1335x1 Array{Float64,2}:  
 8.03086e-52  
 8.03086e-52  
 8.05451e-52  
 1.5926e-51  
 1.60147e-51  
 1.60241e-51  
 1.60288e-51  
 1.60335e-51  
 1.60617e-51  
 1.60806e-51  
 1.6109e-51  
 1.63329e-51  
 2.1823e-51  
 ⋮  
 5.6874e-17  
 6.32693e-17  
 6.33331e-17  
 6.6688e-17  
 7.0995e-17  
 7.41042e-17  
 7.42296e-17  
 7.52177e-17  
 7.52508e-17  
 8.53373e-17  
 8.54678e-17  
 8.89738e-17
```