

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,1}(size(IDs,1))
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5a0/G/1

/home/nicole/Jupyter/JG3/Data/0.5a0/G/1
```

```
In [4]: ;ls

Correlation.G5.G.JC.txt
Correlation.G5.G.N.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.JC.txt
Regression.G5.G.N.txt
all.ID
genotype.ID
noGenotype.ID
sim.bv
sim.phenotype
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID

In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID

In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype

In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv

In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID

In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID

In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID

In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID

In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID

In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID

In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```



```
In [36]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[36]: 1.8124993169693728
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor2 = cor(a[posAi],aHat3[posAi])[1,1]
         reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
         @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3:
         JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation =  0.556
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV =  0.878
```

```
Out[37]: 0.555818145385672
```

```
In [38]: TBV = a[posAi]
         mean(TBV)
```

```
Out[38]: 4.108706222222223
```

```
In [39]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[39]: 3.410962489128093
```

```
In [40]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',heade
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat3[posAi])[1,1]
         reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation =  0.877
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV =  0.995
```

```
Out[40]: 0.8767379006697824
```

```
In [41]: TBV = a[posAi]
         mean(TBV)
```

```
Out[41]: 2.3046546923076923
```

```
In [42]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[42]: 1.4436232003173604
```

```
In [43]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.799
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 1.130
```

```
Out[43]: 0.7990127756656066
```

```
In [44]: TBV = a[posAi]
mean(TBV)
```

```
Out[44]: 0.8388541249999999
```

```
In [45]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[45]: -0.0006331634645465405
```

```
In [46]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.776
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 1.003
```

```
Out[46]: 0.7760287925348034
```

```
In [47]: TBV = a[posAi]
mean(TBV)
```

```
Out[47]: 1.7074885
```

```
In [48]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[48]: 0.8220206254046252
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.745
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 0.961
```

```
Out[49]: 0.7451269979704263
```

```
In [50]: TBV = a[posAi]
mean(TBV)
```

```
Out[50]: 2.43677575
```

```
In [51]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[51]: 1.552212611450559
```

```
In [52]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.734
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.935
```

```
Out[52]: 0.7339263078700347
```

```
In [53]: TBV = a[posAi]
mean(TBV)
```

```
Out[53]: 3.0633003750000003
```

```
In [54]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[54]: 2.2106905765327056
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat3[posAi])[1,1]
reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation =  0.705
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV =  0.874
```

```
Out[55]: 0.7052909069954982
```

```
In [56]: TBV = a[posAi]
mean(TBV)
```

```
Out[56]: 3.6475862500000003
```

```
In [57]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[57]: 2.812858983270985
```

```
In [58]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat3[posAi])[1,1]
reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation =  0.420
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV =  0.867
```

```
Out[58]: 0.4202985326544734
```

```
In [59]: TBV = a[posAi]
mean(TBV)
```

```
Out[59]: 4.163481125000001
```

```
In [60]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[60]: 3.4778462686219083
```

```
In [61]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.889
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 0.960
```

```
Out[61]: 0.888746080232019
```

```
In [62]: TBV = a[posAi]
mean(TBV)
```

```
Out[62]: 2.558755
```

```
In [63]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[63]: 1.6339367750739304
```

```
In [64]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.882
```

```
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.012
```

```
Out[64]: 0.8815735773861826
```

```
In [65]: TBV = a[posAi]
mean(TBV)
```

```
Out[65]: 3.1442850000000004
```

```
In [66]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[66]: 2.285290935091015
```



```
In [67]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.879
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.971
```

```
Out[67]: 0.8793439736010608
```

```
In [68]: TBV = a[posAi]
mean(TBV)
```

```
Out[68]: 3.7104500000000002
```

```
In [69]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[69]: 2.869155254594426
```

```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat3[posAi])[1,1]
reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.882
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.999
```

```
Out[70]: 0.8821532131454335
```

```
In [71]: TBV = a[posAi]
mean(TBV)
```

```
Out[71]: 4.21913
```

```
In [72]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[72]: 3.4468936026894776
```

```
In [73]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat3[posAi])[1,1]
reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCall = cor12
```

SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.438

SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.750

Out[73]: 0.43803154239800746

```
In [74]: TBV = a[posAi]
mean(TBV)
```

Out[74]: 4.719915

```
In [75]: EBV = aHat3[posAi]
mean(EBV)
```

Out[75]: 4.144184698439014

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat3[posAi])[1,1]
reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCall = cor13
```

SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.420

SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.867

Out[76]: 0.4202985326544734

```
In [77]: writedlm("Correlation.G5.G.PBLUP.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.G.PBLUP.txt",reg13)
```

```
In [79]: TBV = a[posAi]
mean(TBV)
```

Out[79]: 4.163481125000001

```
In [80]: EBV = aHat3[posAi]
mean(EBV)
```

Out[80]: 3.4778462686219083

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.785
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 1.142
```

```
Out[81]: 0.7851397821006547
```

```
In [82]: TBV = a[posAi]
mean(TBV)
```

```
Out[82]: 0.7947541025641025
```

```
In [83]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[83]: -0.04254521317066133
```

```
In [84]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.762
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 1.005
```

```
Out[84]: 0.7618454066814878
```

```
In [85]: TBV = a[posAi]
mean(TBV)
```

```
Out[85]: 1.6706475641025644
```

```
In [86]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[86]: 0.784500873874205
```

```
In [87]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat3[posAi])[1,1]
reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.730
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 0.960
```

```
Out[87]: 0.7300473075312068
```

```
In [88]: TBV = a[posAi]
mean(TBV)
```

```
Out[88]: 2.4041174358974358
```

```
In [89]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[89]: 1.5184448513699473
```

```
In [90]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat3[posAi])[1,1]
reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.720
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.934
```

```
Out[90]: 0.7195284806143848
```

```
In [91]: TBV = a[posAi]
mean(TBV)
```

```
Out[91]: 3.033663717948718
```

```
In [92]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[92]: 2.178993063041506
```

```
In [93]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat3[posAi])[1,1]
reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.695
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.881
```

```
Out[93]: 0.6949663101798487
```

```
In [94]: TBV = a[posAi]
mean(TBV)
```

```
Out[94]: 3.6200906410256413
```

```
In [95]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[95]: 2.7787224264718047
```

```
In [96]: numSSBayes
```

```
Out[96]: SSBR.NumSSBayes(54950,45950,9000,40000,39000,1000,0)
```