

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,1}(size(IDs,1))  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5g2k/G/10  
  
/home/nicole/Jupyter/JG3/Data/0.5g2k/G/10
```

```
In [4]: ;ls
```

```
Correlation.G5.G.JC.txt
Correlation.G5.G.PBLUP.txt
G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
GenNF.txt
PedAll.txt
Phe.txt
PheAll.txt
Regression.G5.G.JC.txt
Regression.G5.G.PBLUP.txt
all.ID
genotype.ID
noGenotype.ID
sim.bv
sim.phenotype
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding=false)
nothing
df      = read_genotypes("GenNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped);                # without centering
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes)    # with J
nothing
```

```
In [31]: vG      = 0.858
         vRes    = 0.858
         nIter   = 50000
         @time aHat1,alphaHat,betaHat,epsiHat =
         ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,nIter, outFreq=5000);
         nothing

         This is iteration 5000
         This is iteration 10000
         This is iteration 15000
         This is iteration 20000
         This is iteration 25000
         This is iteration 30000
         This is iteration 35000
         This is iteration 40000
         This is iteration 45000
         This is iteration 50000
         7134.276875 seconds (23.86 G allocations: 736.901 GB, 2.66% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
          32.3899
           3.1136
```

```
In [33]: mu  = betaHat[1]
         mug = betaHat[2]
```

```
Out[33]: 3.11359678150213
```

```
In [34]: (mu+mug)/2
```

```
Out[34]: 17.751726605740842
```

```
In [35]: alphaHat
```

```
Out[35]: 2000-element Array{Float64,1}:
 0.0020614
 0.0146156
-0.012226
 0.00468692
 0.00386603
 0.0081415
-0.00908663
-0.00547834
 0.00324635
-0.0026534
 0.00169894
-0.0111903
 0.00759872
 ⋮
-0.0128452
 0.00849912
-0.0205159
-0.00756835
 0.00425587
 0.00299136
-0.000883805
-0.00841129
-0.00194883
 0.00492376
-0.00104616
 0.0201866
```

```
In [36]: writedlm("alphaEstimates",alphaHat)
```

```
In [37]: using DataFrames
```

```
In [38]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ',header=false)
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [39]: IDs = readtable("all.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor1 = cor(a[posAi],aHat1[posAi])[1,1]
        reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with epsilon
        @printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n", reg1)
        JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.913
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.980
```

```
Out[39]: 0.9125184613002976
```

```
In [40]: TBV = a[posAi]
        mean(TBV)
```

```
Out[40]: 34.115545895833336
```

```
In [41]: GEBV = aHat1[posAi]
        mean(GEBV)
```

```
Out[41]: 1.7172884582259764
```

```
In [42]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor2 = cor(a[posAi],aHat1[posAi])[1,1]
        reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # with epsilon
        @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
        JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.917
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.076
```

```
Out[42]: 0.9167763212394734
```

```
In [43]: TBV = a[posAi]
        mean(TBV)
```

```
Out[43]: 35.388306
```

```
In [44]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[44]: 2.995560314835624
```

```
In [45]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat1[posAi])[1,1]
         reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) # with epsilon
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.881
```

```
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.965
```

```
Out[45]: 0.8814473264494739
```

```
In [46]: TBV = a[posAi]
         mean(TBV)
```

```
Out[46]: 33.82183202564103
```

```
In [47]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[47]: 1.422302645162211
```

```
In [48]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat1[posAi])[1,1]
         reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with epsilon
         @printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
         JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.750
```

```
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.938
```

```
Out[48]: 0.7498273367142502
```



```
In [49]: TBV = a[posAi]
        G0TBV=mean(TBV)
```

```
Out[49]: 32.63486125
```

```
In [50]: GEBV = aHat1[posAi]
        G0GEBV=mean(GEBV)
```

```
Out[50]: 0.1430309533648206
```

```
In [51]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor4 = cor(a[posAi],aHat1[posAi])[1,1]
        reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with epsilon
        @printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", reg4)
        JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation =  0.776
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV =  0.994
```

```
Out[51]: 0.7763455133487692
```

```
In [52]: TBV = a[posAi]
        G1TBV=mean(TBV)
```

```
Out[52]: 33.289144499999999
```

```
In [53]: GEBV = aHat1[posAi]
        G1GEBV=mean(GEBV)
```

```
Out[53]: 0.9046891171099463
```

```
In [54]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", reg5)
JCall = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.764
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 0.995
```

```
Out[54]: 0.7641946393836294
```

```
In [55]: TBV = a[posAi]
G2TBV=mean(TBV)
```

```
Out[55]: 33.902438499999999
```

```
In [56]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[56]: 1.5449693176207224
```

```
In [57]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with epsilon
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", reg6)
JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.755
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 0.996
```

```
Out[57]: 0.7547871775537396
```

```
In [58]: TBV = a[posAi]
G3TBV=mean(TBV)
```

```
Out[58]: 34.439698625
```

```
In [59]: GEBV = aHat1[posAi]
        G3GEBV=mean(GEBV)
```

```
Out[59]: 2.0708956616872527
```

```
In [60]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor7 = cor(a[posAi],aHat1[posAi])[1,1]
        reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with epsilon
        @printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", reg7)
        JCall = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation =  0.756
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV =  0.986
```

```
Out[60]: 0.7562161489449977
```

```
In [61]: TBV = a[posAi]
        G4TBV=mean(TBV)
```

```
Out[61]: 34.985941625
```

```
In [62]: GEBV = aHat1[posAi]
        G4GEBV=mean(GEBV)
```

```
Out[62]: 2.5994314099679787
```

```
In [63]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor8 = cor(a[posAi],aHat1[posAi])[1,1]
        reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with epsilon
        @printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", reg8)
        JCall = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation =  0.904
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV =  1.063
```

```
Out[63]: 0.9036375348993642
```

```
In [64]: TBV = a[posAi]
        G5TBV=mean(TBV)
```

```
Out[64]: 35.44119087500001
```

```
In [65]: GEBV = aHat1[posAi]
        G5GEBV=mean(GEBV)
```

```
Out[65]: 3.0407142896051362
```

```
In [66]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
        posAi = getPos(ped,IDs)
        cor9 = cor(a[posAi],aHat1[posAi])[1,1]
        reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
        @printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
        JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.925
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.064
```

```
Out[66]: 0.9248598716913826
```

```
In [67]: TBV = a[posAi]
        mean(TBV)
```

```
Out[67]: 33.928745000000006
```

```
In [68]: GEBV = aHat1[posAi]
        mean(GEBV)
```

```
Out[68]: 1.734569450944706
```

```
In [69]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCall = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.938
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.084
```

```
Out[69]: 0.9376210821462114
```

```
In [70]: TBV = a[posAi]
mean(TBV)
```

```
Out[70]: 34.484030000000004
```

```
In [71]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[71]: 2.2230494958892204
```

```
In [72]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCall = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.929
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.062
```

```
Out[72]: 0.9287227272959642
```

```
In [73]: TBV = a[posAi]
mean(TBV)
```

```
Out[73]: 34.975065
```

```
In [74]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[74]: 2.6392128778052166
```

```
In [75]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor11 = cor(a[posAi],aHat1[posAi])[1,1]
         reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11 ) # with epsilon
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
         JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.932
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.094
```

```
Out[75]: 0.9317077187803272
```

```
In [76]: TBV = a[posAi]
         mean(TBV)
```

```
Out[76]: 35.536075000000004
```

```
In [77]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[77]: 3.1373306936800707
```

```
In [78]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor12 = cor(a[posAi],aHat1[posAi])[1,1]
         reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12 ) # with epsilon
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
         JCA11 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.863
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.035
```

```
Out[78]: 0.8634995882339408
```

```
In [79]: TBV = a[posAi]
         mean(TBV)
```

```
Out[79]: 35.90222
```

```
In [80]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[80]: 3.4374800650784136
```

```
In [81]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor13 = cor(a[posAi],aHat1[posAi])[1,1]
         reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13 ) # with epsilon
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
         JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.904
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.063
```

```
Out[81]: 0.9036375348993642
```

```
In [82]: writedlm("Correlation.G5.G.J.txt",cor13)
```

```
In [83]: writedlm("Regression.G5.G.J.txt",reg13)
```

```
In [84]: TBVG5Gall = a[posAi]
         TBVG5G=mean(TBVG5Gall)
```

```
Out[84]: 35.44119087500001
```

```
In [85]: GEBVG5Gall = aHat1[posAi]
         GEBVG5G=mean(GEBVG5Gall)
```

```
Out[85]: 3.0407142896051362
```

```
In [86]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation =  0.732
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV =  0.952
```

```
Out[86]: 0.7323383127500533
```

```
In [87]: TBV = a[posAi]
mean(TBV)
```

```
Out[87]: 32.60168474358974
```

```
In [88]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[88]: 0.10222227393969532
```

```
In [89]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation =  0.760
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV =  1.002
```

```
Out[89]: 0.7601317290761455
```

```
In [90]: TBV = a[posAi]
mean(TBV)
```

```
Out[90]: 33.25850641025641
```



```
In [91]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[91]: 0.8708850048335544
```

```
In [92]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor15 = cor(a[posAi],aHat1[posAi])[1,1]
         reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15 ) # with epsilon
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
         JCA11 = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation =  0.749
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV =  0.995
```

```
Out[92]: 0.748975460246022
```

```
In [93]: TBV = a[posAi]
         mean(TBV)
```

```
Out[93]: 33.87493525641025
```

```
In [94]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[94]: 1.5169117904365046
```

```
In [95]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor16 = cor(a[posAi],aHat1[posAi])[1,1]
         reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16 ) # with epsilon
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
         JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation =  0.738
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV =  0.991
```

```
Out[95]: 0.7375020868255808
```

```
In [96]: TBV = a[posAi]
         mean(TBV)
```

```
Out[96]: 34.411586410256405
```

```
In [97]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[97]: 2.043551173687437
```

```
In [98]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor17 = cor(a[posAi],aHat1[posAi])[1,1]
         reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17 ) # with epsilon
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
         JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation =  0.744
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV =  0.979
```

```
Out[98]: 0.7439774229107254
```

```
In [99]: TBV = a[posAi]
         mean(TBV)
```

```
Out[99]: 34.962447307692315
```

```
In [100]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[100]: 2.5779429829138647
```

```
In [101]: IDs = readtable("G5.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor18 = cor(a[posAi],aHat1[posAi])[1,1]
reg18 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.noGenotype.ID : correlation = %6.3f\n", cor18 ) # with epsilon
@printf("SSBRJC from Gibbs - G5.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg18)
JCA11 = cor17
```

```
LoadError: BoundsError: attempt to access 0-element Array{UInt8,1}
  at index [1]
while loading In[101], in expression starting on line 1
```

```
[inlined code] from /home/nicole/.julia/v0.4/DataFrames/src/dataframe/io.jl:167
in readnrows! at /home/nicole/.julia/v0.4/DataFrames/src/dataframe/io.jl:222
in readtable! at /home/nicole/.julia/v0.4/DataFrames/src/dataframe/io.jl:774
in readtable at /home/nicole/.julia/v0.4/DataFrames/src/dataframe/io.jl:862
in readtable at /home/nicole/.julia/v0.4/DataFrames/src/dataframe/io.jl:956
```

```
In [102]: TBVG5NGall = a[posAi]
TBVG5NG=mean(TBVG5NGall)
```

```
Out[102]: 34.962447307692315
```

```
In [103]: GEBVG5NGall = aHat1[posAi]
GEBVG5NG=mean(GEBVG5NGall)
```

```
Out[103]: 2.5779429829138647
```

```
In [104]: numSSBayes
```

```
Out[104]: SSBR.NumSSBayes(54904,45904,9000,40000,39000,1000,2000)
```

```
In [105]: J_Vecs.J1
```

```
Out[105]: 45904x1 Array{Float64,2}:  
  -0.00116985  
  -0.88772  
  -0.536844  
  -0.50481  
  -0.751759  
  -0.752193  
  -0.768557  
  0.0  
  -0.752053  
  -0.962602  
  -0.504807  
  -0.94389  
  -0.501171  
  ⋮  
  -0.962883  
  1.30003e-19  
  -0.756585  
  -0.813766  
  -0.752058  
  -5.81375e-34  
  -0.962551  
  -0.504388  
  -0.887749  
  -0.885169  
  -0.00233475  
  -0.000585138
```

```
In [106]: sortrows(J_Vecs.J1[end-8000:end,:])
```

```
Out[106]: 8001x1 Array{Float64,2}:
```

```
-0.98694  
-0.984724  
-0.982593  
-0.981394  
-0.981345  
-0.98129  
-0.981255  
-0.981254  
-0.981231  
-0.981149  
-0.980921  
-0.980872  
-0.980843  
:  
5.55842e-17  
5.56158e-17  
5.5617e-17  
5.56899e-17  
5.5768e-17  
5.57895e-17  
5.59006e-17  
5.62308e-17  
5.62995e-17  
5.67726e-17  
6.09002e-17  
7.41359e-17
```

```
In [107]: J1 = sortrows(J_Vecs.J1)
```

```
Out[107]: 45904x1 Array{Float64,2}:  
  -0.989598  
  -0.98694  
  -0.986794  
  -0.985679  
  -0.985611  
  -0.985572  
  -0.985511  
  -0.985379  
  -0.985308  
  -0.985286  
  -0.985255  
  -0.984879  
  -0.984724  
  ⋮  
  6.21143e-17  
  6.29141e-17  
  6.3084e-17  
  6.31154e-17  
  6.59642e-17  
  6.61671e-17  
  7.41359e-17  
  7.82785e-17  
  8.88245e-17  
  9.73674e-17  
  1.10202e-16  
  1.11218e-16
```

```
In [108]: J1[J1 .< 0.0,:]
```

```
Out[108]: 43837x1 Array{Float64,2}:  
  -0.989598  
  -0.98694  
  -0.986794  
  -0.985679  
  -0.985611  
  -0.985572  
  -0.985511  
  -0.985379  
  -0.985308  
  -0.985286  
  -0.985255  
  -0.984879  
  -0.984724  
  ⋮  
  -7.24659e-36  
  -7.23354e-36  
  -7.21667e-36  
  -7.2166e-36  
  -7.21273e-36  
  -7.21238e-36  
  -7.19923e-36  
  -7.07921e-36  
  -7.0126e-66  
  -3.5063e-66  
  -8.6437e-98  
  -4.32185e-98
```

```
In [109]: J1[J1 .> 0.0,:]
```

```
Out[109]: 1322x1 Array{Float64,2}:
```

```
 9.59643e-114
 3.89278e-82
 7.78555e-82
 1.59855e-51
 1.60241e-51
 1.60907e-51
 2.80217e-51
 3.17361e-51
 3.19876e-51
 3.202e-51
 4.7946e-51
 4.9225e-51
 6.51627e-51
 ⋮
 6.21143e-17
 6.29141e-17
 6.3084e-17
 6.31154e-17
 6.59642e-17
 6.61671e-17
 7.41359e-17
 7.82785e-17
 8.88245e-17
 9.73674e-17
 1.10202e-16
 1.11218e-16
```

```
In [110]: G = convert(Array,readtable("GenNF.txt", separator = ' ',header=false));
```

```
In [111]: GAll=mean(G[:,2:end],1)
```

```
Out[111]: 1x2000 Array{Float64,2}:
```

```
 0.142111  1.57078  0.644444  1.93133  ...  0.760778  0.988778  0.739778
```

```
In [112]: GG0=mean(G[1:200,2:end],1)
```

```
Out[112]: 1x2000 Array{Float64,2}:
```

```
 0.135  1.63  0.625  1.935  1.685  0.28  ...  1.185  0.555  0.85  0.905  0.64
```



```
In [113]: GG1=mean(G[201:400,2:end],1)
```

```
Out[113]: 1x2000 Array{Float64,2}:  
 0.165  1.645  0.575  1.93  1.71  0.325  ...  1.305  0.565  0.725  0.965  0.7
```

```
In [114]: GG2=mean(G[401:600,2:end],1)
```

```
Out[114]: 1x2000 Array{Float64,2}:  
 0.155  1.595  0.615  1.93  1.72  0.35  ...  1.245  0.5  0.775  0.985  0.72
```

```
In [115]: GG3=mean(G[601:800,2:end],1)
```

```
Out[115]: 1x2000 Array{Float64,2}:  
 0.12  1.535  0.715  1.91  1.68  0.425  ...  1.29  0.605  0.72  0.995  0.765
```

```
In [116]: GG4=mean(G[801:1000,2:end],1)
```

```
Out[116]: 1x2000 Array{Float64,2}:  
 0.145  1.54  0.645  1.945  1.76  0.435  ...  1.255  0.535  0.765  1.01  0.775
```

```
In [117]: GG5=mean(G[1001:9000,2:end],1)
```

```
Out[117]: 1x2000 Array{Float64,2}:  
 0.141875  1.5685  0.645625  1.9315  ...  0.538875  0.76  0.990875  0.74225
```

```
In [118]: writedlm("meanOfSNPGAll",GAll)
```

```
In [119]: writedlm("meanOfSNPGG0",GG0)
```

```
In [120]: writedlm("meanOfSNPGG1",GG1)
```

```
In [121]: writedlm("meanOfSNPGG2",GG2)
```

```
In [122]: writedlm("meanOfSNPGG3",GG3)
```

```
In [123]: writedlm("meanOfSNPGG4",GG4)
```

```
In [124]: writedlm("meanOfSNPGG5",GG5)
```

