

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,size(IDs,1)}
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5a0/M/8

/home/nicole/Jupyter/JG3/Data/0.5a0/M/8
```

```
In [4]: ;ls

G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
MarNF.txt
MarNFCenter.txt
PedAll.txt
Phe.txt
PheAll.txt
all.ID
genotype.ID
noGenotype.ID
sim.bv
sim.phenotype
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' MarNFCenter.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G5.noGenotype.ID
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreedingCoefficients,nothing)
df = read_genotypes("MarNFCenter.txt",numSSBayes) # genotype file - centered
M_Mats = make_MMats(df,A_Mats,ped); # M file centered already
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes) # with W_Mats
nothing
```

```
In [31]: vRes = 0.741
vG = 0.741
nIter = 50000
@time aHat1,alphaHat,betaHat,epsiHat =
ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,nothing)

This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
2400.620501 seconds (23.03 G allocations: 723.640 GB, 7.72% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
 2.56546
-2.84517
```

```
In [33]: alphaHat
```

```
Out[33]: 150-element Array{Float64,1}:  
  0.0206446  
 -0.0576277  
  0.00956102  
  0.026468  
  0.267723  
 -0.0698461  
  0.0567077  
  0.0197038  
 -0.00822948  
  0.00806435  
 -0.174697  
  0.00224031  
  0.0251699  
  ⋮  
 -0.0578916  
  0.0921704  
  0.047118  
  0.0919291  
 -0.00420788  
  0.0347679  
  0.0564126  
  0.0423154  
  0.0553967  
  0.00403897  
  0.0672013  
 -0.0385823
```

```
In [34]: writedlm("alphaEstimatesLeggaraJC",alphaHat)
```

```
In [35]: epsiHat
```

```
Out[35]: 45922-element Array{Float64,1}:
 0.262724
-0.3267
 0.396397
-0.175396
-0.466188
 0.210406
-0.528345
 0.449072
 0.112549
-0.180749
-0.868534
 0.180405
-0.00739324
  ⋮
-0.0370565
-0.141164
-0.0933464
-0.910881
-0.28559
-0.304869
-0.538472
-0.0510051
 0.339869
 0.185026
 0.390784
 0.822403
```

```
In [36]: writedlm("epsiEstimatesLeggaraJC",epsiHat)
```

```
In [37]: using DataFrames
```

```
In [38]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=:a
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [39]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.910
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.980
```

```
Out[39]: 0.9100666221329701
```

```
In [40]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[40]: 1.6274671990268925
```

```
In [41]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor2 = cor(a[posAi],aHat1[posAi])[1,1]
         reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
         @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3:
         JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.882
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.000
```

```
Out[41]: 0.8824703362197117
```

```
In [42]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[42]: 2.8451692881936417
```

```
In [43]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',head
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat1[posAi])[1,1]
         reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.880
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.966
```

```
Out[43]: 0.87998196685487
```

```
In [44]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[44]: 1.3464590246037964
```

```
In [45]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat1[posAi])[1,1]
         reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
         @printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.712
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.875
```

```
Out[45]: 0.7118666694047132
```

```
In [46]: GEBV = aHat1[posAi]
         G1GEBV=mean(GEBV)
```

```
Out[46]: 0.13282630805043072
```

```
In [47]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat1[posAi])[1,1]
         reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
         @printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.771
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.991
```

```
Out[47]: 0.7710547409581873
```

```
In [48]: GEBV = aHat1[posAi]
         G1GEBV=mean(GEBV)
```

```
Out[48]: 0.85175270684589
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor5 = cor(a[posAi],aHat1[posAi])[1,1]
         reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
         @printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.776
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.031
```

```
Out[49]: 0.7764691679123311
```

```
In [50]: GEBV = aHat1[posAi]
         G2GEBV=mean(GEBV)
```

```
Out[50]: 1.441666520117917
```

```
In [51]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
         posAi = getPos(ped,IDs)
         cor6 = cor(a[posAi],aHat1[posAi])[1,1]
         reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
         @printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
         JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.753
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.003
```

```
Out[51]: 0.7530756185474616
```

```
In [52]: GEBV = aHat1[posAi]
        G3GEBV=mean(GEBV)
```

```
Out[52]: 1.9861795435333038
```

```
In [53]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
        posAi = getPos(ped,IDs)
        cor7 = cor(a[posAi],aHat1[posAi])[1,1]
        reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
        @printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
        JCall = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.755
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 0.992
```

```
Out[53]: 0.7549052445447134
```

```
In [54]: GEBV = aHat1[posAi]
        G4GEBV=mean(GEBV)
```

```
Out[54]: 2.463111340360666
```

```
In [55]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
        posAi = getPos(ped,IDs)
        cor8 = cor(a[posAi],aHat1[posAi])[1,1]
        reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
        @printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
        @printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
        JCall = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.866
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 0.974
```

```
Out[55]: 0.8662274519484835
```

```
In [56]: GEBV = aHat1[posAi]
        G5GEBV=mean(GEBV)
```

```
Out[56]: 2.889266775253148
```

```
In [57]: GEBVG5G1=G5GEBV-G1GEBV
```

```
Out[57]: 2.037514068407258
```

```
In [58]: GEBVG1G5=[G1GEBV;G2GEBV;G3GEBV;G4GEBV;G5GEBV]
```

```
Out[58]: 5-element Array{Float64,1}:
         0.851753
         1.44167
         1.98618
         2.46311
         2.88927
```



```
In [59]: reg8 = linreg(aHat1[posAi], a[posAi])
```

```
Out[59]: 2-element Array{Float64,1}:
 2.66779
 0.974316
```

```
In [60]: VarGEBV=var(aHat1[posAi])
```

```
Out[60]: 0.3910569797406603
```

```
In [61]: VarTBV=var(a[posAi])
```

```
Out[61]: 0.49473813778245723
```

```
In [62]: Cov=cov(aHat1[posAi], a[posAi])
```

```
Out[62]: 0.3810128815867415
```

```
In [63]: b=Cov/VarGEBV
```

```
Out[63]: 0.9743155123824161
```

```
In [64]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.858
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.026
```

```
Out[64]: 0.8581047994194432
```

```
In [65]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[65]: 1.645306663795712
```

```
In [66]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.891
```

```
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.000
```

```
Out[66]: 0.8909917391380713
```

```
In [67]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[67]: 2.079778983372257
```

```
In [68]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor10 = cor(a[posAi],aHat1[posAi])[1,1]
         reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
         @printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
         JCall = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.851
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.907
```

```
Out[68]: 0.8506454570316262
```

```
In [69]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[69]: 2.5412926785058945
```

```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor11 = cor(a[posAi],aHat1[posAi])[1,1]
         reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
         JCall = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.836
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.859
```

```
Out[70]: 0.8363599847881019
```

```
In [71]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[71]: 2.924466787888294
```

```
In [72]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=1,
         posAi = getPos(ped,IDs)
         cor12 = cor(a[posAi],aHat1[posAi])[1,1]
         reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
         JCall = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.831
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.909
```

```
Out[72]: 0.8311553771026318
```

```
In [73]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[73]: 3.2711018450258114
```

```
In [74]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor13 = cor(a[posAi],aHat1[posAi])[1,1]
         reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
         JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.866
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.974
```

```
Out[74]: 0.8662274519484835
```

```
In [75]: writedlm("Correlation.G5.M.JC*.txt",cor13)
```

```
In [76]: writedlm("Regression.G5.M.JC*.txt",reg13)
```

```
In [77]: TBVG5Gall = a[posAi]
         TBVG5G=mean(TBVG5Gall)
```

```
Out[77]: 5.482843125
```

```
In [78]: GEBVG5Gall = aHat1[posAi]
         GEBVG5G=mean(GEBVG5Gall)
```

```
Out[78]: 2.889266775253148
```

```
In [79]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.693
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.887
```

```
Out[79]: 0.6927076506532129
```

```
In [80]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[80]: 0.09404476046721838
```

```
In [81]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCA11 = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.753
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.995
```

```
Out[81]: 0.7533729730473585
```

```
In [82]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[82]: 0.820264853601624
```

```
In [83]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat1[posAi])[1,1]
reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCA11 = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.762
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.036
```

```
Out[83]: 0.7622662229770367
```

```
In [84]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[84]: 1.4134709775951482
```

```
In [85]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.739
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.002
```

```
Out[85]: 0.7387081211829564
```

```
In [86]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[86]: 1.9621208962421504
```

```
In [87]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.742
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.986
```

```
Out[87]: 0.7419245390194513
```

```
In [88]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[88]: 2.442393635112841
```

```
In [89]: numSSBayes
```

```
Out[89]: SSBR.NumSSBayes(54922,45922,9000,40000,39000,1000,150)
```

```
In [90]: J1 = sortrows(J_Vecs.J1)
```

```
Out[90]: 45922x1 Array{Float64,2}:
-0.986886
-0.98681
-0.986652
-0.986167
-0.985627
-0.985584
-0.985549
-0.985547
-0.98549
-0.98527
-0.985215
-0.984637
-0.984623
⋮
7.0587e-17
7.35847e-17
7.43413e-17
7.45955e-17
8.59149e-17
8.86198e-17
8.88706e-17
8.9519e-17
9.67177e-17
1.07311e-16
1.22139e-16
1.40744e-16
```

```
In [91]: J1[J1 .< 0.0,:]
```

```
Out[91]: 43953x1 Array{Float64,2}:  
  -0.986886  
  -0.98681  
  -0.986652  
  -0.986167  
  -0.985627  
  -0.985584  
  -0.985549  
  -0.985547  
  -0.98549  
  -0.98527  
  -0.985215  
  -0.984637  
  -0.984623  
  ⋮  
  -7.2166e-36  
  -7.2166e-36  
  -7.2092e-36  
  -6.60657e-36  
  -6.60657e-36  
  -2.1823e-51  
  -5.19078e-65  
  -2.70994e-65  
  -2.58495e-65  
  -1.29248e-65  
  -1.62865e-67  
  -1.62865e-67
```

```
In [92]: J1[J1 .> 0.0,:]
```

```
Out[92]: 1271x1 Array{Float64,2}:  
 2.86987e-81  
 7.33477e-52  
 7.33477e-52  
 1.46695e-51  
 1.60076e-51  
 1.60241e-51  
 1.60241e-51  
 2.1823e-51  
 2.1823e-51  
 2.3838e-51  
 3.20013e-51  
 3.20294e-51  
 3.20397e-51  
 ⋮  
 7.0587e-17  
 7.35847e-17  
 7.43413e-17  
 7.45955e-17  
 8.59149e-17  
 8.86198e-17  
 8.88706e-17  
 8.9519e-17  
 9.67177e-17  
 1.07311e-16  
 1.22139e-16  
 1.40744e-16
```