

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,size(IDs,1)}  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5g2k/G/4  
  
/home/nicole/Jupyter/JG3/Data/0.5g2k/G/4
```

```
In [4]: ;ls  
  
GenNF.txt  
PedAll.txt  
Phe.txt  
PheAll.txt
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID

In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID

In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID

In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID

In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype
        200  200 1200 G0.Genotype.ID
        200  200 1200 G1.Genotype.ID
        200  200 1200 G2.Genotype.ID
        200  200 1200 G3.Genotype.ID
        200  200 1200 G4.Genotype.ID
        8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G
        7800  7800 46800 G0.noGenotype.ID
        7800  7800 46800 G1.noGenotype.ID
        7800  7800 46800 G2.noGenotype.ID
        7800  7800 46800 G3.noGenotype.ID
        7800  7800 46800 G4.noGenotype.ID
        0  0  0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding=false)
        nothing
        y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
        Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
        nothing
```

```
In [31]: vG      = 0.738
        vRes     = 0.738
        aHat3=SSBR.PBLUP(y_Vecs,Z_Mats,A_Mats,numSSBayes,vRes,vG);
```

```
In [32]: using DataFrames
```

```
In [33]: df = readtable("sim.bv", eltypes =[UTF8String, Float64], separator = ' ',header=false)
        a  = Array{Float64,numSSBayes.num_ped}
        for (i,ID) in enumerate(df[:,1])
            j = ped.idMap[ID].seqID
            a[j] = df[i,2]
        end
```

```
In [34]: IDs = readtable("all.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat3[posAi])[1,1]
reg1 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with epsilon
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n", reg1)
JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.890
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.986
```

```
Out[34]: 0.8901631361656762
```

```
In [35]: TBV = a[posAi]
mean(TBV)
```

```
Out[35]: 32.00853329166667
```

```
In [36]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[36]: 1.4232814631771737
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat3[posAi])[1,1]
reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # with epsilon
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.570
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 0.999
```

```
Out[37]: 0.5702145518066815
```

```
In [38]: TBV = a[posAi]
mean(TBV)
```

```
Out[38]: 33.31851788888889
```

```
In [39]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[39]: 2.744951909303156
```

```
In [40]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat3[posAi])[1,1]
         reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) # with epsilon
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.876
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.983
```

```
Out[40]: 0.8764725572294929
```

```
In [41]: TBV = a[posAi]
         mean(TBV)
```

```
Out[41]: 31.706229153846152
```

```
In [42]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[42]: 1.1182805909942548
```

```
In [43]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat3[posAi])[1,1]
         reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with epsilon
         @printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
         JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.708
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.904
```

```
Out[43]: 0.7077652724516275
```

```
In [44]: TBV = a[posAi]
         mean(TBV)
```

```
Out[44]: 30.604240875000002
```

```
In [45]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[45]: 0.00014656797454552084
```

```
In [46]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor4 = cor(a[posAi],aHat3[posAi])[1,1]
         reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with epsilon
         @printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", reg4)
         JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation =  0.772
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV =  0.984
```

```
Out[46]: 0.7724014481257852
```

```
In [47]: TBV = a[posAi]
         mean(TBV)
```

```
Out[47]: 31.180672250000004
```

```
In [48]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[48]: 0.6005205666784162
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", reg5)
JCall = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.772
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 0.999
```

```
Out[49]: 0.7722545404319267
```

```
In [50]: TBV = a[posAi]
mean(TBV)
```

```
Out[50]: 31.753910875000003
```

```
In [51]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[51]: 1.1623539860197225
```

```
In [52]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with epsilon
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", reg6)
JCall = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.767
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.001
```

```
Out[52]: 0.7665008991405596
```

```
In [53]: TBV = a[posAi]
mean(TBV)
```

```
Out[53]: 32.31113225
```

```
In [54]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[54]: 1.728395541593784
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor7 = cor(a[posAi],aHat3[posAi])[1,1]
         reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with epsilon
         @printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", reg7)
         JCall = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation =  0.737
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV =  0.985
```

```
Out[55]: 0.7372428380613955
```

```
In [56]: TBV = a[posAi]
         mean(TBV)
```

```
Out[56]: 32.82390337499999
```

```
In [57]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[57]: 2.2450995971390246
```

```
In [58]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor8 = cor(a[posAi],aHat3[posAi])[1,1]
         reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with epsilon
         @printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", reg8)
         JCall = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation =  0.420
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV =  0.986
```

```
Out[58]: 0.41952687727108323
```



```
In [59]: TBV = a[posAi]
         mean(TBV)
```

```
Out[59]: 33.37734012499999
```

```
In [60]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[60]: 2.80317251965755
```

```
In [61]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor9 = cor(a[posAi],aHat3[posAi])[1,1]
         reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
         @printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
         JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation =  0.886
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV =  0.997
```

```
Out[61]: 0.8858950290283529
```

```
In [62]: TBV = a[posAi]
         mean(TBV)
```

```
Out[62]: 31.773559999999996
```

```
In [63]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[63]: 1.229977523148885
```

```
In [64]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.905
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.048
```

```
Out[64]: 0.9052070537150592
```

```
In [65]: TBV = a[posAi]
mean(TBV)
```

```
Out[65]: 32.321934999999996
```

```
In [66]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[66]: 1.7295522395502037
```

```
In [67]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 ) # with epsilon
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.896
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.022
```

```
Out[67]: 0.8964658348163387
```

```
In [68]: TBV = a[posAi]
mean(TBV)
```

```
Out[68]: 32.875784999999999
```

```
In [69]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[69]: 2.301126759260797
```

```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor11 = cor(a[posAi],aHat3[posAi])[1,1]
         reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11 ) # with epsilon
         @printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
         JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.887
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.054
```

```
Out[70]: 0.8874762341079098
```

```
In [71]: TBV = a[posAi]
         mean(TBV)
```

```
Out[71]: 33.35545
```

```
In [72]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[72]: 2.77570688046458
```

```
In [73]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor12 = cor(a[posAi],aHat3[posAi])[1,1]
         reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12 ) # with epsilon
         @printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
         JCA11 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.460
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.011
```

```
Out[73]: 0.45969595764157967
```

```
In [74]: TBV = a[posAi]
         mean(TBV)
```

```
Out[74]: 33.91297
```

```
In [75]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[75]: 3.3595717299155443
```

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor13 = cor(a[posAi],aHat3[posAi])[1,1]
         reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13 ) # with epsilon
         @printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
         JCA11 = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.420
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.986
```

```
Out[76]: 0.41952687727108323
```

```
In [77]: writedlm("Correlation.G5.G.PBLUP.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.G.PBLUP.txt",reg13)
```

```
In [79]: TBV = a[posAi]
         mean(TBV)
```

```
Out[79]: 33.37734012499999
```

```
In [80]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[80]: 2.80317251965755
```

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation =  0.687
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV =  0.897
```

```
Out[81]: 0.6865122415123651
```

```
In [82]: TBV = a[posAi]
mean(TBV)
```

```
Out[82]: 30.57425833333334
```

```
In [83]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[83]: -0.03138755908120677
```

```
In [84]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14 ) # with epsilon
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation =  0.755
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV =  0.979
```

```
Out[84]: 0.7550150260932633
```

```
In [85]: TBV = a[posAi]
mean(TBV)
```

```
Out[85]: 31.151409102564106
```

```
In [86]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[86]: 0.5715710366047807
```

```
In [87]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor15 = cor(a[posAi],aHat3[posAi])[1,1]
         reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15 ) # with epsilon
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
         JCA11 = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation =  0.756
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV =  1.000
```

```
Out[87]: 0.7557945194214912
```

```
In [88]: TBV = a[posAi]
         mean(TBV)
```

```
Out[88]: 31.72514487179487
```

```
In [89]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[89]: 1.1331546841417464
```

```
In [90]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor16 = cor(a[posAi],aHat3[posAi])[1,1]
         reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16 ) # with epsilon
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
         JCA11 = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation =  0.751
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV =  1.000
```

```
Out[90]: 0.7511795040091406
```

```
In [91]: TBV = a[posAi]
         mean(TBV)
```

```
Out[91]: 32.284354871794875
```

```
In [92]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[92]: 1.7015414046996609
```

```
In [93]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor17 = cor(a[posAi],aHat3[posAi])[1,1]
         reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17 ) # with epsilon
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
         JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation =  0.724
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV =  0.986
```

```
Out[93]: 0.7242560189341465
```

```
In [94]: TBV = a[posAi]
         mean(TBV)
```

```
Out[94]: 32.795978589743584
```

```
In [95]: EBV = aHat3[posAi]
         mean(EBV)
```

```
Out[95]: 2.2165233886062934
```

```
In [96]: numSSBayes
```

```
Out[96]: SSBR.NumSSBayes(54925,45925,9000,40000,39000,1000,0)
```