

```
In [1]: include("/home/nicole/Jupyter/SSBRnoJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,size(IDs,1)}  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5a0/G/10  
  
/home/nicole/Jupyter/JG3/Data/0.5a0/G/10
```

```
In [4]: ;ls  
  
GenNF.txt  
PedAll.txt  
Phe.txt  
PheAll.txt
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' GenNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G5.noGenotype.ID
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreedingCoefficients,nothing)
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
nothing
```

```
In [31]: vRes = 0.460
vG = 0.460
aHat3=SSBR.PBLUP(y_Vecs,Z_Mats,A_Mats,numSSBayes,vRes,vG);
```

```
In [32]: using DataFrames
```

```
In [33]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header = false,
a = Array{Float64,1}(zeros(numSSBayes.num_ped))
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [34]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ', header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat3[posAi])[1,1]
reg1 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with a
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.879
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.956
```

```
Out[34]: 0.8788906609984286
```

```
In [35]: TBV = a[posAi]
mean(TBV)
```

```
Out[35]: 4.902233
```

```
In [36]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[36]: 1.0814786072049103
```

```
In [37]: IDs = readtable("genotype.ID", eltypes=[UTF8String], separator = ' ', header=false)
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat3[posAi])[1,1]
reg2 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # with a
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n",
JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.578
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 0.980
```

```
Out[37]: 0.5781369567560061
```

```
In [38]: TBV = a[posAi]
mean(TBV)
```

```
Out[38]: 5.8692245555555544
```

```
In [39]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[39]: 2.0861874190121252
```

```
In [40]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ', header=false)
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat3[posAi])[1,1]
reg3 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.859
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.951
```

```
Out[40]: 0.8591942217190832
```

```
In [41]: TBV = a[posAi]
mean(TBV)
```

```
Out[41]: 4.679081102564102
```

```
In [42]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[42]: 0.8496227275570918
```

```
In [43]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ', header=false)
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.630
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.718
```

```
Out[43]: 0.6303817358607794
```

```
In [44]: TBV = a[posAi]
mean(TBV)
```

```
Out[44]: 3.8552633749999994
```

```
In [45]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[45]: 0.0007310338910262328
```

```
In [46]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat3[posAi])[1,1]
reg4 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation =  0.771
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV =  0.981
```

```
Out[46]: 0.7706967441306454
```

```
In [47]: TBV = a[posAi]
mean(TBV)
```

```
Out[47]: 4.25242625
```

```
In [48]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[48]: 0.448871006447413
```

```
In [49]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat3[posAi])[1,1]
reg5 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation =  0.754
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV =  0.979
```

```
Out[49]: 0.754001934967578
```

```
In [50]: TBV = a[posAi]
mean(TBV)
```

```
Out[50]: 4.7252624999999995
```

```
In [51]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[51]: 0.8922430872118216
```

```
In [52]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat3[posAi])[1,1]
reg6 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation =  0.753
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV =  0.966
```

```
Out[52]: 0.7530647756993468
```

```
In [53]: TBV = a[posAi]
mean(TBV)
```

```
Out[53]: 5.129282125
```

```
In [54]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[54]: 1.2997358973732942
```

```
In [55]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat3[posAi])[1,1]
reg7 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation =  0.717
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV =  0.936
```

```
Out[55]: 0.7167896819300146
```

```
In [56]: TBV = a[posAi]
mean(TBV)
```

```
Out[56]: 5.53919975
```

```
In [57]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[57]: 1.7171630472479702
```

```
In [58]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat3[posAi])[1,1]
reg8 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.424
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 0.970
```

```
Out[58]: 0.4244087182883081
```

```
In [59]: TBV = a[posAi]
mean(TBV)
```

```
Out[59]: 5.911964
```

```
In [60]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[60]: 2.1301275710579386
```

```
In [61]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',hea
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.899
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.033
```

```
Out[61]: 0.8987059133952757
```

```
In [62]: TBV = a[posAi]
mean(TBV)
```

```
Out[62]: 4.654085
```

```
In [63]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[63]: 0.9288950397184135
```

```
In [64]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat3[posAi])[1,1]
reg9 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9)
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.881
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 0.979
```

```
Out[64]: 0.8810485255744543
```

```
In [65]: TBV = a[posAi]
mean(TBV)
```

```
Out[65]: 5.2092899999999999
```

```
In [66]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[66]: 1.3479528480806715
```

```
In [67]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat3[posAi])[1,1]
reg10 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 )
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10)
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.883
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 0.927
```

```
Out[67]: 0.883361179918933
```

```
In [68]: TBV = a[posAi]
mean(TBV)
```

```
Out[68]: 5.5286800000000005
```

```
In [69]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[69]: 1.7125951792007734
```



```
In [70]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat3[posAi])[1,1]
reg11 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11)
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.847
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 0.942
```

```
Out[70]: 0.8466160224999756
```

```
In [71]: TBV = a[posAi]
mean(TBV)
```

```
Out[71]: 5.93413
```

```
In [72]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[72]: 2.135008926910042
```

```
In [73]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat3[posAi])[1,1]
reg12 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCA12 = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.433
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 0.918
```

```
Out[73]: 0.433383716651992
```

```
In [74]: TBV = a[posAi]
mean(TBV)
```

```
Out[74]: 6.31036
```

```
In [75]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[75]: 2.5488790193181945
```

```
In [76]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat3[posAi])[1,1]
reg13 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCA11 = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.424
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 0.970
```

```
Out[76]: 0.4244087182883081
```

```
In [77]: writedlm("Correlation.G5.G.PBLUP.txt",cor13)
```

```
In [78]: writedlm("Regression.G5.G.PBLUP.txt",reg13)
```

```
In [79]: TBV = a[posAi]
mean(TBV)
```

```
Out[79]: 5.911964
```

```
In [80]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[80]: 2.1301275710579386
```

```
In [81]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCA11 = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.608
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.702
```

```
Out[81]: 0.6083981887002229
```

```
In [82]: TBV = a[posAi]
mean(TBV)
```

```
Out[82]: 3.8347807692307687
```

```
In [83]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[83]: -0.02306804318147088
```

```
In [84]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat3[posAi])[1,1]
reg14 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.753
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 0.973
```

```
Out[84]: 0.7531436169585479
```

```
In [85]: TBV = a[posAi]
mean(TBV)
```

```
Out[85]: 4.227891282051282
```

```
In [86]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[86]: 0.4258176258927141
```

```
In [87]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat3[posAi])[1,1]
reg15 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.738
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 0.980
```

```
Out[87]: 0.7384036304994048
```

```
In [88]: TBV = a[posAi]
mean(TBV)
```

```
Out[88]: 4.704662051282051
```

```
In [89]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[89]: 0.8712084181864638
```

```
In [90]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat3[posAi])[1,1]
reg16 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.737
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 0.967
```

```
Out[90]: 0.7373575732307232
```

```
In [91]: TBV = a[posAi]
mean(TBV)
```

```
Out[91]: 5.108644999999999
```

```
In [92]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[92]: 1.2783186402056852
```

```
In [93]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat3[posAi])[1,1]
reg17 = linreg(aHat3[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.704
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 0.937
```

```
Out[93]: 0.7035512873550543
```

```
In [94]: TBV = a[posAi]
mean(TBV)
```

```
Out[94]: 5.519426410256411
```

```
In [95]: EBV = aHat3[posAi]
mean(EBV)
```

```
Out[95]: 1.695836996682067
```

```
In [96]: numSSBayes
```

```
Out[96]: SSBR.NumSSBayes(54929,45929,9000,40000,39000,1000,0)
```