

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")
        using SSBR
```

```
In [2]: function getPos(ped,IDs)
        posAi = Array{Int64,size(IDs,1)}
        for (i,id) = enumerate(IDs[:,1])
            posAi[i] = ped.idMap[id].seqID
        end
        return posAi
    end
```

```
Out[2]: getPos (generic function with 1 method)
```

```
In [3]: ; cd Data/0.5/Q/4

/home/nicole/Jupyter/JG3/Data/0.5/Q/4
```

```
In [4]: ;ls

G0.Genotype.ID
G0.ID
G0.noGenotype.ID
G1.Genotype.ID
G1.ID
G1.noGenotype.ID
G2.Genotype.ID
G2.ID
G2.noGenotype.ID
G3.Genotype.ID
G3.ID
G3.noGenotype.ID
G4.Genotype.ID
G4.ID
G4.noGenotype.ID
G5.Genotype.ID
G5.ID
G5.noGenotype.ID
PedAll.txt
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' QTLNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```

In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID

In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID

In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID

In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID

In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID

In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID

In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID

In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID

In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID

In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID

In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID

In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID

In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID

In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID

In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID

In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID

In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID

In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID

```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreeding
nothing
df      = read_genotypes("QTLNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped);           # with
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes)      # with
nothing
```

```
In [31]: vRes      = 0.759
vG       = 0.759
nIter    = 50000
@time aHat1,alphaHat,betaHat,epsHat =
ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,
nothing

This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
3003.225992 seconds (22.99 G allocations: 722.856 GB, 8.71% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
 8.7904
 7.62365
```

```
In [33]: mu  = betaHat[1]
mug = betaHat[2]
```

```
Out[33]: 7.623654987570991
```

```
In [34]: (mu+mug)/2
```

```
Out[34]: 8.207029637457525
```

```
In [35]: alphaHat
```

```
Out[35]: 50-element Array{Float64,1}:
 0.179923
 0.207336
 0.174899
 0.184984
 0.188785
 0.214839
 0.180673
-0.0308965
 0.0206879
 0.153438
 0.187602
 0.180958
 0.185885
  ⋮
 0.198725
 0.159716
 0.202475
 0.226858
 0.17993
 0.134334
 0.164276
 0.222166
 0.150627
 0.196219
 0.175135
 0.147756
```

```
In [36]: writedlm("alphaEstimates",alphaHat)
```

```
In [37]: using DataFrames
```

```
In [38]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=:ID,
a = Array{Float64,numSSBayes.num_ped}
for (i,ID) in enumerate(df[:,1])
    j = ped.idMap[ID].seqID
    a[j] = df[i,2]
end
```

```
In [39]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
posAi = getPos(ped,IDs)
cor1 = cor(a[posAi],aHat1[posAi])[1,1]
reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
@printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
JCA11 = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.926
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.970
```

```
Out[39]: 0.9256910322135045
```

```
In [40]: TBV = a[posAi]
         mean(TBV)
```

```
Out[40]: 10.471534229166668
```

```
In [41]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[41]: 1.6873801359693517
```

```
In [42]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor2 = cor(a[posAi],aHat1[posAi])[1,1]
         reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
         @printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
         JCall = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.996
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.032
```

```
Out[42]: 0.9961556295787278
```

```
In [43]: TBV = a[posAi]
         mean(TBV)
```

```
Out[43]: 11.824753222222222
```

```
In [44]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[44]: 3.0879369059338266
```

```
In [45]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
         posAi = getPos(ped,IDs)
         cor3 = cor(a[posAi],aHat1[posAi])[1,1]
         reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
         @printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
         JCall = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.887
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.964
```

```
Out[45]: 0.8866407402709765
```

```
In [46]: TBV = a[posAi]
         mean(TBV)
```

```
Out[46]: 10.159252923076924
```

```
In [47]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[47]: 1.364174727516011
```

```
In [48]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.723
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.899
```

```
Out[48]: 0.7234507328820575
```

```
In [49]: TBV = a[posAi]
G0TBV=mean(TBV)
```

```
Out[49]: 9.017859375
```

```
In [50]: GEBV = aHat1[posAi]
G0GEBV=mean(GEBV)
```

```
Out[50]: 0.13351451217866658
```

```
In [51]: IDs = readtable("G1.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", r
JCall = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.782
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.996
```

```
Out[51]: 0.7823990220871658
```

```
In [52]: TBV = a[posAi]
G1TBV=mean(TBV)
```

```
Out[52]: 9.608738375000001
```

```
In [53]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[53]: 0.8214797724423978
```

```
In [54]: IDs = readtable("G2.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.779
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.018
```

```
Out[54]: 0.7793363201998974
```

```
In [55]: TBV = a[posAi]
G2TBV=mean(TBV)
```

```
Out[55]: 10.183037250000002
```

```
In [56]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[56]: 1.415801554149471
```

```
In [57]: IDs = readtable("G3.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.776
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.002
```

```
Out[57]: 0.7760912843090181
```

```
In [58]: TBV = a[posAi]
G3TBV=mean(TBV)
```

```
Out[58]: 10.773109375
```

```
In [59]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[59]: 2.0076778980346863
```

```
In [60]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.783
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.006
```

```
Out[60]: 0.7828999909716903
```

```
In [61]: TBV = a[posAi]
G4TBV=mean(TBV)
```

```
Out[61]: 11.359387625
```

```
In [62]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[62]: 2.597792109332562
```

```
In [63]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.996
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.031
```

```
Out[63]: 0.9955952257215609
```

```
In [64]: TBV = a[posAi]
G5TBV=mean(TBV)
```

```
Out[64]: 11.887073375
```

```
In [65]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[65]: 3.1480149696783237
```



```
In [66]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.994
```

```
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.030
```

```
Out[66]: 0.9940044207792528
```

```
In [67]: TBV = a[posAi]
mean(TBV)
```

```
Out[67]: 10.192884999999997
```

```
In [68]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[68]: 1.5177310613429311
```

```
In [69]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.995
```

```
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.034
```

```
Out[69]: 0.9946815729556977
```

```
In [70]: TBV = a[posAi]
mean(TBV)
```

```
Out[70]: 10.736695
```

```
In [71]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[71]: 2.035960917283843
```

```
In [72]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10)
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.994
```

```
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.022
```

```
Out[72]: 0.9935170401609932
```

```
In [73]: TBV = a[posAi]
mean(TBV)
```

```
Out[73]: 11.359055000000001
```

```
In [74]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[74]: 2.633041091728659
```

```
In [75]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ',head
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat1[posAi])[1,1]
reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11)
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.994
```

```
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.017
```

```
Out[75]: 0.9938154011293729
```

```
In [76]: TBV = a[posAi]
mean(TBV)
```

```
Out[76]: 11.936440000000003
```

```
In [77]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[77]: 3.1988760183569527
```

```
In [78]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat1[posAi])[1,1]
reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCall = cor12
```

SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.992

SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.026

Out[78]: 0.9922142839447748

```
In [79]: TBV = a[posAi]
mean(TBV)
```

Out[79]: 12.405885000000001

```
In [80]: GEBV = aHat1[posAi]
mean(GEBV)
```

Out[80]: 3.650952891176867

```
In [81]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ',head=1)
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat1[posAi])[1,1]
reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCall = cor13
```

SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.996

SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.031

Out[81]: 0.9955952257215609

```
In [82]: writedlm("Correlation.G5.Q.J.txt",cor13)
```

```
In [83]: writedlm("Regression.G5.Q.J.txt",reg13)
```

```
In [84]: TBVG5Gall = a[posAi]
TBVG5G=mean(TBVG5Gall)
```

Out[84]: 11.887073375

```
In [85]: GEBVG5Gall = aHat1[posAi]
GEBVG5G=mean(GEBVG5Gall)
```

Out[85]: 3.1480149696783237

```
In [86]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.702
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.901
```

```
Out[86]: 0.7016164575734057
```

```
In [87]: TBV = a[posAi]
mean(TBV)
```

```
Out[87]: 8.987730512820514
```

```
In [88]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[88]: 0.09802178014881364
```

```
In [89]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.766
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 1.002
```

```
Out[89]: 0.7662937026765665
```

```
In [90]: TBV = a[posAi]
mean(TBV)
```

```
Out[90]: 9.57981641025641
```

```
In [91]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[91]: 0.7903392302669762
```

```
In [92]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor15 = cor(a[posAi],aHat1[posAi])[1,1]
reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
@printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.762
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.024
```

```
Out[92]: 0.7617257814030578
```

```
In [93]: TBV = a[posAi]
mean(TBV)
```

```
Out[93]: 10.15288294871795
```

```
In [94]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[94]: 1.384590283955133
```

```
In [95]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1)
posAi = getPos(ped,IDs)
cor16 = cor(a[posAi],aHat1[posAi])[1,1]
reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
@printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.758
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.004
```

```
Out[95]: 0.7577217410759168
```

```
In [96]: TBV = a[posAi]
mean(TBV)
```

```
Out[96]: 10.743280384615385
```

```
In [97]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[97]: 1.9771343564879615
```

```
In [98]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor17 = cor(a[posAi],aHat1[posAi])[1,1]
reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
@printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.767
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 1.006
```

```
Out[98]: 0.7666839345837871
```

```
In [99]: TBV = a[posAi]
mean(TBV)
```

```
Out[99]: 11.33255435897436
```

```
In [100]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[100]: 2.57078798672117
```

```
In [101]: numSSBayes
```

```
Out[101]: SSBR.NumSSBayes(54918,45918,9000,40000,39000,1000,50)
```

```
In [102]: J_Vecs.J1
```

```
Out[102]: 45918x1 Array{Float64,2}:
 5.59491e-17
 1.29927e-19
 5.56987e-17
-0.915036
-0.503517
-0.501174
-0.00202606
-0.751906
-0.752065
-0.752516
-0.0520833
-0.751902
-0.962573
 ⋮
-0.963436
-0.00114285
-0.756583
-0.768558
-0.757896
-0.00341179
-0.962595
-0.504417
-0.887904
-0.908344
-0.00234055
-0.00117391
```

```
In [103]: sortrows(J_Vecs.J1[end-8000:end,:])
```

```
Out[103]: 8001x1 Array{Float64,2}:  
  -0.985615  
  -0.982923  
  -0.981929  
  -0.981296  
  -0.981265  
  -0.98125  
  -0.98117  
  -0.98088  
  -0.980879  
  -0.980847  
  -0.9808  
  -0.980416  
  -0.979674  
  ⋮  
  5.55203e-17  
  5.55383e-17  
  5.57304e-17  
  5.57872e-17  
  5.58089e-17  
  5.59567e-17  
  5.70906e-17  
  5.84657e-17  
  6.26384e-17  
  7.96052e-17  
  8.88017e-17  
  1.00706e-16
```

```
In [104]: J1 = sortrows(J_Vecs.J1)
```

```
Out[104]: 45918x1 Array{Float64,2}:  
  -1.00018  
  -0.989621  
  -0.988966  
  -0.988656  
  -0.986208  
  -0.985971  
  -0.985931  
  -0.985615  
  -0.985572  
  -0.985545  
  -0.985116  
  -0.985082  
  -0.984151  
  ⋮  
   8.08e-17  
   8.40541e-17  
   8.56774e-17  
   8.88017e-17  
   9.25384e-17  
   1.00706e-16  
   1.11122e-16  
   1.11366e-16  
   1.11879e-16  
   1.44033e-16  
   1.49661e-16  
   1.682e-16
```



```
In [105]: J1[J1 .< 0.0,:]
```

```
Out[105]: 43970x1 Array{Float64,2}:  
  -1.00018  
  -0.989621  
  -0.988966  
  -0.988656  
  -0.986208  
  -0.985971  
  -0.985931  
  -0.985615  
  -0.985572  
  -0.985545  
  -0.985116  
  -0.985082  
  -0.984151  
  ⋮  
  -1.08419e-35  
  -7.22966e-36  
  -7.22085e-36  
  -7.22085e-36  
  -7.20816e-36  
  -7.20815e-36  
  -7.0501e-36  
  -8.72921e-51  
  -3.55174e-67  
  -1.78225e-67  
  -1.77587e-67  
  -8.91125e-68
```

```
In [106]: J1[J1 .> 0.0,:]
```

```
Out[106]: 1281x1 Array{Float64,2}:
 1.97869e-83
 8.02654e-52
 1.59956e-51
 1.60053e-51
 1.60531e-51
 2.1823e-51
 2.56016e-51
 2.74883e-51
 3.19912e-51
 4.8006e-51
 4.80207e-51
 5.46964e-51
 2.23532e-50
 ⋮
 8.08e-17
 8.40541e-17
 8.56774e-17
 8.88017e-17
 9.25384e-17
 1.00706e-16
 1.11122e-16
 1.11366e-16
 1.11879e-16
 1.44033e-16
 1.49661e-16
 1.682e-16
```

```
In [107]: G = convert(Array,readtable("QTLNF.txt", separator = ' ',header=false));
```

```
In [108]: GAll=mean(G[:,2:end],1)
```

```
Out[108]: 1x50 Array{Float64,2}:
 1.62422  1.05233  1.10722  1.56489  ...  1.71067  1.61933  1.78289  0.2644
 44
```

```
In [109]: GG0=mean(G[1:200,2:end],1)
```

```
Out[109]: 1x50 Array{Float64,2}:
 1.64  0.82  1.005  1.435  1.31  0.845  ...  0.615  1.37  1.315  1.58  0.43
 5
```

```
In [110]: GG1=mean(G[201:400,2:end],1)
```

```
Out[110]: 1x50 Array{Float64,2}:
 1.615  0.845  1.01  1.49  1.355  0.895  ...  0.72  1.53  1.47  1.625  0.37
```

```
In [111]: GG2=mean(G[401:600,2:end],1)
```

```
Out[111]: 1x50 Array{Float64,2}:
 1.65  0.945  1.065  1.56  1.405  0.915  ...  0.835  1.705  1.575  1.725
 0.29
```

```
In [112]: GG3=mean(G[601:800,2:end],1)
```

```
Out[112]: 1x50 Array{Float64,2}:  
 1.61  1.07  1.08  1.595  1.46  0.99  1.2  ...  0.895  1.715  1.63  1.8  0.  
24
```

```
In [113]: GG4=mean(G[801:1000,2:end],1)
```

```
Out[113]: 1x50 Array{Float64,2}:  
 1.62  1.16  1.15  1.61  1.465  1.02  ...  1.05  1.805  1.69  1.855  0.235
```

```
In [114]: GG5=mean(G[1001:9000,2:end],1)
```

```
Out[114]: 1x50 Array{Float64,2}:  
 1.62387  1.06288  1.11288  1.56825  ...  1.72138  1.62975  1.79113  0.2582  
5
```

```
In [115]: writedlm("meanOfSNPQAll",GAll)
```

```
In [116]: writedlm("meanOfSNPQG0",GG0)
```

```
In [117]: writedlm("meanOfSNPQG1",GG1)
```

```
In [118]: writedlm("meanOfSNPQG2",GG2)
```

```
In [119]: writedlm("meanOfSNPQG3",GG3)
```

```
In [120]: writedlm("meanOfSNPQG4",GG4)
```

```
In [121]: writedlm("meanOfSNPQG5",GG5)
```