

```
In [1]: include("/home/nicole/Jupyter/SSBRJ/src/SSBR.jl")  
using SSBR
```

```
In [2]: function getPos(ped,IDs)  
        posAi = Array{Int64,size(IDs,1)}  
        for (i,id) = enumerate(IDs[:,1])  
            posAi[i] = ped.idMap[id].seqID  
        end  
        return posAi  
end
```

Out[2]: getPos (generic function with 1 method)

```
In [3]: ; cd Data/0.5/Q/4  
  
/home/nicole/Jupyter/JG3/Data/0.5/Q/4
```

```
In [4]: ;ls  
  
PedAll.txt  
Phe.txt  
PheAll.txt  
QTLNF.txt
```

```
In [5]: ;awk '{print $1}' PedAll.txt | sort -b > all.ID
```

```
In [6]: ;awk '{print $1}' QTLNF.txt | sort -b > genotype.ID
```

```
In [7]: ;join -v1 all.ID genotype.ID > noGenotype.ID
```

```
In [8]: ;awk '{print $1,$2}' Phe.txt > sim.phenotype
```

```
In [9]: ;awk '{print $1,$3}' PheAll.txt > sim.bv
```

```
In [10]: ; awk 'NR >=1 && NR <=8000 {print $1}' PedAll.txt | sort -b > G0.ID
```

```
In [11]: ; awk 'NR >=8001 && NR <=16000 {print $1}' PedAll.txt | sort -b > G1.ID
```

```
In [12]: ; awk 'NR >=16001 && NR <=24000 {print $1}' PedAll.txt | sort -b > G2.ID
```

```
In [13]: ; awk 'NR >=24001 && NR <=32000 {print $1}' PedAll.txt | sort -b > G3.ID
```

```
In [14]: ; awk 'NR >=32001 && NR <=40000 {print $1}' PedAll.txt | sort -b > G4.ID
```

```
In [15]: ; awk 'NR >=40001 && NR <=48000 {print $1}' PedAll.txt | sort -b > G5.ID
```

```
In [16]: ;join G0.ID genotype.ID > G0.Genotype.ID
```

```
In [17]: ;join G1.ID genotype.ID > G1.Genotype.ID
```

```
In [18]: ;join G2.ID genotype.ID > G2.Genotype.ID
```

```
In [19]: ;join G3.ID genotype.ID > G3.Genotype.ID
```

```
In [20]: ;join G4.ID genotype.ID > G4.Genotype.ID
```

```
In [21]: ;join G5.ID genotype.ID > G5.Genotype.ID
```

```
In [22]: ;join -v1 G0.ID genotype.ID > G0.noGenotype.ID
```

```
In [23]: ;join -v1 G1.ID genotype.ID > G1.noGenotype.ID
```

```
In [24]: ;join -v1 G2.ID genotype.ID > G2.noGenotype.ID
```

```
In [25]: ;join -v1 G3.ID genotype.ID > G3.noGenotype.ID
```

```
In [26]: ;join -v1 G4.ID genotype.ID > G4.noGenotype.ID
```

```
In [27]: ;join -v1 G5.ID genotype.ID > G5.noGenotype.ID
```

```
In [28]: ;wc G0.Genotype.ID;wc G1.Genotype.ID;wc G2.Genotype.ID;wc G3.Genotype.ID;wc G4.Genotype.ID;wc G5.Genotype.ID
200 200 1200 G0.Genotype.ID
200 200 1200 G1.Genotype.ID
200 200 1200 G2.Genotype.ID
200 200 1200 G3.Genotype.ID
200 200 1200 G4.Genotype.ID
8000 8000 48000 G5.Genotype.ID
```

```
In [29]: ;wc G0.noGenotype.ID;wc G1.noGenotype.ID;wc G2.noGenotype.ID;wc G3.noGenotype.ID;wc G4.noGenotype.ID;wc G5.noGenotype.ID
7800 7800 46800 G0.noGenotype.ID
7800 7800 46800 G1.noGenotype.ID
7800 7800 46800 G2.noGenotype.ID
7800 7800 46800 G3.noGenotype.ID
7800 7800 46800 G4.noGenotype.ID
0 0 0 G5.noGenotype.ID
```

```
In [30]: ped,A_Mats,numSSBayes = calc_Ai("PedAll.txt","genotype.ID",calculateInbreedingCoefficients)
nothing
df      = read_genotypes("QTLNF.txt",numSSBayes)
M_Mats = make_MMats(df,A_Mats,ped,center=true); # with centering
y_Vecs = make_yVecs("sim.phenotype",ped,numSSBayes)
J_Vecs = make_JVecs(numSSBayes,A_Mats)
Z_Mats = make_ZMats(ped,y_Vecs,numSSBayes)
X_Mats, W_Mats = make_XWMats(J_Vecs,Z_Mats,M_Mats,numSSBayes) # with W_Mats
nothing
```

```
In [31]: vRes    = 0.759
         vG      = 0.759
         nIter   = 50000
         @time aHat1,alphaHat,betaHat,epsiHat =
         ssGibbs(M_Mats,y_Vecs,J_Vecs,Z_Mats,X_Mats,W_Mats,A_Mats, numSSBayes,vRes,vG,
         nothing
```

```
This is iteration 5000
This is iteration 10000
This is iteration 15000
This is iteration 20000
This is iteration 25000
This is iteration 30000
This is iteration 35000
This is iteration 40000
This is iteration 45000
This is iteration 50000
2671.717662 seconds (22.99 G allocations: 722.855 GB, 9.23% gc time)
```

```
In [32]: betaHat
```

```
Out[32]: 2-element Array{Float64,1}:
         14.996
          7.51387
```

```
In [33]: using DataFrames
```

```
In [34]: df = readtable("sim.bv", eltypes=[UTF8String, Float64], separator = ' ', header=1,
         a = Array{Float64,numSSBayes.num_ped}
         for (i,ID) in enumerate(df[:,1])
             j = ped.idMap[ID].seqID
             a[j] = df[i,2]
         end
```

```
In [35]: IDs = readtable("all.ID", eltypes=[UTF8String], separator = ' ',header=false)
         posAi = getPos(ped,IDs)
         cor1 = cor(a[posAi],aHat1[posAi])[1,1]
         reg1 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - all.ID : correlation = %6.3f\n", cor1 ) # with correlation
         @printf("SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = %6.3f\n",
         JCall = cor1
```

```
SSBRJC from Gibbs - all.ID : correlation = 0.926
SSBRJC from Gibbs - all.ID : regression of TBV on GEBV = 0.970
```

```
Out[35]: 0.9256727117727994
```

```
In [36]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[36]: -4.518544079453201
```

```
In [37]: IDs = readtable("genotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor2 = cor(a[posAi],aHat1[posAi])[1,1]
reg2 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - genotype.ID : correlation = %6.3f\n", cor2 ) # 1
@printf("SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = %6.3f\n", reg2)
JCA11 = cor2
```

```
SSBRJC from Gibbs - genotype.ID : correlation = 0.996
SSBRJC from Gibbs - genotype.ID : regression of TBV on GEBV = 1.033
```

```
Out[37]: 0.9960884120472578
```

```
In [38]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[38]: -3.118868934127046
```

```
In [39]: IDs = readtable("noGenotype.ID", eltypes =[UTF8String], separator = ' ',header=
posAi = getPos(ped,IDs)
cor3 = cor(a[posAi],aHat1[posAi])[1,1]
reg3 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - noGenotype.ID : correlation = %6.3f\n", cor3 ) ;
@printf("SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg3)
JCA11 = cor3
```

```
SSBRJC from Gibbs - noGenotype.ID : correlation = 0.887
SSBRJC from Gibbs - noGenotype.ID : regression of TBV on GEBV = 0.964
```

```
Out[39]: 0.8866300414041278
```

```
In [40]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[40]: -4.841546036066929
```

```
In [41]: IDs = readtable("G0.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = %6.3f\n", reg4)
JCA11 = cor4
```

```
SSBRJC from Gibbs - G0.ID : correlation = 0.723
SSBRJC from Gibbs - G0.ID : regression of TBV on GEBV = 0.899
```

```
Out[41]: 0.7234256823024054
```

```
In [42]: GEBV = aHat1[posAi]
G0GEBV=mean(GEBV)
```

```
Out[42]: -6.072378268332861
```

```
In [43]: IDs = readtable("G1.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor4 = cor(a[posAi],aHat1[posAi])[1,1]
reg4 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.ID : correlation = %6.3f\n", cor4 ) # with e
@printf("SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor4
```

```
SSBRJC from Gibbs - G1.ID : correlation = 0.782
SSBRJC from Gibbs - G1.ID : regression of TBV on GEBV = 0.996
```

```
Out[43]: 0.7823972869802017
```

```
In [44]: GEBV = aHat1[posAi]
G1GEBV=mean(GEBV)
```

```
Out[44]: -5.384016006428472
```

```
In [45]: IDs = readtable("G2.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor5 = cor(a[posAi],aHat1[posAi])[1,1]
reg5 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.ID : correlation = %6.3f\n", cor5 ) # with e
@printf("SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor5
```

```
SSBRJC from Gibbs - G2.ID : correlation = 0.779
SSBRJC from Gibbs - G2.ID : regression of TBV on GEBV = 1.019
```

```
Out[45]: 0.7793579392650087
```

```
In [46]: GEBV = aHat1[posAi]
G2GEBV=mean(GEBV)
```

```
Out[46]: -4.789681044206625
```

```
In [47]: IDs = readtable("G3.ID", eltypes=[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor6 = cor(a[posAi],aHat1[posAi])[1,1]
reg6 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.ID : correlation = %6.3f\n", cor6 ) # with e
@printf("SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = %6.3f\n", re
JCA11 = cor6
```

```
SSBRJC from Gibbs - G3.ID : correlation = 0.776
SSBRJC from Gibbs - G3.ID : regression of TBV on GEBV = 1.002
```

```
Out[47]: 0.7761069213367372
```

```
In [48]: GEBV = aHat1[posAi]
G3GEBV=mean(GEBV)
```

```
Out[48]: -4.198077632222208
```

```
In [49]: IDs = readtable("G4.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor7 = cor(a[posAi],aHat1[posAi])[1,1]
reg7 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.ID : correlation = %6.3f\n", cor7 ) # with e
@printf("SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor7
```

```
SSBRJC from Gibbs - G4.ID : correlation = 0.783
SSBRJC from Gibbs - G4.ID : regression of TBV on GEBV = 1.007
```

```
Out[49]: 0.7828451420597572
```

```
In [50]: GEBV = aHat1[posAi]
G4GEBV=mean(GEBV)
```

```
Out[50]: -3.608241593554165
```

```
In [51]: IDs = readtable("G5.ID", eltypes =[UTF8String], separator = ' ',header=false
posAi = getPos(ped,IDs)
cor8 = cor(a[posAi],aHat1[posAi])[1,1]
reg8 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.ID : correlation = %6.3f\n", cor8 ) # with e
@printf("SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = %6.3f\n", r
JCA11 = cor8
```

```
SSBRJC from Gibbs - G5.ID : correlation = 0.996
SSBRJC from Gibbs - G5.ID : regression of TBV on GEBV = 1.033
```

```
Out[51]: 0.9955144937083548
```

```
In [52]: GEBV = aHat1[posAi]
G5GEBV=mean(GEBV)
```

```
Out[52]: -3.0588699319748764
```

```
In [53]: IDs = readtable("G0.Genotype.ID", eltypes =[UTF8String], separator = ' ',hea
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = %6
JCA11 = cor9
```

```
SSBRJC from Gibbs - G0.Genotype.ID : correlation = 0.994
SSBRJC from Gibbs - G0.Genotype.ID : regression of TBV on GEBV = 1.031
```

```
Out[53]: 0.9939483103997855
```

```
In [54]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[54]: -4.6870632736241085
```

```
In [55]: IDs = readtable("G1.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor9 = cor(a[posAi],aHat1[posAi])[1,1]
reg9 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G1.Genotype.ID : correlation = %6.3f\n", cor9 )
@printf("SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg9 )
JCA11 = cor9
```

```
SSBRJC from Gibbs - G1.Genotype.ID : correlation = 0.995
SSBRJC from Gibbs - G1.Genotype.ID : regression of TBV on GEBV = 1.036
```

```
Out[55]: 0.9946648515146301
```

```
In [56]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[56]: -4.169477100308927
```

```
In [57]: IDs = readtable("G2.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor10 = cor(a[posAi],aHat1[posAi])[1,1]
reg10 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G2.Genotype.ID : correlation = %6.3f\n", cor10 )
@printf("SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg10 )
JCA11 = cor10
```

```
SSBRJC from Gibbs - G2.Genotype.ID : correlation = 0.993
SSBRJC from Gibbs - G2.Genotype.ID : regression of TBV on GEBV = 1.023
```

```
Out[57]: 0.9934377286536419
```

```
In [58]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[58]: -3.5731835848176474
```

```
In [59]: IDs = readtable("G3.Genotype.ID", eltypes =[UTF8String], separator = ' ', head=10)
posAi = getPos(ped,IDs)
cor11 = cor(a[posAi],aHat1[posAi])[1,1]
reg11 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G3.Genotype.ID : correlation = %6.3f\n", cor11 )
@printf("SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg11 )
JCA11 = cor11
```

```
SSBRJC from Gibbs - G3.Genotype.ID : correlation = 0.994
SSBRJC from Gibbs - G3.Genotype.ID : regression of TBV on GEBV = 1.019
```

```
Out[59]: 0.9937471728474684
```

```
In [60]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[60]: -3.0078392766269118
```

```
In [61]: IDs = readtable("G4.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor12 = cor(a[posAi],aHat1[posAi])[1,1]
reg12 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G4.Genotype.ID : correlation = %6.3f\n", cor12)
@printf("SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg12)
JCall = cor12
```

```
SSBRJC from Gibbs - G4.Genotype.ID : correlation = 0.992
```

```
SSBRJC from Gibbs - G4.Genotype.ID : regression of TBV on GEBV = 1.027
```

```
Out[61]: 0.99208031292854
```

```
In [62]: GEBV = aHat1[posAi]
mean(GEBV)
```

```
Out[62]: -2.5567415213444296
```

```
In [63]: IDs = readtable("G5.Genotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor13 = cor(a[posAi],aHat1[posAi])[1,1]
reg13 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G5.Genotype.ID : correlation = %6.3f\n", cor13)
@printf("SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = %6.3f\n", reg13)
JCall = cor13
```

```
SSBRJC from Gibbs - G5.Genotype.ID : correlation = 0.996
```

```
SSBRJC from Gibbs - G5.Genotype.ID : regression of TBV on GEBV = 1.033
```

```
Out[63]: 0.9955144937083548
```

```
In [64]: writedlm("Correlation.G5.Q.JC.txt",cor13)
```

```
In [65]: writedlm("Regression.G5.Q.JC.txt",reg13)
```

```
In [66]: GEBVG5Gall = aHat1[posAi]
GEBVG5G=mean(GEBVG5Gall)
```

```
Out[66]: -3.0588699319748764
```

```
In [67]: IDs = readtable("G0.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
posAi = getPos(ped,IDs)
cor14 = cor(a[posAi],aHat1[posAi])[1,1]
reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : correlation = %6.3f\n", cor14)
@printf("SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
JCall = cor14
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : correlation = 0.702
```

```
SSBRJC from Gibbs - G0.noGenotype.ID : regression of TBV on GEBV = 0.901
```

```
Out[67]: 0.7015977842507288
```



```
In [68]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[68]: -6.1078991656330865
```

```
In [69]: IDs = readtable("G1.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor14 = cor(a[posAi],aHat1[posAi])[1,1]
         reg14 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : correlation = %6.3f\n", cor14)
         @printf("SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg14)
         JCall = cor14
```

```
SSBRJC from Gibbs - G1.noGenotype.ID : correlation = 0.766
SSBRJC from Gibbs - G1.noGenotype.ID : regression of TBV on GEBV = 1.002
```

```
Out[69]: 0.7662944904114929
```

```
In [70]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[70]: -5.415158029662306
```

```
In [71]: IDs = readtable("G2.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor15 = cor(a[posAi],aHat1[posAi])[1,1]
         reg15 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : correlation = %6.3f\n", cor15)
         @printf("SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg15)
         JCall = cor15
```

```
SSBRJC from Gibbs - G2.noGenotype.ID : correlation = 0.762
SSBRJC from Gibbs - G2.noGenotype.ID : regression of TBV on GEBV = 1.024
```

```
Out[71]: 0.7617497706021903
```

```
In [72]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[72]: -4.82087328675506
```

```
In [73]: IDs = readtable("G3.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor16 = cor(a[posAi],aHat1[posAi])[1,1]
         reg16 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : correlation = %6.3f\n", cor16)
         @printf("SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg16)
         JCall = cor16
```

```
SSBRJC from Gibbs - G3.noGenotype.ID : correlation = 0.758
SSBRJC from Gibbs - G3.noGenotype.ID : regression of TBV on GEBV = 1.005
```

```
Out[73]: 0.7577395070504078
```

```
In [74]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[74]: -4.22859656441696
```

```
In [75]: IDs = readtable("G4.noGenotype.ID", eltypes =[UTF8String], separator = ' ', header = 1,
         posAi = getPos(ped,IDs)
         cor17 = cor(a[posAi],aHat1[posAi])[1,1]
         reg17 = linreg(aHat1[posAi], a[posAi])[2,1]
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : correlation = %6.3f\n", cor17)
         @printf("SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = %6.3f\n", reg17)
         JCall = cor17
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : correlation = 0.767
```

```
SSBRJC from Gibbs - G4.noGenotype.ID : regression of TBV on GEBV = 1.007
```

```
Out[75]: 0.766626462076922
```

```
In [76]: GEBV = aHat1[posAi]
         mean(GEBV)
```

```
Out[76]: -3.635203133867235
```

```
In [77]: numSSBayes
```

```
Out[77]: SSBR.NumSSBayes(54918,45918,9000,40000,39000,1000,50)
```

```
In [78]: J1 = sortrows(J_Vecs.J1)
```

```
Out[78]: 45918x1 Array{Float64,2}:
```

```
-1.00018
-0.989621
-0.988966
-0.988656
-0.986208
-0.985971
-0.985931
-0.985615
-0.985572
-0.985545
-0.985116
-0.985082
-0.984151
⋮
8.08e-17
8.40541e-17
8.56774e-17
8.88017e-17
9.25384e-17
1.00706e-16
1.11122e-16
1.11366e-16
1.11879e-16
1.44033e-16
1.49661e-16
1.682e-16
```

```
In [79]: J1[J1 .< 0.0,:]
```

```
Out[79]: 43970x1 Array{Float64,2}:  
  -1.00018  
  -0.989621  
  -0.988966  
  -0.988656  
  -0.986208  
  -0.985971  
  -0.985931  
  -0.985615  
  -0.985572  
  -0.985545  
  -0.985116  
  -0.985082  
  -0.984151  
  ⋮  
  -1.08419e-35  
  -7.22966e-36  
  -7.22085e-36  
  -7.22085e-36  
  -7.20816e-36  
  -7.20815e-36  
  -7.0501e-36  
  -8.72921e-51  
  -3.55174e-67  
  -1.78225e-67  
  -1.77587e-67  
  -8.91125e-68
```

```
In [80]: J1[J1 .> 0.0,:]
```

```
Out[80]: 1281x1 Array{Float64,2}:  
 1.97869e-83  
 8.02654e-52  
 1.59956e-51  
 1.60053e-51  
 1.60531e-51  
 2.1823e-51  
 2.56016e-51  
 2.74883e-51  
 3.19912e-51  
 4.8006e-51  
 4.80207e-51  
 5.46964e-51  
 2.23532e-50  
 ⋮  
 8.08e-17  
 8.40541e-17  
 8.56774e-17  
 8.88017e-17  
 9.25384e-17  
 1.00706e-16  
 1.11122e-16  
 1.11366e-16  
 1.11879e-16  
 1.44033e-16  
 1.49661e-16  
 1.682e-16
```