# **Technical Offer**

Reference: -

Client: Inphase India Air Coil(s), type Harmonic Filter




## **Electrical Characteristics**

Nominal Inductance	189,7	mH
Nominal Impedance	71,5	Ω
Rated Voltage	34,5	kV
Basic Insulation Level (BIL)	200	kVp
Rated Frequency	60	Hz
Tuning Frequency	-	Hz
Rated Current	251.6	A
Rated Short Time Current Thermal	0.5 / 1	kA/s
Mechanical Short Circuit Current	1.27	kAp
Losses per Phase at 75°C / Rated Current	36,1	kW
Q Factor at 75°C / Rated Frequency	117,5	
Rated Power	2263,9	kVAr
Cooling	N.A.	
Insulation Class	F: 155	°C

### Dimensional

Air Coil Height Module	1224,1	mm
Air Coil Diameter	1861,6	mm
Foundation Diameter	1750,0	mm
Weight per Module	2094,0	kg
Total Weight	4476,0	kg



### lote

1 - Air Coil color - Ansi 70 Light Gray.

2 - Orientation design for proposal.


3 - Location of the terminals can be modified to meet the customer's specification.

#### Industry Electrical Testing

Applicable Standard	IEC-60076-6
→ Visual and dimensional.	
ightarrow Measurement of ohmic resistance of the winding.	
→ Reactance measurement.	
→ Measurement of losses at room temperature.	
ightarrow Measurement of inductance and quality factor at tuning frequency.	

#### Magnetic Clearance

Minimum Distance Between Air Coil Axes (DE) 3109 mm
Axial distance from the top / bottom ends to:
→ Small metal parts not formed in closed loops (MC1A) 931 mm
Radial distance from the Air Coil centerline to:
→ Small metal parts not forming closed loops (MC1R) 2048 mm



#### Environmen

ı	Installation	External
ı	Maximum Altitude	1000 manm
	Ambient Temperature	40 °C
	Wind Speed	120 km/h
ı		

## Support information

Not included
16 x TR210
Side-by-side

# **Package Dimensions**

Package Contents 1 x Air Coil
L x W x H (cm): 1861 x 1861 x 1224
Packing Type: Crate
Gross weight (kg): 4692

Date: 22/12/2022