# **Technical Offer**



Client: Inphase India Air Coil(s), type Harmonic Filter




## **Electrical Characteristics**

Nominal Inductance	72,0 mH	
Nominal Impedance	27,1 Ω	
Rated Voltage	34,5 kV	
Basic Insulation Level (BIL)	200 kVp	
Rated Frequency	60 Hz	
Tuning Frequency	- Hz	
Rated Current	200 A	
Rated Short Time Current Thermal	1.3 / 1 kA/s	
Mechanical Short Circuit Current	3.31 kAp	
Losses per Phase at 75°C / Rated Current	12,9 kW	
Q Factor at 75°C / Rated Frequency	77,6	
Rated Power	1085,4 kVAr	
Cooling	N.A.	
Insulation Class	F: 155 °C	

### **Dimensional**

Air Coil Height Module	1204,5	mm
Air Coil Diameter	1437,3	mm
Foundation Diameter	1300,0	mm
Weight per Module	1199,0	kg
Total Weight	1307,0	kg



### Vote

1 - Air Coil color - Ansi 70 Light Gray.

- 2 Orientation design for proposal.
- 3 Location of the terminals can be modified to meet the customer's specification.
- Dimensions in mm

#### Industry Electrical Testing

Applicable Standard IEC-60076-6

→ Visual and dimensional.

→ Measurement of ohmic resistance of the winding.


→ Reactance measurement.

→ Measurement of losses at room temperature.

→ Measurement of inductance and quality factor at tuning frequency.

#### Magnetic Clearance

Minimum Distance Between Air Coil Axes (DE) 2400 mm	
Axial distance from the top / bottom ends to:	
→ Small metal parts not formed in closed loops (MC1A) 719 mm	
Radial distance from the Air Coil centerline to:	
→ Small metal parts not forming closed loops (MC1R) 1581 mm	



#### Environment

ı		
	Installation	External
	Maximum Altitude	1000 manm
	Ambient Temperature	40 °C
	Wind Speed	120 km/h

### Support information

	Insulators	Not included
	Model:	6 x TR210
	Type of Installation	Side-by-side

## **Package Dimensions**

Package Contents 1 x Air Coil
L x W x H (cm): 1437 x 1437 x 1204
Packing Type: Crate
Gross weight (kg): 1348

Date: 22/12/2022