Same Motion, Different Scores: Supplementary Material

Anonymous CVPR submission

Paper ID DRAFT

S1. Native HumanML3D released-output audit

Native loader, repeats and sample counts. This audit uses the public Text2MotionDatasetV2, including sub-caption segments, random caption choice, and native single/double crops to multiples of four. There are 4,648 cached TEST entries and 4,640 after dropping the incomplete 32-item batch. Entry counts include segments and mirrored motions, rather than 4,640 independent recordings. Twenty seeds 1234–1253 control caption/crop draws; independent full real-reference draws use seed plus 100,000. Generation uses seed plus 200,000. MDM's native nominal 1,000 limit emits 1,024 outputs; other methods emit 4,640. Metrics use the same 32-candidate batches in raw/canonical comparisons. Unchanged outputs, captions and reference embeddings are shared between each pair.

Five public methods and inference parity. MDM50 [18] uses 50 native steps, CFG 2.5 and CLIP-B/32. MLD [3] uses DDIM50, CFG 7.5 and CLIP-L/14; MotionLCM-v1 [5] uses one LCM step, CFG 7.5 and Sentence-T5-large. T2M-GPT [21] uses native categorical/EOS sampling, 512 VQ entries, block length 51 and the released net_last decoder. Original T2M [7] uses its recurrent prior and native duration estimator. Native component classes and strict states are retained. Throughput batching grows from 32 to 128 for MLD and GPT; the random draw order can differ, while evaluation batches remain 32. T2M batches share both motion and caption length because its attention does not mask padded caption positions. All valid repetitions remain included; no settings were chosen by TEST scores.

Synthetic native/batched checks give exact decoder/reverse agreement for MLD/LCM, at most 6.5×10^{-5} normalized mean-prior difference for the correct T2M grouping, and 5.7×10^{-4} for GPT convolution decoding. Batched floating-point arithmetic is not claimed bit-identical. Pinned author code, weight hashes, executed source versions and parity fixtures are included with the artifacts.

Metric uncertainty and reader replication. The primary reader is the official MDM-linked T2M evaluator. The official T2M-GPT download contains distinct encoder weights of the same architecture; native normalization arrays are equal. The secondary reader reuses every saved output and independent reference draw. Native mean intervals use $1.96\,\mathrm{std}_0/\sqrt{20}$. Paired gap intervals use t_{19} with ten FID/R1 comparisons per reader; MM-distance is a separate five-comparison family. The two readers' families are reported separately. The repetitions describe generation and native draw variability on this public split, not independent corpora or pretraining uncertainty. No exact published-score reproduction is claimed.

All five primary FID gap intervals exclude zero. Primary raw/canonical mean ordering is T2M-GPT, MLD, MDM, MotionLCM, T2M. Four secondary FID intervals exclude zero; MLD is inconclusive and T2M's gap changes direction. Secondary mean MLD/MotionLCM order differs across encodings by a small amount, but reliable ranking reversal was not established. All secondary R1 gap intervals include zero. This is score sensitivity across official weights, not a claim that canonicalization always improves metrics.

Full native fixed controls and physical verification. Across 20 full reference repetitions, mean real-motion FID is 0.000990 before recoding and 0.000990 after canonicalization. Fixed directional $+0.1/-0.1$ gives 0.06129/0.08336, $+0.35/-0.35$ gives 2.00261/3.63852, and random 0.35 gives 0.02628. The real draws are independent in crop/caption order, explaining the nonzero baseline; these numbers are distinct from the paired-subset FID-zero controls below. Strong directional shifts do not imply natural prevalence at that magnitude.

Independent native conversion checks all 391,680 release raw/canonical pairs; maximum double-precision angle is 3.6×10^{-6} degrees, while the largest native float32 matrix residual is 2.0×10^{-5} for near-degenerate features. Every nonrotation channel is bitwise unchanged. Two native FK pairs per release/repetition give 200 sampled pairs

Table 1. **Two official checkpoints, one evaluator architecture.** All five releases and 20 repetitions are retained. R1 uses native 32-candidate batches. Each reader uses a ten-endpoint FID/R1 interval family; these families are reported separately. GPT weights differ from the MDM-linked weights; the samples and normalization are shared. Intervals describe raw$-C$.

Reader	Release	Raw FID	C FID	FID gap interval	Raw R1	C R1	R1 gap interval
MDM	MDM50	0.4550	0.4504	$[+0.0035, +0.0058]$	0.4115	0.4115	$[-0.0017, +0.0018]$
MDM	MLD	0.4453	0.4491	$[-0.0052, -0.0024]$	0.4118	0.4105	$[+0.0003, +0.0023]$
MDM	MotionLCM-v1	0.5747	0.6062	$[-0.0347, -0.0282]$	0.4374	0.4350	$[+0.0005, +0.0043]$
MDM	T2M-GPT	0.1828	0.1488	$[+0.0325, +0.0354]$	0.4226	0.4240	$[-0.0030, +0.0002]$
MDM	T2M	1.3935	1.3471	$[+0.0441, +0.0486]$	0.3933	0.3930	$[-0.0009, +0.0017]$
GPT	MDM50	0.5129	0.5104	$[+0.0012, +0.0040]$	0.4586	0.4584	$[-0.0015, +0.0019]$
GPT	MLD	0.4206	0.4216	$[-0.0023, +0.0002]$	0.4669	0.4666	$[-0.0012, +0.0017]$
GPT	MotionLCM-v1	0.4195	0.4294	$[-0.0138, -0.0060]$	0.5042	0.5026	$[-0.0004, +0.0035]$
GPT	T2M-GPT	0.1204	0.1115	$[+0.0076, +0.0103]$	0.4909	0.4898	$[-0.0004, +0.0026]$
GPT	T2M	1.0836	1.0917	$[-0.0111, -0.0051]$	0.4547	0.4540	$[-0.0007, +0.0021]$

and maximum position error 9.6×10^{-7}. The complete saved-embedding FID/R1 endpoints are recomputed independently. Real fixed-control geometry receives additional native checks; it is not inferred from embedding equality.

S2. HumanML3D reward-training controls

Own ordinary MDM pilot. We update the existing MDM50 denoiser, without a coefficient head, on the common 2,048-motion TRAIN snapshot. Three seeds 42/123/777 cross MSE-only, raw-reward and canonical-reward arms. Training uses 1,000 steps, batch 16, AdamW 10^{-5}, weight decay 10^{-4} and clipping 1. A uniform native 50-step timestep is drawn; the loss combines normalized coordinate MSE and weight-1 cosine InfoNCE (temperature 0.1) between one denoised prediction and the TRAIN caption, using the frozen standard evaluator. The canonical arm projects only the predicted rotations before reward computation. CLIP remains frozen. All nine final weights are hashed before any pilot TEST generation. Sampling uses one common seed 20261031 and the first fixed 1,024-output native cohort, with the full 4,640-reference draw. This is a controlled denoised-prediction objective; it does not reproduce EasyTune or MotionRFT rollout optimization [16, 17].

Raw-reward mean R1 is 0.35775 raw/0.36393 canonical, below MSE's 0.41048/0.40820. Every raw-reward seed has a negative same-output retrieval gap. Mean FID is 3.320/2.804, versus MSE 0.602/0.602. Both reward arms worsen these sampled metrics. Six-comparison seed-only t_2 intervals are wide: raw-reward R1 gap $[-0.03519, 0.02282]$, FID gap $[-0.06014, 1.09308]$. They do not establish retrieval inflation, nor rule it out for other rewards, durations or rollout methods. All fits and numerical outcomes remain included.

Released reward-trained weights. A separate audit uses author-linked MotionRFT base and released reward-finetuned checkpoints [17], with strict VAE/denoiser loading, Sentence-T5-large, native DDIM50, CFG 7.5 and pure-Gaussian initialization. We execute the native TEST reverse method; reference poses are not generation inputs. Five matched seeds 2101–2105 use native cohorts/reference draws 0–4 from the primary audit. The two official evaluators score 1,024 outputs and 4,640 reference embeddings each. These related checkpoints add a reward-trained comparison, not a sixth independent generator architecture or a 20-repetition leaderboard replication.

Table 2. **Ordinary MDM reward pilot: every fit.** Three training seeds, three arms, one common generation seed, 1,024 outputs and 4,640 real-reference embeddings. No added coefficient layer. The raw-reward arm does not inflate retrieval. This is a denoised-x_0 reward experiment, not a full rollout/RFT reproduction.

Seed	Training arm	Raw FID	C FID	Raw R1	C R1
42	MSE	0.600	0.601	0.4160	0.4141
42	Raw reward	2.914	2.484	0.3525	0.3535
42	Projected reward	2.981	3.143	0.3486	0.3477
123	MSE	0.605	0.604	0.4121	0.4141
123	Raw reward	3.961	3.349	0.3662	0.3740
123	Projected reward	4.040	4.231	0.3623	0.3594
777	MSE	0.602	0.601	0.4033	0.3965
777	Raw reward	3.086	2.579	0.3545	0.3643
777	Projected reward	3.464	3.688	0.3545	0.3564

With the primary reader, R1 rises from 0.43438 to 0.51406 raw and to 0.51426 canonical. With the secondary reader it rises from 0.50449 to 0.58691 raw/0.58574 canonical. FID also improves in both paths. The gains therefore survive removal of this 6D channel. Eight raw/canonical endpoint intervals are reported jointly; attribution of differences between training procedures is outside this supplemental diagnostic. MotionRFT's training reward reads decoded features through its own MotionReward network, not our frozen standard T2M reader. We neither test that reward network's vulnerability nor attribute the released model's gains to hacking.

Table 3. **Released MotionRFT and its author-linked base.** Five matched generation seeds; 1,024 outputs and 4,640 real-reference embeddings per repetition, two official readers. Eight raw$-C$ endpoints share one interval family. This supplemental diagnostic is separate from the 20-repetition audit and published leaderboard numbers. Retrieval gains survive canonicalization.

Reader	Release	Raw FID	C FID	FID gap interval	Raw R1	C R1	R1 gap interval
MDM reader	Linked base	0.573	0.589	$[-0.0390, +0.0066]$	0.4344	0.4344	$[-0.0081, +0.0081]$
MDM reader	Reward-tuned	0.264	0.228	$[+0.0276, +0.0451]$	0.5141	0.5143	$[-0.0127, +0.0123]$
GPT reader	Linked base	0.463	0.466	$[-0.0098, +0.0037]$	0.5045	0.5045	$[-0.0099, +0.0099]$
GPT reader	Reward-tuned	0.166	0.138	$[+0.0081, +0.0484]$	0.5869	0.5857	$[-0.0090, +0.0114]$




Figure 1. **Per-clip optimization budget on 64 PHOENIX DEV clips.** Wrong-target BLEU depends on bound, steps and parameter granularity. Random controls are target-independent. These target-aware searches differ from learned-layer inference; all 60 conditions are retained.

S3. Scope, data and evaluation contracts

Constructed layers receive source text; ordinary denoisers use it as production conditioning. Final BT inference consumes only features, lengths and masks. Raw/canonical evaluation of one output preserves rotations; between-generator comparisons do not. A successful conditional layer is not spontaneous-exploitation evidence.

Release and sample counts. We use SignSparK-BT code revision`8dd7cdf533cd0ee5021c2c350ab4a54e6d2f4cf4`, rotation conversion from SignSparK`916402d0ecd6322fb4a9e5f513229a94a57bf4b6`, BT weights revision`0ced459f6c24d453893809eeca87e9ec80b70198`, and re-optimized data revision`9fe7e04ef59204c787cd6094c747f889efff6ba0`. Motion contains 240 raw 6D features per frame: body 60, left hand 90 and right hand 90. Left-hand features 60–149 are protected during attacks. The physical converter uses normalized orthogonal rows, not SVD projection.

Native valid TRAIN/DEV/TEST counts are 7,096/519/642 PHOENIX,29,630/1,650/2,183 How2Sign, and 18,201/1,064/1,162 CSL. Counts reflect the released loader, its 300-frame cap and filtering, not universal dataset sizes. Native text vocabularies, tokenization, normalization, beam search and punctuation are retained. CSL reader conditioning uses native segmented tokens; reported BLEU uses characters after removing spaces, preserving punctuation. Recognition supervision is disabled in BT fine-tunes; missing How2Sign pseudo-gloss files are therefore not inputs.

External evaluator scope. All public BTs share one Sign Language Transformer architecture. Whole-split real TEST raw scores are 14.9995004460,3.4778651050 and 6.8907036392, versus release-card 15.00/3.53/6.98. Only PHOENIX matches after rounding. Replaying native/prepared features yields the same hypotheses; the cause of the other small differences is unresolved and decoding was not retuned to chase card scores.

SLRTP2025 [19, 20] consumes 178 XYZ joints,534 features. Its 515-clip DEV archive reproduces real-motion BLEU 13.378651856913775 at the native temporal rate. The provided Progressive Transformer artifact has matched n-grams 1,161/88/8/0 at orders 1–4 and BLEU-4 zero despite nonempty predictions. This does not reproduce com-

petitive production. XYZ does not expose this raw 6D channel; incompatible features are not passed to it. M^{3}T [10, 15] describes rotational/facial production, but its official repository still marks code/checkpoints as unreleased at the recorded check. Neither supplies another compatible independent BT attack.

Fitting and validation scope. Clip IDs are disjoint between fitting TRAIN and evaluated DEV/TEST. Last-epoch selection applies to new layer and denoiser fits. All development weights, outcomes and configurations are frozen before the fixed confirmation's inference, with no new fitting or TEST-based checkpoint selection. These public TEST splits had already been evaluated during the project; we do not claim project-wide untouched holdouts. Exploratory diagnostics are labeled and do not choose the fixed 20-epoch primary denoiser settings.

S4. Equivalence, numerical checks and constrained geometry

For nonzero a and noncollinear b, set $u = a/\|a\|$, $b_\perp = b - (u^T b)u$, $v = b_\perp/\|b_\perp\|$. Under $a' = \alpha a$, $b' = \beta b + \eta a$ with positive α, β, the perpendicular vector is $\beta b_\perp$, so the physical matrix $[u; v; u \times v]$ is fixed. Conversely, every feature in this fiber has unique $a = \rho u$, $b = \sigma v + \tau u$, with $\rho, \sigma > 0$. This established property of the 6D converter [22] supplies the intervention, not a new rotation representation.

Composition of parameters is

$$(\alpha_2\alpha_1,\ \beta_2\beta_1,\ \beta_2\eta_1 + \eta_2\alpha_1). \tag{1}$$

The inverse is $(\alpha^{-1}, \beta^{-1}, -\eta/(\alpha\beta))$. Negative scales can alter rows and are excluded. Zero/collinear features lie outside the domain. The canonicalization $C(a, b) = (u, v)$ is idempotent and constant on fibers. Its derivative vanishes along $(a, 0), (0, b), (0, a)$. A 4,096-sample double-precision test gives reconstruction error 4.61×10^{-15}, canonical invariance 4.89×10^{-15} and directional derivatives below 3×10^{-14}. Four degenerate cases are rejected. Independent normalization agrees with the official converter to 4.45×10^{-16}.

Canonical input equality guarantees deterministic predictions or identical stochastic output distributions. Tiny floating-point changes can affect a nearly tied decoder. Every experimental hypothesis-equality claim is therefore checked against saved strings separately from matrix equivalence. Relative-rotation angles use SciPy rotation magnitude in double precision rather than trace/arccos near zero. Source/coefficient/output arrays allow independent reconstruction.

Fixed-distance and fixed-norm controls. For fixed rows u, v, write $s = (\rho - 1, \sigma - 1, \tau)$. Squared distance to canonical features is

$$E = \|d - C(d)\|^2 = \|s\|^2. \tag{2}$$

Any auxiliary rotation Q of s preserves E. If $\|s\| < 0.95$, reconstructed $\rho', \sigma' > 0.05$; otherwise the layer returns the identity. This auxiliary rotation changes redundant scalars, not physical joint rotations.

Squared 6D norm $N = \rho^2 + \sigma^2 + \tau^2$ obeys

$$N - E = 2(\rho + \sigma) - 2. \tag{3}$$

A rotation around $(1, 1, 0)/\sqrt{2}$ additionally preserves $\rho+\sigma$, hence both N and E per frame/joint. The circle layer predicts a bounded phase. The sphere layer predicts three bounded axis-angle coordinates and preserves E but not N. Its experiment was registered after the circle's negative result; both remain reported. Positive-scale safety, padding and left-hand protection apply to both.

The auxiliary-coordinate geometry is distinct from physical joint rotation or an intrinsic diffusion process.

The circle's text-conditioned DEV gain 0.0649 has paired interval $[-0.3860, 0.5297]$; the sphere's -0.0525 has $[-0.4955, 0.3909]$. RMS-detector AUC is approximately 0.50, but there is no reliable gain. Motion-only and canonical-loss controls are included. Independent reconstruction verifies 4,671 pairs in each study. Maximum circle errors in E/N are 1.32×10^{-6}/1.37×10^{-6}; sphere E error is 8.17×10^{-7}, while N can change by 4.08. These are successful invariant controls and unsuccessful attacks, not evidence of detector evasion with useful score inflation.

S5. Adaptive per-clip detector-statistic tests

The fixed-statistic learned layers and iterative per-clip attacks have different access and fitting requirements. DEV64 is selected uniformly with seed 20261012 before the new per-clip optimization; it uses the frozen generator's raw DEV outputs. Both 80- and 200-step endpoints are retained. Full TEST642 confirmation fixes the final 200-step endpoint and four geometry/target conditions before inference. Source motions come from the existing raw generator archive; no real reference pose is used to generate them. Baselines differ from the canonical-input learned layer: raw source BLEU is 6.62, versus 6.39 after canonicalization, for the same represented motion.

Optimization uses Adam 0.1, zero-initialized per-frame/joint coefficients and frozen BT weights. A scalar q predicts circle phase $\pi \tanh q$, bounded by π, identical to the learned circle's phase domain. Sphere coordinates are $(\pi/\sqrt{3}) \tanh q_i$, giving auxiliary rotation magnitude at most π; the learned sphere used coordinate bound 1. Thus sphere success is not an isolated test of amortization at the identical angular budget. Radius ≥ 0.95 remains identity, and left-hand joints 10–24 remain byte-identical. Target

Table 4. Fixed-distance/norm controls, full PHOENIX DEV 519, three seeds. All canonical hypotheses remain identical. Neither text-conditioned raw-loss layer gives a reliable positive gain.

Constraint	Condition	Raw	Gain	Paired95%	Seed+clip95%
Circle: distance + norm	Text / raw CE	6.60	0.06	$[-0.39, 0.53]$	$[-0.41, 0.57]$
Circle: distance + norm	Motion / raw CE	6.74	0.20	$[-0.20, 0.63]$	$[-0.24, 0.71]$
Circle: distance + norm	Text / canonical CE	6.48	-0.06	$[-0.36, 0.23]$	$[-0.42, 0.30]$
Sphere: distance only	Text / raw CE	6.48	-0.05	$[-0.50, 0.39]$	$[-0.55, 0.48]$
Sphere: distance only	Motion / raw CE	6.40	-0.13	$[-0.52, 0.26]$	$[-0.58, 0.31]$
Sphere: distance only	Text / canonical CE	6.31	-0.22	$[-0.46, -0.02]$	$[-0.51, 0.02]$

captions are either the original source or the fixed circular shift; all 642 TEST shifts differ. No decoded-score checkpoint selection occurs.

On DEV64, circle actual-caption BLEU is 6.59 to 10.06 at 200 steps, gain 3.46; its eight-endpoint-adjusted interval is $[1.15, 6.49]$. Circle wrong-target gain is 2.82, with lower adjusted endpoint zero. Sphere actual/wrong-target gains are 26.79/20.72, with adjusted intervals $[17.09, 37.53]$/$[11.93, 31.93]$. These DEV results motivated prospective fixed TEST confirmation; they are not pristine validation.

TEST circle gains are 4.09 actual and 2.10 shifted, with four-comparison-adjusted intervals $[3.04, 5.24]$/$[1.22, 3.12]$. Sphere gains are 26.45/21.27, intervals $[23.46, 29.52]$/$[18.50, 24.22]$. Random coefficient controls use prespecified seeds 42/123/777 per surface. Canonical-reader CE optimization is run for 200 steps per surface. Their wrong-target gain intervals do not exclude zero on the positive side. Every source/target, full loss trace and output array is retained; randomization seeds are not independent training seeds.

RMS threshold AUC is 0.5003 for the circle and 0.5007 for the sphere. The circle preserves both statistics; the sphere does not preserve feature norm and may be detectable by it. Preservation of E, N is not indistinguishability of all redundant-coordinate distributions. Geometric invariants, decoded canonical strings, finite values and reconstruction are verified independently. Complete numerical residuals and source hashes accompany the results.

Other fixed-rotation attack capabilities. Wrong-caption optimization reaches 85.19 PHOENIX BLEU against an incorrect target and zero against the actual caption (Tab. 6). How2Sign/CSL show the same failure with different token conventions. Three CSL targets duplicate actual captions and remain included. These are attack capability scores, not production quality.

The CTC model's wrong-target WER falls from 118.07% to 3.76%, while actual-reference WER reaches 121.58%. Reversal or identity hands raises full TEST WER from 50.11% to 91.48% or 93.95%. It responds to physical changes and redundant coordinates. All 1,024 BT/CTC attack pairs preserve canonical hypotheses.

Additional scalar detectors and the limit of statistic matching. After observing the attack outcomes, an exploratory diagnostic fits scalar thresholds on DEV64 source/attacked clips and applies their fixed orientation/threshold to TEST642. All nine statistics are reported: canonical RMS, mean squared 6D norm, means of $|\tau|$, $|\rho-\sigma|$, ρ, σ, and standard deviations of ρ, σ, τ. Circle TEST AUCs span 0.500–0.530 with DEV-fitted orientation; TEST balanced accuracies span 0.500–0.521. Sphere statistics are more informative: $|\rho - \sigma|$ AUC is 0.877 and balanced accuracy 0.801, with source false-positive rate 0.319 and attack detection rate 0.922. These post-hoc diagnostics are not independently validated security guarantees, and do not cover temporal, joint-wise or learned multivariate detectors.

For fixed canonical rows, the full Gram matrix of (a, b) is

$$\begin{pmatrix} \rho^2 & \rho\tau \\ \rho\tau & \sigma^2 + \tau^2 \end{pmatrix}. \tag{4}$$

Fixing all three entries determines positive ρ, σ and τ, hence the original features. Thus preserving E, N leaves a circle, whereas fixing the entire Gram matrix at unchanged rotation leaves no channel. This elementary limit prevents interpreting two-statistic matching as general invisibility. It does not prove a practical detector's performance without evaluating that detector.

S6. Ordinary denoiser training and diagnostics

S6.1. An ordinary generator under two motion objectives

For a denoised prediction $\hat{x}_\phi$, we compare standardized coordinate MSE with mean squared geodesic angle:

$$\mathcal{L}_{\text{geo}} = \frac{1}{TJ} \sum_{t,j} \theta\big(R(\hat{x}_{\phi,tj})^T R(x_{tj})\big)^2. \tag{5}$$

Angles use stable atan2, in radians. Because this loss factors through R, its derivative vanishes along $(a, 0), (0, b), (0, a)$; coordinate MSE generally penalizes these directions. This

Table 5. **Adaptive per-clip attacks, full PHOENIX TEST642.** All four final 200-step endpoints. Circle preserves canonical distance E and 6D norm N per joint/frame; sphere preserves only E. Intervals adjust for four target-gain comparisons. Target text is explicitly provided; these are neither learned-layer transfer nor ordinary training.

Surface	Target caption	Before	After	Gain	Family 95% CI
Circle	Actual	6.62	10.72	4.09	[3.04, 5.24]
Circle	Shifted	1.25	3.35	2.10	[1.22, 3.12]
Sphere	Actual	6.62	33.07	26.45	[23.46, 29.52]
Sphere	Shifted	1.25	22.51	21.27	[18.50, 24.22]




Figure 2. **Learned-layer budget on full PHOENIX TEST.** Left: mean raw gains, paired 95% intervals and individual seeds. Right: RMS distance to canonical features, against the same raw generator's natural output. A scalar RMS detector separates most attacked outputs. Rotations/canonical hypotheses stay fixed; smaller magnitude is not undetectability.

Table 6. **Wrong-caption attacks at fixed rotations.** Each row uses 128 real TEST clips and target-aware optimization. Columns report BLEU-4 against the shifted target or actual caption. Scores across languages use distinct tokenization.

	Wrong target		Actual caption	
Corpus	Before	After	Raw after	Canon. after
PHOENIX	0.00	85.19	0.00	13.95
How2Sign	1.23	47.34	0.00	4.76
CSL-Daily	0.67	32.44	1.26	8.10

follows from the chain rule; we verify it numerically instead of claiming new geometry.

The ordinary denoiser has no coefficient head or constrained layer. All weights are fine-tuned with

$$\mathcal{L} = \mathcal{L}_{\text{motion}} + \lambda \mathcal{L}_{\text{CE}}(f(\hat{x}_\phi), c), \tag{6}$$

or with $f(\mathcal{C}(\hat{x}_\phi))$ as the matched semantic control. Motion-only training omits CE. Physical rotations can differ across models. Only raw/canonical evaluation of one saved output is a fixed-rotation comparison.

Writing S_r, S_c for raw/canonical corpus BLEU, we report the absolute gap $S_r - S_c$ and its contrast against a control:

$$E = (S_r - S_c)_{\text{rawCE}} - (S_r - S_c)_{\text{control}}. \tag{7}$$

Positive E identifies a representation-dependent change relative to that control. Alone it does not prove caption transmission: it can reflect coordinate drift in motion-only training. Absolute gaps, canonical-CE training and coordinate-transplant controls test stronger interpretations.

Shared generator. The local denoiser has 128-dimensional token/position embeddings, a two-layer text Transformer (four heads, feed-forward 512, dropout 0.1), six temporal Conv1d blocks with dilations 1/2/4/8/16/32, GroupNorm, and cross-attention in blocks 3/6. It predicts 240 features, supports 300 frames and 64 tokens, and receives diffusion-time embeddings. Canonically converted TRAIN targets are standardized by TRAIN mean/std with std floor 0.05. A cosine schedule has 1,000 steps and x_0 prediction [9]. The shared initialization was trained 20 epochs at learning rate 0.0003 and selected by fixed-noise DEV reconstruction loss.

Objective study. All 42 fits start from that same shared checkpoint. Within each seed, first-epoch batches, diffusion noise and timesteps are matched across objectives. Every objective runs five epochs; geodesic no-CE/raw-CE 1/canonical-CE 1 reach 20 epochs with fixed endpoint selection. AdamW uses learning rate 10^{-4}, weight decay 10^{-4}, batch 64, clipping 1 and caption dropout 0.1.

Table 7. **Ordinary denoiser training, not an attack layer.** Three seeds, declared 20-epoch endpoint. Rotations can change across models; each raw/canonical pair evaluates the same output. TEST confirms the gap contrast over no CE, but not absolute positive gap or contrast over canonical CE.

Split	Motion / semantic objective	Raw	Canonical	Raw–canonical
DEV	Geodesic / no CE	2.48	4.46	-1.98
DEV	Geodesic / raw CE1	5.44	4.46	0.97
DEV	Geodesic / canonical CE1	2.89	3.34	-0.44
TEST	Geodesic / no CE	2.64	5.10	-2.45
TEST	Geodesic / raw CE1	5.13	4.79	0.35
TEST	Geodesic / canonical CE1	3.41	3.55	-0.14

Raw/canonical teacher weights are frozen. Auxiliary CE uses at most 16 nonnull-caption examples with $t \leq 800$ per batch, averaging per-clip token losses. Both motion losses use all valid joints/frames. Geodesic loss is mean squared angle in radians; coordinate loss is standardized 6D MSE. Their units and gradient scales differ, so equal CE weights are not asserted as equal physical/semantic influence.

The stable angle computation uses atan2 of skew magnitude and trace, with finite gradients at identical rotations. Unit tests check identity, equivalent-feature invariance and directional derivatives. First-batch gradient norms, CE-to-motion norm ratios and redundant-direction contractions are archived. For coordinate MSE, the output gradient is differentiated with respect to the standardized prediction and rescaled to the original feature units. Execution diagnostics and version records accompany the released artifacts.

All arms and endpoints appear in Tab. 8; weights are not selected on BLEU. The three primary 20-epoch contrasts are raw-CE gap minus no-CE gap, raw-CE gap minus canonical-CE gap, and raw-CE absolute gap. Their family-adjusted percentile tails use 0.8333%/99.1667%. DEV supports all three; TEST supports only the first. A positive contrast over no-CE does not isolate caption coding from no-CE coordinate drift. TEST raw/canonical means 5.13/4.79 versus 2.64/5.10 produce excess 2.80, but absolute gap 0.35 and canonical-CE contrast 0.48 have intervals containing zero. Full per-seed values are included below.

Coordinate transplantation. After freezing the objective study, each of its nine primary DEV models generates another-caption motion with the same source duration/noise. For each output pair we retain source canonical rows and insert the other output's ρ, σ, τ, keeping the original left-hand stream. This has no fitting, per-clip gradients or added network. Rotations are preserved and all 4,671 canonical predictions remain identical. Wrong-caption BLEU gains are 0.0652 (no CE),0.1644 (raw CE) and 0.1035 (canonical CE), with paired intervals $[-0.3790, 0.5476]$, $[-0.0524, 0.4994]$ and $[-0.3190, 0.4793]$. This exploratory control does not confirm strong source-caption transmission by the ordinary denoiser.

Target-independent representations. Four frozen local diffusion variants also generate 642 TEST motions each. Raw, canonical, fixed scales 0.9/1.1 and shear 0.1 are equivalent encodings with protected left hands, independent of captions. In the generated-near variant, scale 0.9 minus raw is -0.6592, family interval $[-1.2267, -0.0949]$; scale 1.1 minus 0.9 is +0.8554, family interval $[0.1734, 1.5347]$. These 20-contrast,20,000-resample results establish within-system representation effects. Between-generator opposite rank orderings are not supported as a primary claim. Geometry/velocity/reader-CE/generated-near variant definitions and raw arrays remain in the machine-readable evidence map.

New-seed replication and stronger-CE stress grid. Seven new fitting seeds 11/97/909/1337/2027/2718/31415 repeat geodesic/raw CE1 for 20 epochs, with seven matched canonical-CE fits. The seven-new-seed gap is the primary replication; pooling the three historical runs produces a separate ten-seed extension. None is discarded or selected on BLEU. All share the original pretrained generator. The raw/canonical cohort gap and canonical-CE contrast remain inconclusive on TEST; the full per-seed extension is in Tab. 11.

Nine fresh fits cross the historical seeds with CE weights 1/3/10 through epoch40, storing checkpoints at 20/40. They start from the shared pretrained weights; they do not silently continue old checkpoints missing optimizer/RNG states. New checkpoints retain optimizer and RNG states. Resource scheduling partitions exclusive jobs across processes without changing the fitting loop. All new weights are saved and hashed before inference, and the historical weight1/epoch20 replay gives identical DEV/TEST BLEU. Batch/noise/timestep/caption-drop arrays match across each seed's paired conditions.

For TEST, larger weights 3/10 have positive same-output

Table 8. Complete PHOENIX DEV objective sweep. All means average three seeds. Excess compares each objective with matched motion-only training at the same loss/epoch; intervals condition on frozen models. Only declared geodesic20-epoch endpoints define TEST confirmation.

Motion loss	CE path	Weight	Epoch	Raw	Canonical	Excess	95% interval
geodesic	none	0	5	5.28	5.14	0.00	$[0.00, 0.00]$
geodesic	none	0	20	2.48	4.46	0.00	$[0.00, 0.00]$
geodesic	raw	0.02	5	5.84	6.22	-0.52	$[-1.17, 0.11]$
geodesic	raw	0.1	5	6.08	5.80	0.14	$[-0.47, 0.73]$
geodesic	raw	0.3	5	4.89	4.83	-0.08	$[-0.71, 0.55]$
geodesic	raw	1	5	5.25	4.50	0.61	$[-0.05, 1.27]$
geodesic	raw	1	20	5.44	4.46	2.95	$[1.95, 4.01]$
geodesic	canonical	0.1	5	5.27	4.82	0.32	$[-0.36, 1.00]$
geodesic	canonical	1	5	4.64	3.93	0.57	$[-0.21, 1.37]$
geodesic	canonical	1	20	2.89	3.34	1.54	$[0.52, 2.60]$
mse	none	0	5	6.25	5.81	0.00	$[0.00, 0.00]$
mse	raw	0.02	5	6.43	6.11	-0.13	$[-0.56, 0.28]$
mse	raw	0.1	5	6.25	6.37	-0.57	$[-1.03, -0.12]$
mse	raw	0.3	5	6.77	6.30	0.03	$[-0.57, 0.61]$
mse	raw	1	5	6.21	5.95	-0.19	$[-0.88, 0.50]$
mse	canonical	0.1	5	5.95	6.07	-0.56	$[-1.04, -0.10]$
mse	canonical	1	5	6.00	5.37	0.18	$[-0.42, 0.80]$

Table 9. Every ordinary-generator TEST seed; no checkpoint is selected by these scores. The raw/canonical gap varies across seeds.

Objective	Seed	Raw	Canonical	Gap
Geodesic / no CE	42	2.59	5.05	-2.47
Geodesic / no CE	123	3.30	5.47	-2.17
Geodesic / no CE	777	2.04	4.76	-2.72
Geodesic / raw CE1	42	6.02	6.03	-0.01
Geodesic / raw CE1	123	4.90	3.82	1.08
Geodesic / raw CE1	777	4.48	4.51	-0.03
Geodesic / canonical CE1	42	3.57	3.87	-0.29
Geodesic / canonical CE1	123	2.24	2.05	0.19
Geodesic / canonical CE1	777	4.43	4.74	-0.31

gaps at both 20/40 endpoints after adjustment across six endpoints and five contrasts. Their canonical scores fall relative to weight1. Weight3-minus-weight1 and weight10-minus-weight3 differences at each duration, plus the mean duration difference, all have adjusted intervals containing zero. This does not establish monotonicity, independent-pretraining replication, better motion, or caption coding. Units/gradient-scale effects remain confounded with geometry. Bootstrap seed sensitivity and seed-only t intervals are reported; neither makes ten runs a universal adequacy threshold [4].

Complete dose-coordinate transplant diagnostic. The mechanism diagnostic is registered before the new dose BLEU results and uses full DEV519. It covers all six raw-CE dose/epoch combinations plus original no-CE and canonical-CE20 controls, each at seeds 42/123/777. Another caption is the fixed circular shift, generated with the source duration and sampler seed. Source canonical rows are retained; alternate ρ, σ, τ are inserted outside the protected left-hand stream. No extra model is fitted and no reader-gradient attack is applied. All 12,456 canonical predictions remain identical. Gains at weights1/3/10 and epochs20/40 are 0.164/0.277,0.233/0.082,0.528/0.180; every eight-condition-adjusted seed-plus-clip interval includes zero. The new stress gaps therefore do not confirm the semantic mechanism. Arrays and all condition intervals accompany the artifacts.

Cluster sensitivity. A post-hoc audit groups the 642 PHOENIX TEST IDs by the native name prefix before the final sentence suffix, yielding 331 groups. This is a source-name clustering sensitivity, not independently verified signer/video metadata. Circle

Table 10. **Same-output TEST gaps under ordinary-denoiser objectives.** All fits use geodesic motion loss, without an attack head. Seven new seeds define replication; ten pool historical/new runs. Stress endpoints use the three historical seeds, with eleven-comparison-adjusted seed+clip intervals. New-seed/pooled intervals are nominal. Physical motions differ across fitted models; raw/canonical pairs share one output.

Endpoint	Seeds	Raw	Canonical	Gap	Seed+clip 95% interval
CE1/20, new	7	5.81	5.68	0.13	[-0.57, 0.81]
CE1/20, pooled	10	5.60	5.41	0.20	[-0.43, 0.80]
CE1/40, stress	3	6.62	5.83	0.79	[-0.75, 2.30]
CE3/40, stress	3	6.07	4.11	1.97	[0.26, 3.64]
CE10/40, stress	3	5.39	3.40	1.99	[0.59, 3.59]

Table 11. **Ten-seed CE1/20 TEST extension.** Historical three plus seven new, one shared pretraining initialization; all runs retained.

Seed	Cohort	Raw	Canonical	Gap
42	Historical	6.02	6.03	-0.01
123	Historical	4.90	3.82	1.08
777	Historical	4.48	4.51	-0.03
11	New	6.37	6.89	-0.52
97	New	6.71	6.26	0.46
909	New	5.95	5.20	0.75
1337	New	5.10	5.91	-0.81
2027	New	6.21	5.88	0.33
2718	New	6.44	5.75	0.69
31415	New	3.85	3.83	0.02

actual/shifted gains retain positive four-comparison-adjusted intervals $[2.99, 5.23]/[1.19, 3.12]$. New-seven/pooled-ten seed-plus-group gap intervals remain $[-0.55, 0.80]/[-0.43, 0.79]$. Stress weight3/10 at epoch40 retains positive eleven-comparison-adjusted seed-plus-group intervals $[0.23, 3.59]/[0.54, 3.55]$. Registered clip intervals remain the primary analysis; the clustering is disclosed as sensitivity rather than post-hoc replacement.

S7. Conditional output layers and budgets

Generated PHOENIX motion. A frozen geometry generator produces 7,096 TRAIN and 519 DEV motions using text, capped reference duration, DDIM 50 [14], CFG 3 [8], seed 102 and inference batch 16. No reference poses, glosses or anchors enter the sampler. Canonical outputs are cached; fixed TEST reuses 642 saved outputs of the same generator.

The 299,384-parameter layer copies the generator's frozen 128-wide text encoder, including eval-mode dropout. Motion projection 240 to 128, frame embeddings 300, four-head cross-attention, and three residual temporal convolutions (dilations 1/2/4, kernel 3, GroupNorm 8) feed a zero-initialized 120-channel head. Padding is masked after blocks; text cap 64. Bounded coefficients $q = B \tanh h$ produce $(e^{q_1}a, e^{q_2}b + q_3 a)$. Joints 10–24 are identity. Nine original fits cross three seeds with text/raw loss, motion/raw loss and text/canonical loss; all use 20 epochs, batch 64, AdamW 0.001, weight decay 0.0001, clipping 1 and matched minibatches. Final checkpoints are used. Source text is available to this amortized attack [1, 13]; final reader decoding receives no text prefix.

Canonical-loss numerical drift is retained: raw gain 0.0058 DEV/-0.1347 TEST, intervals containing zero. A circular text shift changes only layer conditioning; all 519 DEV/642 TEST shifted captions differ. It raises agreement with that caption while lowering actual-caption BLEU, keeping canonical predictions identical. Exact TRAIN-caption overlaps are 25 DEV/32 TEST; excluding them preserves positive gain, but does not test unseen vocabulary or signers. The constructed attack is therefore distinct from the ordinary-generator experiment.

Real How2Sign/CSL motion. Each corpus uses raw native real TRAIN features. The temporal stack is unchanged; source text uses native 512-wide reader embeddings (frozen), a fitted 512 to 128 projection and two 128-wide Transformer layers with dropout 0. Trainable parameters are 769,784. This is not the PHOENIX generator encoder or a language-transfer experiment. Caption tokens come from the native TRAIN input, capped at 64. Three seeds fit text/raw CE; one seed 42 fits each exploratory motion/raw and text/canonical control. A control-budget amendment was recorded before any control fitting/scoring; all primary three-seed fits remained unchanged. The schedule matches the generated-motion layer.

Full TEST primary gains are 2.6363 How2Sign, VIDEO_ID interval $[2.2654, 3.0291]$, and 0.5426 CSL, clip interval $[0.1436, 0.9719]$. Seed-plus-group intervals remain positive. All canonical hypotheses are unchanged across primary/control models. Controls have one seed and cannot estimate training-seed variability. Raw-source motion is retained, rather than canonicalized before fitting; baseline canonical scores consequently differ from raw scores.

Table 12. **Complete exploratory geodesic/raw-CE dose grid.** Three historical seeds, all fixed endpoints, seed+clip percentile intervals adjusted across six endpoints and five contrasts.

Split	CE weight	Epoch	Raw	Canonical	Gap	Adjusted interval
DEV	1	20	5.44	4.46	0.97	[-0.23, 2.56]
DEV	1	40	6.04	5.04	1.00	[-0.35, 2.44]
DEV	3	20	4.85	3.27	1.57	[0.40, 2.88]
DEV	3	40	5.23	3.07	2.16	[0.93, 3.67]
DEV	10	20	4.89	3.11	1.78	[0.76, 2.98]
DEV	10	40	5.07	2.49	2.57	[1.11, 4.33]
TEST	1	20	5.13	4.79	0.35	[-1.11, 1.68]
TEST	1	40	6.62	5.83	0.79	[-0.75, 2.30]
TEST	3	20	4.99	3.82	1.17	[0.04, 2.31]
TEST	3	40	6.07	4.11	1.97	[0.26, 3.64]
TEST	10	20	4.85	3.56	1.29	[0.34, 2.39]
TEST	10	40	5.39	3.40	1.99	[0.59, 3.59]




Figure 3. **Learning changes the evaluation while the rotations stay fixed.** Source text and frozen generated motion condition a bounded output layer. TRAIN caption loss updates only that layer. At evaluation it performs one pass, with no per-clip search. The raw reader can respond to its coefficients; canonicalization removes them before reading. The three layer objectives use matched batches and initialization.




Figure 4. **A learned channel on DEV.** Bars average three seeds; dots show seeds. Whiskers are paired 95% raw-gain intervals anchored at the fixed baseline. Canonical hypotheses are identical. TEST confirmation is reported in the main paper.

Small bounds and detectability. Nine additional PHOENIX fits use bounds 0.01/0.05/0.1 with the original three seeds and identical epochs/batches. Natural RMS is computed on the same generator's raw features; attack input is its canonical encoding. For each clip, RMS is $\sqrt{\text{mean}(x - C(x))^2}$. The detector is a single threshold on this statistic. AUC reports the better of the two orientations, not a separate trained detector or a general privacy guarantee.

Bound 0.05 has paired TEST gain interval $[0.4807, 1.2343]$, but seed-plus-clip interval $[-0.0055, 1.6770]$ includes zero. Bound 0.1 remains positive under seed sensitivity $[0.3189, 2.8077]$. TEST RMS-detector AUC is 1.00 at 0.01/0.05 and 0.917–0.941 at 0.1. The raw generator RMS is around 0.10; attacked RMS 0.027/0.055 can lie below it and still be separable. Lower norm distortion is not stealth. Fixed-distance experiments above explicitly test a stronger matching condition and

Table 13. Native real-motion TEST layers and every control. Controls use one seed, so their intervals do not estimate seed variation. All canonical predictions stay fixed.

Corpus	Objective	Seeds	Raw	Gain	Paired95%	Seed+group95%
How2Sign	Text / raw CE	3	6.11	2.64	$[2.27, 3.03]$	$[2.24, 3.06]$
How2Sign	Motion / raw CE	1	3.33	-0.14	$[-0.35, 0.06]$	$[-0.35, 0.06]$
How2Sign	Text / canonical CE	1	3.48	0.00	$[-0.18, 0.20]$	$[-0.18, 0.20]$
CSL-Daily	Text / raw CE	3	7.43	0.54	$[0.14, 0.97]$	$[0.11, 1.00]$
CSL-Daily	Motion / raw CE	1	6.74	-0.16	$[-0.64, 0.29]$	$[-0.64, 0.29]$
CSL-Daily	Text / canonical CE	1	6.79	-0.10	$[-0.40, 0.09]$	$[-0.40, 0.09]$

Table 14. Small-bound PHOENIX TEST layers, all three seeds; baseline 6.3905. RMS is distance to canonical features. Detector AUC uses the better threshold orientation against the same raw generator. At 0.05 the seed-sensitive gain interval includes zero.

Bound	Raw	Gain	Paired95%	Seed+clip95%	RMS	AUC range
0.01	6.44	0.05	$[-0.20, 0.29]$	$[-0.22, 0.32]$	0.0056	1.000–1.000
0.05	7.24	0.85	$[0.48, 1.23]$	$[-0.01, 1.68]$	0.0274	1.000–1.000
0.1	8.04	1.65	$[1.15, 2.16]$	$[0.32, 2.81]$	0.0548	0.917–0.941

yield negative gains.

Per-clip target-aware budgets. Sixty DEV conditions cross four bounds, four iteration counts and three parameter granularities, with the available combinations retained exactly. Global coefficients, per-frame coefficients and per-frame/joint coefficients have sharply different capacity. Random transforms do not use targets. At 0.35/80 steps wrong-target BLEU is 0.9166/0.5845/83.3517 for global/frame/frame-joint; at 0.1 frame-joint gives 32.47. These searches use caption access at optimization time and are not production performance.

S8. Public generation replay and no-fit transfer

A PHOENIX text-plus-duration replay without ground-truth keyframes has canonical BLEU 0.7381; the PHOENIX layer reaches mean 12.6456. This weak replay is supplementary capability evidence. The released SignSparK checkpoint is explicitly not trained on PHOENIX. The paper's gloss-free/sign-retrieval T2P table does not report comparable BT scores, so matching a published number would not validate this setup.

The corrected native CSL replay uses official retrieval code revision`b1ed92705cafd2c9ff0c72a89df14b0a9ee62258`, public assets revision`a883bc2d13a5d7f85e64591b32bae4cb48950b97`, released DEV text-to-gloss predictions and a TRAIN-only isolated-sign dictionary. A uniform 128-clip DEV subset is fixed with seed 2027 before scoring. Same-signer retrieval uses release metadata where available; no DEV pose anchors or ground-truth glosses are used. The dictionary has 18201 available TRAIN videos;200 additional annotated videos are unavailable in the release. Official no-embedding exact/fuzzy OOV handling is used, with all mappings/drop counts saved. First/middle/last retrieved TRAIN keyframes condition CFM completion; generated face is outside the 240-feature reader.

Body/hand CFM weights are the public frozen release. Generation uses 50 ODE steps, native CFG-off, batch 16, one candidate, seq_len 304, and feature cap 300. The sampler uses global seed 102. The complete sampler configuration and generated filenames are included with the artifacts. The archived wrapper initializes XLM-Roberta locally before loading the full text encoder and strict EMA states; weights match release bytes, but RNG initialization consumption need not be byte-identical to the native online loader. Left hands use the official flip conversion and original retrieved keyframes are pasted back. This is a release-pipeline replay, not published-SOTA reproduction.

All 128 clips generate valid outputs. Raw/canonical BT is 9.3227/9.1231; stitched motion scores 8.9800 and native real motion on the same subset 6.8541. None establishes better signing. Applying all three frozen real-CSL layers without fitting gives 9.7504/9.4424/9.2348, mean gain 0.1532, paired interval $[-0.8588, 1.1519]$ and seed-plus-clip interval $[-0.9052, 1.2270]$. Canonical hypotheses remain identical. Transfer is inconclusive. Source hashes, complete configurations and generated arrays accompany the replay artifacts.

S9. Canonical-reader adaptation and independent recognizer

Reader adaptation. Twelve fits cross How2Sign/CSL, three seeds and raw/canonical TRAIN input. Matched pairs share public initialization and batch/dropout choices. Five

Table 15. Exact checkpoint SHA256 identifiers. The full hashes, configurations, dataset revisions and code snapshots accompany the artifacts.

Checkpoint	SHA256
PHOENIX BT	`80c67168ddadcc6f0517ea995dd9340da6c4f3e424bb667197d9282ce4774279`
How2Sign BT	`acf8794c594f9b58701c85c390264cf30807d89f399960768f30c7a9e637e01f`
CSL BT	`5ea787537b11d7b3e14e6a5c3ae711931b8abf939f6a7f25e5a9b8dd3e91a2c0`
Local CTC	`32e5c1022e5b753c0b7943df0ce52c177eef8e82cebc92cea3a620eec21f7556`
Geometry	`c78566bace1113358eacde2aeed47cc4f157bb83eb3d8bfb22b1d325d9b9f66d`
Velocity	`ec72aa705bec2fd46b2f41718b0a349e43385a7b270d056bf766d0c71ae9e8f2`
Reader CE	`ed5799d024dd4bde095d04908fe39a85b69117ce49f697f268ddb19a659b79ae`
Generated near	`ae7bd92c0f99ebb55d54591e89543d8d0a68ec995821c255402c48377b3fe52f`
Shared initial DDPM	`abdddac25d5e63887242e9af08ac440c2929617f26cff947b5a2a023f3bc8ae1`

epochs, batch 64, AdamW 10^{-5}, weight decay 10^{-4} and last-checkpoint selection apply. Both use translation CE, with recognition loss disabled. Canonical readers receive canonical features during training and decoding. Raw adaptation controls for the effect of fine-tuning itself.

DEV canonical-minus-raw differences are -0.0620 How2Sign/+0.1577 CSL; seed-plus-group intervals $[-0.2646, 0.1424]/[-0.1529, 0.5316]$. TEST differences are +0.0991/-0.0217, intervals $[-0.0332, 0.2493]/[-0.2261, 0.1859]$. Exploratory margins 0.2/0.3 BLEU are sensitivity choices, not human-equivalence thresholds. How2Sign does not establish noninferiority to its original public reader under seed-plus-group uncertainty; closure is not uniformly free accuracy.

Fresh 64-clip DEV attacks per seed/arm/corpus use 80 Adam steps, learning rate 0.1 and bound 0.35. All 384 canonical-reader pairs preserve hypotheses; nonzero wrong-target BLEU can reflect shared n-grams in unchanged predictions. Independent reconstruction verifies 768 raw/canonical attack pairs. Fixed equivalent TEST encoding (scale 1.1,shear 0.1, protected left hand) preserves all 10,035 canonical-reader hypotheses.

Local CTC architecture and inference. The 2,562,867-parameter recognizer has a 1075-entry gloss vocabulary, two 128-channel temporal convolutions (kernel 5,stride 2), a two-layer bidirectional 256-unit GRU and greedy CTC head [6]. TRAIN normalization has std floor 0.05 and remasked padding. Training uses 7096 clips, batch 64, AdamW 0.001, cosine decay over 40 epochs, clipping 1 and seed 42; DEV best WER is epoch 21. CuDNN is disabled consistently to support recurrent input gradients. Empty glosses retain insertion errors in micro-WER; one infeasible shifted CTC target is retained with zero-infinity loss, not removed.

Per-clip attack and feature-only decoding. BT minimizes target-token CE and CTC minimizes gloss CTC loss, with model weights frozen. Coefficients begin at zero and use bound 0.35. Selections are uniform without replacement, seed 2027, sorted by dataset index. CSL has three shifted-caption collisions retained. Final BT uses autoregressive decoding, not teacher forcing. A separate 768-hypothesis CSL replay forbids teacher-forced forward, asserts exactly features/lengths/masks at inference, and loads references only after predictions; every hypothesis matches the saved result. This is an input-contract check, not another independent performance experiment.

S10. HumanML3D: an independent public evaluator

Representation and native inference. HumanML3D [7] has root features 0–3, relative positions 4–66, 21 continuous rotations 67–192, velocities 193–258 and foot contacts 259–262. Its native converter uses the first two matrix columns. The released movement encoder consumes features 0–258 without a rotation projection. We alter only 67–192 before normalization, then use the released evaluation mean/std and remask padded frames. Position-based reconstruction ignores the altered block; native FK additionally verifies rotation-based reconstruction. Other feature channels are checked bitwise, separately from floating-point matrix equality.

Public T2M weights come from the MDM evaluator download script; all three frozen encoder states load strictly into the author architecture. The native MDM evaluation wrapper and our ordering-preserving adapter agree within 4.8×10^{-7} on validation fixtures. Native R-precision, MM-distance and FID match saved metrics. The encoder reads 259 channels, not a canonicalized or position-only replacement. Source hash inventories identify the pinned author code and checkpoints.

Data origin and fixed subsets. The MDM-linked processed-motion Drive archive exceeded its public download quota. We use a public mirror pinned by revision and SHA256; its 4,297,557,992-byte size matches the author-linked inventory. The mirror's 012314 example is float64 while the author Git example is float32: maximum/RMS differences are 1.94×10^{-5}/7.67×10^{-7}. This is numerical compatibility, not proof of byte identity for the full archive. Author text/split files and normalization are used. All motion matrices and physical controls are checked on the actual saved inputs.

Eligible full-caption clips have 40–199 frames. Selection seed 20261012 samples 128 VAL and 1,024 TEST clips without replacement, with fixed caption draws and crops to multiples of four. These are subset audits, not full-score leaderboard reproductions. Real and generated inputs use the same captions and durations. MDM50 [18] uses the official encoder checkpoint, 50 native sampling steps, CFG 2.5 and seed 42. No reference poses enter generation. Its eager unused SMPL constructor is replaced with a converter that raises if called; denoiser/CLIP/diffusion operations and parameters are unchanged. This enables tensor sampling without claiming licensed mesh rendering.

Attack and scoring. Nine fixed controls include identity, canonicalization, signed global bounds 0.05/0.1/0.35 and seeded random coefficients. Per-clip attacks optimize actual or shifted-caption embedding distance using 80 final Adam steps, learning rate 0.1, zero initialization and coefficient bound 0.35. A third control applies the loss after canonicalization. Evaluator weights remain frozen. A no-dropout recurrent flag enables input gradients; forward parity is checked and final scoring uses eval mode. Shifted text changes the optimization target without changing motion.

R-precision top1 averages five fixed 32-candidate permutations (seeds 11/97/909/1337/2027). FID always compares motion embeddings with a fixed real-reference subset. The target-caption objective improves retrieval and MM-distance while worsening FID; no metric is interpreted as a human-quality gain at unchanged physical motion. All fixed controls and both splits are in Tab. 17; TEST attack/control endpoints are in Tab. 16. Original/mirrored IDs are grouped for 10,000 paired bootstrap draws; six source/attack endpoints are adjusted together. These intervals condition on the five fixed candidate pools and one generator seed, not unseen evaluators or pretraining variability.

Wrong-target R1 changes are 0.028 to 0.839 for real motion and 0.033 to 0.788 for MDM, adjusted intervals $[0.782, 0.838]$/$[0.724, 0.787]$ for gains. Actual-caption retrieval falls to 0.030/0.036. Canonical-gradient wrong-target controls preserve their baseline R1. Across all 27,648 encoding pairs, maximum independent rotation error is 3.8×10^{-5} degrees, native RIC positions are exactly unchanged, and 384 sampled native FK pairs differ by at most 9.6×10^{-7} in coordinate units. Canonical embeddings differ by at most 7.2×10^{-7}.

Table 16. **HumanML3D attack and canonical-loss controls.** Full fixed TEST subset, 1,024 clips per source. R1/MM use the row's target (source caption for Source/Actual; shifted caption for Shifted/Can. loss). FID always uses the fixed real-motion reference. The target-caption attack improves retrieval while worsening FID.

Source	Target/loss	R1	MM	FID
Real	Source	0.462	3.200	0.000
Real	Actual	0.996	0.613	1.311
Real	Shifted	0.839	1.479	2.247
Real	Can. loss	0.028	9.599	0.000
MDM50	Source	0.397	3.582	0.369
MDM50	Actual	0.993	0.659	1.287
MDM50	Shifted	0.787	1.821	2.352
MDM50	Can. loss	0.033	9.741	0.369

S11. Caption-blind FID manipulation using TRAIN motion

Access and fresh source groups. This study follows the target-aware audit but excludes every previously evaluated TEST source ID and its mirror. Seed 20261013 selects 960 eligible TEST clips and 2,048 TRAIN motions; there is no TRAIN/TEST source-group overlap. The same native MDM50 settings generate a fresh cohort. The attack numerically consumes only its generated arrays, TRAIN motion embeddings and the frozen evaluator. It never invokes the text encoder or deserializes/encodes real TEST references. Integrity preflight hashes held-out files, which is a byte-level read but supplies no caption, pose or embedding target. All attack outputs and hashes are saved before the evaluator consumes TEST reference content.

Regularized Gaussian transport targets. Let μ_s, Σ_s be the generated cohort's embedding moments and μ_t, Σ_t those of TRAIN real motion. The standard Gaussian transport construction [2] gives the symmetric map

$$T = \Sigma_s^{-1/2}\left(\Sigma_s^{1/2}\Sigma_t\Sigma_s^{1/2}\right)^{1/2}\Sigma_s^{-1/2}. \quad (8)$$

Targets are $\mu_t + (e_i - \mu_s)T$. Our numerical version symmetrizes matrices and floors eigenvalues in each root at $10^{-4}\,\mathrm{tr}(\Sigma)/512$. It is a regularized transport-based target, not a new transport theorem or an exact unregularized optimum. Per-clip coefficients minimize squared distance to these fixed targets for 80 Adam steps at learning rate 0.1. Both coefficient bounds 0.1/0.35 and canonical-gradient/random controls are fixed before scoring; FID does not choose an iterate.

Table 17. **All target-independent HumanML3D encoding controls.** 128 VAL (DEV) and 1,024 TEST clips per source. Signed global coefficients are $(b, -b, b)$, with $b = \pm 0.05, \pm 0.1, \pm 0.35$. No target text enters the transform. FID reference is the fixed real subset for each split.

Split	Source	Encoding	R1	MM	FID
DEV	Real	source	0.459	3.036	0.000
DEV	Real	canonical	0.459	3.036	0.000
DEV	Real	plus005	0.464	3.036	0.017
DEV	Real	minus005	0.456	3.040	0.023
DEV	Real	plus010	0.452	3.046	0.081
DEV	Real	minus010	0.458	3.053	0.123
DEV	Real	plus035	0.389	3.541	2.325
DEV	Real	minus035	0.392	3.699	4.236
DEV	Real	random035	0.466	3.061	0.043
DEV	MDM	source	0.409	3.622	1.153
DEV	MDM	canonical	0.409	3.619	1.151
DEV	MDM	plus005	0.406	3.617	1.185
DEV	MDM	minus005	0.405	3.623	1.127
DEV	MDM	plus010	0.403	3.616	1.244
DEV	MDM	minus010	0.398	3.634	1.127
DEV	MDM	plus035	0.341	4.013	3.113
DEV	MDM	minus035	0.355	4.012	3.382
DEV	MDM	random035	0.400	3.632	1.128
TEST	Real	source	0.462	3.200	0.000
TEST	Real	canonical	0.462	3.200	0.000
TEST	Real	plus005	0.457	3.196	0.013
TEST	Real	minus005	0.459	3.212	0.015
TEST	Real	plus010	0.459	3.208	0.062
TEST	Real	minus010	0.456	3.238	0.081
TEST	Real	plus035	0.401	3.667	2.032
TEST	Real	minus035	0.376	3.850	3.547
TEST	Real	random035	0.456	3.219	0.027
TEST	MDM	source	0.397	3.582	0.369
TEST	MDM	canonical	0.398	3.580	0.366
TEST	MDM	plus005	0.401	3.579	0.391
TEST	MDM	minus005	0.396	3.588	0.346
TEST	MDM	plus010	0.403	3.582	0.424
TEST	MDM	minus010	0.392	3.600	0.347
TEST	MDM	plus035	0.365	3.904	2.125
TEST	MDM	minus035	0.337	4.052	3.433
TEST	MDM	random035	0.389	3.582	0.318

Results and interpretation. Bound 0.1 reduces FID from 0.3839 to 0.2099 against the withheld TEST real reference, while actual R1 is 0.4133/0.4113. Bound 0.35 instead increases FID to 1.0850. The canonical-gradient control has FID 0.3838544, compared with source 0.3838538; random coefficients give 0.3526. Therefore success is not monotonic in bound, and both endpoints remain reported. Canonical FID remains 0.3799403 across equivalent encodings. This demonstrates a caption-blind score change for one fixed cohort, not generator improvement or routine exploitation.

Independent reconstruction checks all 5,760 encoding pairs and 48 sampled native FK pairs. Maximum rotation error is 1.5×10^{-5} degrees; RIC positions and nonrotation channels are bitwise unchanged, native FK error is at most 6.0×10^{-7} and canonical embedding error at most 7.2×10^{-7}. Gaussian targets and native metrics are independently recomputed. FID is a registered descriptive endpoint. A post-hoc 200-draw paired original/mirror-group sensitivity gives two-bound-adjusted intervals for the FID change of $[-0.268, -0.049]$ at bound 0.1 and $[0.404, 1.166]$ at bound 0.35. The bootstrap holds the generated cohort and evaluator fixed; it does not estimate generation-seed variability, and its tail precision is limited by 200 draws.

Table 18. **Caption-blind distribution attack.** 960 previously uninspected TEST clips; targets use 2,048 TRAIN motions, not caption content or TEST reference moments. Both fixed bounds and controls are kept. Canonical FID is invariant to equivalent encodings within numerical precision.

Condition	Raw FID	Can. FID	Actual R1
Source	0.384	0.380	0.413
Canonical input	0.380	0.380	0.412
Blind OT, bound 0.1	0.210	0.380	0.411
Blind OT, bound 0.35	1.085	0.380	0.417
Canonical-loss control	0.384	0.380	0.413
Random control	0.353	0.380	0.409

S12. Statistics, presentation and reproducibility

Corpus BLEU is recomputed from clipped 1–4 gram counts, native tokenization and brevity penalty [11, 12]. CSL removes spaces and preserves punctuation. A standard-library Counter implementation reproduces saved scores to 10^{-10}. WER is verified by full-matrix edit distance and micro aggregation. Attack scores against wrong captions remain separate from actual-reference scores.

New intervals use 20000 paired bootstrap draws, seed 42, recomputing corpus metrics from sufficient statistics. How2Sign uses official VIDEO_ID groups (115 DEV/149 TEST), not verified signer identity. Within each sampled unit set, model-specific scores are computed separately before averaging differences across seeds. Sensitivity analysis resamples the three training seeds, all sharing one initialization; it does not estimate pretraining variation. One-seed controls have no seed uncertainty. Ordinary-generator family intervals cover three fixed contrasts, while target-independent representation intervals cover 20. Layer/budget/transfer intervals are nominal per contrast. Shifted-caption mappings remain fixed during resampling. Target-aware 128-clip audit intervals use 2000 draws and do not estimate training-seed variability.

The 15.2053 learned PHOENIX score minus 14.9995 real-motion score is 0.2058, paired 642-clip interval $[-0.8454, 1.2357]$. This comparison is not statistically supported superiority and does not assess human signing quality. The teaser uses three unaltered original RGB frames of`04January_2010_Monday_heute-7395`, chosen after outputs for illustration. English explanations do not replace German metric references. These are source photographs, not before/after avatar renderings; rotation equality is checked numerically.

Frozen inputs and all outcomes are retained. Experiments use Python 3.10.13, PyTorch 2.11.0+cu128, CUDA 12.8 and RTX PRO 6000 Blackwell Max-Q. Geometry and hypotheses are verified separately.

Table 19. **Caption-blind attack repetitions.** FID for 960 outputs per cohort, common TRAIN reference. Bounds 0.1/0.35 and canonical-gradient/random controls are retained. The new cohorts overlap by 493 source groups and overlap the first by 494/496; these are not independent clip samples.

Gen. seed	Raw	0.1	0.35	C-grad.	Random
42	0.384	0.210	1.085	0.384	0.353
4242	0.376	0.176	1.148	0.376	0.323
7777	0.327	0.199	1.429	0.327	0.301

S13. Caption-blind repetition details

The same TRAIN embeddings, transport regularization, 80-step Adam optimizer and two fixed bounds are used in all cohorts. New selection seeds 20261021/20261022 and generation seeds 4242/7777 produce two further 960-output cohorts. They exclude the original caption-targeted audit's source/mirror groups, but overlap the first blind cohort by 494/496 groups and each other by 493. The public native release audit also uses this TEST split; project-wide untouched TEST validation is not claimed. Neither overlap nor caption metadata is used to optimize the attack.

At bound 0.1, FID reductions are 45.3%, 53.2% and 39.2%; bound 0.35 worsens all three cohorts. Canonical-gradient controls remain at baseline. The repeats demonstrate sensitivity to generation/selection draws, not monotonicity or independent population validation. Each new cohort verifies 5,760 encoding pairs and 48 sampled native FK pairs, bitwise protected channels and independently reconstructed TRAIN transport targets. Attack arrays precede their own TEST reference scoring; no real TEST embedding or caption target enters attack optimization.

References

[1] Shumeet Baluja and Ian Fischer. Learning to attack: Adversarial transformation networks. In *AAAI Conference on Artificial Intelligence*, 2018. 9

[2] Rajendra Bhatia, Tanvi Jain, and Yongdo Lim. On the Bures–Wasserstein distance between positive definite matrices, 2017. 13

[3] Xin Chen, Biao Jiang, Wen Liu, Zilong Huang, Bin Fu, Tao Chen, and Gang Yu. Executing your commands via motion diffusion in latent space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 18000–18010, 2023. 1

[4] Cédric Colas, Olivier Sigaud, and Pierre-Yves Oudeyer. How many random seeds? statistical power analysis in deep reinforcement learning experiments, 2018. 8

[5] Wenxun Dai, Ling-Hao Chen, Jingbo Wang, Jinpeng Liu, Bo Dai, and Yansong Tang. MotionLCM: Real-time controllable motion generation via latent consistency model. In *Computer Vision – ECCV 2024*, pages 390–408, 2025. 1

[6] Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. Connectionist temporal classification: Labelling unsegmented sequence data with recurrent neural networks. In *International Conference on Machine Learning*, pages 369–376, 2006. 12

[7] Chuan Guo, Shihao Zou, Xinxin Zuo, Sen Wang, Wei Ji, Xingyu Li, and Li Cheng. Generating diverse and natural 3D human motions from text. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5152–5161, 2022. 1, 12

[8] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. arXiv:2207.12598, 2022. 9

[9] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems*, pages 6840–6851, 2020. 6

[10] M3T contributors. M3T official repository, 2026. Consulted 11 October 2026; code and model checkpoints marked unreleased. 4

[11] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. BLEU: A method for automatic evaluation of machine translation. In *Annual Meeting of the Association for Computational Linguistics*, pages 311–318, 2002. 15

[12] Matt Post. A call for clarity in reporting BLEU scores. In *Conference on Machine Translation: Research Papers*, pages 186–191, 2018. 15

[13] Omid Poursaeed, Isay Katsman, Bicheng Gao, and Serge Belongie. Generative adversarial perturbations. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 9

[14] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2021. 9

[15] Alexandre Symeonidis-Herzig, Jianhe Low, Ozge Mercanoglu Sincan, and Richard Bowden. M3T: Discrete multi-modal motion tokens for sign language production. arXiv:2603.23617v2, 2026. 4

[16] Xiaofeng Tan, Wanjiang Weng, Haodong Lei, and Hongsong Wang. EasyTune: Efficient step-aware fine-tuning for diffusion-based motion generation. In *International Conference on Learning Representations*, 2026. 2

[17] Xiaofeng Tan, Wanjiang Weng, Hongsong Wang, Fang Zhao, Xin Geng, and Liang Wang. Motionrft: Unified reinforcement fine-tuning for text-to-motion generation, 2026. 2

[18] Guy Tevet, Sigal Raab, Brian Gordon, Yoni Shafir, Daniel Cohen-Or, and Amit H. Bermano. Human motion diffusion model. In *International Conference on Learning Representations*, 2023. 1, 13

[19] Harry Walsh. Slrtp sign production evaluation: Official implementation and data, 2025. Commit db35105a94e126feb04619d56f6103ba8369d382. 3

[20] Harry Walsh, Ed Fish, Ozge Mercanoglu Sincan, Mohamed Ilyes Lakhal, Richard Bowden, Neil Fox, Bencie Woll, Kepeng Wu, Zecheng Li, Weichao Zhao, Haodong Wang, Wengang Zhou, Houqiang Li, Shengeng Tang, Jiayi He, Xu Wang, Ruobei Zhang, Yaxiong Wang, Lechao Cheng, Meryem Tasyurek, Tugce Kiziltepe, and Hacer Yalim Keles. SLRTP2025 sign language production challenge: Methodology, results, and future work. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 2025. 3

[21] Jianrong Zhang, Yangsong Zhang, Xiaodong Cun, Yong Zhang, Hongwei Zhao, Hongtao Lu, Xi Shen, and Ying Shan. Generating human motion from textual descriptions with discrete representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14730–14740, 2023. 1

[22] Yi Zhou, Connelly Barnes, Jingwan Lu, Jimei Yang, and Hao Li. On the continuity of rotation representations in neural networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5745–5753, 2019. 4