IN Line Bridge	Table of Dimensions. (61end)
Span Girder Length of Girder Endskew of Girder Numbers 16 Heast Distribution of Type No Line 16 16 16 16 16 16 16 16 16 16 16 16 16	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
No. 1 D 02:04 30:33: 1 1 9 6 8 3 04:	(e, end) (e) end (e) end (f) end (f
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
IW Line Bridge A Control National Cont	Release helddowns 15: Release helddowns 15: Between (2) 6(3) Mixdesigned to achieve 5000 psi min. O stress transfer 6006 psi min. O stress transfer 6006 psi min. Steel & Jacking Force As per Wash State Dept. of Highways Drawged speeds. All measurements are out to out. Strand Mit', Cut all strands flush with the Girder ends t pain: with an asyrs.
Ramp E Span Span Span Span Span Span Span Span	Strand Pattern 18: Strand
Sount Span2 Span3	Tukwila Interchange W Briage over B and E Ramp Bridge over B W Briage over B and E Ramp Bridge over B Western Bridge Construction Co.