


Dimensions in mm

Execution: Base














Technical Data


Marel Poultry B.V.
Boxmeer, The Netherlands

Marel, Inc.
Gainesville, USA

3690377_03_E

SI units [US units]

MEDIUM			UNIT	TEMPERATURE	CONNECTION	CONSUMPTION
terminal box		TB1			3 x 1 mm ² [3 x 16 AWG]	
AC valve (solenoid valve)		Y1	24 VAC [110VAC]		3 x 1,5 mm ² [3 x 16 AWG]	12 W
AC sensor		S1	24 VAC [110VAC]		factory wired	0,5 W
cold water			100 - 300 kPa [14.5 - 43.5 PSI]	1 - 20°C [34 - 68 °F]	 Rp 1/2 [1/2 NPT]	4 m ³ /h [18 GPM]
compressed air			400 - 500 kPa [58 - 72.5 PSI]		 ø8 mm	< 0,1 Nm ³ /h [< 0,05 CFM]
drainage					 ø110 mm [4" pvc pipe]	
centre of gravity						
airborne noise emission			LpA = 71 dB(A)			
mass			620 kg [1366 lb.]			



Technical Data

Marel Poultry B.V.
Boxmeer, The Netherlands

Marel, Inc.
Gainesville, USA

3690377_03_E















Inside/outside washer

RW-16 RS
RW-8 RS

RW-16 RS+HV
RW-12 RS (8")

C3838
C3839 C3841

SI units [US units]

MEDIUM		UNIT	TEMPERATURE	CONNECTION	CONSUMPTION
terminal box		TB1		3 x 1 mm ² [3 x 16 AWG]	
AC solenoid		Y1	24 VAC [110VAC]	3 x 1,5 mm ² [3 x 16 AWG]	12 W
AC sensor		S1	24 VAC [110VAC]	factory wired	0,5 W
emergency stop*		ES1 ES2		2 x (3 x 1,5 mm ²) [2 x (3 x 16 AWG)]	
cold water			830 kPa [120 PSI]	 ø 50 mm (2")	18 m ³ /h [80 GPM]
water containing detergent or disinfectant			100 - 300 kPa [14.5 - 43.5 PSI]	 Rp 1/2 [NPT]	0,5 m ³ /h [2.2 GPM]
compressed air			400 - 500 kPa [58 - 72.5 PSI]	 ø8 mm	< 0,1 Nm ³ /h [$< 0,05$ CFM]
drainage				 ø110 mm [4" pvc pipe]	
centre of gravity					
airborne noise emissions			LpA = 71 dB(A)		
mass			725 kg [1600 lb.]		

* optional for US market

Technical Data

Marel Poultry B.V.
Boxmeer, The Netherlands

Marel, Inc.
Gainesville, USA

3690377_03_E


Inside/outside washer

RW-16 RS
RW-8 RS

RW-16 RS+HV
RW-12 RS (8")

C3838
C3839 C3841

Option RW-16 RS + HV exection: Pump




Technical Data





Marel Poultry B.V.
Boxmeer, The Netherlands

Marel, Inc.
Gainesville, USA

3690377_03_E

Option RW-16 RS execution: Water saving technology



MEDIUM		UNIT	TEMPERATURE	CONNECTION	CONSUMPTION
cold water		200 - 500 kPa [29 - 72.5 PSI]	1 - 20°C [34 - 68 °F]	 Rp 3/4 [NPT]	2,6 m³/h [11 GPM]
compressed air*		150 - 350 kPa [21.8 - 50.8 PSI]		 Rp 3/4 [NPT]	49 Nm³/h [29 CFM]
mass		10 kg [22 lb.]			

Technical Data

Marel Poultry B.V.
Boxmeer, The Netherlands

Marel, Inc.
Gainesville, USA

3690377_03_E