



Provisioning OCI AI 'all-in-one' Data Science Image

Description: The purpose of this guide is to provision the **OCI AI 'all-in-one' Data Science** Marketplace Image within OCI and set up the Jupyter Server and an Anaconda Environment to execute your Data Science Notebooks.

Step	Screenshots
<p>Login to the OCI Cloud Console at: cloud.oracle.com</p>	
<p>First, we will create a new Network for the Data Science VM to live within.</p> <p>Navigate from the OCI Menu > Networking > Virtual Cloud Networks.</p>	

In this tutorial we will create a basic **Virtual Cloud Network** with a **Public Subnet** with **Internet Connectivity**.

Click on **Start VCN Wizard**.

Oracle Cloud Cloud Classic > Search resources, service

Networking

Virtual Cloud Network

A Virtual Cloud Network is a virtual private network that you can choose to use.

Overview

- Virtual cloud networks**
- Web Application Acceleration
- Load balancers
- DNS management
- Customer connectivity
- IP management

Create VCN **Start VCN Wizard**

Name	State	IPv4
xxxxxx	Available	10.0.0.0/16
xxxxxx	Available	10.0.0.0/16
xxxxxx	Available	10.0.0.0/16

Select **Create VCN with Internet Connectivity**.

Select **Start VCN Wizard**.

Start VCN Wizard

Create VCN with Internet Connectivity

Add Internet

☐ Connectivity and Site-to-Site VPN to a VCN

Start VCN Wizard [Cancel](#)

Creates a VCN with a public subnet that can be reached from the Internet. Also creates a private subnet that can connect to the Internet through a NAT gateway, and also privately connect to the Oracle Services Network.

Includes: VCN, public subnet, private subnet, Internet gateway (IG), NAT gateway (NAT), service gateway (SG).

Enter **VCN Name**.

Select **Compartment**.

Select **VCN CIDR Block Range**.

Basic information

VCN name ⓘ

my-vcn

Compartment ⓘ

my-compartment

Configure VCN

VCN IPv4 CIDR block ⓘ

10.0.0.0/16

If you plan to peer this VCN with another VCN, the VCNs must not have overlapping CIDR blocks. [Learn more.](#)

IPv6 prefixes *Optional*

☐ Enable IPv6 in this VCN

DNS resolution

☒ Use DNS hostnames in this VCN

Required for instance hostname assignment if you plan to use VCN DNS or a third-party DNS. This choice cannot be changed after the VCN is created. [Learn more.](#)

Enter CIDR Block Ranges for both your **Public and Private Subnet**.

Click **Next**.

Review the remaining default options.


By default, you'll be able to SSH into the Public Network.




Click **Create**.

This will take a minute to Create.

Once your VCN is created, we will provision our VM Image inside the Public Network.

From the **OCI Menu > Compute > Instances**.



<p>Click on Create Instance.</p>	
<p>Enter Name.</p> <p>Select Compartment.</p> <p>Choose Availability Domain.</p>	
<p>We will change both the Image and Shape.</p> <p>First the Image, Click on Change Image.</p>	

Select **Marketplace**.

Select AI **'all-in-one'**
Data Science Image
Intel/AMD.

You can select the GPU
version if deploying to
GPUs.

**Read and Accept the
Terms and Restrictions.**

Click **Select Image**.

Select an image

Oracle Linux Ubuntu Red Hat CentOS Windows SUSE AlmaLinux Rocky Linux

Marketplace My images

Partner images Community images

Partner images are trusted third-party images published by Oracle partners. Learn more about [Marketplace listings](#).

App name	Publisher	Price
<input type="checkbox"/> (GovtCloud) Palo Alto Networks VM-Series Next Generation Firewall	Palo Alto Networks Public Sector, LLC	BYOL
<input type="checkbox"/> A10 vThunder Application Delivery Controller - BYOL	A10 Networks	BYOL
<input checked="" type="checkbox"/> AI 'all-in-one' Data Science Image Intel/AMD	Oracle	Free
<input type="checkbox"/> AI 'all-in-one' Data Science Image for GPU	Oracle	Free
<input type="checkbox"/> APEX Office Print (AOP)	APEX R&D	BYOL
<input type="checkbox"/> API AutoFlow for ORDS integration	Interactor	BYOL

Agreement for partner image AI 'all-in-one' Data Science Image Intel/AMD

☒ I have reviewed and accept the [Oracle Standard Terms and Restrictions](#)

Select image Cancel

Then we will change
the Shape.

Select **Virtual Machine**.

Select **AMD**.

Select Shape Name as
VM.Standard.E4.Flex

Select OCPU as **4**.

Click **Select Shape**.

Instance type

Virtual machine Bare metal machine

Shape series

AMD Intel Ampere Specialty and previous generation

Image: Oracle Linux 8

Shape name	OCPU	Memory (GB)	Security
<input checked="" type="checkbox"/> VM.Standard.E4.Flex	4 (114 max)	64 (1,760 max)	

Network bandwidth (Gbps): 4

Maximum VNICS: 4

You can customize the number of OCPUs and the amount of memory allocated to a flexible shape. The other resources scale proportionately. [Learn more about flexible shapes](#).

Number of OCPUs Extended OCPU

Amount of memory (GB) Extended memory

Select shape Cancel



Now time to define the Network we created earlier.

Choose **Select existing virtual cloud network.**

Select the **VCN we created earlier.**

Choose **Select existing subnet.**

Select the **Public Subnet we created earlier.**

Select **Assign a public IPv4 address.**

We will then generate a public/private key pair.

Select **Generate a key pair for me.**

Click **Save private key.**

Click **Save public key.**

Leave all the other options as default.

Click **Create.**



This will take a few minutes to provision.

While it is provisioning, make note of a few of the details being displayed.

Public IP Address

Username

You can also open up the usage instructions using the link above the Public IP Address - <https://cloud.oracle.com/marketplace/application/134110504/usage?region=eu-frankfurt-1>

I will be referencing this when continuing.

Instance access

You [connect to a running Linux instance](#) using a Secure Shell (SSH) connection. You'll need the private key from the SSH key pair that was used to create the instance.

[Usage information for this image](#)

Public IP address: -----

Username: -----

While the provisioning is taking place, I have opened a Terminal on my laptop and renamed and updated the private key permissions to 600.





chmod 600 <private-key-file>




```
(base) Ismails-MBP:Downloads isyed$ chmod 600 [redacted]private.key
(base) Ismails-MBP:Downloads isyed$ ls -la
total 32
drwx-----@ 7 isyed  staff   224 19 May 16:12 .
drwxr-xr-x+ 68 isyed  staff  2176 17 May 15:05 ..
-rw-r--r--@ 1 isyed  staff  6148 19 May 14:56 .DS_Store
drwxr-xr-x 11 isyed  staff   352  7 Apr 2022 .ipynb_checkpoints
-rw----- 1 isyed  staff    0  6 Jul 2019 .localized
-rw-----@ 1 isyed  staff  1675 19 May 16:08 [redacted]private.key
-rw-r--r--@ 1 isyed  staff   399 19 May 16:08 [redacted]public.pub
(base) Ismails-MBP:Downloads isyed$
```



<p>If using a Mac, I would recommend moving your keys to the <code>~/ssh</code> folder where all keys are stored.</p> <pre>mv <private-key-file> ~/ssh</pre> <pre>mv <public-key-file> ~/ssh</pre> <p>Navigate to your .ssh directory.</p> <pre>cd ~/ssh</pre>	<pre>(base) Ismails-MBP:Downloads isyed\$ (base) Ismails-MBP:Downloads isyed\$ (base) Ismails-MBP:Downloads isyed\$ mv [redacted] private.key ~/ssh (base) Ismails-MBP:Downloads isyed\$ mv [redacted] public.pub ~/ssh (base) Ismails-MBP:Downloads isyed\$ (base) Ismails-MBP:Downloads isyed\$ cd ~/ssh</pre>
<p>We will now test connecting into the VM.</p> <p>Let's SSH into the VM.</p> <pre>ssh -i <private-key> <user>@<public-ip></pre>	<pre>(base) Ismails-MBP:~ ssh isyed\$ (base) Ismails-MBP:~ ssh isyed\$ (base) Ismails-MBP:~ ssh isyed\$ ssh -i [redacted] The authenticity of host '[redacted]' can't be established. This key is not known by any other names Are you sure you want to continue connecting (yes/no/[fingerprint])? yes Warning: Permanently added '[redacted]' to the list of known hosts. Activate the web console with: systemctl enable --now cockpit.socket Last login: Thu Sep 1 21:05:13 2022 from [redacted] [opc@~]\$ [opc@~]\$ [opc@~]\$ pwd /home/opc [opc@~]\$</pre>
<p>We will reset the Jupyter Notebook Password.</p> <pre>jupyter notebook password</pre>	<pre>[opc@~]\$ [opc@~]\$ [opc@~]\$ jupyter notebook password Enter password: Verify password: [NotebookPasswordApp] Wrote hashed password to [redacted] [opc@~]\$ [opc@~]\$</pre>



<p>Now before connecting into the Jupyter Notebook, we will need to open port 8888 on our Subnet Security List.</p> <p>Navigate back to the OCI Console, OCI Menu > Networking > Virtual Cloud Network.</p>	
<p>Select our VCN.</p>	
<p>Select our Public Network.</p>	
<p>Select our Security List.</p>	

<p>Click Add Ingress Rule.</p>	
<p>Add Source Type – CIDR</p> <p>Source CIDR – 0.0.0.0/0 (<i>access from anywhere, you can adjust as needed.</i>)</p> <p>IP Protocol – TCP</p> <p>Destination Range – 8888</p> <p>Click Add Ingress Rule.</p> <p>This will allow us to connect to Port 8888 on the VM.</p>	
<p>We can now test creating an SSH Tunnel into the VM and access Jupyter Lab from our Local Browser.</p> <p>In your Terminal which is SSH'd into the VM, start the Jupyter Notebook Server.</p> <p>jupyter notebook</p>	


In another Terminal window navigate to the `~/ssh` directory.

`cd ~/ssh`

Open up an SSH Tunnel to map the VM Host and Jupyter Port to the local host.

`ssh -L`

`8888:127.0.0.1:8888 -i`
`<vm-private-key-file>`
`opc@<vm-ip-address>`



```
(base) Ismails-MBP:~ isyed$ cd ~/ssh
(base) Ismails-MBP:~/ssh isyed$
(base) Ismails-MBP:~/ssh isyed$ ssh -L 8888:127.0.0.1:8888 -i [redacted] private.key opc@[redacted]
Activate the web console with: systemctl enable --now cockpit.socket


Last login: Fri May 19 15:49:34 2023 from 62.64.130.47
[opc@oci-ds-vm ~]$
```

Within a local browser visit the webpage:

<http://localhost:8888/lab>


When prompted with a password, enter the new password we created earlier.

We are now into the Jupyter Environment.



Once we can login, lets close down the Notebook Server (for now) within the SSH Session you have open.

`Ctrl-C.`



```
^C[I 16:08:44.931 NotebookApp] interrupted
Serving notebooks from local directory: /home/opc
0 active kernels
Jupyter Notebook 6.4.8 is running at:
http://localhost:8888/
Shutdown this notebook server (y/[n])? y
[C 16:08:47.232 NotebookApp] Shutdown confirmed
[I 16:08:47.232 NotebookApp] Shutting down 0 kernels
[I 16:08:47.233 NotebookApp] Shutting down 0 terminals
[opc@[redacted]]$
```



We will now **create** a **custom Conda Environment** to use within the Jupyter Notebook.

First, we must initialise the terminal for conda.

conda init bash

Once this is done, we will have to **logout and log back into the VM via SSH**.

```
[opc@redacted ~]$ echo $SHELL
/bin/bash
[opc@redacted ~]$ conda init bash
no change      /home/opc/anaconda3/condabin/conda
no change      /home/opc/anaconda3/bin/conda
no change      /home/opc/anaconda3/bin/conda-env
no change      /home/opc/anaconda3/bin/activate
no change      /home/opc/anaconda3/bin/deactivate
no change      /home/opc/anaconda3/etc/profile.d/conda.sh
no change      /home/opc/anaconda3/etc/fish/conf.d/conda.fish
no change      /home/opc/anaconda3/shell/condabin/Conda.psm1
no change      /home/opc/anaconda3/shell/condabin/conda-hook.ps1
no change      /home/opc/anaconda3/lib/python3.9/site-packages/xontrib/conda.xsh
no change      /home/opc/anaconda3/etc/profile.d/conda.csh
modified       /home/opc/.bashrc

==> For changes to take effect, close and re-open your current shell. <==

[opc@redacted ~]$
```

Once logged back in we can **create a new python 3.9 environment**.

conda create --name yolov8_p39 python=3.9

```
(base) [opc@redacted ~]$ conda create --name yolov8_p39 python=3.9
Collecting package metadata (current_repodata.json): done
Solving environment: done

==> WARNING: A newer version of conda exists. <==
  current version: 4.14.0
  latest version: 23.3.1

Please update conda by running

    $ conda update -n base -c defaults conda

## Package Plan ##

environment location: /home/opc/anaconda3/envs/yolov8_p39
```

Once created, lets activate the conda.

conda activate yolov8_p39

```
#
# To activate this environment, use
#
#     $ conda activate yolov8_p39
#
# To deactivate an active environment, use
#
#     $ conda deactivate

Retrieving notices: ...working... done
(base) [opc@redacted ~]$
(base) [opc@redacted ~]$
(base) [opc@redacted ~]$ conda activate yolov8_p39
(yolov8_p39) [opc@redacted ~]$
(yolov8_p39) [opc@redacted ~]$
```




<p>We will now install two libraries to enable use within Jupyter Lab,</p> <p><i>conda install ipykernel</i></p> <p><i>conda install nb_conda_kernels</i></p>	<pre>(yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ conda install ipykernel Collecting package metadata (current_repodata.json): done Solving environment: done ==> WARNING: A newer version of conda exists. <== current version: 4.14.0 latest version: 23.3.1 Please update conda by running \$ conda update -n base -c defaults conda ## Package Plan ## environment location: /home/opc/anaconda3/envs/yolov8_p39</pre>
<p>Once done we will now register the conda environment for use within the Jupyter Lab Environment.</p> <p><i>ipython kernel install --user --name=yolov8_p39</i></p>	<pre>(yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ ipython kernel install --user --name=yolov8_p39 Installed kernelspec yolov8_p39 in /home/opc/.local/share/jupyter/kernels/yolov8_p39 (yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$</pre>
<p>Switch back to the base conda environment.</p> <p><i>conda activate base</i></p>	<pre>Installed kernelspec yolov8_p39 in /home/opc/.local/share/ (yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ (yolov8_p39) [opc@ ~]\$ conda activate base (base) [opc@ ~]\$ (base) [opc@ ~]\$ (base) [opc@ ~]\$</pre>
<p>Now let's start the Jupyter Notebook Session back up.</p> <p><i>jupyter notebook</i></p>	<pre>(base) [opc@ ~]\$ (base) [opc@ ~]\$ jupyter notebook [W 2023-05-19 16:30:17.163 LabApp] 'password' has moved from NotebookApp to ServerApp. This config w ill be passed to ServerApp. Be sure to update your config before our next release. [W 2023-05-19 16:30:17.164 LabApp] 'password' has moved from NotebookApp to ServerApp. This config w ill be passed to ServerApp. Be sure to update your config before our next release. [I 2023-05-19 16:30:17.172 LabApp] JupyterLab extension loaded from /home/opc/anaconda3/lib/python3. 9/site-packages/jupyterlab [I 2023-05-19 16:30:17.172 LabApp] JupyterLab application directory is /home/opc/anaconda3/share/jup yter/lab [I 16:30:17.177 NotebookApp] Serving notebooks from local directory: /home/opc [I 16:30:17.177 NotebookApp] Jupyter Notebook 6.4.8 is running at: [I 16:30:17.177 NotebookApp] http://localhost:8888/ [I 16:30:17.177 NotebookApp] Use Control-C to stop this server and shut down all kernels (twice to s kip confirmation). [W 16:30:17.180 NotebookApp] No web browser found: could not locate runnable browser.</pre>



In our local browser navigate to the Jupyter Lab homepage.

<http://localhost:8888/lab>

We can now see our new Conda environment ready for use.



Name	Last Modified
anaconda3	9 months ago
Desktop	9 months ago
Documents	9 months ago
Downloads	9 months ago
Music	9 months ago
Pictures	9 months ago
Public	9 months ago
pycharm-community-2022.1.3	9 months ago
sample-envs	9 months ago
Templates	9 months ago
Videos	9 months ago
Anaconda3-2022.05-Linux-x86_64...	a year ago
pycharm-community-2022.1.3.tar....	a year ago

You can now create a new notebook and start running your code.

