

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

Introduction

CFTools Cloud provides a public API interface for everyone to use at <https://data.cftools.cloud>. The page is only served via HTTPS and acts as root url for all API methods.

Server Id

CFTools Cloud's Steamrelay service automatically queries all game servers for specific games in a 30 to 60 second interval. To retrieve information about game servers you need to generate a Data API specific server resource id, referenced to as server_id in the following.

The server_id generates from following datasets:

- IPv4 of the game server
- Gameport of the game server
- Game identifier

Game	Identifier
DayZ	1

Once you have gathered this information, build a string with these parameters in the following order:
`{game_identifier}{ipv4}{game_port}`
Do not use any spacers or other additional symbols.

After you have this string use a sha1 hashing function on it. The digest in hexademical form can then be used as server_id.

Example with ipv4 = 127.0.0.1 , game_port = 2302, game_identifier = 1:

- Build string: `1127.0.0.12302`
- sha1 hash string `sha1(1127.0.0.12302)`
- Use hex-digest of hashed string as server_id:
`c0d1db47b89ade22740fd3b2a5e79393dfc56c90`

Authentication

All requests must contain a User-Agent header containing your application id.

Some routes require authentication in the form of Bearer tokens in the request headers.

To log in send a **POST** request with your application_id and secret to `/v1/auth/register`. You will receive a token that is valid for 24 hours.

Add this token to your Authorization request header in the format of `Bearer {token}`

Upon expiration you receive the error message expired-token and are forced to reauthenticate as described above.

Register

[POST] `/v1/auth/register`  2/minute

Log in and claim an authorization token

Parameter	Value	Status
<code>application_id</code>	Your application id	Required
<code>secret</code>	Your application secret	Required

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

Grant process and access permissions

When trying to access restricted routes or data, an API application must be granted access by the resource owner.
This permission can be granted by sending the resource owner the **"Grant URL"** you can find on your application dashboard.

Get Grants

[GET] /v1/@app/grants 🕒1/minute

Get list of all grants and their respective id's.

Game-Server

This references to **GAME SERVER ENTITIES**. This is not the scope which allows you to retrieve information about CFCloud instances.

All subsequent routes require a **Server Id**, which can be generated as documented at [Server Id](#).

Get server details

[GET] /v1/gameserver/{server_id}

Get server details by **Server Id**.

Server

All subsequent routes require a **Server API Id** and an active application grant.

[GET] /v1/server/{server_api_id}/info

Get general information about the registered server

[GET] /v1/server/{server_api_id}/statistics

Get server statistics

[GET] /v1/server/{server_api_id}/GSM/list

Get full player list

[POST] /v1/server/{server_api_id}/kick

Kick a player

Parameter	Value	Status
gamesession_id	An active gamesession id (See /v1/server/{server_api_id}/GSM/list for details)	Required
reason	Reason length: 1-128	Required

Returns 204 on success

[POST] /v1/server/{server_api_id}/message-private

Send a private message to a player

Parameter	Value	Status
gamesession_id	An active gamesession id (See /v1/server/{server_api_id}/GSM/list for details)	Required
content	Message content length: 1-256	Required

Returns 204 on success

[POST] /v1/server/{server_api_id}/message-server

Send a public message to the server

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

Parameter	Value	Status
<code>content</code>	Message content length: 1-256	Required

Returns 204 on success

[POST] `/v1/server/{server_api_id}/raw`

Send a raw RCon command to the server

Parameter	Value	Status
<code>command</code>	Command length: 1-256	Required

Returns 204 on success

[GET] `/v1/server/{server_api_id}/GameLabs/actions`

Retrieve list of all available dynamic actions for designated game server. GameLabs required

Not all games supported

Parameter	Value	Status
-----------	-------	--------

Returns 200 on success

[GET] `/v1/server/{server_api_id}/GameLabs/entities/events`

Retrieve list of all entities of category events. GameLabs required Not all games supported

Parameter	Value	Status
-----------	-------	--------

Returns 200 on success

[GET] `/v1/server/{server_api_id}/GameLabs/entities/vehicle`

Retrieve list of all entities of category vehicles. GameLabs required Not all games supported

Parameter	Value	Status
-----------	-------	--------

Returns 200 on success

[POST] `/v1/server/{server_api_id}/GameLabs/action`

Issue a GameLabs Poll2 style dynamic action remotely GameLabs required Not all games supported

Parameter	Value	Status
<code>actionCode</code>	Action code as defined in local action	Required
<code>actionContext</code>	<code>world</code> or <code>player</code> or <code>vehicle</code> or <code>object</code>	Required
<code>referenceKey</code>	Reference key for entity. Either SteamID 64 or GameLabs key for vehicle, event or none for world context actions	Required
<code>parameters</code>	Parameters populated as defined in local action	Required

Returns 204 on success

[POST] `/v1/server/{server_api_id}/GameLabs/batch-actions`

Issue a GameLabs Poll2 style dynamic action remotely in batches GameLabs required

Not all games supported

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

Parameter	Value	Status	
actions	List of actions. Minimum: 1, Maximum: 10;		
	Parameter	Value	Status
	actionCode	Action code as defined in local action	Required
	actionContext	world or player or vehicle or object	Required
	referenceKey	Reference key for entity. Either SteamID 64 or GameLabs key for vehicle, event or none for world context actions	Required
	parameters	Parameters populated as defined in local action	Required

Returns 204 on success

Queue Priority

[GET] /v1/server/{server_api_id}/queuepriority

Get a list of all queue priority entries

Streamed response

Parameter	Value	Status
cftools_id	CFTools ID	Optional Query Parameter
comment	String	Optional Query Parameter

[POST] /v1/server/{server_api_id}/queuepriority

Create a new queue priority entry

Parameter	Value	Status
cftools_id	A CFTools account id	Required
expires_at	Expiration datetime object or null; Null is a permanent entry	Optional, defaults to null
comment	A note or comment	Required

Returns 204 on success

[DELETE] /v1/server/{server_api_id}/queuepriority

Delete an existing queue priority entry

Parameter	Value	Status
cftools_id	A CFTools account id	Required

Returns 204 on success

Whitelist

[GET] /v1/server/{server_api_id}/whitelist

Get a list of all whitelist entries

Streamed response

Parameter	Value	Status
cftools_id	CFTools ID	Optional Query Parameter

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

Parameter	Value	Status
<code>comment</code>	String	Optional Query Parameter

`[POST] /v1/server/{server_api_id}/whitelist`

Create a new whitelist entry

Parameter	Value	Status
<code>cftools_id</code>	A CFTools account id	Required
<code>expires_at</code> <code>ISO8601</code>	Expiration datetime object or null; Null is a permanent entry	Optional, defaults to null
<code>comment</code>	A note or comment	Required

Returns 204 on success

`[DELETE] /v1/server/{server_api_id}/whitelist`

Delete an existing whitelist entry

Parameter	Value	Status
<code>cftools_id</code>	A CFTools account id	Required

Returns 204 on success

Leaderboard

`[GET] /v1/server/{server_api_id}/leaderboard`

`🕒7/minute`

Request the generation of a leaderboard based on internally kept player stats. This may fail if no stats are present.

Parameter	Value	Status
<code>stat</code>	One of <code>kills</code> <code>deaths</code> <code>suicides</code> <code>playtime</code> <code>longest_kill</code> <code>longest_shot</code> <code>kdratio</code> <code>kdratio_pve</code> <code>kills_infected</code>	Required
<code>order</code>	<code>1</code> (Ascending) or <code>-1</code> (Descending)	Required
<code>limit</code>	An integer between 1 and 100; Defaults to 10	Required

Player

`[GET] /v2/server/{server_api_id}/player` `🕒120/minute`

Individual stats of a player for a server.

Parameter	Value	Status
<code>cftools_id</code>	A CFTools account id	Required

`[DELETE] /v2/server/{server_api_id}/player`

`🕒60/minute`

Reset player statistics for individual player

Parameter	Value	Status
<code>cftools_id</code>	A CFTools account id	Required

Banlist

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes

All subsequent routes require a `Banlist Id` and an active application grant.

Bans

`[GET] /v1/banlist/{banlist_id}/bans`

Get a list of all bans. `Streamed response`

Parameter	Value	Status
<code>filter</code>	Either an IPv4 or a CFTools account id	Optional

`[POST] /v1/banlist/{banlist_id}/bans`

Issue a new ban. `Triggers an in-game kick`

Parameter	Value	Status
<code>format</code>	<code>cftools_id</code> or <code>ipv4</code>	Required
<code>identifier</code>	A CFTools account id or an IPv4; IPv4 may contain wildcard substitutes in form of an asteriks	Required
<code>expires_at</code> <code>ISO8601</code>	Expiration datetime object or null; Null is a permanent entry	Optional, defaults to null
<code>reason</code>	A ban reason	Required

`Returns 204 on success`

`[DELETE] /v1/banlist/{banlist_id}/bans`

Revoke an existing ban

Parameter	Value	Status
<code>ban_id</code>	The ban id of an existing ban	Required

`Returns 204 on success`

Users

Lookup

`[GET] /v1/users/lookup` `🕒20/minute`

Search CFTools Cloud database for a user

Parameter	Value	Status
<code>identifier</code>	Either a Steam64, BattlEye GUID or Bohemia Interactive UID	Required

Error codes

Status code	Error text	Meaning
400	<code>invalid-method</code>	The HTTP method is not supported by this route.
400	<code>parameter-required</code>	A required parameter was not supplied. Check response for details.
400	<code>failed-type-validation</code>	A supplied argument failed the type validation. Check response for details.

		Status code	Error text	Meaning
Introduction		400	invalid-option	The supplied option is not available for the selected route. Check response for details.
Server Id		400	max-length-exceeded	The supplied argument exceeded the allowed length for this parameter. Check response for details.
Authentication		400	min-length-too-small	The supplied argument undercut the required length for this parameter. Check response for details.
Grant process and access		400	length-mismatch	The supplied argument did not match the required length of the parameter. Check response for details.
Game-Server		400	duplicate	The attempted creation of an entity failed as the same or a similar entity already exists.
Server		401	login-required	This route requires you to supply an authentication token.
Banlist		403	token-regeneration-required	The supplied token has been invalidated and must be regenerated.
Users		403	bad-secret	The supplied secret does not match the current application secret.
Error codes		403	bad-token	A token parameter does not match the request identity.
		403	expired-token	The supplied token exhausted its 24 hour lifetime.
		403	invalid-api-key	The supplied API key is invalid.
		403	no-grant	You were not granted access to request this resource. See grant flow.
		404	not-found	The requested route did not match any known routes.
		404	invalid-resource	The requested resource by the supplied id could not be found.
		404	invalid-bucket	The resource has been found, but the action could not be executed as the respective bucket was not been found or was not configured.
		404	invalid-bucket	The resource has been found, but the action could not be executed as the respective bucket was not been found or was not configured.
		429	rate-limited	You have exceeded the allowed rate limit for this route.
		500	unexpected-error	An internal error occurred. Should this error persist, contact CFTools Cloud support with the supplied <code>request_id</code> .
		500	timeout	The requested action timed out and must be retried.
		500	system-unavailable	The requested service could not be reached. You must re-attempt your request.

Introduction

Server Id

Authentication

Grant process and access

Game-Server

Server

Banlist

Users

Error codes