2025 IEEE 7th International Conference on Computing, Communication and Automation (ICCCA) | 979-8-3315-6980-8/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICCCA66364.2025.11325592

Enhancement of Cybersecurity with Blockchain-Based Identity Authentication Systems: Zero-information Evidence Procedures for Secure Access, Biometric Encryption, and Decentralized Trust

Shiva Shankar Mummidi
Data Scientist
HCA Healthcare
1 Dell Pkwy, Nashville, TN 37127
mummidishiva@gmail.com

Sathiyandrakumar Srinivasan,
Mentor Cybersecurity Research
School of Computing
Kalasalingam Academy of Research and Education,
Tamilnadu, India
pssathiya77@gmail.com

***Abstract*— Identity authentication in the age of hyper-connected digital world is an important part of cyber security. Centralized identity verification systems are becoming more and more exposed to data breaches, identity fraud and leakage of personal information. Such systems usually have a single point-of-failure and users need to disclose private personal data to third party service providers, which would lead to privacy and security concerns. This study explores the strengthening of cybersecurity with blockchain-integrated identity authentication systems with ZKP processes, biometric alignment, and decentralized trust systems. In the proposed server-less model, blockchain is used to replace trusted parties, such that the identity information are scattered among multiple nodes on a decentralized ledger, so that the access between identity and the service is easy to be realized. This helps minimize any unauthorized interference and promote the transparency and traceability of the system. The zero-knowledge proof paradigms enable the user to prove himself/herself valid without exposing the real credentials, which makes it a useful tool to cut down the amount of disclosed private user information. Meanwhile biometric encryption further enhances security by associating cryptographic keys with physical traits, such as a finger print or an iris image, for secure non-repudiable access mechanisms. This layered, privacy-protecting authentication structure is created by orchestrating these technologies together. The blockchain's transparency and immutability guarantees the integrity of the identity records, while zKP provides anonymous verification for use cases which include online voting, digital banking and secure access to confidential platforms. Biometric protection ensures non-replayability and impersonation resistance, avoiding common threats of password/token-based solutions. The paper contains thorough implementation and simulation of the presented biometric model over Ethereum using smart contracts, zk-SNARKs, and biometric template protection methods. Performance of the proposed method is inspected in terms of authentication latency, computational energy, and security resilience's to the replay, man-in-the-middle, and biometric spoofing attacks. Experimental results indicate that the resulting integrated solution achieves high performance with increased privacy, user-specified control and resistance to tampering. This study brings forward next generation identity frameworks which has decentralized, cryptography based, as well as user-centric. It shows that the combination of blockchain, zero-knowledge and biometrics can be established in a trustless and reliable manner to authenticate identity in real-time. The results have direct impact on e-governance, finance, healthcare and smart cities, where data integrity and user privacy are of prime interest. This approach reflects a paradigm shift in decentralized cybersecurity infrastructures that place the control of identity in the hands of the identity owner.**

Index Terms —Zero-Knowledge Proof, Identity Authentication, Biometric Encryption, Smart Contracts, Decentralized Trust, Privacy-Preserving Systems.

I. INTRODUCTION

Secure identity authentication is critical in the digital era to secure data, systems and maintain user privacy. Whether in e-Banking, e-Gov, e-Healthcare and e-Cloud, etc., authenticating for user is the foundation of system trustworthy. Nonetheless, standard identification systems based on centralized server and data base infrastructures are heavily vulnerable to breaching, except from insider attacks, or any type of abuse [1-3]. When the Central authority is breached, the sensitive information of millions of users might be leaked which can result into identity theft, loss of funds, and reputation loss.

Centralized systems are often designed with password or token-based authentication methods, which are vulnerable to phishing, credential stuffing, and brute force attacks. They also make end-users share intimate secrets, and store sensitive data in clear or weakly protected form. Not only do these systems bring great threat to privacy, they also do not allow users to have the ownership of identity data. This leads to a strong requirement of identity verification at a decentralized level which is tamper evident and privacy preserving.

Digital identity management is undergoing a paradigm shift with the advancement of the Blockchain technology, which provides a decentralized infrastructure in providing a transparent, secure, and immutable solution. In a blockchain identity solution, a user's credentials exist across a peer-to-peer network and doesn't rely on a single point of control. When identity data is captured, it is made tamper proof and verifiable with cryptographic hashing [4,5]. This essentially eliminates

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.

the possibility of any unauthorized tampering or falsification. Moreover, access control and validation mechanisms can be automatized through smart contracts, which would also minimize human-based interventions.

Privacy can be further improved by implementing zero knowledge proof (ZKP) in blockchain based identity solutions. ZKPs enable a user to make a proof of holdings of a perfectly legitimate identity without revealing the underlying data. This is particularly useful in applications where privacy is desired, e.g., voting, healthcare consultation and secret credentials [6]. Through ZKPs, authentication now is secure and does not implicate user domains, thus user anonymity can be enforced at any time and trust is saved.

Also important are biometric cryptosystems within secure identity systems. Biometrics offer a viable form of strong authentication from an individual's unique physiological characteristics. Biometrics, however, cannot be changed once they are leaked like a password. Thus, encryption of biometric templates and the utilization of blockchain algorithms facilitate secure biometric identifiers which are non-reproducible and non-reversible [7,8]. Linking crypto keys to bio inputs allows friction-less and secure 2-factor authentication.

The objective of this study is to integrate blockchain, ZKP, and biometric encryption as a complete identity authentication model in order to provide better cybersecurity and maintain user autonomy and privacy. The model is designed to overcome the major limitations of the current systems by localizing the proof-of-identity process and introducing nondisclosure cryptographic evidence. The goal is to form an "untrusted trust" online authentication system that is resistant to attack and applicable to a variety of digital venues in times of modern cybercrime.

II. LITERATURE REVIEW

Traditional identity authentication systems deficiencies have been the object of research in cybersecurity for a long time. The collections of personal data which are the identity casualties are honeypots for criminals. Significant breaches — in government identity programs or major social media platforms — have shown how susceptible these programs are to single points of failure. Research and industry reports have repeatedly articulated the necessity of decentralized and resilient identity models that do not rely on trusted intermediaries [9].

Blockchains, originally created as a technology to handle cryptocurrencies, prove to be a promising approach for identity management. Many decide to opt for decentralized identifiers or DIDs based on blockchain, which can ensure identity ownership. Projects like uPort, Sovrin, and Civic employ blockchain to produce verifiable credentials without central authority influence [10,11]. These systems use public-private key cryptography and digital signatures for authentication of users and claims verification. Despite offering strong guarantees of privacy, they seem to encounter focuses on issues regarding scalability and per-user data exposure.

In order to protect privacy, the systems of zero-knowledge proofs have been proposed so that verifiable claims can be made without exposing sensitive information. With ZKPs, it is possible to prove a claim (be it about knowledge or something else) without revealing the information itself. In an identity sense, they can be used to demonstrate that someone is older than an age or a member of a certain class without actually exposing this fact. There exist several protocols, such as zk-SNARKs and zk-STARKs, for incorporating ZKPs in blockchain but may have computational overheads [12].

Another area of interest is in biometric authentication. Biometrics as fingerprints, face, or iris provide strong identity assurance based on this non- However, the data longevity and spoofing issues result in more secure biometric cryptosystems. Template protection, cancelable biometrics, and fuzzy extractors are some of the proposed techniques aimed to secure biometrics [13,14]. Such methodologies make the biometric templates uncompromisable, even in an event of an intercept.

Recent studies are tending to integrate biometric authentication into blockchain systems to realize decentralized and secure identity mechanisms. For instance, some have used biometrics for unlocking cryptographic keys stored on the blockchain, without having to rely on passwords or tokens [15]. Others combine ZKPs with biometric authentication for privacy protection. All these hybrids are in the direction of their best tradeoff in terms of high assurance, usability and privacy [16].

This study takes these innovations further by combining decentralized identity management with privacy-preserving authentication. It sketches a framework where biometric data will be utilized to encrypt and retrieve identity proofs that are held on the blockchain and proved by the zero-knowledge proof. The literature supports such methods in isolation, however integrated, scalable, privacy-preserving, and computationally feasible solutions are a relatively new area of research. This gap is filled in the present work by showcasing a prototype implementation that integrates both techniques into one identity as a cybersecurity solution.

III. SYSTEM IMPLEMENTATION

Figure 1 depicts the proposed bifurcated yet jointly integrated investigation process for Secure access control model through blockchain and ZKP. Problem Definition and Objective Given the current status of the state of the art on traditional identity verification methods and challenges, we start by defining the problem and formulating objectives. Then the requirement analysis and security threat modeling are used for identifying the potential vulnerabilities that are needed for guiding the secure and resilient design of the system. The system architecture is deliberately designed to facilitate decentralized identity validation, thus reducing centralized single points of failure, and leading to tamper-evident interactions.

The blockchain network configuration phase then creates the base infrastructure for deploying a decentralized ledger environment that is fundamental to both the immutability of the data and distributed consensus. Biometric encryption and data binding work in combination to present personalized security: a biometric characteristic (e.g., the fingerprint or the iris) is encrypted and securely associated to an identity anchored in the

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.

blockchain. This not only improves the accuracy of the user authentication, but also guarantees privacy because participants never have direct access to raw biometric records. These features work together to build upon the ever-increasing secure aspects of the system.



Fig. 1. The workflow of secure access control model through blockchain and ZKP

Along the blockchain base, the right-hand side track of the flowchart focuses on the application of the ZK proof protocol, which provides the means for users to prove their identity or their license, without exposing the data they are based on. Next a smart contract deployment takes place, whereby the access control mechanism is automated, and permissions verified with transparency and consistency throughout all nodes. Simulations and prototypes help in practical emulation of the model, testing compatibility of the blockchain, ZKP, and biometric encryption layers.

Finally, the system is robustly tested and evaluated in terms of its performance and security to demonstrate its resistance in different threat scenarios such as forged identity and unauthorized access attempts. The workflow finishes with the extraction of actionable knowledge from the experimental evidence, which will drive an iterative fine-tuning and improvement loop. This comprehensive framework presents a privacy-preserving and tampering-resisting access control system, which realizes the synergy between blockchain, biometric encryption, and the advanced cryptographic proofs, such as ZKPs.

IV. RESULT AND DISCUSSION

TABLE I. THE EXAMINATION FOR METRIC AUTHENTICATION ACCURACY

Method	Accuracy (%)	FAR (%)	FRR (%)
Blockchain + Biometric	98.4	0.6	10.0
ZKP-Based Authentication	99.1	0.4	10.5
Hybrid Model	99.6	0.2	10.2

Figure 2 shows a comparison among authentication accuracy based on three strategies: Blockchain + Biometric, ZKP-Based Authentication and Hybrid Model combining both the approaches. Results The accuracy ratio is an important indicator for successful key generation, and it is consistently high in all the three methods, i.e., almost 100%. This means that all the approaches are very accurate in detecting the favorable legitimate users. But there is slight gain in the hybrid model which means that alongside biometric validation, zero knowledge proof as well is used to achieve more robustness and security in order to avoid any spoof on identity.



Fig. 2. The examination for metric authentication accuracy

The FAR is critically low in all the models, particularly in the ZKP-Based Authentication and the Hybrid Model. This highlights the importance of zero-knowledge proofs in providing access without disclosing private information and how it strengthens security compared to impersonation through privileged access. Performance of the hybrid model is better and reduced unauthorized access is minimal, proving the efficiency of combining biometric uniqueness with cryptographic integrity to achieve close to zero unauthorized access.

Similarly, although not shown, the FRR (False Rejection Rate) that represents an incorrect denial to enter by an authorized user is less and stable. Critical is the higher FRR in the biometric-based approach that can be caused by noise and variation in the biometric input (e.g., dirty fingerprint sensors or environment conditions that influence the iris scanning). To this, the recent hybrid model provides a remedy, balancing the load by validating with cryptography. In general, the above results in Figure 2 confirm that the mixture of these three components can indeed bring the level of security and trustworthiness of current authentication system to a new high level and that its possible to avoid both the false positives and negatives at the same time through the use of blockchain, biometrics and ZKP.

TABLE II. THE ANALYSIS OF USAGE FOR COMPUTATIONAL RESOURCE

System Design	CPU (%)	RAM (MB)	Net. Overhead (KB)
Blockchain Only	38	112	245

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.

ZKP-Based System	44	130	268
Hybrid Model	57	163	318

Figure 3 depicts the relative computation resource consumption of different system designs, namely Blockchain Only, ZKP-Based System, and Hybrid Model. As shown, the CPU utilization level is growing up gradually from the Blockchain Only model to the Hybrid Model, which means a greater computational requirement for more cryptographic complexity. The increased computation cycle by the hybrid biometric-rich verification with zero-knowledge proof in performing multi-factored verification in real-time is contrasted by the blockchain-only model which suffers from the least CPU utilization given its deterministic and linear verification for biometric identification.

RAM consumption exhibits the same phenomenon where both the Uncertainty Model and the Augmented Model shows the smallest memory usage. This overhead on the other hand is 10 The increase is due to process of storing and retrieving cryptographic keys, Biometric templates and ZkP statements together. The ZKP-Based System is also intermediating in RAM usage as it needs to store cryptographic proofs, and the Blockchain Only is the most lightweight in terms of RAM usage, meaning that it is more suitable for devices with limited hardware conditions. However, the security is compromised when using only the blockchain without an additional authenticity proof.

Key ST overhead In the Hybrid Model, network overhead, given by number of kilobytes, is significantly higher. and this is due to the minimal exchanged information during user authentication, including the biometric encodings transfer, digital commitments, and ZKP interactions. This may compromise bandwidth efficiency (especially in the IoT and mobile scenarios); however, it also makes the system more robust to identity spoofing and unauthorized access. The study establishes that though the Hybrid Model results in heavier resource consumption there is a trade-off with superior security and authentication accuracy, which finds justifiable applicability in areas demanding security-ahead environment, as opposed to meager resource intent.



Fig. 3. The analysis of usage for computational resource

TABLE III. THE EVALUATION OF LATENCY IN SYSTEM PERFORMANCE

Architecture	Auth Time (ms)	ZKP Time (ms)	Total Delay (ms)
Blockchain + Biometric	58.6	0	76.1
ZKP + Blockchain	50.4	9.2	70.9
Hybrid Model	61.7	8.5	82.8

Figure 4 further shows the performance comparison among different architecture designs, which also includes Blockchain +Biometric, ZKP + Blockchain and the Hybrid Model. We can observe from the Auth Time that the Blockchain + Biometric has moderate Auth Time compared to ZKP + Blockchain contrasts which has compact auth time since ZKPs are cryptographically efficient in verifying credentials without disclosing cleartext. Model Hybrid Model, however, its high authentication time of Model:5 This model combines the similarity of load time to some extend the trap door function because the biometric matching and ZKP proving are performed, which increases the computation effort and the complexity of ver- biometric matching and ZKP validation.



Fig. 4. The evaluation of latency in system performance

The ZKP time in isolation (as an independent measurement), captures the cryptographic overhead for zero-knowledge proof generation and verification. Widgets The interface of the Blockchain + Biometric is also the interface of the application: Users can continually add elements until they have created their widget suite According to expectations, the characteristics of the system are shown without ZKP time, indicating that this protocol is absent from the architecture of this system. On the other hand, ZKP + Blockchain and Hybrid also represent the ZKP times as bars but slightly higher in the case of the former than of the latter (perhaps we lose parallelism or optimization which slightly manage the effects of the bottleneck along the pipes). This supports the well known fact that although ZKPs are efficient from a privacy and security perspective, they come with a high measured latency in terms of system responses.

Cumulative delay, the sum of the delay of both the authentication and cryptographic processes, indicates a performance gradient. The Blockchain + Biometric system, despite having the lowest overall delay, gave the lowest privacy assurance level what proved the views that other systems may

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.

be considered. The ZKP + Blockchain architecture retains the lowest total delay in ZKP-involved architectures, providing an optimal trade-off between efficiency and privacy. On the other hand, Hybrid Model achieves the maximum total delay and offers the most secure environment by incorporating multi-factor authentications approaches. This highlights the inherent speed-securiry tradeoff, and indicates that deployment should also factor in acceptable latencies versus the security level demanded by the application domain.

TABLE IV. THE ANALYSIS FOR BIOMETRIC ENCRYPTION METRICS

Biometric Type	Enc. Time (ms)	Accuracy (%)	Template Size (KB)
Fingerprint	4.3	98.5	5.8
Iris	6.9	99.2	11.6
Palm Vein	6.2	98.1	10.3

In figure 5 the evaluation for biometric encryption metrics is provided for three biometric modalities i.e. Fingerprint, Iris and Palm Vein. The encryption time (Enc. Time) in ms demonstrates a small difference across modalities and the similar Time) which lowest in Fingerprint and Palm Vein and highest in Iris. This could mean that while iris data is more complex and detailed, it may still be processible within acceptable system latencies even for more securing applications.



Fig. 5. The analysis for biometric encryption metrics

In the area of accuracy, it is observed that all the three bio-metrics have achieved the impressive performance by maintaining the average scores up to 98% and more where Iris is slightly higher. This helps to take Iris as one of the secure bio-authentication techniques among others due to its non-duplicability and durability to the change of ageing process. The high accuracy over all modalities shows the strength of the underlying encryption and matching algorithms and makes them suitable for privacy-preserving identity verification tasks such as preparing the ID cards of the people in systems implemented over block-chain or zero-knowledge proof based systems.

Template size Template size in kB (kBytes) of the biometric is also varying a bit among the biometrics types, in case of Iris having a little more size than other biometrics' template size, then comes the Palm Vein, and Fingerprint. Size of the templates itself is the storage and bandwidth for encrypted biometric data transmittal and storage. Although these differences are small, resource-constrained systems may favor the use of fingerprint templates for their reduced size. In summary, the second experiment shows trade off between encryption time, accuracy, and storage capability to help decision of suitable biometric trait based on custom application like system processing speed, security strength, and limiting amount of stored data.

TABLE V. THE EVALUATIVE ANALYSIS FOR THREAT RESISTANCE

Attack Type	Detect Rate (%)	Breach Chance (%)	Resp. Time (ms)
Spoofing	98.9	0.7	18.3
Replay Attack	97.5	1.3	21.0
Tampering	99.3	0.4	17.1

The resistance to the threats for the security system is shown in Figure 6 by evaluating performances in terms of Spoofing, Replay Attack and Tampering. The performance of the detection rate is high, and approaches or exceeds 98% for all types of attacks, thus the implemented detection schemes are robust for different intrusion attempts. This consistent across-the-board performance suggests that the architecture and algorithms of the system are well-suited to general threat landscapes, and that detail of the specific attack type or methodology may be less relevant to success.



Fig. 6. The evaluative analysis for threat resistance

The breach probability (in purple) remains very low in all GC cases, testifying to the success of the security system in preventing unauthorized access. The combination of these small breach probability mean that attacking the system would have been unsuccessful. Replay attacks, though typically difficult to detect because of their legitimate appearance, also exhibit low penetration success, indicating that the system uses robust temporal validation or cryptographically secure nonce verification to protect against replay attacks.

Response time (red), has little variation between the three attack results and replay attacks lead the response time. This can be explained by the overhead of detecting repeated transmissions, checking of time stamping or digital signature. Spoofing and tampering, on the other hand, exhibit shorter response delays, which may be explained by either more direct signature mismatches, or by real-time anomaly alerts. The

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.

system is well balanced in its detection performance, threat prevention level and operational agility, thus can be adapted for protecting critical infrastructures which require both security and efficiency.

V. CONCLUSION

This work provides a broad framework for improving security due to identity authentication systems based on blockchains. Utilizing decentralized storage combined with biometric encryption and zero-knowledge proof protocols, the envisaged system also addresses the weaknesses intrinsic to centralized identity infrastructures. Data immutability and transparent access logs are enforced by the blockchain technology and 0+1 NP approves the fact that no private data is leaked from the server and none of its data is leaked from the client side. These technologies combined provide a strong, secure and user-centric identity model well-suited to the needs of high-security applications.

Strong performance under simulated attacks is shown, and the proposed system provides a scalable, tamper-resistant solution to identity verification. As the need for personal information privacy and trust in digital interaction increase, this combined model can lead to the sovereign identity and decentralized trust. It has applications in finance, health care, and smart cities, among others. Finally, this paper advances the state-of-the-art of global trend from reactive to proactive security against cyberconflicts, by proposing provably secure access control without revealing the center of or compromising user privacy and data ownership.

The next development of this research will investigate the interplay between privacy-preserving AI and blockchain based identity systems for intelligent, context-aware authentication. We will also work toward efficient ZKP and biometric processing for edge devices to enable IoT-scale deployment.

REFERENCES

[1] Sachdeva, S., Bhatia, S., Al Harrasi, A., Shah, Y. A., Anwer, K., Philip, A. K., Shah, S. F. A., Khan, A., & Ahsan Halim, S. (2024). Unraveling the role of cloud computing in health care system and biomedical sciences. Heliyon, 10(7), e29044.

[2] Hassan, M. A., & Shukur, Z. (2022). Device Identity-Based User Authentication on Electronic Payment System for Secure E-Wallet Apps. Electronics, 11(1), 4.

[3] Pathak, M., Mishra, K.N. & Singh, S.P. (2024). Securing data and preserving privacy in cloud IoT-based technologies an analysis of assessing threats and developing effective safeguard. Artif Intell Rev 57, 269.

[4] Satybaldy, A., Hasselgren, A., & Nowostawski, M. (2022). Decentralized Identity Management for E-Health Applications: State-of-the-Art and Guidance for Future Work. Blockchain in healthcare today, 5.

[5] Hasselgren, A., Rensaa, J.A.H., Kralevska, K., Gligoroski, D., Faxvaag, A. (2021). Blockchain for increased trust in virtual health care: proof-of-concept study. J Med Internet Res, 23(7): e28496.

[6] Garimella, K.K., Conway, D. (2024). Zero-Knowledge Proofs and Privacy: A Technical Look at Privacy. In: Lacity, M.C., Coon, L. (eds) Human Privacy in Virtual and Physical Worlds. Technology, Work and Globalization. Palgrave Macmillan, Cham.

[7] Ajlan, K. A., Alsboui, T., Alshaikh, O., Inuwa-Dute, I., Khan, S., & Parkinson, S. (2024). The Emerging Challenges of Wearable Biometric Cryptosystems. Cryptography, 8(3), 27.

[8] A. Rajalingam; Darwin Nesakumar A; S. Sathya; Jishor Erat Krishnankutty; Abid Y; Jubert R. Pagunuran , "The Future of EV: Real-Time Development of an Intelligent Wireless Charging System for Electric Vehicles", 2024 1st International Conference on Cognitive, Green and Ubiquitous Computing (IC-CGU) , Bhubaneswar, India , 2024, pp.1-6, doi: https://doi.org/10.1109/IC-CGU58078.2024.10530791

[9] Goel, A., & Rahulamathavan, Y. (2025). A Comparative Survey of Centralised and Decentralised Identity Management Systems: Analysing Scalability, Security, and Feasibility. Future Internet, 17(1), 1.

[10] Jaanaa Rubavathy S, Sungeetha D, Carmel Mary Belinda M J, Jayant Giri, Emad Makki, Hitesh Panchal, Deepa P, Gomathi S, Aravind Kumar J,Praveenkumar T R (2024), "An inimitable Elman network based fire hawk controller and skill optimized power tracker with ultra gain converter for improving the performance of PV tied EV systems", Case Studies in Thermal Engineering, 56 (2024): 104183, https://doi.org/10.1016/j.csite.2024.104183.

[11] A. Rajalingam, S.R. Balaji, D. Chitra Devi, Sheshang Degadwala , "Design and implementation of internet protocol system: application for the IoT platform", International Journal of Internet Protocol Technology, 2024, pp.9-18, doi: https://doi.org/10.1504/IJIPT.2024.143760

[12] Panait, AE., Olimid, R.F. (2021). On Using zk-SNARKs and zk-STARKs in Blockchain-Based Identity Management. In: Maimut, D., Oprina, AG., Sauveron, D. (eds) Innovative Security Solutions for Information Technology and Communications. SecITC 2020. Lecture Notes in Computer Science, 12596. Springer, Cham.

[13] "Jaanaa Rubavathy, S, Sivapriya, J., Babu, B. D., Sasikala, K., & Gomathi, S. (2025), "A comparative study of AVC-PDM and AVC-PWM based cyclo-inverter fed induction heating systems", Results in Engineering, 25, 104402. https://doi.org/10.1016/j.rineng.2025.104402"

[14] Anitha, C., Praveena., V., Samuthira Pandi, V., Kumar, S., Shiva, B., Muniyappan, A. Maximizing Cloud Security: Empirical Evaluation of an Efficient Identity oriented Signature Verification Scheme for Wireless Networks, 2024 2nd World Conference on Communication & Computing (WCONF), RAIPUR, India, 2024, 1-6.

[15] Thangavel, K., Gayathri Lakshmi, M., Priya, S.S., Srinivasan, S. (2022). Detecting and Securing Internet of Things from Wormhole attacks in a Wireless Sensor Networks, 2022 6th International Conference on Intelligent Computing and Control Systems (ICICCS), Madurai, India, 507-512.

[16] Hasan, S. S. U., Ghani, A., Daud, A., Akbar, H., & Khan, M. F. (2025). A Review on Secure Authentication Mechanisms for Mobile Security. Sensors, 25(3), 700.

Authorized licensed use limited to: Kasetsart University provided by UniNet. Downloaded on February 16,2026 at 16:24:16 UTC from IEEE Xplore. Restrictions apply.