Parallel Self-Assembly under Uniform Control Inputs

Sheryl Manzoor, Sam Sheckman, Hoyeon Kim, Jarrett Lonsford, Minjun Kim, and Aaron T. Becker

Abstract—We present fundamental progress on parallel self-assembly using large swarms of micro-scale particles in complex environments, controlled not by individual navigation, but by a uniform global, external force with the same effect on each particle. Consider a 2D grid world, in which all obstacles and particles are unit squares, and for each actuation, robots move maximally until they collide with an obstacle or another robot. We present algorithms that, given an arbitrary 2D structure, designs an obstacle layout. When actuated, this layout generates copies of the input 2D structure. We analyze the spatial and time complexity of the factory layouts. We present hardware results on both a macro-scale, gravity-based system and a milliscale, magnetically actuated system.

I. INTRODUCTION

One of the exciting new directions of robotics is the design and development of micro- and nanorobot systems, with the goal of letting a massive swarm of robots perform complex operations in a complicated environment. Due to scaling issues, individual control of the involved robots becomes physically impossible: while energy storage capacity drops with the third power of robot size, medium resistance decreases much slower. As a consequence, current micro- and nanorobot systems with many robots are steered and directed by an external force that acts as a common control signal [1]–[7]. These common control signals include global magnetic or electric fields, chemical gradients, and turning a light source on and off.

A. Selective Control with Global Inputs

Clearly, having only one global signal that uniformly affects all robots at once poses a strong restriction on the ability of the swarm to perform complex operations. This control symmetry can be broken using interactions between the robot swarm and obstacles in the environment. The key challenge is to establish if interactions with obstacles are sufficient to perform complex operations, ideally by analyzing the complexity of possible logical operations. In previous work [8]–[10], we were able to demonstrate how a subset of logical functions can be implemented; however, devising a fan-out gate (and thus the ability to replicate and copy information) appeared to be prohibitively challenging. In this paper, we resolve this crucial question by showing that only using unit-sized robots is insufficient for achieving






Fig. 1. (a) A milli-scale magnetic based prototype. (b) A seven tile factory. Each particle is actuated simultaneously by the same global field. The factory is designed so each clockwise control input assembles another component.

computational universality. Remarkably, adding a limited number of domino-shaped objects *is sufficient* to let a common control signal, mobile particles, and unit-sized obstacles simulate a computer. While this does not imply that large-scale computational tasks should be run on these particle computers instead of current electronic devices, it establishes that future nano-scale systems are able to perform arbitrarily complex operations *as part of the physical system*, instead of having to go through external computational devices.

B. Model

This paper builds on the techniques for controlling many simple robots with uniform control inputs presented in [8]–[10], using the following rules:

- 1) A planar grid *workspace* W is filled with a number of unit-square robots (each occupying one cell of the grid) and some fixed unit-square blocks. Each unit square in the workspace is either *free*, which a robot may occupy or *obstacle* which a robot may not occupy. Each square in the grid can be referenced by its Cartesian coordinates x = (x, y).
- 2) All robots are commanded in unison: the valid commands are "Go Up" (u), "Go Right" (r), "Go Down" (d), or "Go Left" (l).
- 3) Robots all move in the commanded direction until they
 - a) hit an obstacle
 - b) hit a stationary robot.

^{*}This work was supported by the National Science Foundation under Grant No. [IIS-1553063] and [IIS-1619278].

S. Manzoor and A. Becker are with the Department of Electrical and Computer Engineering, University of Houston, Houston, TX 77204 USA {smanzoor2, jlonsford, atbecker}@uh.edu S. Sheckman, H. Kim and M. Kim are with Lyle School of Engineering, Southern Methodist University, Dallas, TX 75205 USA {sheckel, hoyeonk, mjkim}@uh.edu

c) share an edge with a compatible robot

If a robot shares an edge with a compatible robot the two robots bond and from then on move as a unit. A move sequence m consists of an ordered sequence of moves m_k , where each $m_k \in \{u,d,r,l\}$ A representative move sequence is $\langle u,r,d,l,d,r,u,\ldots \rangle$. We assume the area of W is finite and issue each command long enough for the robots to reach their maximum extent.

II. RELATED WORK

Our efforts have similarities with *mechanical computers*, computers constructed from mechanical, not electrical components. For a fascinating nontechnical review, see [11]. These devices have a rich history, from the *Pascaline*, an adding machine invented in 1642 by a nineteen-year old Blaise Pascal; Herman Hollerith's punch-card tabulator in 1890; to the mechanical devices of IBM culminating in the 1940s. These devices used precision gears, pulleys, or electric motors to carry out calculations. Though our GRID-WORLD implementations are rather basic, we require none of these precision elements—merely unit-size obstacles and particles.

A. Sliding-Block Puzzles

Sliding-block puzzles use rectangular tiles that are constrained to move in a 2D workspace. The objective is to move one or more tiles to desired locations. They have a long history. Hearn [12] and Demaine [13] showed tiles can be arranged to create logic gates, and used this technique to prove PSPACE complexity for a variety of sliding-block puzzles. Hearn expressed the idea of building computers from the sliding blocks—many of the logic gates could be connected together, and the user could propagate a signal from one gate to the next by sliding intermediate tiles. This requires the user to know precisely which sequence of gates to enable/disable. In contrast to such a hands-on approach, with our architecture we can build circuits, store parameters in memory, and then actuate the entire system in parallel using a global control signal.

B. Other Related Work on Programmable Matter

Clearly there is a wide range of interesting scenarios for developing approaches to programmable matter. One such model is the *abstract Tile-Assembly Model* (aTAM) by Winfree [14]–[16], which has sparked a wide range of theoretical and practical research. In this model, unit-sized pixels ("tiles") interact and bond with the help of differently labeled edges, eventually composing complex assemblies. Even though the operations and final objectives in this model are quite different from our particle computation with global inputs (e.g., key features of the aTAM are that tiles can have a wide range of different edge types, and that they keep sticking together after bonding), there is a remarkable geometric parallelism to a key result of our present paper: While it is widely believed that at the most basic level of interaction (called *temperature 1*), computational universality




Fig. 2. Any polyomino can be constructed with two compatible robot species.

cannot be achieved [17]–[19] in the aTAM with only unitsized pixels, very recent work [20] shows that computational universality can be achieved as soon as even slightly bigger tiles are used. This resembles the results of our paper, which shows that unit-size particles are insufficient for universal computation, while employing bigger particles suffices

III. THEORY

Two design factories that build arbitrary 2D shaped polyominos, we first assign species to individual tiles of the polyomino, next discover a build path, then iteratively build factory components that add each tile to partially assembled polyomino.

A. Arbitrary 2D shapes require two particle species

A *polyomino* is a 2D geometric figure formed by joining one or more equal squares edge to edge. Polyominoes have four-point connectivity.

Lemma 1: Any polyomino can be constructed using just two species

Proof: Label a grid with an alternating pattern like a checkerboard. Any desired polyomino can be constructed on this checkerboard, and all joints are between dissimilar species. An example shape is shown in Fig. 2.

The sufficiency of two species to construct any shape gives many options for implementation. The two species could correspond to any gendered connection, including electric charge, ionic charge, magnetic polarity, or hook-and-loop type fasteners.

B. Complexity Handled in This Paper

Different 2D part geometries are more difficult to construct than others. Fig. 3 shows three parts of varying complexity. The part of the left is shaped as a '#' symbol. Though it has an interior hole, any of the 16 particles could serve as the seed particle, and the shape could be constructed around it. The second shape is a spiral, and must be constructed from the inside-out. If the outer spiral was completed first, there would be no path to add particles to finish the interior because added particles would have to slide past compatible particles. Increasing the number of species would not solve this problem, because there is a narrow passage through the spiral that forces incoming parts to slide past the edges of all the bonded particles.




Fig. 3. Polyomino parts. Difficulty increases from left to right. The rightmost part cannot be built by additive construction.

The third shape on the right is two mirrored spirals that are connected. This part cannot be assembled by adding one particle at a time, because each spiral must be constructed from the inside-out. Instead, this part must be divided into sub-assemblies that are each constructed, and then combined.

A polyomino is said to be *column convex* if each column has no holes. Similarly, a polyomino is said to be row convex if each row has no holes. A polyomino is said to be *convex* if it is row and column convex.

Lemma 2: Any convex polyomino can be constructed by adding one particle at a time

Proof: Select any pixel as the *seed block*, or root node. Perform a breadth-first search starting at the seed block, labelling each block in the order they are expanded. Constructing the shape according to the ordering ensures that the polyomino is convex at every step of construction.

The proof of 2 assumes the existence of fixtures for assembly.

Some non-convex polynominos cannot be constructed one particle at a time, as illustrated in Fig. 3. For instance, a polynomino consisting of a clockwise and a counterclockwise square spiral, joined at the ends with a gap of one unit between the spirals must be constructed by first assembling each spiral, and then combining the sub assemblies.

C. Discovering a Build Path

Algorithm 1 FINDBUILDPATH(**P**)

 \mathbf{P} is the x, y coordinates of a 4-connected polyomino. Returns \mathbf{C} , \mathbf{c} and \mathbf{m} where \mathbf{C} contains sequence of polyomino coordinates, \mathbf{c} is a vector of color labels and \mathbf{m} is a vector of directions.

```
1: \mathbf{C} \leftarrow \{\}, \mathbf{c} \leftarrow \{\}, \mathbf{m} \leftarrow \{\}
 2: for m \leftarrow 1, m \leq |\mathbf{P}| do
            \mathbf{C} \leftarrow \mathsf{DEPTHFIRSTSEARCH}(\mathbf{P}_m, \mathbf{P})
 3:
            if \{\} \neq C then
 4:
                  c \leftarrow LabelColor(P)
 5:
                  \mathbf{m} \leftarrow \mathsf{CHECKPATHTILE}(\mathbf{C}, \mathbf{c})
 6:
                  break
 7:
            end if
 8:
 9: end for
10: return \{C, c, m\}
```

D. Assembling Tiles

1) Hopper Construction: Two-part adhesives react when the components mix. Placing the components in separate




Fig. 4. Hopper with delays. The hopper is filled with similarly-labelled robots that will not combine. Every clockwise command sequence $\langle u, r, d, l \rangle$ releases one robot from the hopper.



Fig. 5. A twenty-four tile factory

containers prevents mixing. Similarly, storing many particles of a single species in separate containers allows controlled mixing.

We can design *part hoppers*, containers that store similarly labelled particles. These particles will not bond with each other. The hopper shown in Fig. 4 releases one particle every cycle.

E. Part Assembly Jigs

Algorithm 2 BUILDFACTORY(\mathbf{P}, n)

 ${f P}$ is the x,y coordinates of a 4-connected polyomino. n is the number of parts desired. Returns a two dimensional array ${f F}$ containing the factory obstacles and filled hoppers.

```
1: F ← {}

    b the factory obstacle array

 2: b ← {}
                                                           ⊳ the part being built
 3: \{C, c, m\} \leftarrow FINDBUILDPATH(P)
 4: if \{\} \neq \mathbf{m} then
           for i \leftarrow 1, i \leq |\mathbf{m}|) do
 5:
                 \{\mathbf{A}, \mathbf{b}\} \leftarrow \text{FACTORYADDTILE}(n, \mathbf{b}, \mathbf{m}_i, \mathbf{C}_i, \mathbf{c}_i, 4)
 6:
                 \mathbf{F} \leftarrow \text{ConcatFactories}(\mathbf{F}, \mathbf{A})
 7:
           end for
 8:
 9: end if
10: return F
```

Algorithm 3 FACTORYADDTILE $(n, \mathbf{b}, m, C, c, w)$

```
1: \{\mathbf{hopper}\} \leftarrow \mathsf{HOPPER}(c,n,w)

2: if m = d and (C_y \leq \max \mathbf{b}_y \text{ or } C_y > \min \mathbf{b}_x) then

3: \{\mathbf{A}, \mathbf{b}\} \leftarrow \mathsf{DOWNDIR}(\mathbf{hopper}, \mathbf{b}, \mathbf{C})

4: else if m = l and (C_x \leq \max \mathbf{b}_x \text{ or } C_y > \min \mathbf{b}_y) then

5: \{\mathbf{A}, \mathbf{b}\} \leftarrow \mathsf{LEFTDIR}(\mathbf{hopper}, \mathbf{b}, \mathbf{C})

6: else if m = u and (C_y \leq \min \mathbf{b}_y \text{ or } C_x > \min \mathbf{b}_x) then

7: \{\mathbf{A}, \mathbf{b}\} \leftarrow \mathsf{UPDIR}(\mathbf{hopper}, \mathbf{b}, \mathbf{C})

8: else if m = r and (C_y \leq \min \mathbf{b}_x \text{ or } C_y > \min \mathbf{b}_y) then

9: \{\mathbf{A}, \mathbf{b}\} \leftarrow \mathsf{RIGHTDIR}(\mathbf{hopper}, \mathbf{b}, \mathbf{C})

10: end if

11: return \{\mathbf{A}, \mathbf{b}\}
```




Fig. 6. Running time plotted against number of tiles (N). add max and min bounds, show results for column and row parts and arbitrary parts

IV. ANALYSIS

- A. Running Time
- B. Space Required
- C. Simulation Results

Algorithms 1, 2, and 3 were coded in MATLAB and are available at [21].

This section examines experiments that generate actual running time and space required for different parts.

FIG: xy plot that shows number of tiles on the x-axis, and running time on y-axis.

FIG: xy plot that shows number of tiles on the x-axis, and space required on y-axis. (two lines: vertical space and horizontal space and a line for the best and the worst case bounds from your previous section)



Fig. 7. A large-scale demonstration of particle assembly using gravity as the external force and magnetic attraction between red and blue particles for assembly.




Fig. 8. Experiment

V. EXPERIMENT

- A. Macro-scale, Gravity-Based Prototype
- B. Milli-scale, Magnetic-Based Prototype

A. Experimental setup

In order to demonstrate the algorithm, we developed a magnetic control stage. This stage is to generate a magnetic drag force by moving a permanent magnet. The permanent magnet is able to move x, y direction as following two mail shafts. The permanent magnet has T and the dimension is cm2. The main channel is made up PDMS and it was filled with motility buffer. The alginate microrobot was fabricated using . After the alginate microrobots were located at each chamber in the channel, the experimental channel was located on the center of the stage where a magnet was positioned initially. The stage controller was manipulated by a C++ programming through an Ardunio UNO. The channel was observed by a stereo microscope and the installed camera captured all sequent images (fps). The scheme of system is shown in Fig. . B. Experimental result Using one of construction maps, it is available to




Fig. 9. Fig. Construction of a microrobotic polyomino from four alginate artificial cells. (a) Initial position of alginate microrobots at all chambers, (b) First assemble by two microrobots from two chambers, (c) Final result of construction.

demonstrate the map using multiple alginate microrobots. The initial scene is shown in Fig. (a) and the first assemble was manipulated moving the magnet in a clockwise direction as indicated in Fig. (b). The alginate microrobots moved in the oriented direction until coming into contact with an object. The final completion of a square polyomino is shown in the lower right corner in Fig. (c). In addition, the another polyominoes were simultaneously being manufactured.

VI. CONCLUSION

This work, along with [8]–[10], introduces a new model for additive assembly. Interesting applications will aim at microfluidics work.

Future work could extend Algorithms 1–3 to three dimensions. Parts can be decomposed into subassemblies, which would enable more complex parts to be created and enable construction in logarithmic time.

REFERENCES

- [1] B. R. Donald, C. G. Levey, I. Paprotny, and D. Rus, "Planning and control for microassembly of structures composed of stressengineered MEMS microrobots," *The International Journal of Robotics Research*, vol. 32, no. 2, pp. 218–246, 2013. [Online]. Available: http://ijr.sagepub.com/content/32/2/218.abstract
- [2] P.-T. Chiang, J. Mielke, J. Godoy, J. M. Guerrero, L. B. Alemany, C. J. Villagómez, A. Saywell, L. Grill, and J. M. Tour, "Toward a light-driven motorized nanocar: Synthesis and initial imaging of single molecules," ACS Nano, vol. 6, no. 1, pp. 592–597, Feb. 2011.
- [3] H.-W. Tung, D. R. Frutiger, S. Panè, and B. J. Nelson, "Polymer-based wireless resonant magnetic microrobots," in *IEEE International Conference on Robotics and Automation*, May 2012, pp. 715–720.

- [4] E. Diller, J. Giltinan, and M. Sitti, "Independent control of multiple magnetic microrobots in three dimensions," *The International Journal* of Robotics Research, vol. 32, no. 5, pp. 614–631, 2013. [Online]. Available: http://ijr.sagepub.com/content/32/5/614.abstract
- [5] W. Jing, N. Pagano, and D. Cappelleri, "A tumbling magnetic microrobot with flexible operating modes," in *Robotics and Automation* (ICRA), 2013 IEEE International Conference on, May 2013, pp. 5514– 5519
- [6] Y. Ou, D. H. Kim, P. Kim, M. J. Kim, and A. A. Julius, "Motion control of magnetized tetrahymena pyriformis cells by magnetic field with model predictive control," *Int. J. Rob. Res.*, vol. 32, no. 1, pp. 129–139, Jan. 2013.
- [7] D. de Lanauze, O. Felfoul, J.-P. Turcot, M. Mohammadi, and S. Martel, "Three-dimensional remote aggregation and steering of magnetotactic bacteria microrobots for drug delivery applications," *The International Journal of Robotics Research*, 11 2013. [Online]. Available: http://ijr.sagepub.com/content/early/2013/11/11/0278364913500543
- [8] A. Becker, E. Demaine, S. Fekete, G. Habibi, and J. McLurkin, "Reconfiguring massive particle swarms with limited, global control," in *International Symposium on Algorithms and Experiments for Sensor Systems, Wireless Networks and Distributed Robotics (ALGOSEN-SORS)*, Sophia Antipolis, France, Sep. 2013, pp. 51–66.
- [9] A. Becker, E. Demaine, S. Fekete, and J. McLurkin, "Particle computation: Designing worlds to control robot swarms with only global signals," in *IEEE International Conference on Robotics and Automation (ICRA)*. Hong Kong: IEEE, May 2014, pp. 6751–6756.
- [10] A. Becker, E. D. Demaine, S. P. Fekete, G. Habibi, and J. McLurkin, "Reconfiguring massive particle swarms with limited, global control," in *Algorithms for Sensor Systems*, ser. Lecture Notes in Computer Science, P. Flocchini, J. Gao, E. Kranakis, and F. Meyer auf der Heide, Eds. Springer Berlin Heidelberg, 2014, vol. 8243, pp. 51–66. [Online]. Available: http://dx.doi.org/10.1007/978-3-642-45346-5_5
- [11] S. McCourtney, ENIAC, the triumphs and tragedies of the world's first computer. United States of America: Walker Publishing, 1999.
- [12] R. A. Hearn, "The complexity of sliding-block puzzles and plank puzzles," *Tribute to a Mathemagician*, pp. 173–183, 2005.
- [13] E. D. Demaine and R. A. Hearn, Games of No Chance 3. Mathematical Sciences Research Institute Publications, Cambridge University Press, 2009, vol. 56, ch. Playing Games with Algorithms: Algorithmic Combinatorial Game Theory, pp. 3–56. [Online]. Available: http://arXiv.org/abs/cs.CC/0106019
- [14] E. Winfree, "Algorithmic self-assembly of DNA," Ph.D. dissertation, California Institute of Technology, June 1998.
- [15] E. Winfree, F. Liu, L. Wenzler, and N. Seeman, "Design and self-assembly of two-dimensional DNA crystals," *Nature*, vol. 394, pp. 539–544, 1998.
- [16] T. LaBean, E. Winfree, and J. Reif, "Experimental progress in computation by self-assembly of DNA tilings," *DNA Based Computers*, vol. 5, pp. 123–140, 1999.
- [17] D. Doty, M. J. Patitz, and S. M. Summers, "Limitations of self-assembly at temperature 1," in *Proceedings of The Fifteenth International Meeting on DNA Computing and Molecular Programming (Fayetteville, Arkansas, USA, June 8-11, 2009)*, 2009, pp. 283–294.
- [18] J. Maňuch, L. Stacho, and C. Stoll, "Two lower bounds for self-assemblies at temperature 1," *Journal of Computational Biology*, vol. 17, no. 6, pp. 841–852, 2010.
- [19] P.-E. Meunier, M. J. Patitz, S. M. Summers, G. Theyssier, A. Winslow, and D. Woods, "Intrinsic universality in tile self-assembly requires cooperation," in *Proceedings of the ACM-SIAM Symposium on Discrete Algorithms (SODA 2014)*, (Portland, OR, USA, January 5-7, 2014), 2014, pp. 752–771.
- [20] S. P. Fekete, J. Hendricks, M. J. Patitz, T. A. Rogers, and R. T. Schweller, "Universal computation with arbitrary polyomino tiles in non-cooperative self-assembly," in *Proceedings of the 26th ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 2015, to appear.
- [21] S. Manzoor and A. T. Becker, "Particle Assembly, https://github.com/aabecker/particlecomputation/tree/master/assembly," Feb. 2017.

CONTENTS

I	Introduction		
	I-A	Selective Control with Global Inputs .	1
	I-B	Model	1
П	Related	Work	2
	II-A	Sliding-Block Puzzles	2
	II-B	Other Related Work on Programmable	
		Matter	2
Ш	Theory		2
	III-A	Arbitrary 2D shapes require two par-	
		ticle species	2
	III-B	Complexity Handled in This Paper	2
	III-C	Discovering a Build Path	3
	III-D	Assembling Tiles	3
		III-D.1 Hopper Construction	3
	III-E	Part Assembly Jigs	3
IV	Analysis		4
	IV-A	Running Time	4
	IV-B	Space Required	4
	IV-C	Simulation Results	4
V	Experiment		4
	V-A	Macro-scale, Gravity-Based Prototype	4
	V-B	Milli-scale, Magnetic-Based Prototype	4
VI	Conclus	sion	5
Refe	erences		5