

Lecture 11

Molecular phylogenetics



Course: Practical Bioinformatics (BIOL 4220)
Instructor: Michael Landis
Email: michael.landis@wustl.edu



Lecture 11 outline

Last time: regex

This time: phylogenetics


- interpreting trees
- tree-thinking
- inferring trees
- inference methods

Phylogenetics

Phylogenetics studies the relationships among heritable biological entities (often called **taxa**)

Phylogenies are useful for


- gene annotation
- tracking viral spread
- identifying zoonosis
- reconstructing tumorigenesis
- conservation biology assays
- inferring species relationships



phylogeny sketch
by Darwin

Reading a phylogeny


Phylogenetic relationships are hierarchical,
and most often represented as bifurcating **trees**



Human and Chimp are more closely related to each other than to Gorilla or Orang

Reading a phylogeny

Phylogenetic relationships are hierarchical, and most often represented as bifurcating **trees**




Human, Chimp and Gorilla are more closely related to each other than to Orang

Reading a phylogeny

Taxa that are most closely related to one another, over any other taxa, are called ***clades***

***most recent
common ancestor***
(MRCA) for
Clade 2



Clade 1: H+C

Clade 2: H+C+G


Clade 3: H+C+G+O

“Tree-thinking”

Taxon	Gene variant	Location
PT1	ACCGTG	Missouri
PT2	ACCGTG	Missouri
PT3	GAGGTA	Texas
PT4	GCGGTA	Texas

Four sequences,
but no historical context


“Tree-thinking”



Phylogeny informs when and where variation arose, which can guide future biological research

Inferring phylogeny

How are taxa T1, T2, and T3 related?



Which phylogeny generated the observed pattern of molecular variation?

Inferring phylogeny

Phylogenetic inference methods take a matrix of characters (e.g. *DNA alignment*) as input

Measure how well any possible phylogenetic estimate explains the data matrix pattern by assigning a **cost** to each considered estimate

Methods generally **optimize** the cost to estimate the phylogeny with the lowest cost for the provided data matrix

Tree-space is large

# taxa	# rooted trees
3	3
4	15
5	105
6	945
7	10395
8	135135
9	2027025
10	34459425

A major challenge: how to efficiently search
for trees with optimal scores?


Phylogenetic method types

Most methods used to infer phylogenies compute scores based on

1. event counting (***parsimony***)
2. event probabilities (***likelihood***)
3. pattern distances (e.g. ***neighbor joining***)


Method choice often relates to concerns regarding accuracy, speed, scalability, etc.

Parsimony




What phylogeny requires the fewest character change events?

Parsimony




What phylogeny requires the fewest character change events?

Parsimony




What phylogeny requires the fewest character change events?


Parsimony



3 events




6 events



13 events

What phylogeny requires the fewest character change events?


Likelihood



What phylogeny and model of evolution is *most likely* to generate the character data?

Likelihood


Compute probability for
all ways that each character
could have evolved
under model



What phylogeny and model of evolution is
most likely to generate the character data?

Likelihood


Compute probability for
all ways that each character
could have evolved
under model



What phylogeny and model of evolution is
most likely to generate the character data?

Likelihood


Compute probability for
all ways that each character
could have evolved
under model



What phylogeny and model of evolution is
most likely to generate the character data?

Likelihood


Compute probability for
all ways that each character
could have evolved
under model



What phylogeny and model of evolution is
most likely to generate the character data?

Likelihood


Compute probability for
all ways that each character
could have evolved
under model



What phylogeny and model of evolution is
most likely to generate the character data?


Likelihood

Compute probability for
all ways that each character
could have evolved
under model




What phylogeny and model of evolution is
most likely to generate the character data?


Likelihood



log-likelihood = -32.14



log-likelihood = -42.77




log-likelihood = -39.08

What phylogeny and model of evolution is *most likely* to generate the character data?

Neighbor-joining

	Hu	Ch	Go	Or
Hu	0	1	3	5
Ch	1	0	3	5
Go	3	3	0	2
Or	5	5	2	0

distance matrix
for sequence pairs





Select pairs of taxa with short
sequence distances, and join
them as neighbors

Neighbor-joining


	Hu	Ch	Go	Or
Hu	0	1	3	5
Ch	1	0	3	5
Go	3	3	0	2
Or	5	5	2	0

distance matrix
for sequence pairs


Select pairs of taxa with short
sequence distances, and join
them as neighbors



Newick strings



`(((Human,Chimp),Gorilla),Orang);`




`((Gorilla,Chimp),(Human,Orang));`

Taxa in parentheses define clades;
commas define divergence events

Newick strings

Branch lengths measure molecular distances in expected # substitutions per site

Clade support measures reliability of clade in a tree estimate



```
((Human:0.37,Chimp:0.11)0.99:0.21,  
Gorilla:0.46)0.68:0.24,Orang:0.30);
```

Overview for Lab 11