users	
id 🔑	integer
username	varchar
password	varchar
full_name	varchar
phone	varchar
user_type	varchar
status	varchar
created_at	timestamp

tickets	
id 🔑	integer
user_id	integer
subject	varchar
description	text
status	varchar
created_at	timestamp

plans		
id 🔑	integer	
name	varchar	
price	decimal	
speed	varchar	
duration	varchar	

notifications	
id 🔑	integer
user_id	integer
message	text
type	varchar
created_at	timestamp

transactions		
)	id 🔑	integer
<u> </u>	user_id	integer -
	amount	decimal
	transaction_id	varchar
	payment_method	varchar
	created_at	timestamp

I	usage	
	id 🔑	integer
<	user_id	integer
	data_used	decimal
	data_limit	decimal
	session_start	timestamp
	session_end	timestamp



users	
id 🔑	integer -
username	varchar
password	varchar
full_name	varchar
phone	varchar
user_type	varchar
status	varchar
created_at	timestamp

tickets	
id 🔑	integer
user_id	integer
subject	varchar
description	text
status	varchar
created_at	timestamp

	olans	
i	d 🔑	integer
r	name	varchar
ķ	orice	decimal
5	speed	varchar
(duration	varchar

notifications	
id 🔑	integer
user_id	integer
message	text
type	varchar
created_at	timestamp

	transactions			us
	id 🔑	integer		id
X	user_id	integer	*	US
	amount	decimal		da
	transaction_id	varchar		da
	payment_method	varchar		ses
	created_at	timestamp		ses

	usage	
	id 🔑	integer
*	user_id	integer
	data_used	decimal
	data_limit	decimal
	session_start	timestamp
	session_end	timestamp

