

# Computer Networks Assignment 1

This is my report for the first assignment of the Computer Networks course. The report is written in markdown and can be viewed in any markdown viewer. Each individual question has its own folder with a report and any images used in the report.

## Problem 1


### Part a

```
root@ur-mum-virtual-machine:/home/ur-mum/Documents/CN# ifconfig
ens33: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.232.129 netmask 255.255.255.0 broadcast 192.168.232.255
    inet6 fe80::1eaf:8055:f765:2a0b prefixlen 64 scopeid 0x20<link>
    ether 00:0c:29:cd:f6:82 txqueuelen 1000 (Ethernet)
    RX packets 296954 bytes 327149471 (327.1 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 108355 bytes 23366001 (23.3 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 97843 bytes 11792754 (11.7 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 97843 bytes 11792754 (11.7 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

Using ifconfig:  
*local/private ip address*

### Part b



Using What is my ip address:  
*global/public ip address*

Both the IP addresses are different.

The difference between the two is that the local ip address is the ip address of the device on the local network, while the global ip address is the ip address of the device on the internet. The local ip address is assigned by the router, while the

global ip address is assigned by the ISP company that provides internet service to the user. This is done to reduce the number of IP addresses and abstract the IP addresses for security.

## Problem 2

### Part a

An authoritative answer is a response we get directly from the primary DNS server holding the master copy of the zone file.

To receive an authoritative answer we first must find the primary DNS server for the domain we are looking for. We can do this by using the `nslookup` command. For example, if we want to find the primary DNS server for `google.com` we can run the command `nslookup -type=soa google.com` which will return the primary DNS server for `google.com` which is `ns1.google.com`.

Now that we have the primary DNS server for `google.com` we can run the command `nslookup google.com ns1.google.com` which will return an authoritative answer for `google.com` which is in the image below:

```
root@urum-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q2# nslookup -type=soa google.in
Server:      127.0.0.53
Address:     127.0.0.53#53

Non-authoritative answer:
google.in
  origin = ns1.google.com
  mail addr = dns-admin.google.com
  serial = 556730683
  refresh = 900
  retry = 900
  expire = 1800
  minimum = 60

Authoritative answers can be found from:
ns1.google.com internet address = 216.239.32.10
ns1.google.com has AAAA address 2001:4860:4802:32::a

root@urum-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q2# nslookup google.in ns1.google.com
Server:      ns1.google.com
Address:     216.239.32.10#53

Name:   google.in
Address: 172.217.167.228
Name:   google.in
Address: 2404:6800:4002:80f::2004

root@urum-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q2#
```

Figure 1: plot

for part (b):

Time to live of google.com DNS is 5 seconds. It will then be

## Problem 3

### Part a

The total hops are 10. One intermediary router is `_gateway(192.168.232.2)`. The average latency was is 0.506ms. The other is `del1s22-in-f14.1e100.net(142.250.206.174)`.

```

root@ur-mum-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q2# nslookup -debug google.in
Server:      127.0.0.53
Address:     127.0.0.53#53

-----
QUESTIONS:
  google.in, type = A, class = IN
ANSWERS:
-> google.in
  internet address = 142.250.192.196
  ttl = 5
AUTHORITY RECORDS:
ADDITIONAL RECORDS:
-----
Non-authoritative answer:
Name:   google.in
Address: 142.250.192.196
-----
QUESTIONS:
  google.in, type = AAAA, class = IN
ANSWERS:
-> google.in
  has AAAA address 2404:6800:4002:817::2004
  ttl = 5
AUTHORITY RECORDS:
ADDITIONAL RECORDS:
-----
Name:   google.in
Address: 2404:6800:4002:817::2004

```

Figure 2: plot

The average latency was 5.802ms. Rest of the routers are not shown in the output of the command `traceroute www.google.com -I`.

The output of the command `traceroute www.google.com -I` is shown below:

```

root@ur-mum-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1# traceroute -I google.com
traceroute to google.com (142.250.206.174), 30 hops max, 60 byte packets
 1  _gateway (192.168.232.2)  0.564 ms  0.495 ms  0.415 ms
 2  * * *
 3  * * *
 4  * * *
 5  * * *
 6  * * *
 7  * * *
 8  * * *
 9  * * *
10  dell11s22-in-f14.1e100.net (142.250.206.174)  5.876 ms  5.821 ms  5.765 ms

```

Figure 3: plot

## Part b

After pinging the URL “www.google.com” 50 times, I got an average of 9.009 ms. The exact output is shown below:

```

--- google.in ping statistics ---
50 packets transmitted, 50 received, 0% packet loss, time 49099ms
rtt min/avg/max/mdev = 5.516/9.009/64.666/8.123 ms

```

Figure 4: plot

## Part c

Adding up all intermediate router latencies, we get  $0.506\text{ms} + 5.802\text{ms} = 6.308\text{ms}$ . This is less than the average latency of pinging the URL “www.google.com” 50

times which is 9.009 ms. This are similar but dont exactly match due to a variety of network factors such as congestion. We also have a very small traceroute sample size of 1. This can be improved by increasing the sample size of the traceroute.

#### Part d


Maximum of all intermediate router latencies is 5.802ms. This is less than the average latency of pinging the URL “www.google.com” 50 times which is 9.009 ms. This is because the latency of any one intermediate router will be less than all the intermediate routers.

#### Part e

The multiple entries in the traceroute output are due to the fact that the packets are being routed through different paths. This is because the routers are using different routing algorithms to route the packets. The routers are using different routing algorithms because they are different routers and they are using different routing algorithms to route the packets.

#### Part f

The average latency is 329.266 ms. The output of the command `ping stanford.edu -c 50` is shown below:



```
--- stanford.edu ping statistics ---
50 packets transmitted, 50 received, 0% packet loss, time 49084ms
rtt min/avg/max/mdev = 326.331/329.266/344.812/2.648 ms
```

Figure 5: plot

#### Part g

The number of hops to stanford.edu is 27. This is much lower than google.com’s 10 hops. The output of the command `traceroute stanford.edu -I` is shown below:

#### Part h

The latency difference between stanford.edu and google.com is 329.266 ms - 9.009 ms = 320.257 ms. This is due to stanford.edu being farther away from my location than google.com. This is because the packets have to travel a longer distance to reach stanford.edu than google.com. This is also leads to the higher number of hops to stanford.edu than google.com.

```

root@urmun-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1# traceroute -I stanford.edu
traceroute to stanford.edu (171.67.215.200), 30 hops max, 60 byte packets
 1 _gateway (192.168.232.2) 0.189 ms 0.108 ms 0.079 ms
 2 * * *
 3 * * *
 4 * * *
 5 * * *
 6 * * *
 7 * * *
 8 * * *
 9 * * *
10 * * *
11 * * *
12 * * *
13 * * *
14 * * *
15 * * *
16 * * *
17 * * *
18 * * *
19 * * *
20 * * *
21 * * *
22 * * *
23 * * *
24 * * *
25 * * *
26 * * *
27 web.stanford.edu (171.67.215.200) 382.297 ms 382.253 ms 374.441 ms

```

Figure 6: plot

## Problem 4

To fail the localhost (127.0.0.1) with 100% packetloss, I made the firewall reject any input connection to the localhost. This can be done by running the command `sudo iptables -A INPUT -p icmp --icmp-type echo-request -s 127.0.0.1 -j DROP`. This will reject any input connection to the localhost. To test this I ran the command `ping 127.0.0.1` which returned the below image:

```

root@urmun-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q4# ping 127.0.0.1
PING 127.0.0.1 (127.0.0.1) 56(84) bytes of data.
^C
--- 127.0.0.1 ping statistics ---
5 packets transmitted, 0 received, 100% packet loss, time 4089ms

```

Figure 7: plot

To restore the localhost I ran the command `sudo iptables -D INPUT -p icmp --icmp-type echo-request -s 127.0.0.1 -j DROP` which will remove the rule that rejects any input connection to the localhost. To test this I ran the command `ping 127.0.0.1` which returned the below image:

```

root@urmun-virtual-machine:/home/ur-mum/Documents/CN/CSE232-ComputerNetworks-Assignments/Assignment-1/Q4# ping 127.0.0.1 -c 5
PING 127.0.0.1 (127.0.0.1) 56(84) bytes of data:
64 bytes from 127.0.0.1: icmp_seq=1 ttl=64 time=0.039 ms
64 bytes from 127.0.0.1: icmp_seq=2 ttl=64 time=0.051 ms
64 bytes from 127.0.0.1: icmp_seq=3 ttl=64 time=0.087 ms
64 bytes from 127.0.0.1: icmp_seq=4 ttl=64 time=0.068 ms
64 bytes from 127.0.0.1: icmp_seq=5 ttl=64 time=0.059 ms
--- 127.0.0.1 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4083ms
rtt min/avg/max/mdev = 0.039/0.060/0.087/0.016 ms

```

Figure 8: plot

## Problem 5

```
root@urmum-virtual-machine:/home/ur-mum# telnet 192.168.24.12 9900
Trying 192.168.24.12...
Connected to 192.168.24.12.
Escape character is '^]'.
GET /secret
Host:192.168.24:9900

HTTP/1.1 200 OK
Content-Type: text/plain
ip: 192.168.1.99
X-secret: U2FsdGVkX1/FRtU+minEV2D1U125PKOCWrnuR16vSrB4bvMAkMgOXThQKNT+1P8Q
Date: Fri, 18 Aug 2023 15:09:05 GMT
Connection: close

Success
Connection closed by foreign host.
```

Figure 9: plot

## Problem 6

```
root@urmum-virtual-machine:/home/ur-mum# telnet 192.168.24.12 smtp
Trying 192.168.24.12...
Connected to 192.168.24.12.
Escape character is '^]'.
220 Welcome to CSE232 Mail Server
helo cse232.com
250 xeon01-rs-iiitd.iiitd.edu.in
MAIL FROM: 21038@cse232.com
250 2.1.0 Ok
RCPT TO: 21038@cse232.com
250 2.1.5 Ok
DATA
354 End data with <CR><LF>.<CR><LF>
testing.
.
250 2.0.0 Ok: queued as 344B76F6457B
```

Figure 10: plot

## Sources:

<https://www.linode.com/docs/guides/how-to-use-nslookup-command/>

<https://www.baeldung.com/cs/dns-authoritative-server-ip#:~:text=An%20authoritative%20answer%20is%20a,c>

<https://www.howtouselinux.com/post/dns-ttl#:~:text=The%20best%20way%20to%20check,is%20available%20c>

<https://superuser.com/questions/1137399/why-iptables-rules-are-impacting-ping-localhost>

<https://www.cloudservus.com/blog/using-telnet-to-send-mail>

<https://www.novell.com/documentation/extend5/Docs/help/Composer/books/TelnetAppendixB.html>

<https://www.wikihow.com/Send-Email-Using-Telnet>

<https://www.cloudservus.com/blog/using-telnet-to-send-mail>