

Advanced Css3

By: Hesham Mohamed



Targeted Selectors

```
<div>
  <p>Lorem ipsum dolor sit amet</p>
  <p>Lorem ipsum dolor sit amet</p>
  <ol style="list-style: lower-roman">
    <li>
      <p>item1</p>
    </li>
    <li>item2</li>
    <li>item3</li>
  </ol>
  <p>Lorem ipsum dolor sit amet.</p>
</div>
<p>Lorem ipsum dolor sit amet.</p>
<p>Lorem ipsum dolor sit amet.</p>
<a href="#" target="_blank"> Click Link </a>
<form action="">
  <input type="text" placeholder=" Type UserName ">
</form>
```



Targeted Selectors

```
/* Select Direct Child */  
div > p{  
    color: #007bff;  
}  
/* Select P => directly After div */  
div + p {  
    background: #2f2f2f;  
    color: #fff;  
}  
/* Style By Attribute */  
a[target='_blank']{  
    color: red;  
}  
/* Style Placeholder */  
input[type="text"]::placeholder{  
    color: #007bff;  
}
```



Pseudo Selectors

```
<body>
  <ul type="circle">
    <li>Item 1</li>
    <li>Item 2</li>
    <li>Item 3</li>
    <li>Item 4</li>
    <li>Item 5</li>
    <li>Item 6</li>
    <li>Item 7</li>
    <li>Item 8</li>
    <li>Item 9</li>
    <li>Item 10</li>
  </ul>
</body>
```



Pseudo Selectors

```
ul li{
    margin: 10px;
    padding: 10px;
    list-style: none;
}
/* Select Item Number 5 */
li:nth-child(5){
    background: #2f2f2f;
    color: #fff;
}
/* Increment By 3 */
li:nth-child(3n){
    background-color: yellow;
}
/* Increment By 3 And Add Offset */
li:nth-child(3n+2){
    background-color: #080;
}
```



Pseudo Selectors

```
/* Style Only Odd */
li:nth-child(odd){
    background-color: #00f;
}
/* Style Only Even */
li:nth-child(even){
    background-color: #f00;
}
/* Style First Child */
li:first-child{
    background: #000;
    color: #fff;
}
/* Style Last Child */
li:last-child{
    color: #fff;
}
```



Animations

```
#animate{
  width: 120px;
  height: 120px;
  position: relative;
  background-color: orange;
  animation-name: animate; /* Add Name */
  animation-duration: 1s; /* Add Duration */
  /* Add a delay for the start of an animation*/
  animation-delay: 2s;
  /*Add Number Of Times Animation Should Run*/
  animation-iteration-count: 5;
  /*speed curve of the animation.*/
  animation-timing-function: linear;
}
/* Use @keyframes to animate element*/
@keyframes animate{
  0% {background-color: orange; left: 0 ; top: 0}
  25%{background-color: yellow; left: 250px; top : 0}
  50%{background-color: green; left: 250px; top: 250px}
  75%{background-color: red; left: 0; top: 250px;}
  100%{background-color: blue; left: 0; top: 0;}
}
```



Animations

```
#animate{
  width: 120px;
  height: 120px;
  position: relative;
  background-color: orange;
  animation-name: animate; /* Add Name */
  animation-duration: 1s; /* Add Duration */
  /* Add a delay for the start of an animation*/
  animation-delay: 2s;
  /*Add Animation Fill Mode*/
  animation-fill-mode: backwards;
  /*Animation Direction */
  animation-direction: alternate;
  /* Shorthand Property */
  /* name duration timing-function delay count direction*/
  animation: animate 5s linear 2s infinite alternate;
}
/* Use @keyframes to animate element*/
@keyframes animate{
  from{top: 0px; background-color: yellow;}
  to {top: 250px}
}
```



Transition

```
.effect{
  width: 100px;
  height: 100px;
  background: red;
  /* Add Transition Effect For Both Width and Height */
  transition: width 2s, height 1s;
  /* Add speed curve of the transition effect */
  transition-timing-function: ease-in-out;
  /* Add Transition Delay */
  transition-delay: 1s;
  /* Shorthand Property */
  transition: width height 2s linear 1s;
}
.effect:hover{
  width: 200px;
  height: 200px;
}
```



Transforms

```
div{
  width: 300px;
  height: 100px;
  background-color: yellow;
  /* moves an element from its current position */
  transform: translate(50px , 100px);
  /*rotates an element clockwise or counter-clockwise
    according to a given degree*/
  transform: rotate(35deg);
  /*increases or decreases the size of an element*/
  transform: scale(2 , 3);
  /*skews an element along the X and Y-axis */
  transform: skew(10deg , 20deg);
  /* method combines all the 2D transform methods into one
    matrix(scaleX(),skewY(),skewX(),scaleY(),translateX(),translateY())
  */
  transform: matrix(1, -0.3, 0, 1, 0, 0);
}
```



Media Query

```
<div class="wrapper">
  <div id="leftsidebar">
    <ul id="menulist">
      <li class="menuitem">Menu-item 1</li>
      <li class="menuitem">Menu-item 2</li>
      <li class="menuitem">Menu-item 3</li>
      <li class="menuitem">Menu-item 4</li>
      <li class="menuitem">Menu-item 5</li>
    </ul>
  </div>
  <div id="main">
    <h1>Resize the browser window to see the effect!</h1>
    <p>This example shows a menu that will float to the left
      of the page if the viewport is 480 pixels wide or wider.
      If the viewport is less than 480 pixels,
      the menu will be on top of the content.</p>
  </div>
</div>
```



Media Query

```
.wrapper {overflow: auto;}
#main {margin-left: 4px;}
#leftsidebar {
  float: none;
  width: auto;
}
#menulist {
  margin: 0;
  padding: 0;
}
.menuitem {
  background: #CDF0F6;
  border: 1px solid #d4d4d4;
  border-radius: 4px;
  list-style-type: none;
  margin: 4px;
  padding: 2px;
}
@media screen and (min-width: 480px) {
  #leftsidebar {width: 200px; float: left;}
  #main {margin-left: 216px;}
}
```



Let's Play

```
<p>Hover over the div element below:</p>  
<div></div>
```

```
div {  
  width: 100px;  
  height: 100px;  
  background: red;  
  transition: width 2s, height 2s, transform 2s;  
}  
div:hover {  
  width: 300px;  
  height: 300px;  
  transform: rotate(180deg);  
}
```



Useful Websites

- <https://codepen.io/>
- <https://caniuse.com/>
- <https://fonts.google.com/>
- <https://fontawesome.com/>
- <https://cdnjs.com/>
- <https://webdesign.tutsplus.com/tutorials/comprehensive-guide-when-to-use-em-vs-rem--cms-23984>
- <https://colours.neilorangepeel.com/>
- <https://colors.co/>
- <https://randoma11y.com/>



Thank You 😊

