

# מסלול Full Stack

קמפוס ת"א

זום 2021

שם המרצה: דורון

אזולאי



# ברוכים הבאים



# Lesson Agenda

- Load CSS – inline, element, external
- Selector Combination
- Smart Use
- Position
- Properties and Values
  - Basic
  - Box Model
- Exercise
- Q&A

# Load CSS:

## Three ways to load css:

### Inline:

```
<h1 style="color:red;">Hello World.</h1>
```

### Style:

```
<style>
    h1{
        color:red;
    }
</style>
```

### External:

```
<link rel="stylesheet" href="mystyle.css">
```

# Selector Combination :

## tag and class:

```
a.btn{
  display: inline-block;
  color:white;
  padding: 10px 15px;
}
a.btn-1{
  background-color: green;
}

<a class="btn btn-1" href="#">Button 1</a> <br>
<button class="btn btn-1" href="#">Button 2</button>
```



## multi class:

```
button.btn.btn-2{
  display: inline-block;
  color:white;
  padding: 10px 15px;
  background-color: red;
}

<a class="btn btn-2" href="#">Button 1</a> <br>
<button class="btn btn-2" href="#">Button 2</button>
```



# Selector Combination : child select

## child tag:

```
p span{
  background-color: lightcoral;
}

<p>Some - <span>Example</span> - 3</p>
<span>some regular span</span>
```

Some - Example - 3

some regular span

## child class:

```
p .my-marker{
  background-color: lightcoral;
}

<p>Some - <span class="my-marker">Example</span> - 4</p>
```

# Smart use:

## Try to create efficient classes to use:

```
.btn{
    color:white;
    padding: 10px 15px;
    display: inline-block;
}
.btn-1{
    background-color: green;
}
.btn-2{
    background-color: purple;
}
.btn-3{
    background-color: dodgerblue;
}
```

```
<a class="btn btn-1" href="#">Button 1</a> <br>
<a class="btn btn-2" href="#">Button 2</a> <br>
<a class="btn btn-3" href="#">Button 3</a>
```



# In Class Exercise:

- create folder – inClassExercise3
- create one file
  - navbar.html

## Navbar Page

Create a page that navigation bar  
Logo and links

## Design

add style to body  
add style to navigation bar and links

**Logo**

Home

About

Contact



# In Class Exercise:


- create folder – inClassExercise3
- create one file
  - todo-list.html

## Todo list Page

Create a page that displays list of the things need to do

## Design

add style to body  
add style to list and list items



# Position: State

more – [https://www.w3schools.com/cssref/pr\\_class\\_position.asp](https://www.w3schools.com/cssref/pr_class_position.asp)

## CSS Syntax:

position: static | absolute | fixed | relative | sticky | initial | inherit;

## Position: Coordinates

When using a non-static position value:

- top ,left ,bottom ,right

Value	Description
static	Default value. Elements render in order, as they appear in the document flow
absolute	The element is positioned relative to its first positioned (not static) ancestor element
fixed	The element is positioned relative to the browser window
relative	The element is positioned relative to its normal position, so "left:20px" adds 20 pixels to the element's LEFT position
sticky	<p>The element is positioned based on the user's scroll position</p> <p>A sticky element toggles between <b>relative</b> and <b>fixed</b> , depending on the scroll position. It is positioned relative until a given offset position is met in the viewport - then it "sticks" in place (like position:fixed).</p> <p><b>Note:</b> Not supported in IE/Edge 15 or earlier. Supported in Safari from version 6.1 with a -webkit- prefix.</p>
initial	Sets this property to its default value. <a href="#">Read about <i>initial</i></a>
inherit	Inherits this property from its parent element. <a href="#">Read about <i>inherit</i></a>

# Box Shadow: more – [https://www.w3schools.com/cssref/css3\\_pr\\_box-shadow.asp](https://www.w3schools.com/cssref/css3_pr_box-shadow.asp)

## CSS Syntax:

box-shadow: none | h-offset v-offset blur spread color | inset | initial | inherit;

Value	Description	Demo
<i>none</i>	Default value. No shadow is displayed	
<i>h-offset</i>	Required. The horizontal offset of the shadow. A positive value puts the shadow on the right side of the box, a negative value puts the shadow on the left side of the box	
<i>v-offset</i>	Required. The vertical offset of the shadow. A positive value puts the shadow below the box, a negative value puts the shadow above the box	
<i>blur</i>	Optional. The blur radius. The higher the number, the more blurred the shadow will be	
<i>spread</i>	Optional. The spread radius. A positive value increases the size of the shadow, a negative value decreases the size of the shadow	
<i>color</i>	Optional. The color of the shadow. The default value is the text color. Look at <a href="#">CSS Color Values</a> for a complete list of possible color values.  <b>Note:</b> In Safari (on PC) the color parameter is required. If you do not specify the color, the shadow is not displayed at all.	
<i>inset</i>	Optional. Changes the shadow from an outer shadow (outset) to an inner shadow	
<i>initial</i>	Sets this property to its default value. <a href="#">Read about initial</a>	
<i>inherit</i>	Inherits this property from its parent element. <a href="#">Read about inherit</a>	

# CSS Basic: commons

more - <https://www.tutorialrepublic.com/css-reference/css3-properties.php>

Property name	Value	Use for	Example
width   height	px,em,rem,%,vw,vh	box width & height	width:150px;   height:20em;
min-width   min-height	px,em,rem,%,vw,vh	box min width & height	min-width:100%;   min-height:15rem;
max-width   max-height	px,em,rem,%,vw,vh	box max width & height	max-width:50%;   max-height:150px;
position	static absolute fixed relative sticky initial inherit	element position state	position:absolute;
top   left   right   bottom	px,em,rem,%	position the element	top 0px;   right:0px;
box-shadow	none h-offset v-offset blur spread color  inset initial inherit;	box back shadow	box-shadow:0 0 4px 1px red;
display	block, inline,inline-block,none	element flow in the page	

# Exercise:

- create folder – exercise5
- create one file
  - personalPage.html

## Personal Page

Create a page that displays  
**navigation bar** – with 3 link and logo  
**todo list row** – with 2 todo lists  
todo today, todo tomorrow  
**message box** – make message in the  
bottom right of the page

Logo

Home

About

Contact

## Todo Today



- i. take the dog out
- ii. start my one website
- iii. buy some food to the house

## Todo Tomarrow



- i. take the dog out
- ii. start my one website
- iii. buy some food to the house

This is Some message

# Q&A



