

```

1 -- Task 4: Most-watched series (unique viewers), with brand classification
2
3 SELECT
4     -- Classify external_id prefixes to readable source names
5     CASE
6         WHEN c.external_id LIKE 'PGA%' THEN 'AJA'           -- PGA → Al Jazeera Arabic
7         WHEN c.external_id LIKE 'PGD%' THEN 'AJD'           -- PGD → Al Jazeera Documentary
8         WHEN c.external_id LIKE 'PGV%' THEN 'Atheer'         -- PGV → Ather Podcasts
9         WHEN c.external_id LIKE 'PGL%' THEN 'LIVE'           -- PGL → Live channels
10        WHEN c.external_id LIKE 'PGC%' THEN 'Originals'      -- PGC → Originals / Commissions
11        ELSE 'Other'                                         -- Everything else
12    END AS source,
13
14    -- Series information
15    v.SERIES_ID,
16
17    -- coalesce replaces null values with "Unknown Series"
18    COALESCE(v.SERIES_TITLE, 'Unknown Series') AS series_title,
19
20    -- Count unique viewers (one user per series)
21    COUNT(DISTINCT v.CUSTOMER_EXID) AS unique_viewers,
22
23    -- Total number of view events (all plays, including repeats)
24    COUNT(*) AS total_views
25
26 FROM viewership v
27
28 -- Join to catalog to pull external_id (needed for source classification)
29 LEFT JOIN catalog c
30     ON v.CONTENT_ID = c.vod_dve_id
31
32 -- Keep only rows where SERIES_ID is available
33 WHERE v.SERIES_ID IS NOT NULL
34
35 -- Group by source + series
36 GROUP BY source, v.SERIES_ID, v.SERIES_TITLE
37
38 -- Order by unique viewers (biggest series first)
39 ORDER BY unique_viewers DESC;
40

```