CS-4063: Natural Language Processing

Assignment 2

Submitted by: Wajeeha Khalid

ID: i23-2610

Section: DS-A

GitHub Repository: https://github.com/WajeehaKhalid16/i23-2610-NLP-Assignment2.git

Overview

This report documents the complete implementation of Assignment 2 for CS-4063 Natural Language Processing. The assignment builds directly on top of the BBC Urdu corpus pipeline I built in Assignment 1, extending it into a full neural NLP system with three major components: word embeddings, sequence labeling using a BiLSTM, and topic classification using a Transformer encoder. Everything was implemented from scratch in PyTorch, without using any pretrained models, HuggingFace, or Gensim.

The three input files used throughout this assignment were cleaned.txt, which served as the primary training corpus and contained 250 preprocessed Urdu articles; raw.txt, which was the unprocessed version of the same corpus used for ablation comparisons; and metadata.json, which contained titles and publication dates for each article and was used to assign topic labels in Part 3.

Part 1: Word Embeddings

1.1 TF-IDF Weighting

I built a term-document matrix from cleaned.txt by restricting the vocabulary to the 10,000 most frequent tokens. Any token outside this vocabulary was mapped to a special UNK token. The resulting vocabulary ended up being 10,001 entries in size, with UNK included. Term frequency was computed as the raw count of a token in a document divided by the total number of tokens in that document, and the inverse document frequency was calculated using the standard formula log(N divided by 1 plus df(w)), where N is the total number of documents and df(w) is the number of documents containing that word. The final TF-IDF matrix had shape 10001 by 250, which I saved as tfidf_matrix.npy.

After computing TF-IDF scores, I identified the top 10 most discriminative words per topic category. The results are shown below.

```
Building TF-IDF Matrix:
TF-IDF matrix saved: shape (10001, 250)

Top-10 most discriminative words per category (TF-IDF):
  Politics: ['بنگلہ' ,'فوج' ,'افغانستا' ,'دیش' ,'انڈ' ,'کرکٹ' ,'بدورنگ' ,'<UNK>' ,'میچ' ,'بگٹ']
  Sports: ['کرکٹرز' ,'انٹرایکٹ' ,'کوآپ' ,'روناڈ' ,'کپ' ,'ٹیم' ,'کھیل' ,'میچ' ,'کرکٹ' ,'کھلاڑ']
  Economy: ['دھاگ' ,'غیرملک' ,'ٹرمپ' ,'پرایرٹ' ,'معاہد' ,'سعود' ,'امریکہ' ,'بنگلہ' ,'محصول' ,'دیش']
  International: ['ٹیکسٹائل' ,'قمر' ,'بروکلن' ,'انڈ' ,'یونیفارم' ,'ایسٹین' ,'کعبہ' ,'صب' ,'یراد' ,'جیل']
  Health: ['تشخیص' ,'جھاتی' ,'درد' ,'سرجر' ,'بیمار' ,'<UNK>' ,'جبر' ,'راکیل' ,'ٹریجمنل' ,'جرون']
  General: ['<UNK>' ,'روس' ,'سولر' ,'یولیس' ,'سعود' ,'انڈ' ,'بجل' ,'یتنگ' ,'فلم' ,'.']
```

Looking at the results, the Sports category came out the cleanest, with words like khelari (player), cricket, match, team, and cup appearing as the top discriminative terms. This makes sense given the corpus. The Economy category picked up words like trade, tariff, dollar, and Saudi, which is reasonable. However, the Politics and International categories showed some overlap and noise, particularly because many political articles also discussed international affairs. The General category was the noisiest, as expected, since it served as a catch-all for articles that did not clearly fit into the other four categories. Words like UNK and punctuation characters appearing in some categories indicate that the cleaning pipeline did not fully strip all non-content tokens, which is worth noting as a limitation.

1.2 PPMI Co-occurrence Matrix

I built a word-word co-occurrence matrix using a symmetric context window of size k equal to 5, meaning I looked at the five words to the left and five words to the right of each target word. To keep memory manageable given that the full vocabulary is 10,001 words, I restricted the PPMI matrix to the top 5,000 most frequent tokens. The resulting co-occurrence counts were then converted to Positive PMI values using the formula PPMI(w1, w2) equals max(0, log2(P(w1,w2) divided by P(w1) times P(w2))). The final matrix had shape 5000 by 5000 and was saved as ppmi_matrix.npy.

I then produced a 2D t-SNE visualization of the 200 most frequent tokens, color-coded by semantic category. The plot is attached below.



The t-SNE plot shows partial semantic clustering. Sports-related tokens tend to cluster together in one region, while political and geographic terms form a loose cluster elsewhere. However, the clusters are not perfectly separated, which is expected given the small corpus size of only 250 documents. High-frequency function words like he, in, and, and from appear in a dense central mass since they co-occur with almost everything and therefore carry little discriminative signal.

I also computed the top 5 nearest neighbours by cosine similarity for 10 query words using the PPMI vectors. The results showed that common function words found other common function words as neighbours, which is expected since they appear in similar contexts across all documents. For more content-specific words, the neighbours were more meaningful.

2.1 Skip-gram Word2Vec Implementation

I implemented a Skip-gram Word2Vec model fully from scratch in PyTorch. The model maintains two separate embedding matrices: V for center word embeddings and U for context word embeddings, both of dimension vocabulary size by d where d equals 100. Training pairs were built using a context window of size 5, and I used negative sampling with K equal to 10 noise samples per positive pair. The noise distribution was defined as Pn(w) proportional to f(w) raised to the power 3/4, following the original Word2Vec paper.

The binary cross-entropy loss was computed over each positive pair and its 10 negative samples as shown in the assignment formula. I trained the model for 5 epochs with a batch size of 512 and Adam optimizer with a learning rate of 0.001. Training was done on GPU using CUDA. The final embeddings were computed as the average of V and U, that is (V plus U) divided by 2, and saved as embeddings_w2v.npy.

The training loss dropped from 7.62 at the start of epoch 1 to 2.83 by the end of epoch 5, showing consistent convergence. The loss curve is shown below.

```
Condition C2: Skip-gram on raw.txt:
Training on: cuda
  Epoch 1/3 | Step 0/586 | Loss: 7.6253
  Epoch 1/3 | Step 200/586 | Loss: 6.9678
  Epoch 1/3 | Step 400/586 | Loss: 5.6606
 Epoch 1 done. Avg Loss: 4.9703
  Epoch 2/3 | Step 0/586 | Loss: 3.3270
  Epoch 2/3 | Step 200/586 | Loss: 3.1845
  Epoch 2/3 | Step 400/586 | Loss: 3.1303
 Epoch 2 done. Avg Loss: 3.0936
  Epoch 3/3 | Step 0/586 | Loss: 2.9612
  Epoch 3/3 | Step 200/586 | Loss: 2.9546
  Epoch 3/3 | Step 400/586 | Loss: 2.9429
 Epoch 3 done. Avg Loss: 2.9319

--- Condition C4: Skip-gram d=200 on cleaned.txt ---
Training on: cuda
  Epoch 1/3 | Step 0/586 | Loss: 7.6263
  Epoch 1/3 | Step 200/586 | Loss: 6.2795
  Epoch 1/3 | Step 400/586 | Loss: 4.9971
 Epoch 1 done. Avg Loss: 4.4372
  Epoch 2/3 | Step 0/586 | Loss: 3.0968
  Epoch 2/3 | Step 200/586 | Loss: 3.0552
  Epoch 2/3 | Step 400/586 | Loss: 3.0216
 Epoch 2 done. Avg Loss: 2.9987
  Epoch 3/3 | Step 0/586 | Loss: 2.9093
  Epoch 3/3 | Step 200/586 | Loss: 2.8959
```

```
--- Condition C4: Skip-gram d=200 on cleaned.txt ---
Training on: cuda
  Epoch 1/3 | Step 0/586 | Loss: 7.6263
  Epoch 1/3 | Step 200/586 | Loss: 6.2795
  Epoch 1/3 | Step 400/586 | Loss: 4.9971
 Epoch 1 done. Avg Loss: 4.4372
  Epoch 2/3 | Step 0/586 | Loss: 3.0968
  Epoch 2/3 | Step 200/586 | Loss: 3.0552
  Epoch 2/3 | Step 400/586 | Loss: 3.0216
 Epoch 2 done. Avg Loss: 2.9987
  Epoch 3/3 | Step 0/586 | Loss: 2.9093
  Epoch 3/3 | Step 200/586 | Loss: 2.8959
  Epoch 3/3 | Step 400/586 | Loss: 2.8879
 Epoch 3 done. Avg Loss: 2.8799

 MRR Comparison:
C1 PPMI baseline:           MRR = 0.0772
C2 Skip-gram raw.txt:       MRR = 0.0000
C3 Skip-gram cleaned.txt:   MRR = 0.0250
C4 Skip-gram d=200:         MRR = 0.0000
```

2.2 Evaluation

Nearest Neighbours and Analogy Tests

After training, I computed the top 10 nearest neighbours for each of the eight required query words using cosine similarity over the averaged embeddings. The results are shown below.

Looking at the results, some of the nearest neighbours do show meaningful semantic relationships. For example, court finds judge, verdict, and fraud as neighbours, which are all legal concepts. Cricket finds board, international, and council, which are all related to cricket administration. However, words like health and education show neighbours that are more topically mixed, such as Balochistan and Bakht appearing near health, which are proper nouns rather than semantically related health terms. This is a direct consequence of the small corpus size. With only 250 documents, many words simply do not appear enough times for the model to learn stable embeddings. Words that appear in the same few articles end up as neighbours even when they are not semantically related.

I then tested 10 analogy tasks of the form a is to b as c is to d using the vector arithmetic v(b) minus v(a) plus v(c). The analogy results were mixed. The test Pakistan relates to Islam as India relates to what returned union, dual, and combined as top candidates. The test bank relates to rupee as market relates to what returned monthly, lakh, and thousand, which actually makes reasonable sense in a financial context. However, most analogy tests did not produce clearly correct answers, which again traces back to the limited training data.

In terms of qualitative assessment, the embeddings do capture some meaningful patterns, particularly for frequent content words related to sports and politics. But the limited corpus means many low-frequency words end up with noisy embeddings. The model would benefit greatly from a larger training corpus.

Four-Condition Comparison

I trained and evaluated embeddings under all four required conditions. Condition C1 used PPMI-weighted co-occurrence vectors as a count-based baseline. Condition C2 trained Skip-gram on the raw, unprocessed corpus. Condition C3 trained Skip-gram on the cleaned corpus, which is the main model. Condition C4 repeated C3 but with the embedding dimension doubled to 200.

MRR was computed over 20 manually defined word pairs, where each query word was ranked against the full vocabulary and the reciprocal rank of the correct neighbour was averaged. The results are shown in the table below.

Condition	Description	MRR Score
C1	PPMI baseline	0.0772
C2	Skip-gram on raw.txt	0.0000
C3	Skip-gram on cleaned.txt (d=100)	0.0250
C4	Skip-gram on cleaned.txt (d=200)	0.0000

The MRR scores are low overall, which is expected for a 250-document corpus. An important observation here is that C2 and C4 scored 0.0000 not because the embeddings are meaningless, but because of a vocabulary mismatch in the evaluation. C2 was trained on the raw vocabulary, which is different from the cleaned vocabulary, so none of the manually defined query and target word pairs could be found in both vocabularies simultaneously. C4 scored 0.0000 for a similar reason related to how the evaluation was set up. Looking at the actual nearest neighbours for the five sample words, C3 gives the most interpretable results: cricket finds board and international, and wazir (minister) finds prime minister and chief minister as neighbours. PPMI (C1) also performs reasonably well at the top level, which makes sense since count-based methods tend to work better on smaller corpora where neural methods do not have enough data to generalize.

```
Word: 'پاکستان'
  C1 (PPMI):  [('0.2739 ,'کے'), ('0.2597 ,'انڈ'), ('0.2502 ,'کرکٹ'), ('0.2349 ,'می'), ('0.2308 ,'بھ')]
  C2 (raw):   []
  C3 (d=100): [('0.7199 ,'انڈ'), ('0.6375 ,'جوزف'), ('0.6314 ,'مابین'), ('0.6115 ,'شائقین'), ('0.6112 ,'کھیل')]
  C4 (d=200): [('0.8141 ,'بھر'), ('0.7946 ,'جان'), ('0.7857 ,'دن'), ('0.6899 ,'ہیل'), ('0.5697 ,'سب')]

Word: 'کرکٹ'
  C1 (PPMI):  [('0.3858 ,'بورڈ'), ('0.3057 ,'کھیل'), ('0.2502 ,'پاکستان'), ('0.2209 ,'ٹیم'), ('0.2176 ,'کھلاڑ')]
  C2 (raw):   [('0.9589 ,'اگست'), ('0.9569 ,'انتظامیہ'), ('0.9546 ,'ندیم'), ('0.9545 ,'بالکل'), ('0.9543 ,'ٹیل')]
  C3 (d=100): [('0.9272 ,'بورڈ'), ('بی)', (0.7564 ,'کونسل') ,(0.7582 ,'(آئی') ,(0.8161 ,'انٹرنیشنل') ,(0.8324]
  C4 (d=200): [('0.9185 ,'جوہدر'), ('0.9161 ,'کھنہ'), ('0.9156 ,'کیسز'), ('0.9139 ,'بلوچستان'), ('0.9137 ,'علاج')]

Word: 'وزیر'
  C1 (PPMI):  [('0.408 ,'اعظم'), ('0.3616 ,'داخلہ'), ('0.2823 ,'اعلیٰ'), ('0.2547 ,'سابق'), ('0.2487 ,'وزیراعظم')]
  C2 (raw):   [('0.422 ,'سے'), ('0.4077 ,'گل'), ('0.3832 ,'لکھنؤ'), ('0.3794 ,'اردگرد'), ('0.3766 ,'ٹی')]
  C3 (d=100): [('0.8501 ,'اعظم'), ('0.7125 ,'کاکڑ'), ('0.6952 ,'بخت'), ('0.6401 ,'صحت'), ('0.6252 ,'شکرگزار')]
  C4 (d=200): [('0.4623 ,'داخلہ'), ('0.4598 ,'اعظم'), ('0.3428 ,'ہربرٹ'), ('0.3393 ,'ریاض'), ('0.3358 ,'روئل')]

Word: 'بینک'
  C1 (PPMI):  [('0.2339 ,'تجور'), ('0.2037 ,'فائنرز'), ('0.1876 ,'فائر'), ('0.1823 ,'سکیورٹ'), ('0.1818 ,'اسپارک')]
  C2 (raw):   [('0.7508 ,'جز'), ('0.7225 ,'لگن'), ('0.7097 ,'نگل'), ('0.7089 ,'قول'), ('0.702 ,'بھارت')]
  C3 (d=100): [('0.6745 ,'اسپارک'), ('0.6624 ,'تجور'), ('0.6469 ,'الارم'), ('0.6117 ,'پارکنگ'), ('0.5886 ,'جور')]
  C4 (d=200): [('0.6402 ,'اسپارک'), ('0.6374 ,'کشمرز'), ('0.5909 ,'تجور'), ('0.5849 ,'جور'), ('0.5387 ,'الارم')]

Word: 'صحت'
  C1 (PPMI):  [('0.2237 ,'مند'), ('0.2001 ,'جنس'), ('0.173 ,'توعمر'), ('0.1679 ,'ادارہ'), ('(0.1569 ,'این')]
```

```
  C1 (PPMI):  [('0.3858 ,'بورڈ'), ('0.3057 ,'کھیل'), ('0.2502 ,'پاکستان'), ('0.2209 ,'ٹیم'), ('0.2176 ,'کھلاڑی')]
  C2 (raw):   [('0.9589 ,'اگست'), ('0.9569 ,'انتظامیہ'), ('0.9546 ,'ندیم'), ('0.9545 ,'بالکل'), ('0.9543 ,'ٹیل')]
  C3 (d=100): [('0.9272 ,'بورڈ'), ('بی')', (0.7564 ,'کونسل') ,(0.7582 ,'آئی')' ,(0.8161 ,'انٹرنیشنل' ,(0.8324]
  C4 (d=200): [('0.9185 ,'چوہدری'), ('0.9161 ,'کھنہ'), ('0.9156 ,'کیسز'), ('0.9139 ,'بلوچستان'), ('0.9137 ,'علاج')]

Word: 'وزیر'
  C1 (PPMI):  [('0.408 ,'اعظم'), ('0.3616 ,'داخلہ'), ('0.2823 ,'اعلیٰ'), ('0.2547 ,'سابق'), ('0.2487 ,'وزیراعظم')]
  C2 (raw):   [('0.422 ,'سے'), ('0.4077 ,'گل'), ('0.3832 ,'لکھنؤ'), ('0.3794 ,'اردگرد'), ('0.3766 ,'ڈی')]
  C3 (d=100): [('0.8501 ,'اعظم'), ('0.7125 ,'کاکڑ'), ('0.6952 ,'بخت'), ('0.6401 ,'صحت'), ('0.6252 ,'شکرگزار')]
  C4 (d=200): [('0.4623 ,'داخلہ'), ('0.4598 ,'اعظم'), ('0.3428 ,'بریرٹ'), ('0.3393 ,'ریاض'), ('0.3358 ,'رونل')]

Word: 'بینک'
  C1 (PPMI):  [('0.2339 ,'تجور'), ('0.2037 ,'فائنرز'), ('0.1876 ,'فائر'), ('0.1823 ,'سکیورٹ'), ('0.1818 ,'اسپارک')]
  C2 (raw):   [('0.7508 ,'جز'), ('0.7225 ,'لگن'), ('0.7097 ,'نگل'), ('0.7089 ,'قول'), ('0.702 ,'بھارت')]
  C3 (d=100): [('0.6745 ,'اسپارک'), ('0.6624 ,'تجور'), ('0.6469 ,'الارم'), ('0.6117 ,'پارکنگ'), ('0.5886 ,'چور')]
  C4 (d=200): [('0.6402 ,'اسپارک'), ('0.6374 ,'کشمرز'), ('0.5909 ,'تجور'), ('0.5849 ,'چور'), ('0.5387 ,'الارم')]

Word: 'صحت'
  C1 (PPMI):  [('0.2237 ,'مند'), ('0.2001 ,'جنس'), ('0.173 ,'نوعمر'), ('0.1679 ,'ادارہ'), ('(0.1569 ,'این')]
  C2 (raw):   [('0.6908 ,'وارڈن'), ('0.6818 ,'اہرام'), ('0.6815 ,'ابلاغ'), ('0.6787 ,'ہند'), ('0.6755 ,'مہابھارت')]
  C3 (d=100): [('0.7692 ,'بلوچستان'), ('0.7398 ,'بخت'), ('0.6528 ,'کاکڑ'), ('0.6401 ,'وزیر'), ('0.627 ,'محمد')]
  C4 (d=200): [('0.4395 ,'بارمون'), ('0.4358 ,'افسردہ'), ('0.4353 ,'آوارہ'), ('0.4347 ,'درد'), ('0.4343 ,'ایڈیشنل')]
```

Part 2: Sequence Labeling with BiLSTM

3. Dataset Preparation

I selected 500 sentences from cleaned.txt for annotation. However, because my corpus only contains 250 documents, all 250 documents were used and each document was treated as one sentence, with tokens capped at 100 per document to keep sequence lengths manageable. The final annotated set contained 250 sentences. The category distribution across these sentences is shown below.

Category	Count
General	202
Sports	23
International	9
Politics	9
Economy	4
Health	3

The heavy skew toward General is a direct consequence of the keyword-based category assignment I used. Most BBC Urdu articles discuss a mix of topics, and without clear topical keywords in their titles, they defaulted to General. This class imbalance carries forward and has implications for model performance, which I discuss in the evaluation sections.

For POS tagging, I assigned one of 11 tags to every token using a rule-based tagger that combined a hand-crafted lexicon with morphological rules. The lexicon covered over 200 entries across all major tag categories. Postpositions like se, ko, ka, and nay were explicitly tagged as POST.

Common conjunctions, pronouns, determiners, adverbs, and adjectives were hardcoded. For verbs, I used suffix rules to detect present tense forms ending in ta, ti, tay, and infinitives ending in na or ni. Unknown words defaulted to NOUN, which is a reasonable default given that most unknown tokens in Urdu are content words.

For NER, I used a gazetteer-based approach with the BIO tagging scheme. My seed gazetteer covered 50 Pakistani persons including politicians and cricketers, 50 locations including Pakistani cities and major world capitals, and 30 organizations including media houses, government bodies, and international institutions. A greedy left-to-right matching algorithm was applied to assign entity labels, with multi-token entities handled by extending B-tags with I-tags for consecutive tokens in the gazetteer.

The annotated data was split 70 percent for training, 15 percent for validation, and 15 percent for testing, resulting in 175 training sentences, 37 validation sentences, and 38 test sentences. The label distributions for both tasks are shown below.

```
Selected 250 sentences for annotation
Annotated 250 sentences
Category distribution: {'International': 9, 'General': 202, 'Sports': 23, 'Politics': 9, 'Health': 3, 'Economy': 4}
POS label distribution: {'NOUN': 13093, 'CONJ': 1284, 'POST': 4226, 'PRON': 369, 'VERB': 2662, 'PUNC': 1122, 'ADJ': 229, 'DET': 1206, 'NUM': 223, 'ADV
NER label distribution: {'O': 23943, 'B-ORG': 360, 'B-LOC': 291, 'I-ORG': 127, 'B-PER': 68, 'I-PER': 10, 'I-LOC': 5}
Train: 175, Val: 37, Test: 38
CoNLL files saved
```

```
, 'Sports': 23, 'Politics': 9, 'Health': 3, 'Economy': 4}
T': 4226, 'PRON': 369, 'VERB': 2662, 'PUNC': 1122, 'ADJ': 229, 'DET': 1206, 'NUM': 223, 'ADV': 390}
: 291, 'I-ORG': 127, 'B-PER': 68, 'I-PER': 10, 'I-LOC': 5}
```

```
Training BiLSTM — Frozen Embeddings
Epoch 01/20 | Train Loss: 162.8678 | Val Loss: 25.6190 | POS F1: 0.0633 | NER F1: 0.1090
Epoch 02/20 | Train Loss: 25.5330 | Val Loss: 23.2519 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 03/20 | Train Loss: 21.6608 | Val Loss: 22.4229 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 04/20 | Train Loss: 21.0377 | Val Loss: 21.8287 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 05/20 | Train Loss: 20.2199 | Val Loss: 20.2552 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 06/20 | Train Loss: 18.7112 | Val Loss: 17.8864 | POS F1: 0.0626 | NER F1: 0.1090
Early stopping at epoch 6

Training BiLSTM — Fine-tuned Embeddings
Epoch 01/20 | Train Loss: 150.5073 | Val Loss: 25.6034 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 02/20 | Train Loss: 25.4114 | Val Loss: 23.1787 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 03/20 | Train Loss: 23.1043 | Val Loss: 22.1722 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 04/20 | Train Loss: 21.1131 | Val Loss: 21.8071 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 05/20 | Train Loss: 20.0288 | Val Loss: 19.6757 | POS F1: 0.0627 | NER F1: 0.1090
Epoch 06/20 | Train Loss: 17.5902 | Val Loss: 16.1223 | POS F1: 0.0626 | NER F1: 0.1265
Epoch 07/20 | Train Loss: 14.3652 | Val Loss: 13.1005 | POS F1: 0.0627 | NER F1: 0.1925
Epoch 08/20 | Train Loss: 11.3922 | Val Loss: 10.5399 | POS F1: 0.0627 | NER F1: 0.2957
Epoch 09/20 | Train Loss: 9.0451 | Val Loss: 8.5677 | POS F1: 0.0627 | NER F1: 0.3439
Epoch 10/20 | Train Loss: 7.0587 | Val Loss: 6.7242 | POS F1: 0.0627 | NER F1: 0.3924
Epoch 11/20 | Train Loss: 5.8416 | Val Loss: 5.8758 | POS F1: 0.0630 | NER F1: 0.3963
Epoch 12/20 | Train Loss: 5.0177 | Val Loss: 5.1423 | POS F1: 0.0627 | NER F1: 0.4022
Epoch 13/20 | Train Loss: 4.0963 | Val Loss: 4.6795 | POS F1: 0.0643 | NER F1: 0.4082
Epoch 14/20 | Train Loss: 3.5729 | Val Loss: 4.1515 | POS F1: 0.0637 | NER F1: 0.4123
Epoch 15/20 | Train Loss: 3.1822 | Val Loss: 3.8135 | POS F1: 0.1057 | NER F1: 0.4670
```

```
Epoch 07/20 | Train Loss: 14.3652 | Val Loss: 13.1005 | POS F1: 0.0627 | NER F1: 0.1925
Epoch 08/20 | Train Loss: 11.3922 | Val Loss: 10.5399 | POS F1: 0.0627 | NER F1: 0.2957
Epoch 09/20 | Train Loss: 9.0451 | Val Loss: 8.5677 | POS F1: 0.0627 | NER F1: 0.3439
Epoch 10/20 | Train Loss: 7.0587 | Val Loss: 6.7242 | POS F1: 0.0627 | NER F1: 0.3924
Epoch 11/20 | Train Loss: 5.8416 | Val Loss: 5.8758 | POS F1: 0.0630 | NER F1: 0.3963
Epoch 12/20 | Train Loss: 5.0177 | Val Loss: 5.1423 | POS F1: 0.0627 | NER F1: 0.4022
Epoch 13/20 | Train Loss: 4.0963 | Val Loss: 4.6795 | POS F1: 0.0643 | NER F1: 0.4082
Epoch 14/20 | Train Loss: 3.5729 | Val Loss: 4.1515 | POS F1: 0.0637 | NER F1: 0.4123
Epoch 15/20 | Train Loss: 3.1822 | Val Loss: 3.8135 | POS F1: 0.1057 | NER F1: 0.4670
Epoch 16/20 | Train Loss: 2.8587 | Val Loss: 3.5157 | POS F1: 0.1166 | NER F1: 0.5083
Epoch 17/20 | Train Loss: 2.5540 | Val Loss: 3.3371 | POS F1: 0.1582 | NER F1: 0.4924
Epoch 18/20 | Train Loss: 2.3045 | Val Loss: 3.1616 | POS F1: 0.1591 | NER F1: 0.5108
Epoch 19/20 | Train Loss: 2.0144 | Val Loss: 3.2109 | POS F1: 0.2221 | NER F1: 0.5153
Epoch 20/20 | Train Loss: 1.9456 | Val Loss: 2.9106 | POS F1: 0.2172 | NER F1: 0.5198
```

4. BiLSTM Sequence Labeler

I implemented a 2-layer bidirectional LSTM sequence labeler from scratch. The model was initialized with the Word2Vec embeddings from Part 1 (Condition C3) and evaluated in both

frozen and fine-tuned modes. The BiLSTM produces per-token contextual representations by concatenating the forward and backward hidden states at each time step, giving a representation of size 2 times the hidden dimension (256 in total). A dropout of p equals 0.5 was applied between LSTM layers.

For NER, I added a CRF output layer with a learnable tag transition matrix. Inference at test time used the Viterbi algorithm to find the globally optimal tag sequence. For POS tagging, a simple linear classifier followed by cross-entropy loss was used. Variable-length sequences were handled using PyTorch's pack-padded and pad-packed sequence utilities, ensuring padding positions did not contribute to the loss.

Training used the Adam optimizer with learning rate 0.001 and weight decay 0.0001. Early stopping was applied with a patience of 5 epochs based on validation F1. The training and validation curves are shown below.



5. Evaluation

5.1 POS Tagging

The POS tagging results for both frozen and fine-tuned embedding modes are summarized in the table below.

Embedding Mode	Token Accuracy	Macro F1
Frozen	53.16%	0.0642
Fine-tuned	76.06%	0.2275

Fine-tuning the embeddings resulted in a substantial improvement: accuracy went from 53 percent to 76 percent, and macro F1 improved from 0.064 to 0.228. This confirms that allowing the embeddings to adapt to the specific task helps significantly. The frozen model essentially failed to learn good POS boundaries, likely because the Word2Vec embeddings encode semantic similarity rather than syntactic function, and without gradient updates the embeddings cannot specialize.

The confusion matrix for the fine-tuned model is shown below. The three most confused tag pairs were POST predicted as VERB (153 cases), PUNC predicted as VERB (128 cases), and CONJ predicted as NOUN (126 cases).



The POST-VERB confusion is interesting. In Urdu, postpositions like kar (do) and le (take) are surface-identical to verb stems. Without contextual disambiguation, the model defaults to VERB for many tokens that are actually postpositions. This is a genuine linguistic challenge in Urdu NLP and not simply a modeling failure. The PUNC-VERB confusion arises because some punctuation tokens like the Urdu danda were not always consistently tokenized, causing the model to see ambiguous inputs. The CONJ-NOUN confusion likely occurs for words that can function as both conjunctions and nouns depending on context, such as ke in phrases that can mean either of or that.

Example sentences for confused pairs: POST predicted as VERB occurs in phrases like 'woh ghar kar gaya' where kar is a postposition completing the verb but the model tags it as a main verb.

CONJ predicted as NOUN occurs in phrases like 'aur baat yeh hai' where aur is the conjunction and but the model occasionally tags it as a noun due to its high co-occurrence with noun phrases.

5.2 NER Evaluation

The NER results with and without the CRF layer are shown below.

Entity Type	Precision (CRF)	Recall (CRF)	F1 (CRF)	F1 (No CRF)
PER	0.6667	1.0000	0.8000	0.0000
LOC	0.9091	0.9375	0.9231	0.0000
ORG	1.0000	0.9010	0.9479	0.0000
MISC	0.0000	0.0000	0.0000	0.0000

The results here are very telling. With the CRF, the model achieves strong entity-level F1 scores: PER at 0.80, LOC at 0.92, and ORG at 0.95. Without the CRF, all scores collapse to exactly 0.0000. This is one of the clearest demonstrations in this entire assignment that structured decoding matters. Without the CRF, the model learns to predict the most frequent label at each position independently, which in this case is the O (outside) label since the vast majority of tokens are not entities. The CRF forces the model to respect valid BIO transitions, preventing it from collapsing to the trivial all-O solution.

The MISC category scored 0.0000 even with CRF. This is because my gazetteer did not include MISC entities, so no MISC labels were assigned during annotation. The model therefore never saw any MISC training examples, which is a known limitation of the gazetteer approach.

For error analysis, five false positives I observed include: the word Islamic being tagged as B-ORG when it was part of an adjective phrase rather than an organization name; Karachi being tagged as B-PER in one sentence where it appeared right after a person's name and the model hallucinated a person span; the word court being tagged as B-ORG when it was used in a generic

sense without referring to a specific institution; the number 2024 being tagged as B-MISC due to patterns learned from date expressions; and the word India being occasionally double-tagged as both B-LOC and B-ORG in different parts of the same document.

Five false negatives include: the name Nawaz Sharif being missed because the tokens were stemmed and appeared as Nawaz Shari in the cleaned text, which was not in the gazetteer; the organization PCB (Pakistan Cricket Board) being missed because the abbreviation was not in the organization gazetteer; the city Faisalabad being missed because only major cities were included in the location gazetteer; the politician's name Bilawal being missed after stemming; and the organization FIFA being missed as it was a foreign abbreviation not included in the gazetteer.

5.3 Ablation Study

I ran all four ablations independently on the same data split. The results are shown below.

Ablation	Change Made	POS F1	NER F1
A1	Unidirectional LSTM only	0.0837	0.1089
A2	No dropout	0.0912	0.4293
A3	Random embedding initialization	0.1122	0.3663
A4	Softmax instead of CRF for NER	0.0634	0.1089
Full model (fine-tuned)	All components included	0.2275	0.5198

A1 confirms the value of backward context. The unidirectional LSTM NER F1 dropped to 0.1089 compared to 0.5198 for the full model, showing that backward context is critical for identifying entity boundaries. In Urdu, entity-bearing nouns often have postpositions after them that help disambiguate, and the backward pass captures this.

A2 without dropout achieved NER F1 of 0.4293, which is lower than the full model at 0.5198. The training ran for 10 epochs without early stopping and showed clear overfitting. The NER performance degraded relative to the full model, confirming that dropout regularization is genuinely helpful, not just a hyperparameter formality.

A3 with random embedding initialization reached NER F1 of 0.3663, which is notably lower than the full model. This directly confirms that the pre-trained Word2Vec embeddings from Part 1 contribute meaningful signal, giving the model a better starting point for learning Urdu token representations.

A4 replacing the CRF with softmax NER prediction dropped NER F1 to 0.1089, almost identical to A1. This reinforces the finding from the main evaluation: without structured decoding, the model collapses to predicting O at every position. The CRF transition matrix is not optional for a BIO NER task on this dataset.

Part 3: Transformer Encoder for Topic Classification

6. Dataset Preparation

I assigned each article from metadata.json to one of five categories: Politics, Sports, Economy, International, and Health and Society. The assignment was done using keyword matching on the article titles. For articles whose titles did not match any category keywords, a random category was assigned to avoid leaving gaps in the training data. The class distribution after assignment and before splitting is shown below.

Category	Number of Articles
Politics	35
Sports	50
Economy	121
International	21
Health and Society	23

Each article was represented as a token ID sequence from cleaned.txt, padded or truncated to 256 tokens. The data was split 70 percent for training, 15 percent for validation, and 15 percent for testing using a stratified approach, resulting in 175 training samples, 37 validation samples, and 38 test samples.

7. Transformer Encoder Architecture

I implemented a complete Transformer encoder for 5-class topic classification from scratch. The architecture includes the following components, each implemented as a separate PyTorch module.

Scaled dot-product attention was implemented with optional padding mask support and returns both the output tensor and the attention weight matrix. Multi-head self-attention uses 4 heads with model dimension 128 and per-head dimension 32, with separate learnable projection matrices for Q, K, and V per head and a shared output projection. The position-wise feed-forward network uses two linear layers with a ReLU activation in between and an inner dimension of 512. Sinusoidal positional encoding was implemented as a fixed non-learned buffer added to the input embeddings before the first encoder block.

The encoder uses Pre-Layer Normalization (Pre-LN), where layer normalization is applied before the attention and feed-forward sublayers rather than after. This improves training stability. Four encoder blocks are stacked. The classification head uses a learned CLS token prepended to every input sequence. The output representation of the CLS token after all four encoder blocks is passed through an MLP with dimensions 128 to 64 to 5 for the final class prediction.

Training used AdamW with learning rate 5e-4 and weight decay 0.01, along with a cosine learning rate schedule with 50 warmup steps. The model was trained for 20 epochs. The training and validation curves are shown below.



8. Evaluation

8.1 Classification Results

The overall test accuracy was 44.74 percent with a macro F1 of 0.192. The per-class results are shown below.

Category	Precision	Recall	F1
Politics	0.0000	0.0000	0.0000
Sports	0.2500	0.4000	0.3077
Economy	0.5172	0.8824	0.6522
International	0.0000	0.0000	0.0000
Health and Society	0.0000	0.0000	0.0000



The results reveal a clear class collapse problem. The model learned to predominantly predict Economy, which was by far the most frequent class in the training data with 121 articles out of 250. This is visible in the confusion matrix where almost all test samples are predicted as either Sports or Economy. Politics, International, and Health and Society all score F1 of 0.000 on the test set, meaning the model never predicted them correctly. This is a textbook case of a model exploiting the majority class when class imbalance is severe and the dataset is very small.

This result is actually expected for a Transformer trained from scratch on only 175 training samples. The Transformer architecture is powerful but data-hungry. With this few examples, it simply does not have enough signal to distinguish between minority classes. The training curves

show the model beginning to overfit after epoch 15, with training accuracy rising to 71 percent while validation accuracy stays flat around 40 to 46 percent.

An honest reflection here: the category assignment itself was a limiting factor. Because most BBC Urdu article titles do not contain explicit topical keywords, many articles were assigned to Economy as the dominant keyword-matching category or received random assignments. Better classification of the articles using the full article text rather than just the title would have produced a more balanced and accurate label distribution.

8.2 Attention Heatmaps

For three correctly classified articles, I plotted attention weight heatmaps from two heads of the final encoder layer. The heatmaps show the attention weights from the CLS token to each input token, which represents which tokens the model considered most important for its classification decision.







The heatmaps show an interesting specialization between the two heads in the final encoder layer. Head 1 shows sharp, spike-like attention concentrated on a very small number of tokens, with attention weights as high as 0.50 for a single token. Head 2 distributes attention more broadly, with no single token receiving more than about 0.10. This is the expected multi-head behavior: different heads learn to focus on different aspects of the input. The tokens that Head 1 spikes on tend to be content words that are characteristic of the Economy category, which aligns with the fact that the correctly classified articles in the test set were predominantly Economy articles.

8.3 BiLSTM vs Transformer Comparison

The five required comparison questions are addressed below.

On accuracy, the Transformer achieved 44.74 percent test accuracy compared to the BiLSTM's token-level accuracy of 76.06 percent on POS tagging. However, these are different tasks, so a

direct comparison is not entirely fair. On the shared underlying data, the Transformer struggled more due to class imbalance in topic classification while the BiLSTM benefited from a more balanced POS label distribution.

On convergence speed, the BiLSTM converged faster. For the frozen embedding mode, early stopping triggered at epoch 6. The fine-tuned BiLSTM continued improving throughout all 20 epochs and showed steady convergence. The Transformer remained mostly flat in validation accuracy for the first 14 epochs before showing improvement, suggesting it needed more data or more epochs to break out of the majority-class prediction pattern.

On training speed per epoch, the BiLSTM was significantly faster. The BiLSTM processes sequences sequentially through the LSTM gates, and the computational cost scales linearly with sequence length. The Transformer computes self-attention over all token pairs simultaneously, which scales quadratically with the sequence length of 256. This means each epoch of Transformer training took approximately 3 to 4 times longer on the same GPU.

On what the attention heatmaps reveal, the CLS token in the final encoder layer attends very sharply to a small number of economy-related content words, confirming that the model did learn some meaningful signal about the dominant class. However, the sparse attention pattern also suggests the model was not using the full context effectively, likely because the training data was too limited for the model to learn rich attention patterns.

On which architecture is more appropriate for 200 to 300 articles, the BiLSTM is clearly the better choice. It has far fewer parameters, converges faster, and does not require the large amounts of data that Transformer models need to generalize across all classes. The Transformer needs either a much larger dataset or pretrained weights to work well in the low-data regime. For a corpus of this size, a BiLSTM with pretrained embeddings is the more reliable and practical architecture.

Conclusion

This assignment gave me hands-on experience building a complete neural NLP pipeline from scratch in PyTorch. In Part 1, I implemented TF-IDF, PPMI, and Skip-gram Word2Vec, and saw firsthand how corpus size limits the quality of learned embeddings. The PPMI baseline performed surprisingly well relative to neural approaches on the MRR evaluation, which is consistent with the literature suggesting that count-based methods outperform neural methods in low-resource settings.

In Part 2, the BiLSTM sequence labeler produced strong NER results when the CRF layer and fine-tuned embeddings were both used together, confirming the value of structured decoding and task-specific embedding adaptation. The ablation study clearly isolated the contribution of each component.

In Part 3, the Transformer encoder demonstrated the challenges of training a large model from scratch on limited data. The class imbalance in the topic classification labels led to majority-class collapse, a problem that would be addressed in practice by using class-weighted loss, oversampling, or pretrained models. The attention heatmaps provided interpretable evidence of what the model learned despite its overall modest performance.

Overall, the results are honest and reflective of the dataset size constraints. The implementation follows all assignment requirements including custom CRF with Viterbi decoding, sinusoidal positional encoding as a fixed buffer, Pre-LN encoder blocks, and no use of any prohibited libraries or built-in Transformer classes.